For State Use Only:

APPROVED BY:

Patricia L Martinez

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 326534 District II WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** Phone:(575) 748-1283 Fax:(575) 748-9720 30-025-48725 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS PROMETHEUS STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 101H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location line and feet 229 from the W 33E NMPM Township 24S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3547 GR Pit or Below-grade Tank Application or Closure \_\_ Depth to Groundwater\_\_\_ \_\_\_ Distance from nearest fresh water well\_\_ \_ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume\_ Pit Liner Thickness: bbls: Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 6/6/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Dpth Yield Open Size Size lb/ft TOC Held Drop Hole 06/06/22 Surf FreshWater 17.5 13.375 54.5 J55 0 1336 995 1.36 С 1500 0 Ν 09/02/22 Int1 Brine 12.25 9.625 40 J55 0 5346 1170 1.34 С 1500 0 Ν 09/13/22 OilBasedMud 20 P110 Prod 6.75 5.5 2042 19797 1605 С Ν 1.46 I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines  $\square$ , a general permit  $\square$  or an (attached) alternative OCD-approved plan  $\square$ SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 10/4/2022 Type or print name Christian Combs E-mail address ccombs@taprk.com Telephone No. 720-360-4028

TITLE

DATE

10/13/2022 1:04:28 PM

Prometheus State Com 101H Intermediate and Production Casing

8/31/2022: Test BOPS. Drill 12.25 intermediate hole to 5361 ft.

9/2/2022: Run 9.625 inch 40 lb J-55 intermediate casing to 5346 ft. Pump 20 bbls fresh water, followed by 840 sks of 11.0 ppg lead cmt, 330 sks of 14.8 ppg tail cmt. Drop plug and displace with 402 bbls fresh water. 80 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test.

9/2/2022: Drill 8.75 inch production hole to 9007 ft then switch to 6.75 in hole to 19811 ft.

7/31/2022: Run 5.5 inch 20 lb P-110 production casing to 19797 ft MD. Pump 40 bbls gel spacer, then 480 sks of 10.5 lead cmt, 1125 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls retarder and 427 bbls fresh water. 0 bbls returned to surface. Est TOC at 2042 ft.

Intermediate Casing Details: Casing ran: 9/2/2022, Fluid Type Brine, Hole 12.25 inch to 5361 ft, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 5346 ft, Cement 1170 sks, Yield 2.50 lead/1.34 tail, Class C, Pressure Held 1500 psi, Pres Drop 0.

Production Casing details: Casing Date: 9/13/2022, Fluid Type Oil Based Mud, Hole 8.75 inch to 9007, 6.75 inch to 19811 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 19797 ft, EST TOC 2042 ft, Cement 1605 sacks, yield 3.35 lead/1.46 tail, Class C.

9/12/2022: TD Reached at 19811 ft MD, 9370 ft TVD. Plug Back Measured depth at 19751 ft MD, 9365 ft TVD. Rig Release on 9/16/2022 at 06:00.