For State Use Only:

APPROVED BY:

Patricia L Martinez

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 326838 District II WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** 30-025-50360 Phone:(575) 748-1283 Fax:(575) 748-9720 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS HYPERION STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 143H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location <u>A</u> : <u>634</u> feet from the N line and feet 1140 Unit Letter A from the E Township 33E NMPM 24S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3562 GR Pit or Below-grade Tank Application or Closure \_\_ Depth to Groundwater\_\_\_ \_\_\_ Distance from nearest fresh water well\_\_ \_ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume\_ bbls; Construction Material Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 8/4/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Dpth Yield Open Size Size lb/ft TOC Held Drop Hole 08/05/22 Surf FreshWater 17.5 13.375 54.5 J55 0 1294 995 1.36 С 1500 0 Ν 09/28/22 Int1 Brine 12.25 9.625 40 J55 0 5367 1170 1.34 С 1500 0 Ν 10/05/22 OilBasedMud 20 P110 Prod 6.75 5.5 3081 15599 1160 Ν 1.44 Н I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines  $\square$ , a general permit  $\square$  or an (attached) alternative OCD-approved plan  $\square$ SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 10/11/2022 Type or print name Christian Combs E-mail address ccombs@taprk.com Telephone No. 720-360-4028

TITLE

DATE

10/13/2022 2:07:14 PM

Hyperion State Com 143H Intermediate and Production Casing

9/26/2022: Test BOPS. Drill 12.25 intermediate hole to 5381 ft.

9/28/2022: Run 9.625 inch 40 lb J-55 intermediate casing to 5367 ft. Pump 20 bbls spacer, followed by 845 sks of 11.0 ppg lead cmt, 325 sks of 14.8 ppg tail cmt. Drop plug and displace with 404 bbls fresh water. 120 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test.

9/28/2022: Drill 8.75 inch production hole to 10086 ft then switch to 6.75 in hole to 15613 ft.

10/5/2022: Run 5.5 inch 20 lb P-110 production casing to 15599 ft MD. Pump 40 bbls gel spacer, then 420 sks of 10.5 lead cmt, 740 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls retarder and 325 bbls fresh water. 0 bbls returned to surface. Est TOC at 3081 ft.

Intermediate Casing Details: Casing ran: 9/23/2022, Fluid Type Brine, Hole 12.25 inch to 5381 ft, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 5367 ft, Cement 1170 sks, Yield 2.50 lead/1.34 tail, Class C, Pressure Held 1500 psi, Pres Drop 0.

Production Casing details: Casing Date: 10/5/2022, Fluid Type Oil Based Mud, Hole 8.75 inch to 10086, 6.775 inch to 15613 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 15599 ft, EST TOC 3081 ft, Cement 1160 sacks, yield 3.32 lead/1.44 tail, Class H.

10/4/2022: TD Reached at 15613 ft MD, 10537 ft TVD. Plug Back Measured depth at 15550 ft MD, 10538 ft TVD. Rig Release on 10/62022 at 18:00.