

<b>Well Name:</b> JICARILLA APACHE B	<b>Well Location:</b> T24N / R5W / SEC 29 / SESE / 36.279875 / -107.37936	<b>County or Parish/State:</b> RIO ARRIBA / NM
<b>Well Number:</b> 6	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b> JICARILLA APACHE
<b>Lease Number:</b> JIC11	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 3003905290	<b>Well Status:</b> Producing Gas Well	<b>Operator:</b> DJR OPERATING LLC

**Notice of Intent**

**Sundry ID:** 2697745

**Type of Submission:** Notice of Intent

**Type of Action:** Plug and Abandonment

**Date Sundry Submitted:** 10/12/2022

**Time Sundry Submitted:** 12:02

**Date proposed operation will begin:** 10/12/2022

**Procedure Description:** This request is being submitted for engineering & geological review prior to onsite inspection as approved by Dave M. of the BLM. DJR Operating, LLC requests permission to Plug & Abandon the subject well according to the attached Procedure, Current & Proposed Wellbore Diagram.

**Surface Disturbance**

**Is any additional surface disturbance proposed?:** No

**NOI Attachments**

**Procedure Description**

NOI\_PA\_BLM\_Submittal\_20221012120210.pdf

Well Name: JICARILLA APACHE B

Well Location: T24N / R5W / SEC 29 / SESE / 36.279875 / -107.37936

County or Parish/State: RIO ARRIBA / NM

Well Number: 6

Type of Well: CONVENTIONAL GAS WELL

Allottee or Tribe Name: JICARILLA APACHE

Lease Number: JIC11

Unit or CA Name:

Unit or CA Number:

US Well Number: 3003905290

Well Status: Producing Gas Well

Operator: DJR OPERATING LLC

### Conditions of Approval

#### Specialist Review

24N5W29\_Jicarilla\_Apache\_B\_6\_Geo\_KGR\_20221024145648.pdf

2697745\_NOIA\_B\_6\_3003905290\_KR\_10242022\_20221024145625.pdf

General\_Requirement\_PxA\_20221024145604.pdf

### Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: SHAW-MARIE FORD

Signed on: OCT 12, 2022 12:02 PM

Name: DJR OPERATING LLC

Title: Regulatory Specialist

Street Address: 1 Road 3263

City: Aztec

State: NM

Phone: (505) 632-3476

Email address: sford@djrlc.com

### Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

### BLM Point of Contact

BLM POC Name: KENNETH G RENNICK

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5055647742

BLM POC Email Address: krennick@blm.gov

Disposition: Approved

Disposition Date: 10/24/2022

Signature: Kenneth Rennick

**DJR Operating, LLC**  
**Plug and Abandonment Procedure**  
**Jicarilla Apache B 6**  
**API # 30-039-05290**  
**SE/SE, Unit P, Sec. 29, T24N, R5W**  
**Rio Arriba County, NM**

1. Hold pre-job meeting, comply with all NMOCD, BLM, and environmental regulations.
2. Check and record tubing, casing and bradenhead pressures.
3. Remove existing piping from casing valve, RU blow lines from casing valves and blow down casing pressure. Kill well as necessary. Ensure that well is dead or on a vacuum.
4. ND WH, NU BOP, function test BOP.
5. Trip out of hole with 1-1/2" tubing. LD tubing to be sent in for storage/salvage.
6. PU work string, TIH with bit and scraper, make sure that the bit and scraper will go below 2060'. TOOH.
7. Plug 1: Pictured Cliffs perforations: TIH with CR and set near 2060'. Pressure test tubing to 1000 psi. Sting out of CR. Roll hole Pressure test casing to 600 psi. Sting back into CR and attempt to squeeze below CR with 20 sx. Sting out, and pump water to ensure tubing is clear. TOOH.
8. MIRU logging truck. Run CBL log from CR to surface. Hold 600 psi on casing if possible. Electronic copy of CBL to be sent to; Monica Kuehling, NMOCD [mkuehling@state.nm.us](mailto:mkuehling@state.nm.us), Kenneth Renneck, BLM [krenneck@blm.gov](mailto:krenneck@blm.gov), Scott Lindsay, DJR [slindsay@djrlc.com](mailto:slindsay@djrlc.com), and Loren Diede, DJR [ldiede@djrlc.com](mailto:ldiede@djrlc.com).
9. Plug 2. Pictured Cliffs, Fruitland, Kirtland, and Ojo Alamo: Spot cement from top of CR to 1580'. Pump water to ensure tubing is clear. TOOH.
10. Plug 3. Perforate holes at 1145'. Set CR near 1095'. Mix and pump sufficient volume to bring TOC to 1045', inside and outside. Pump water to ensure tubing is clear.
11. Plug 4: Surface casing shoe and surface: Perforate holes at 183'. Mix and pump sufficient volume to bring cement to surface inside and outside.
12. RD cementing equipment. Cut off wellhead, fill annuli with cement, as necessary. **Install P&A marker as per BIA requirements.** Record GPS coordinates for P&A marker and the final P&A report. Photograph the P&A marker and attach to the report.
13. RD and MO all rig and cement equipment. Assure that location is free of trash before moving off.

14. Send all reports and attachments to DJR Aztec office for regulatory filings.

**Note: All cement is to be Class G mixed at 15.8 ppg yield 1.15 cu. Ft. /sk. Cement volumes are based on inside capacities +50' and outside capacities + 100% excess.**

**PxA marker is to be 12"x18" with rounded corners and installed below grade no deeper than 2'.**

**DJR Operating, LLC**  
**Current Wellbore Diagram**  
**Jicarilla Apache B 6**  
 API # 30-039-05290  
 SE/SE, Unit P, Sec 29, T24N, R5W  
 Rio Arriba County, NM

GL N/A  
 KB 6602'  
 Spud Date 10/22/1955

SURF CSG

Hole size 12.25"  
 Csg Size: 8.625"  
 Wt: 24#  
 Grade: N/A  
 ID: 8.097"  
 Depth 133'  
 casing cap ft<sup>3</sup>/ft: 0.3575  
 TOC: Circ. cement to surface.

FORMATION TOPS


San Jose	Surface
Nacimiento	1095'
Ojo Alamo	1630'
Kirtland	1818'
Fruitland	2030'
Pictured Cliffs	2173'

PROD CSG

Hole size 7.875"  
 Csg Size: 5.5"  
 Wt: 15.5#  
 Grade: N/A  
 ID: 4.950"  
 Depth 2082'  
 Casing cap ft<sup>3</sup>/ft: 0.1336  
 Csq/csq Ann. ft<sup>3</sup>/ft 0.1926  
 Csq/OH ft<sup>3</sup>/ft 0.1733  
 TOC: 1015' (TS)

<b>Production Tubing Detail</b>
Possibly 1-1/2" @ 2197'

7-7/8" OH 2176-2200'



**DJR Operating, LLC**  
**Proposed Wellbore Diagram**  
**Jicarilla Apache B 6**  
 API # 30-039-05290  
 SE/SE, Unit P, Sec 29, T24N, R5W  
 Rio Arriba County, NM

GL N/A  
 KB 6602'  
 Spud Date 10/22/1955

SURF CSG

Hole size 12.25"  
 Csg Size: 8.625"  
 Wt: 24#  
 Grade: N/A  
 ID: 8.097"  
 Depth 133'  
 casing cap ft<sup>3</sup>/ft: 0.3575  
 TOC: Circ. cement to surface.

FORMATION TOPS

San Jose	Surface
Nacimiento	1095'
Ojo Alamo	1630'
Kirtland	1818'
Fruitland	2030'
Pictured Cliffs	2173'


PROD CSG

Hole size 7.875"  
 Csg Size: 5.5"  
 Wt: 15.5#  
 Grade: N/A  
 ID: 4.950"  
 Depth 2082'  
 casing cap ft<sup>3</sup>/ft: 0.1336  
 Csg/csg Ann. ft<sup>3</sup>/ft 0.1926  
 Csg/OH ft<sup>3</sup>/ft 0.1733  
 TOC: 1015' (TS)

**Note: Inside plugs will include 50' excess, while outside plugs will include 100% excess.**

Cement Ret. 2060'

7-7/8" OH 2176-2200'



**Plug 4: Surface casing shoe, surface: Perf holes at 183'. Mix and pump sufficient cement to bring TOC to surface, inside and outside.**

**Plug 3: Nacimiento: Perf holes at 1145'. Set CR near 1095'. Mix and pump sufficient volume to bring TOC to 1045', inside and outside.**

**Plug 2: Pictured Cliffs, Fruitland, Kirtland, and Ojo Alamo: Spot plug from CR to 1580'.**

**Plug 1: Pictured Cliffs perfs: Set CR near 2060'. Attempt to pump 20 sx cement (includes excess) through CR into open hole.**

**UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
FARMINGTON DISTRICT OFFICE  
6251 COLLEGE BLVD.  
FARMINGTON, NEW MEXICO 87402**

AFMSS 2 Sundry ID 2697745

Attachment to notice of Intention to Abandon

Well: Jicarilla Apache B 6

**CONDITIONS OF APPROVAL**

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
2. Farmington Office is to be notified at least 24 hours before the plugging operations commence at (505) 564-7750.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.

K. Rennick 10/24/2022

**GENERAL REQUIREMENTS FOR  
PERMANENT ABANDONMENT OF WELLS ON FEDERAL AND INDIAN LEASES  
FARMINGTON FIELD OFFICE**

- 1.0 The approved plugging plans may contain variances from the following minimum general requirements.
- 1.1 Modification of the approved plugging procedure is allowed only with the prior approval of the Authorized Officer, Farmington Field Office.
  - 1.2 Requirements may be added to address specific well conditions.
- 2.0 Materials used must be accurately measured. (densometer/scales)
- 3.0 A tank or lined pit must be used for containment of any fluids from the wellbore during plugging operations and all pits are to be fenced with woven wire. These pits will be fenced on three sides and once the rig leaves location, the fourth side will be fenced.
- 3.1 Pits are not to be used for disposal of any hydrocarbons. If hydrocarbons are present in the pit, the fluids must be removed prior to filling in.
- 4.0 All cement plugs are to be placed through a work string. Cement may be bull-headed down the casing with prior approval. Cement caps on top of bridge plugs or cement retainers may be placed by dump bailer.
- 4.1 The cement shall be as specified in the approved plugging plan.
  - 4.2 All cement plugs placed inside casing shall have sufficient volume to fill a minimum of 100' of the casing, or annular void(s) between casings, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.
  - 4.3 Surface plugs may be no less than 50' in length.
  - 4.4 All cement plugs placed to fill annular void(s) between casing and the formation shall be of sufficient volume to fill a minimum of 100' of the annular space plus 100% excess, calculated using the bit size, or 100' of annular capacity, determined from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.
  - 4.5 All cement plugs placed to fill an open hole shall be of sufficient volume to fill a minimum of 100' of hole, as calculated from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug. In the absence of a caliper log, an excess of 100% shall be required.
  - 4.6 **A cement bond log or other accepted cement evaluation tool is required to be run if one had not been previously ran or cement did not circulate to surface during the original casing cementing job or subsequent cementing jobs.**

5.0 All cement plugs spotted across, or above, any exposed zone(s), when; the wellbore is not full of fluid or the fluid level will not remain static, and in the case of lost circulation or partial returns during cement placement, shall be tested by tagging with the work string.

- 5.1 The top of any cement plug verified by tagging must be at or above the depth specified in the approved plan, without regard to any excess.
- 5.2 Testing will not be required for any cement plug that is mechanically contained by use of a bridge plug and/or cement retainer, if casing integrity has been established.
- 5.3 Any cement plug which is the only isolating medium, for a fresh water interval or a zone containing a prospectively valuable deposit of minerals, shall be tested by tagging.
- 5.4 If perforations are required below the surface casing shoe, a 30 minute minimum wait time will be required to determine if gas and/or water flows are present. If flow is present, the well will be shut-in for a minimum of one hour and the pressure recorded. Short or long term venting may be necessary to evacuate trapped gas. **If only a water flow occurs with no associated gas, shut well in and record the pressures. Contact the Engineer as it may be necessary to change the cement weight and additives.**

6.0 Before setting any cement plugs the hole needs to be rolled. All wells are to be controlled by means of a fluid that is to be of a weight and consistency necessary to stabilize the wellbore. This fluid shall be left in place as filler between all plugs.

- 6.1 Drilling mud may be used as the wellbore fluid in open hole plugging operations.
- 6.2 The wellbore fluid used in cased holes shall be of sufficient weight to balance known pore pressures in all exposed formations.

7.0 A blowout preventer and related equipment (BOPE) shall be installed and tested prior to working in a wellbore with any exposed zone(s); (1) that are over pressured, (2) where the pressures are unknown, or (3) known to contain H<sub>2</sub>S.

8.0 Within 30 days after plugging work is completed, file a Sundry Notice, Subsequent Report of Abandonment (Form 3160-5), five copies, with the Field Manager, Bureau of Land Management, 6251 College Blvd., Suite A, Farmington, NM 87402. The report should show the manner in which the plugging work was carried out, the extent, by depth(s), of cement plugs placed, and the size and location, by depth(s), of casing left in the well. Show date well was plugged.

9.0 All permanently abandoned wells are to be marked with a permanent monument as specified in 43 CFR 3162.6(d). Unless otherwise approved.

10.0 If this well is located in a Specially Designated Area (SDA), compliance with the appropriate seasonal closure requirements will be necessary.

All of the above are minimum requirements. Failure to comply with the above conditions of approval may result in an assessment for noncompliance and/or a Shut-in Order being issued pursuant to 43 CFR 3163.1. You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to administrative review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

(October 2012 Revision)

**BLM FLUID MINERALS  
P&A Geologic Report**

**Date Completed:** 10/24/2022

Well No. Jicarilla Apache B 6 (API# 30-039-05290)	Location	SESE			
Lease No. JIC11	Sec. 29	T24N			R5W
Operator DJR Operating, LLC	County	Rio Arriba	State		New Mexico
Total Depth 2200'	PBTD Open Hole	Formation	Pictured Cliffs		
Elevation (GL) NA		Elevation (KB)	6602'		

Geologic Formations	Est. Top	Est. Bottom	Log Top	Log Bottom	Remarks
San Jose Fm					Surface/freshwater sands
Nacimiento Fm			1095		Possible freshwater sands
Ojo Alamo Ss			1630		Aquifer (possible freshwater)
Kirtland Shale			1818		
Fruitland Fm			2030		Coal/Gas/Possible water
Pictured Cliffs Ss			2173		Gas
Lewis Shale					
Chacra					Gas
Cliff House Ss					Water/Possible gas
Menefee Fm					Coal/Ss/Water/Possible O&G
Point Lookout Ss					Probable water/Possible O&G
Mancos Shale					
Gallup					O&G/Water
Greenhorn					
Graneros Shale					
Dakota Ss					O&G/Water

Remarks:  
P & A

Reference Well:

- Pictured Cliffs open hole 2176 - 2200'.

**Prepared by: Kenneth Rennick**

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 153420

**CONDITIONS**

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 153420
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

**CONDITIONS**

Created By	Condition	Condition Date
kpickford	CBL required	10/27/2022
kpickford	Notify NMOCD 24 Hours Prior to beginning operations	10/27/2022
kpickford	Adhere to BLM approved COAs and plugs. See BLM COAs and GEO report.	10/27/2022