

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-38552
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator SPUR ENERGY PARTNERS LLC		6. State Oil & Gas Lease No.
3. Address of Operator 9655 KATY FREEWAY, SUITE 500, HOUSTON, TX 77024		7. Lease Name or Unit Agreement Name BOOT HILL 25
4. Well Location Unit Letter <u>O</u> : <u>2590</u> feet from the <u>SOUTH</u> line and <u>2145</u> feet from the <u>EAST</u> line Section <u>25</u> Township <u>19S</u> Range <u>25E</u> NMPM <u>EDDY</u> County		8. Well Number <u>1H</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3396' GR		9. OGRID Number 328947
		10. Pool name or Wildcat N. SEVEN RIVERS; GLORIETA-YESO

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
DOWNHOLE COMMINGLE ☐	P AND A ☐
CLOSED-LOOP SYSTEM ☐	CASING/CEMENT JOB ☐
OTHER: ☐	OTHER: ☐

Notify OCD 24 hrs. prior to any work done

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. POOH w/ rods & tbq. Test casing 500psi / 30 min
2. Set 7" CIBP @ 2,900'. Pressure test csg. Spot 60 sx Class C cmt on top of CIBP. Circ MLF. WOC & Tag @ 2570'
3. Spot 25 sx Class C Cmt plug f/ 1,700'-1,550' (T/ San Andres). WOC & Tag.
4. Perf & Sqz 50 sx Class C Cmt f/ 1,028'-928' (9 5/8" Shoe). WOC & Tag.
5. Perf & Sqz 50 sx Class C Cmt f/ 100'-Surf.
6. Verify cmt to surface, cutoff well head, weld on dry hole marker.

Please find current and proposed WBDs attached for your review.

Spud Date:

Rig Release Date:

****SEE ATTACHED COA's****

MUST BE PLUGGED BY 12/2/2023

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sarah Chapman TITLE REGULATORY DIRECTOR DATE 12/02/2022

Type or print name SARAH CHAPMAN E-mail address: SCHAPMAN@SPURENERGY.COM PHONE: 832-930-8613

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 12/8/22
 Conditions of Approval (if any):

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Cherry Canyon - Eddy County
 - L) Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3. API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

API #	30-015-38552	Boot Hill 25 #1H	County, ST	Eddy County, NM
Operator	Spur Energy Partners		Sec-Twn-Rng	25-19S-25E
Field	North Seven Rivers		Footage	2590' FSL and 2145' FEL, 330' FSL and 2145' FEL
Spud Date	12/4/2011		Survey	

RKB	
GL	3425'

Hole Size	12-1/4"
TOC	surf
Method	circ returns

Surface csg

Csg Depth	978'
Size	9-5/8"
Weight	40ppf
Grade	N80
Connections	LTC
Cement	610sx

Well History

1/20/2012 Frac Yeso from 2965'-4850' (3 stages).
Total prop: 340k# 20/40 brady
Total fluid: 12800bbl water, 2373bbl 10# gel, 740bbl 15# gel, 9522bbl 15# BXL gel, 500bbl 15% HCL
Rate: avg=64bpm, max=82bpm
STP: avg=1780#, max=2730#
ISIP: 1580#, 1410# (15min)
3/13/2012 Final report.
9/22/2017 RTP - Pump was stuck open. All SBs pitted.
Scanned tbg 52 out of 72 jts scanned bad.
Downsized pump f/ 1-3/4" to 1-1/4"
Ran new SBs & new 7/8" guided rods.
Lowered pump depth ~300 ft
2/5/2018 Bad pump? Discovered 7 bad FG rods. Replaced w/ steel rods on top of string. Replaced pump.
4/12/2018 Tested csg w/ Packer. 1/2 bbl/min @ 2600 psi
1 bbl/min @ 3100 psi
8/27/2018 Parted pull rod. Had to pull tbg. Replaced 3 bad mud jts and 10 bad k-bars. Changed out 18- 7/8" couplings and 8- 3/4" couplings.
1/30/2019 HIT

Hole Size	8-3/4"	7-7/8"
TOC	surf	
Method	circ returns	

XO @ 3033-3035

Csg Depth	3033'	4892'
Size	7"	5-1/2"
Weight	26ppf	17ppf
Grade	J55	J55
Connections	LTC	LTC
Cement	930sx	

Int/Prod csg

Top Perf

2965'

Bottom Perf

4850'

Perforations

2965'-3630' (Yeso): 1/28/2012 (46 holes)
3810'-4240' (Yeso): 1/28/2012(42 holes)
4390'-4850' (Yeso): 1/20/2012 (46 holes)

Tubing Detail				
Jts	Size	Depth	Length	Detail
76	2 7/8"	2432	2432	2 7/8" J-55 Tubing
	7"	2435	3	7" x 2 7/8" TAC
4	2 7/8"	2563	128	2 7/8" J-55 Tubing
	2 7/8"	2564	1	2 7/8" API SN
	2 7/8"	2568	4	4' x 2 7/8" Pup Jt
	2 7/8"	2587	19	Cavins D/S
5	2 7/8"	2747	160	5 mud jts w/ BP

Rod Detail				
Rods	Size	Depth	Length	Detail
1		13	26	P.R-1 1/4"x26' with 1 1/2"x16' P.R.L
11		288	275	3/4 bare rods
28		1338	1050	7/8" x 37.5' FG Rods
20		1838	500	1 1/2" Sinkers
6		1988	150	7/8" bare rods
22		2538	550	7/8" guided rods
1		2562	24	2 1/2"x1 1/4"x24' RHBC (HVR)

Last Update	1/12/2022
By	

PBTD	4850'
TD MD	4892'
TD TVD	2809'

API #	30-015-38552	Boot Hill 25 #1H	County, ST	Eddy County, NM
Operator	Spur Energy Partners		Sec-Twn-Rng	25-19S-25E
Field	North Seven Rivers		Footage	2590' FSL and 2145' FEL, 330' FSL and 2145' FEL
Spud Date	12/4/2011		Survey	

RKB	
GL	3425'

Hole Size	12-1/4"
TOC	surf
Method	circ returns

Surface csg

Csg Depth	978'
Size	9-5/8"
Weight	40ppf
Grade	N80
Connections	LTC
Cement	610sx

Perf & Sqz 50 sx cmt f/ 100'-Surf

Perf & Sqz 50 sx cmt f/ 1,028'-928' (9-5/8" Shoe)

Spot 25 sx cmt f/ 1,700'-1,550' (T. San Andres)


Proposed CIBP @ 2,900' w/ 60 sx Class C cmt
(TOC +/- 2,530')

Tops:
San Andres: 1,644'
Glorieta: 2,623'
Paddock: 2,745'

Tubing Detail				
Jts	Size	Depth	Length	Detail
76	2 7/8"	2432	2432	2 7/8" J-55 Tubing
	7"	2435	3	7" x 2 7/8" TAC
4	2 7/8"	2563	128	2 7/8" J-55 Tubing
	2 7/8"	2564	1	2 7/8" API SN
	2 7/8"	2568	4	4' x 2 7/8" Pup Jt
	2 7/8"	2587	19	Cavins D/S
5	2 7/8"	2747	160	5 mud jts w/ BP

Rod Detail				
Rods	Size	Depth	Length	Detail
1		13	26	P.R-1 1/4"x26' with 1 1/2"x16' P.R.L
11		288	275	3/4 bare rods
28		1338	1050	7/8" x 37.5' FG Rods
20		1838	500	1 1/2" Sinkers
6		1988	150	7/8" bare rods
22		2538	550	7/8" guided rods
1		2562	24	2 1/2"x1 1/4"x24' RHBC (HVR)

Last Update	8/17/2022
By	



Well History

1/20/2012 Frac Yeso from 2965'-4850' (3 stages).
Total prop: 340k# 20/40 brady
Total fluid: 12800bbl water, 2373bbl 10# gel, 740bbl 15# gel,
9522bbl 15# BXL gel, 500bbl 15% HCL
Rate: avg=64bpm, max=82bpm
STP: avg=1780#, max=2730#
ISIP: 1580#, 1410# (15min)
3/13/2012 Final report.
9/22/2017 RTP - Pump was stuck open. All SBs pitted.
Scanned tbg 52 out of 72 jts scanned bad.
Downsized pump f/ 1-3/4" to 1-1/4"
Ran new SBs & new 7/8" guided rods.
Lowered pump depth ~300 ft
2/5/2018 Bad pump? Discovered 7 bad FG rods. Replaced w/ steel rods on top of string. Replaced pump.
4/12/2018 Tested csg w/ Packer. 1/2 bbl/min @ 2600 psi
1 bbl/min @ 3100 psi
8/27/2018 Parted pull rod. Had to pull tbg. Replaced 3 bad mud jts and 10 bad k-bars. Changed out 18- 7/8" couplings and 8- 3/4" couplings.
1/30/2019 HIT

Hole Size	8-3/4"	7-7/8"
TOC	surf	
Method	circ returns	

XO @ 3033-3035

Csg Depth	3033'	4892'
Size	7"	5-1/2"
Weight	26ppf	17ppf
Grade	J55	J55
Connections	LTC	LTC
Cement	930sx	

Int/Prod csg

Top Perf
2965'

Bottom Perf
4850'

PBTD	4850'
TD MD	4892'
TD TVD	2809'

Perforations

2965'-3630' (Yeso): 1/28/2012 (46 holes)
3810'-4240' (Yeso): 1/28/2012(42 holes)
4390'-4850' (Yeso): 1/20/2012 (46 holes)

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 163256

CONDITIONS

Operator: Spur Energy Partners LLC 9655 Katy Freeway Houston, TX 77024	OGRID: 328947
	Action Number: 163256
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	12/8/2022