

Date Drawn: April 2022 (KTM)



Casing Record						
Surface						
OD	WT/FT	GRADE	Top	Bottom	Thread	Bit Size
10-3/4"	32.7		0	118		
Production						
OD	WT/FT	GRADE	Top	Bottom	Thread	Bit Size
5-1/2"	15.5		0	2202		

Cement		
String/Stage	Cement Type and Volume	TOC/Method
Surface	Lead: 100 sxs	Surface
	Lead: 150 sxs	
1st Stage Production		UNK

Perforations (Depth, SPF, EHD)
OPEN HOLE COMPLETION FROM 2205'-2281'

Stimulation Detail
7,700 gal diesel oil and 10,000# sand. Flushed w/ 2300 gal diesel. Treated from 2205'-2281'

[illegible][illegible]

Production Tubing Detail						
	Length	WT			Top	Bottom
KB Adjustment	10.00					10.00
Baker Model G Packer set at 2136'						10.00
4' perforated sub						10.00
2-3/8" tubing	2219.00					2229.00

Rod Detail - UNK						
					Top	Bottom
7/8" guided						
3/4" guided						
3/4 snap on guides						
1ea 2' 1ea 4' 2ea 6' pony rods						

Pumping Unit:	Gear Sheave:
API Designation:	Stroke Length:
Samson Post SN:	Gear Ratio:
Gear Box SN:	SPM:
Structural Unbalance:	Horse Power:
Power:	Volts:
Power SN:	Amps:
Sheave Size:	Belts:

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 181171

CONDITIONS

Operator: EPIC ENERGY, L.L.C. 332 Road 3100 Aztec, NM 87410	OGRID: 372834
	Action Number: 181171
	Action Type: [UF-WBS] Wellbore Schematic (WELLBORE SCHEMATICS)

CONDITIONS

Created By	Condition	Condition Date
mkuehling	None	1/31/2023