Page 1 of 12 Form C-144 Revised April 3, 2017

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method BGT1 Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
I. Operator: Dugan Production Corp. OGRID #: 006515
Address: PO Box 420, Farmington, NM 87499-0420
Facility or well name: McDougall #2
API Number: 30-045-28619 OCD Permit Number: BGT1 U/L or Qtr/Qtr I Section 9 Township 23N. Range 10W County: San Juan
Center of Proposed Design: Latitude 36.23956 Longitude 107.89488 NAD83
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L_x W_x D_
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC
Volume: 40 bbl Type of fluid: Produced Water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
✓ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _ + Leak detection
Liner type: Thicknessmil
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution, or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet
✓ Alternate. Please specify <u>4' = 3' Hog Wire + Top Rail</u>

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen □ Netting □ Other	,
✓ Monthly inspections (If netting or screening is not physically feasible)	
5. Signs: Subsection C of 19.15.17.11 NMAC ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.16.8 NMAC	
Signed in compnance with 19.13.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	∏₁Yes ☐ No ☐′NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	¹□ Yes□ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	_
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search? Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Form C-144
Released to Imaging: 2/9/2023 1:53:46 PM

Oil Conservation Division

(

Page 2 of 6

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Temporary Pit Non-low chloride drilling fluid			
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No		
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No		
Permanent Pit or Multi-Well Fluid Management Pit			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).			
- Topographic map; Visual inspection (certification) of the proposed site	Yes No		
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	☐ Yes ☐ No		
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No		
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
n. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	2000 1-8 10 10 10 10 10 10 10 10 10 10 10 10 10		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:			

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	1
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	,
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No ·
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	│ □ Yes □ No

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written appr Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Min 	,	
	oval obtained from the municipality	☐ Yes ☐ No
without committee of verification of map from the ravi in the	ing and Mineral Division	Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geol Society; Topographic map 	ogy & Mineral Resources; USGS; NM Geological	
Within a 100-year floodplain.		Yes No
- FEMA map	to a second seco	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements Construction/Design Plan of Burial Trench (if applicable) based upon the Construction/Design Plan of Temporary Pit (for in-place burial of a dryin Protocols and Procedures - based upon the appropriate requirements of 19 Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements Disposal Facility Name and Permit Number (for liquids, drilling fluids an Soil Cover Design - based upon the appropriate requirements of Subsection Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate Plan - based upon the appropriate Plan - based upon the appropriate Plan - bas	requirements of 19.15.17.10 NMAC of Subsection E of 19.15.17.13 NMAC appropriate requirements of Subsection K of 19.15.17.13 g pad) - based upon the appropriate requirements of 19. 1.15.17.13 NMAC requirements of 19.15.17.13 NMAC of 19.15.17.13 NMAC d drill cuttings or in case on-site closure standards cannot H of 19.15.17.13 NMAC on H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accu	rate and complete to the best of my knowledge and beli	ief.
Name (Print):	tle:	
Signature:	Date:	
	1	
e-mail address: Telephone:		
	Report	
18. Ţ	Report	/2023
18. OCD Approval: Permit Application (including closure plan) X Closure	Report Plan (only) OCD Conditions (see attachment)	/2023
18. OCD Approval: Permit Application (including closure plan) Closure OCD Representative Signature: Jaclyn Burdine	Report Plan (only)	the closure report.
OCD Approval: Permit Application (including closure plan) Closure OCD Representative Signature: Jaclyn Burdine Title: Environmental Specialist-A 19. Closure Report (required within 60 days of closure completion): 19.15.17.1. Instructions: Operators are required to obtain an approved closure plan prior The closure report is required to be submitted to the division within 60 days of	Report Plan (only)	the closure report.

Form C-144
Released to Imaging: 2/9/2023 1:53:46 PM

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure r belief. I also certify that the closure complies with all applicable closure requirem	
Name (Print): Kevin Smaka	Title: Regulatory Engineer
Signature: 18 Marka	Date: 2-9-23
e-mail address:_kevin.smaka@duganproduction.com	Telephone: 505-325-1821 x1049

Form C-144
Released to Imaging: 2/9/2023 1:53:46 PM

McDougal #2 BGT Closure Report

- 1. On 1/16/23 Soil samples were collected as part of BGT closure at the Grigsby Federal #3 well site.
- 2. During the sampling it was noted there were no signs of contamination nor odors in the soil.
- 3. A 5-point composite sample was collected from the soils directly beneath the BGT and taken to the lab. The lab analyzed the samples for TPH, BTEX and Chlorides. The samples were collected by JAKD Solutions. The base of the BGT was approximately 5' below grade surface.
- 4. Lab results indicate no contamination is present.
- 5. Dugan will seed this location in the coming spring. As part of reclamation efforts Dugan will follow all NMOCD guidelines relating to soil cover and topping to ensure the soil will be able to sustain vegetation once the site is permanently abandoned. Once successful reseeding has occurred Dugan will provide photos to the division.
- Since no groundwater data was submitted with the closure plan Dugan agreed to meet the most stringent standards for BGT closures. The lab results meet those standards.

As part of this report Dugan has included the following items:

- 1. A copy of the labs results
- 2. A table of the labs results that are grouped by sample ID. (Table 1)
- 3. A copy of the notice of sampling
- 4. Pictures of the BGT vault prior to backfilling

Table 1

				Chlorides	
Sample ID	TPH Result		BTEX Result	Result	
BGT Composite		0	0		0

Kevin Smaka

From: Kevin Smaka

Sent: Wednesday, January 11, 2023 4:07 PM

To: 'James McDaniel'; 'Burdine, Jaclyn, EMNRD'; 'Adeloye, Abiodun A'; 'Velez, Nelson,

EMNRD

Cc: Neil Haws; Carlos Ramos; Marty Foutz; Alvaro Alba

Subject: Notice Of Sampling

Everyone,

Dugan intends to collect soil samples this coming Monday, 1/16/23, starting at 10:00 AM from two well sites. The first location will be the Grigsby Federal #3. The second will be the McDougal #2. Sampling at the Grigsby is related to a historical spill found under the recently closed BGT.

Sampling at the McDougal #2 is related to a planned BGT Closure.

Here are the wells' information:

Grigsby Federal #3 30-045-21623 D-08-25N-10W 840 FNL 850 FWL

McDougal #2 30-045-28619 I-09-23N-10W 1980 FSL 790 FEL

Please contact me if you have any questions.

Kevin Smaka P.E. Regulatory Engineer Dugan Production Corp. 505-486-6207 **CLIENT: JAKD Solutions**

Analytical ReportLab Order **2301588**

Date Reported:

Hall Environmental Analysis Laboratory, Inc.

Client Sample ID: BGT Composite

 Project:
 Mc Dougall 2
 Collection Date: 1/16/2023 12:10:00 PM

 Lab ID:
 2301588-001
 Matrix: SOIL
 Received Date: 1/17/2023 7:10:00 AM

Analyses	Result	PQL Qua	al Units	DF	Date Analyzed
EPA METHOD 8015M/D: DIESEL RANGE OR	GANICS				Analyst: DGH
Diesel Range Organics (DRO)	ND	8.8	mg/Kg	1	1/20/2023 5:10:36 PM
Motor Oil Range Organics (MRO)	ND	44	mg/Kg	1	1/20/2023 5:10:36 PM
Surr: DNOP	103	69-147	%Rec	1	1/20/2023 5:10:36 PM
EPA METHOD 8015D: GASOLINE RANGE					Analyst: JJP
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	1/20/2023 1:01:20 PM
Surr: BFB	107	37.7-212	%Rec	1	1/20/2023 1:01:20 PM
EPA METHOD 8021B: VOLATILES					Analyst: JJP
Benzene	ND	0.023	mg/Kg	1	1/20/2023 1:01:20 PM
Toluene	ND	0.047	mg/Kg	1	1/20/2023 1:01:20 PM
Ethylbenzene	ND	0.047	mg/Kg	1	1/20/2023 1:01:20 PM
Xylenes, Total	ND	0.094	mg/Kg	1	1/20/2023 1:01:20 PM
Surr: 4-Bromofluorobenzene	99.4	70-130	%Rec	1	1/20/2023 1:01:20 PM
EPA METHOD 300.0: ANIONS					Analyst: NAI
Chloride	ND	60	mg/Kg	20	1/21/2023 11:46:26 AM

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of standard limits. If undiluted results may be estimated.
- B Analyte detected in the associated Method Blank
- E Above Quantitation Range/Estimated Value
 J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Limit
- orting Limit Page 1 of 0





District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 184596

CONDITIONS

Operator:	OGRID:	
DUGAN PRODUCTION CORP	6515	
PO Box 420	Action Number:	
Farmington, NM 87499	184596	
	Action Type:	
	[C-144] Below Grade Tank Plan (C-144B)	

CONDITIONS

Created By		Condition Date
jburdine	None	2/9/2023