

<b>Well Name:</b> SUN PEARL FED	<b>Well Location:</b> T19S / R34E / SEC 28 / SWNE /	<b>County or Parish/State:</b> LEA / NM
<b>Well Number:</b> 03	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM56263	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 3002530892	<b>Well Status:</b> Oil Well Shut In	<b>Operator:</b> CHEVRON USA INCORPORATED

### Notice of Intent

**Sundry ID:** 2711697

**Type of Submission:** Notice of Intent

**Type of Action:** Plug and Abandonment

**Date Sundry Submitted:** 01/19/2023

**Time Sundry Submitted:** 01:46

**Date proposed operation will begin:** 02/20/2023

**Procedure Description:**

### Surface Disturbance

**Is any additional surface disturbance proposed?:** No

### NOI Attachments

#### Procedure Description

Sun\_Pearl\_Fed\_3\_Proposed\_WBD\_20230119134558.pdf

Sun\_Pearl\_Fed\_3\_Current\_WBD\_20230119134540.pdf

Sun\_Pearl\_Fed\_3\_Procedure\_20230119134523.pdf

Accepted for record – NMOCD

JRH 3/24/23

Well Name: SUN PEARL FED

Well Location: T19S / R34E / SEC 28 / SWNE /

County or Parish/State: LEA / NM

Well Number: 03

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM56263

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002530892

Well Status: Oil Well Shut In

Operator: CHEVRON USA INCORPORATED

**Conditions of Approval****Specialist Review**

SUN\_PEARL\_FED\_03\_\_2711697\_\_COA\_AND\_PROCEDURE\_20230212141951.pdf

**Operator**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: MARK TORRES

Signed on: JAN 19, 2023 01:46 PM

Name: CHEVRON USA INCORPORATED

Title: Well Abandonment Engineer

Street Address: 6301 DEAUVILLE BLVD

City: MIDLAND

State: TX

Phone: (989) 264-2525

Email address: MARKTORRES@CHEVRON.COM

**Field**

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

**BLM Point of Contact**

BLM POC Name: KEITH P IMMATTY

BLM POC Title: ENGINEER

BLM POC Phone: 5759884722

BLM POC Email Address: KIMMATTY@BLM.GOV

Disposition: Approved

Disposition Date: 02/12/2023

Signature: KEITH IMMATTY

**Sun Pearl Fed #3****API:** 30-025-30892**Fresh Water Depth:** 200'**Potash Area:** No**Notes:**

- The subject well was shut-in 1/12/22, is on the NMOCD 9-month IAW list as of 10/1/22 and carries a 4/1/23 deadline. Last production test was 12/10/21: 4 bopd & 7 bwpd. Due to economics, a return to an active status cannot be justified (unable to progress work through WIO's without assuming business risk). Lease is held by Sun Pearl F 4 (30-025-31047). Therefore, abandonment is the preferred route for the Sun Pearl Fed 3.
- Reference [Onshore Operating Guidelines](#) and Business Partner SOPs for detailed guidance.
- Contact engineer for additional well history if needed.
- WSR to assess crew competency and utilize SWA and contact Superintendent with any concerns.

**Rig Work**

1. Prior to rig arrival, verify well prep and confirm if any special or welded flanges are present that will require further intervention.
2. Contact BLM at least 24 hours prior to performing any work.
3. MIRU pulling unit.
  - a. Intrinsically safe fans and H2S scavenger required due to unknown quantities of H2S in the field.
4. Verify pressures and kill well as per [Chevron Global Well Control Document](#).
  - a. Bubble test intermediate and surface casings for 30 minutes each and share results in WellView under daily pressure.
  - b. Attempt to pressure test tubing to utilize as work string.
5. Install hydraulic rod BOP and function test.
6. Pull and lay down rods.
  - a. If paraffin is encountered or rods are stuck contact engineer.
  - b. Stop work and contact Superintendent if stripping operations are required.
7. N/U BOPE using rubber coated hangers provided by Chevron, and pressure test, 250 psi low and MASP + 500 psi high (per Chevron operating guidelines) for 5 minutes each.
  - a. On a chart, no bleed off allotted.
  - b. Contact engineer if unable to unset TAC, do not shear TAC without the BOP N/U first to mitigate any risks of well control events.
8. TOH w/ production string. If TAC removed from wellbore, will serve as gauge ring run for CIBP.
  - a. Stop work and contact Superintendent if tubing is pulling wet.
9. If unable to pull TAC or alternatively want to leave TAC in place:
  - a. Plan to set CIP adjacent to TAC or set in profile plug per tubing tally
  - b. Jet cut tubing above CIP
10. MIRU wireline unit.
11. R/U 5K lubricator system w/ pack-off and pressure test t/ 1,000 psi f/ 10 min.
  - a. Consider grease injection if MASP + 500 psi is above 1,000 psi.
12. M/U and set CIBP in 5-1/2" prod csg at +/- 3,779' (100' above top perf).

13. RDMO wireline unit.
14. Fill well with fresh water and pressure test casing to 500 psi to confirm CIBP as barrier.
  - a. 5% bleed off allotted. **30mins**
  - b. Contact the engineer if pressure test fails, document test results.
  - c. Verify max test pressure does not exceed casing burst strength.
15. TIH w/ work string, tag CIBP
16. Attempt to break circulation, verify lifting pressures.
17. Spot 34 sx Class C Cement from 3,779' – 3,444' (Perfs, Yates).
  - a. Plug must be at or above 3,494'.
18. WOC
19. Tag TOC and pressure test casing to 1,500 psi for 15 minutes.
  - a. **Do not exceed burst pressure of casing.**
20. Spot MLF to appropriate depth to ensure it is spaced out between plugs.
  - a. Do not pump MLF past the first perforation because it will be pumped away during the P&S procedure. Also, if the casing failed a pressure test, do not spot MLF until it tests properly.
21. **3250' to 3118'. Base of Salt. 25sx. Tag and verify**
22. Spot **5** sx Class C Cement from 1,8**50**' – 1,300' (Salt top, Surface csg shoe). **Tag and verify**
23. Conduct bubble test for 30 minutes on all casing annuli.
  - a. If bubble test fails, contact engineer to discuss running a CBL to confirm cement quality behind pipe and/or adjusting forward plan for a perforate and squeeze contingency, cement plug or identify any opportunity to cut & pull casing, or R/D and monitor well.
  - b. Ultimate goal is to address failed test prior to fresh water depths
  - c. Confirm forward plan with engineer and request forward plan approval from BLM
24. If bubble test passes, proceed to isolate fresh water to surface.
  - a. Notify BLM of any proposed changes to cement volumes
25. Due to est. TOC of 200', perforate at 200', and attempt to establish circulation.
  - a. Spot Cement from 250' to surface circulating cement through annulus if circulation was established.
  - b. If unable to circulate through perforations, spot cement to surface from 250'.
26. Verify cement to surface.
27. RDMO

KEITH

IMMATTY

Digitally signed by  
KEITH IMMATTY  
Date: 2023.02.12  
14:19:23 -07'00'

FIELD: Pearl  
 LEASE/UNIT: Sun Pearl Federal  
 WELL NO.: 3  
 COUNTY: Lea ST: New Mexico  
 LOCATION: 2310 FNL & 1940 FEL, Section 28, Township 19S, Range 34E

API NO.: 30-025-30892  
 CHEVNO: IZ6692  
 PROD FORMATION: Queen  
 STATUS: SI Oil Well  
 Spud Date: 5/24/1990  
 TD Date: 6/5/1990  
 Comp Date: 6/20/1990  
 GL: 3708'  
 KB: 3718'  
 Base of Fresh Water: 200'

**CURRENT WELLBORE DIAGRAM**

Estimated TOC @ 200'

**SURFACE CSG**

Size: 8-5/8"  
 Hole Size: 12-1/4"  
 Weight: 24#  
 Grade: J-55  
 Depth: 1,372'  
 Cmt: 600 sx  
 Circ: Yes, 85 sx  
 TOC: Surface

**PRODUCTION CSG**

Size: 5-1/2"  
 Hole Size: 7-7/8"  
 Weight: 17#  
 Grade: J-55  
 Depth: 5,120'  
 Cmt: 1425 sx 50/50 Pozmix  
 Circ: No  
 TOC: 200' est.

FORMATION	TOP (MD)
Rustler	1,740'
Salt Top	1,800'
Salt Bottom	3,200'
Yates	3,594'
Seven Rivers	3,958'
Queen	4,504'
Penrose	4,784'
Grayburg	4,971'

**H2S Concentration >100 PPM? YES**  
**NORM Present in Area? NO**

5/24/90 Spud well.

6/20/90 Initial completion date. Perforate Penrose f/ 4787-4795', 4837-4844' and 4933-4939'. Stim 4787-95' and 4837-44': acidize w/ 1600 gals 15% HCl, frac w/ 35k gals XL gel & 73k lbs sand. Stim 4933-39': acid w/ 750 gals 15% HCl, frac w/ 15k XL gel & 34k lbs sand.

5/19/97 Perf Yates f/ 3879-84' and 3888-97'. Acidize w/ 1000 gals 10% NEFE acid. Frac w/ 400 bbls 30# gelled Borate System & 41k lbs 16/30 Brady sand. Run prod equip.

12/17/13 Pump repair. MIRU, load & test to 500# - good. Unset pump, POOH w/ rods & pmp. LD old pmp. PU new pmp & KBars, RIH w/ rods, space well, load & test to 500# - good. Check pmp action, RDMO.

Yates Perfs (5/1997):

3879-3884'

3888-3897'

2-3/8" tbg @ 4971'

w/ SN @ 4938'

53 jts 7/8" rods &amp; 130 jts 3/4" rods @ 4817'

w/ bottom of 20' rod pump @ 4837'

(see 'Tubulars' tab for details)

Penrose Perfs (6/1990):

4787-4795'

4837-4844'

4933-4939'

5070' PBTD

5170' TD

FIELD: Pearl  
 LEASE/UNIT: Sun Pearl Federal  
 WELL NO.: 3  
 COUNTY: Lea ST: New Mexico  
 LOCATION: 2310 FNL & 1940 FEL, Section 28, Township 19S, Range 34E

API NO.: 30-025-30892  
 CHEVNO: IZ6692  
 PROD FORMATION: Queen  
 STATUS: SI Oil Well  
 Spud Date: 5/24/1990  
 TD Date: 6/5/1990  
 Comp Date: 6/20/1990  
 GL: 3708'  
 KB: 3718'  
 Base of Fresh Water: 200'

**PROPOSED WELLBORE DIAGRAM**

Estimated TOC @ 200'

**Isolate Fresh Water**

Perf @ 200', attempt to establish injection/circ  
 Spot cement to surf w/ +/- 52 sx Class C

**SURFACE CSG**

Size: 8-5/8"  
 Hole Size: 12-1/4"  
 Weight: 24#  
 Grade: J-55  
 Depth: 1,372'  
 Cmt: 600 sx  
 Circ: Yes, 85 sx  
 TOC: Surface

**H2S Concentration >100 PPM? YES**  
**NORM Present in Area? NO**

**Isolate Salt Top/Surface Shoe**

Spot ~~50~~ sx Class C f/ 1,800' - 1,300'  
 Min: ~~1,322~~ **1850' to 1300'. 55sx. Tag and verify**

**PRODUCTION CSG**

Size: 5-1/2"  
 Hole Size: 7-7/8"  
 Weight: 17#  
 Grade: J-55  
 Depth: 5,120'  
 Cmt: 1425 sx 50/50 Pozmix  
 Circ: No  
 TOC: 200' est.

**3250' to 3118'. Base of Salt. 25sx. Tag and verify****Isolate Perfs/Yates**

Set CIBP at +/- 3,779' (within 100' of perfs) **Leak test 500psi, 30mins**  
 Spot 34 sx Class C f/ 3,779' - 3,444'  
 Min: 3,494'

FORMATION	TOP (MD)
Rustler	1,740'
Salt Top	1,800'
Salt Bottom	3,200'
Yates	3,594'
Seven Rivers	3,958'
Queen	4,504'
Penrose	4,784'
Grayburg	4,971'

Yates Perfs (5/1997):  
 3879-3884'  
 3888-3897'

Penrose Perfs (6/1990):  
 4787-4795'  
 4837-4844'  
 4933-4939'

5070' PBTD  
 5170' TD

Sundry ID 2711697

Plug Type	Top	Bottom	Length	Tag	Sacks	Notes
Surface Plug	0.00	200.00	200.00	Verify circulated to surface	52.00	Perf and sqz
Shoe Plug	1308.28	1422.00	113.72	WOC and Tag	55.00	Same as below
Top of Salt @ 1800	1732.00	1850.00	118.00	WOC and Tag	55.00	
Base of Salt @ 3200	3118.00	3250.00	132.00	WOC and Tag	25.00	
Yates @ 3594	3508.06	3644.00	135.94		34.00	Same as below
CIBP Plug	3744.00	3779.00	35.00	Verify CIBP depth	34.00	Leak test 500psi, 30mins

**No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole.**

**Class H >7500'**

**Class C <7500'**

**Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.**

**Critical, High Cave Karst: Cave Karst depth to surface**

**R111P: Solid plug in all annuli - 50' from bottom of salt to surface.**

**Class C: 1.32 ft<sup>3</sup>/sx**

**Class H: 1.06 ft<sup>3</sup>/sx**

**Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.**

<b>Cave Karst/Potash Cement</b>	<b>Low</b>	500.00
---------------------------------	------------	--------

Shoe @ 1372.00

Shoe @ 5120.00

Perforatons Top @	3879.00	Perforations	4939.00
-------------------	---------	--------------	---------

CIBP @	3779.00
--------	---------

**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval (LPC Habitat)**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.** Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

**Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:**

From March 1<sup>st</sup> through June 15<sup>th</sup> annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm



In Reply Refer To: 1310

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo “interim” reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo “final” reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines **(Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure)**. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. **This will apply to well pads, facilities, and access roads.** Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

- have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
  6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
  7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech/Environmental Protection Specialist  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Jose Martinez-Colon  
Environmental Protection Specialist  
575-234-5951

Mark Mattozzi  
Environmental Protection Specialist  
575-234-5713

Robert Duenas  
Environmental Protection Specialist  
575-234-2229

Trishia Bad Bear, Hobbs Field Station  
Natural Resource Specialist  
575-393-3612



**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

COMMENTS  
  
Action 186031

COMMENTS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 186031
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
john.harrison	Accepted for record - NMOCD JRH 3/24/23 BLM approved P&A 2/12/23	3/24/2023

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS  
  
Action 186031

CONDITIONS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 186031
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
john.harrison	None	3/24/2023