<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 337727

APPLICATION FOR PERMIT TO DRILL, I	RE-ENTER, DEEPEN	, PLUGBACK,	OR ADD A ZONE
------------------------------------	------------------	-------------	---------------

74 1 E107	A HOIL OIL EIGHT TO DIGEL, ILE LIVER, DELI LIV, I LOODAGI, OILADD	ALONE
1. Operator Name and Address		2. OGRID Number
MEWBOURNE OIL CO		14744
P.O. Box 5270		3. API Number
Hobbs, NM 88241		30-025-51337
4. Property Code	5. Property Name	6. Well No.
333923	BELGIAN BLUE 28 21 STATE COM	501H

7 Surface Location

ſ	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	N	28	18S	35E	N	205	S	1880	W	Lea

8. Proposed Bottom Hole Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	21	18S	35E	D	100	N	500	W	Lea

9. Pool Information

AIRSTRIP;BONE SPRING	960

Additional Well Information

11. Work Type	12. Well Type	13. Cable/Rotary	14. Lease Type	15. Ground Level Elevation
New Well	OIL		State	3911
16. Multiple	17. Proposed Depth	18. Formation	19. Contractor	20. Spud Date
N	20031	2nd Bone Spring Sand		4/6/2023
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☑ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

			Zi. Fioposeu casing a	and Cement Frogram		
Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.75	48	1496	0	0
Surf	17.5	13.375	54	1900	1320	0
Int1	12.25	9.62	36	3385	685	0
Prod	8.75	7	26	9144	730	3185
Liner1	6.125	4.5	13.5	20031	710	8944

Casing/Cement Program: Additional Comments

MOC proposed to drill & test the Bone Springs formation. H2S rule 118 does not apply because MOC has researched the area & no high concentrations were found. Will have on location & working all H2S safety equiptment before Yates formation for safety & insurance purposes. Will stimulate as needed for production.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	5000	2500	Schaffer
Double Ram	5000	5000	Shcaffer
Annular	5000	2500	Schaffer

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC ☑ and/or 19.15.14.9 (B) NMAC ☑, if applicable. Signature:				OIL CONSERVATIO	ON DIVISION
			Approved By:	Paul F Kautz	
Title:	Vice President Operations			Geologist	
Email Address: fking@mewbourne.com			Approved Date:	4/18/2023	Expiration Date: 4/18/2025
Date:	4/11/2023	Conditions of Appr	oval Attached		

District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720 District III 1000 Rio Brazos Road, Aztec, NM 87410 Phone: (505) 334-6178 Fax: (505) 334-6170 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3460 Fax: (505) 476-3462 State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505


Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT AIRSTRIP;BONE

30-025	API Number -51337	r		² Pool Code	960					
⁴ Property Co 333923	ode	BELG				roperty Name E 28/21 STATE COM			⁶ Well Number 501H	
70GRID 1474		*Operator Name MEWBOURNE OIL COMPANY 9 Elevation 3911'								
					10 Surface	Location				
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet From the	East/Wes	st line County	7
N	28	18S	35E		205	SOUTH	1880	WES	T LEA	
	,		11]	Bottom F	Iole Locatio	n If Different Fr	om Surface		·	
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/Wes	st line County	,
D	21	18S	35E		100	NORTH	500	WES	T LEA	
12 Dedicated Acre	s 13 Joint	or Infill 14	Consolidation	Code 15 (Order No.					
320										

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.



<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Form APD Conditions

Permit 337727

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
MEWBOURNE OIL CO [14744]	30-025-51337
P.O. Box 5270	Well:
Hobbs, NM 88241	BELGIAN BLUE 28 21 STATE COM #501H

OCD Reviewer	Condition
pkautz	Notify OCD 24 hours prior to casing & cement
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud

		_	Belgian Blue 28	21 State Com 501	lH			
			SHL: 205' FSL &	1880' FWL (Sec	28)			
			BHL: 100' FNL &	& 500' FWL (Sec	21)			
Casing Type	Fluid Type	Hole Size	Casing Descripion	Casing Weight	Top MD	Setting Depth	Sacks Cement	Top of Lead/Top of Tail
Surface	Fresh Water	17.5"	13.375" 48# H40 STC	48.0 lb/ft	0'	1496'		
Surface	Fresh Water	17.5"	13.375" 54.5# J55 STC	54.5 lb/ft	1496'	1900'	1320	0'/1708'
Intermediate	Brine	12.25"	9.625" 36# J55 LTC	36.0 lb/ft	0'	3385'	685	0'/2691'
Production	Cut-Brine	8.75"	7" 26# P110 LTC	26.0 lb/ft	0'	9144'	730	3185'/6744'
Liner	OBM	6.125"	4.5" 13.5# P110 LTC	13.5 lb/ft	8944'	20031'	710	8944'

Mewbourne Oil Company

Lea County, New Mexico NAD 83 Belgian Blue 28/21 State Com #501H

Sec 28, T18S, R35E

SHL: 205' FSL & 1880' FWL (Sec 28) BHL: 100' FNL & 500' FWL (Sec 21)

Plan: Design #1

Standard Planning Report

05 April, 2023

Hobbs Database:

Company:

Mewbourne Oil Company Lea County, New Mexico NAD 83

Project: Site: Belgian Blue 28/21 State Com #501H

Well: Sec 28, T18S, R35E

Wellbore: Design:

BHL: 100' FNL & 500' FWL (Sec 21) Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Site Belgian Blue 28/21 State Com #501H WELL @ 3939.0usft (Original Well Elev) WELL @ 3939.0usft (Original Well Elev)

Minimum Curvature

Project Lea County, New Mexico NAD 83

Map System: Geo Datum:

Map Zone:

US State Plane 1983 North American Datum 1983 New Mexico Eastern Zone

System Datum:

Mean Sea Level

Belgian Blue 28/21 State Com #501H Site

Site Position: From: Мар Northing: Easting:

623,831.50 usft Latitude: 808,447.50 usft

Longitude:

32.7119463 -103.4648914

Position Uncertainty: 0.0 usft Slot Radius: 13-3/16 "

Well Sec 28, T18S, R35E

Well Position +N/-S +E/-W

0.0 usft 0.0 usft 0.0 usft

Northing: Easting:

623,831.50 usft 808,447.50 usft Latitude: Longitude:

32.7119463 -103.4648914

Position Uncertainty Grid Convergence:

0.47°

Wellhead Elevation:

3,939.0 usft

Ground Level:

3,911.0 usft

BHL: 100' FNL & 500' FWL (Sec 21) Wellbore

Declination Magnetics **Model Name** Sample Date Dip Angle Field Strength (°) (°) (nT) 48,562.23059214 IGRF2010 12/31/2014 7.13 60.56

Design #1 Design

Audit Notes:

Version:

Phase: Vertical Section: Depth From (TVD) PROTOTYPE +N/-S

(usft)

0.0

Tie On Depth: +E/-W

(usft)

0.0

0.0

Direction (°) 351.79

Plan Survey Tool Program

Date 4/5/2023

Depth From Depth To (usft)

(usft)

Survey (Wellbore)

(usft)

0.0

Tool Name

Remarks

20,030.9 0.0 Design #1 (BHL: 100' FNL & 500'

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,950.0	0.00	0.00	1,950.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,553.6	12.07	261.70	2,549.2	-9.1	-62.7	2.00	2.00	0.00	261.70	
8,605.1	12.07	261.70	8,466.8	-191.9	-1,315.1	0.00	0.00	0.00	0.00	
9,208.7	0.00	0.00	9,066.0	-201.0	-1,377.8	2.00	-2.00	0.00	180.00	KOP: 10' FSL & 500' I
10,157.8	94.59	359.44	9,639.0	419.8	-1,383.9	9.97	9.97	0.00	-0.56	
20,030.9	94.59	359.44	8,849.0	10,260.8	-1,479.9	0.00	0.00	0.00	0.00	BHL: 100' FNL & 500'

Database: Hobbs

Company: Mewbourne Oil Company
Project: Lea County, New Mexico NAD 83
Site: Belgian Blue 28/21 State Com #501H

Well: Sec 28, T18S, R35E

Wellbore: BHL: 100' FNL & 500' FWL (Sec 21)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Site Belgian Blue 28/21 State Com #501H WELL @ 3939.0usft (Original Well Elev) WELL @ 3939.0usft (Original Well Elev)

Grid

ed Survey									
Measured			Vertical			Vertical	Dogleg	Build	Turn
Depth (usft)	Inclination (°)	Azimuth (°)	Depth (usft)	+N/-S (usft)	+E/-W (usft)	Section (usft)	Rate (°/100usft)	Rate (°/100usft)	Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
SHL: 205'	FSL & 1880' FWL	(Sec 28)							
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,950.0	0.00	0.00	1,950.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	1.00	261.70	2,000.0	-0.1	-0.4	0.0	2.00	2.00	0.00
2,100.0	3.00	261.70	2,099.9	-0.6	-3.9	0.0	2.00	2.00	0.00
2,200.0	5.00	261.70	2,199.7	-1.6	-10.8	0.0	2.00	2.00	0.00
2,300.0	7.00	261.70	2,299.1	-3.1	-21.1	0.0	2.00	2.00	0.00
2,400.0	9.00	261.70	2,398.2	-5.1	-34.9	-0.1	2.00	2.00	0.00
2,500.0	11.00	261.70	2,496.6	-7.6	-52.1	-0.1	2.00	2.00	0.00
2,553.6	12.07	261.70	2,549.2	-9.1	-62.7	-0.1	2.00	2.00	0.00
2,600.0	12.07	261.70	2,594.5	-10.5	-72.3	-0.1	0.00	0.00	0.00
2,700.0	12.07	261.70	2,692.3	-13.6	-93.0	-0.2	0.00	0.00	0.00
2,800.0	12.07	261.70	2,790.1	-16.6	-113.7	-0.2	0.00	0.00	0.00
2,900.0	12.07	261.70	2,887.9	-19.6	-134.4	-0.2	0.00	0.00	0.00
3,000.0		261.70	2,985.7	-22.6	-155.1	-0.3	0.00	0.00	0.00
3,100.0	12.07	261.70	3,083.5	-25.6	-175.8	-0.3	0.00	0.00	0.00
3,200.0	12.07	261.70	3,181.2	-28.7	-196.5	-0.3	0.00	0.00	0.00
3,300.0		261.70	3,279.0	-31.7	-217.2	-0.4	0.00	0.00	0.00
3,400.0		261.70	3,376.8	-34.7	-237.9	-0.4	0.00	0.00	0.00
3,500.0		261.70	3,474.6	-37.7	-258.6	-0.4	0.00	0.00	0.00
3,600.0		261.70	3,572.4	-40.7	-279.2	-0.5	0.00	0.00	0.00
3,700.0	12.07	261.70	3,670.2	-43.8	-299.9	-0.5	0.00	0.00	0.00
3,800.0		261.70	3,768.0	-46.8	-320.6	-0.5	0.00	0.00	0.00
3,900.0		261.70	3,865.8	-49.8	-341.3	-0.6	0.00	0.00	0.00
4,000.0		261.70	3,963.6	-52.8	-362.0	-0.6	0.00	0.00	0.00
4,100.0		261.70	4,061.3	-55.8	-382.7	-0.6	0.00	0.00	0.00
4,200.0) 12.07	261.70	4,159.1	-58.9	-403.4	-0.7	0.00	0.00	0.00
4,300.0		261.70	4,256.9	-61.9	-424.1	-0.7	0.00	0.00	0.00
4,400.0		261.70	4,354.7	-64.9	-444.8	-0.7	0.00	0.00	0.00
4,500.0		261.70	4,452.5	-67.9	-465.5	-0.8	0.00	0.00	0.00
4,600.0		261.70	4,550.3	-70.9	-486.2	-0.8	0.00	0.00	0.00
4,700.0	12.07	261.70	4,648.1	-74.0	-506.9	-0.8	0.00	0.00	0.00
4,800.0		261.70	4,745.9	-77.0	-527.6	-0.9	0.00	0.00	0.00
4,900.0		261.70	4,843.7	-80.0	-548.3	-0.9	0.00	0.00	0.00
5,000.0	12.07	261.70	4,941.4	-83.0	-569.0	-0.9	0.00	0.00	0.00

Database: Hobbs

Company: Mewbourne Oil Company
Project: Lea County, New Mexico NAD 83
Site: Belgian Blue 28/21 State Com #501H

Well: Sec 28, T18S, R35E

Wellbore: BHL: 100' FNL & 500' FWL (Sec 21)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Site Belgian Blue 28/21 State Com #501H WELL @ 3939.0usft (Original Well Elev) WELL @ 3939.0usft (Original Well Elev)

Grid

Planne	d Survey									
	Measured			Vertical			Vertical	Dogleg	Build	Turn
	Depth	Inclination	Azimuth	Depth	+N/-S	+E/-W	Section (upft)	Rate (°/100usft)	Rate	Rate
	(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(*/100usit)	(°/100usft)	(°/100usft)
	5,100.0	12.07	261.70	5,039.2	-86.0	-589.7	-1.0	0.00	0.00	0.00
	5,200.0	12.07	261.70	5,137.0	-89.1	-610.4	-1.0	0.00	0.00	0.00
	5,300.0	12.07	261.70	5,234.8	-92.1	-631.1	-1.0	0.00	0.00	0.00
	5,400.0	12.07	261.70	5,332.6	-95.1	-651.8	-1.1	0.00	0.00	0.00
	5,500.0	12.07	261.70	5,430.4	-98.1	-672.5	-1.1	0.00	0.00	0.00
	5,600.0 5,700.0	12.07 12.07	261.70 261.70	5,528.2 5,626.0	-101.1 -104.1	-693.2 -713.9	-1.1 -1.2	0.00 0.00	0.00 0.00	0.00 0.00
	5,800.0	12.07	261.70	5,723.7	-107.2	-734.6	-1.2	0.00	0.00	0.00
	5,900.0 6,000.0	12.07 12.07	261.70 261.70	5,821.5 5,919.3	-110.2 -113.2	-755.3 -775.9	-1.2 -1.3	0.00 0.00	0.00 0.00	0.00 0.00
	6,100.0	12.07	261.70	6,017.1	-116.2	-775.9	-1.3 -1.3	0.00	0.00	0.00
	6,200.0	12.07	261.70	6,114.9	-119.2	-817.3	-1.3	0.00	0.00	0.00
	6,300.0 6,400.0	12.07 12.07	261.70 261.70	6,212.7 6,310.5	-122.3 -125.3	-838.0 -858.7	-1.4 -1.4	0.00 0.00	0.00 0.00	0.00 0.00
	6,500.0	12.07	261.70	6,408.3	-123.3 -128.3	-879.4	-1.4 -1.4	0.00	0.00	0.00
	6,600.0	12.07	261.70	6,506.1	-131.3	-900.1	-1.5	0.00	0.00	0.00
	6,700.0	12.07	261.70	6,603.8	-134.3	-920.8	-1.5	0.00	0.00	0.00
	6,800.0	12.07	261.70	6,701.6	-137.4	-941.5	-1.6	0.00	0.00	0.00
	6,900.0	12.07	261.70	6,799.4	-140.4	-962.2	-1.6	0.00	0.00	0.00
	7,000.0	12.07	261.70	6,897.2	-143.4	-982.9	-1.6	0.00	0.00	0.00
	7,100.0	12.07	261.70	6,995.0	-146.4	-1,003.6	-1.7	0.00	0.00	0.00
	7,200.0	12.07	261.70	7,092.8	-149.4	-1,024.3	-1.7	0.00	0.00	0.00
	7,300.0	12.07	261.70	7,190.6	-152.5	-1,045.0	-1.7	0.00	0.00	0.00
	7,400.0	12.07	261.70	7,288.4	-155.5	-1,065.7	-1.8	0.00	0.00	0.00
	7,500.0	12.07	261.70	7,386.1	-158.5	-1,086.4	-1.8	0.00	0.00	0.00
	7,600.0	12.07	261.70	7,483.9	-161.5	-1,107.1	-1.8	0.00	0.00	0.00
	7,700.0	12.07	261.70	7,581.7	-164.5	-1,127.8	-1.9	0.00	0.00	0.00
	7,800.0	12.07	261.70	7,679.5	-167.6	-1,148.5	-1.9	0.00	0.00	0.00
	7,900.0	12.07	261.70	7,777.3	-170.6	-1,169.2	-1.9	0.00	0.00	0.00
	8,000.0	12.07	261.70	7,875.1	-173.6	-1,189.9	-2.0	0.00	0.00	0.00
	8,100.0	12.07	261.70	7,972.9	-176.6	-1,210.6	-2.0	0.00	0.00	0.00
	8,200.0	12.07	261.70	8,070.7	-179.6	-1,231.3	-2.0	0.00	0.00	0.00
	8,300.0	12.07	261.70	8,168.5	-182.7	-1,251.9	-2.1	0.00	0.00	0.00
	8,400.0	12.07	261.70	8,266.2	-185.7	-1,272.6	-2.1	0.00	0.00	0.00
	8,500.0	12.07	261.70	8,364.0	-188.7	-1,293.3	-2.1	0.00	0.00	0.00
	8,605.1	12.07	261.70	8,466.8	-191.9	-1,315.1	-2.2	0.00	0.00	0.00
	8,700.0	10.17	261.70	8,559.9	-194.5	-1,333.2	-2.2	2.00	-2.00	0.00
	8,800.0	8.17	261.70	8,658.6	-196.8	-1,349.0	-2.2	2.00	-2.00	0.00
	8,900.0	6.17	261.70	8,757.8	-198.6	-1,361.3	-2.2	2.00	-2.00	0.00
	9,000.0	4.17	261.70	8,857.4	-199.9	-1,370.3	-2.3	2.00	-2.00	0.00
	9,100.0 9,208.7	2.17 0.00	261.70 0.00	8,957.3 9,066.0	-200.7 -201.0	-1,375.7 -1,377.8	-2.3 -2.3	2.00 2.00	-2.00 -2.00	0.00 0.00
		0.00 - & 500' FWL (Se		3,000.0	-201.0	-1,311.0	-2.3	2.00	-2.00	0.00
				.						
	9,250.0	4.11	359.44	9,107.2	-199.5	-1,377.8	-0.8	9.97	9.97	0.00
	9,300.0 9,350.0	9.10 14.08	359.44 359.44	9,156.9 9,205.8	-193.8 -183.7	-1,377.9 -1,378.0	4.9 14.8	9.97 9.97	9.97 9.97	0.00 0.00
	9,400.0	19.06	359.44 359.44	9,205.6	-163. <i>1</i> -169.5	-1,376.0 -1,378.1	29.0	9.97	9.97 9.97	0.00
	9,450.0	24.05	359.44	9,300.2	-151.1	-1,378.3	47.2	9.97	9.97	0.00
	9,500.0 9,534.8	29.03 32.50	359.44 359.44	9,344.9 9,374.8	-128.8 -111.0	-1,378.5 -1,378.7	69.3 86.9	9.97 9.97	9.97 9.97	0.00 0.00
				9,374.0	-111.0	-1,3/0./	00.9	9.97	9.97	0.00
	9,550.0	L & 500' FWL (S 34.01	ec 28) 359.44	9,387.6	-102.7	-1,378.8	95.2	9.97	9.97	0.00
	9,600.0	39.00	359.44	9,427.7	-102.7 -72.9	-1,376.6	124.7	9.97	9.97	0.00
L	9,650.0	43.98	359.44	9,465.2	-39.8	-1,379.4	157.5	9.97	9.97	0.00

Database: Hobbs

Company: Mewbourne Oil Company
Project: Lea County, New Mexico NAD 83

Site: Belgian Blue 28/21 State Com #501H

Well: Sec 28, T18S, R35E

Wellbore: BHL: 100' FNL & 500' FWL (Sec 21)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

Survey Calculation Method:

Site Belgian Blue 28/21 State Com #501H WELL @ 3939.0usft (Original Well Elev) WELL @ 3939.0usft (Original Well Elev)

Grid

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
9,700.0	48.96	359.44	9,499.6	-3.6	-1,379.7	193.4	9.97	9.97	0.00
9,750.0	53.95	359.44	9,530.7	35.5	-1,380.1	232.2	9.97	9.97	0.00
9,800.0	58.93	359.44	9,558.4	77.2	-1,380.5	273.4	9.97	9.97	0.00
9,850.0	63.91	359.44	9,582.3	121.1	-1,380.9	316.9	9.97	9.97	0.00
9,900.0	68.90	359.44	9,602.3	166.9	-1,381.4	362.3	9.97	9.97	0.00
9,950.0	73.88	359.44	9,618.2	214.2	-1,381.8	409.3	9.97	9.97	0.00
10,000.0	78.87	359.44	9,630.0	262.8	-1,382.3	457.4	9.97	9.97	0.00
10,050.0	83.85	359.44	9,637.5	312.2	-1,382.8	506.4	9.97	9.97	0.00
10,100.0	88.83	359.44	9,640.7	362.1	-1,383.3	555.9	9.97	9.97	0.00
10,109.9	89.82	359.44	9,640.8	372.0	-1,383.4	565.6	9.97	9.97	0.00
LP: 583' FSL	& 500' FWL (Se	c 28)							
	•	,	0.000.0	440.4	1 202 0	COF 4	0.07	0.07	0.00
10,150.0	93.82	359.44	9,639.6	412.1 419.8	-1,383.8	605.4 613.0	9.97 9.97	9.97	0.00 0.00
10,157.8 10,200.0	94.59 94.59	359.44 359.44	9,639.0 9,635.6	419.8 461.9	-1,383.9 -1,384.3	654.8	9.97 0.00	9.97 0.00	0.00
10,200.0	94.59	359.44 359.44	9,635.6	561.6	-1,364.3 -1,385.2	753.6	0.00	0.00	0.00
10,400.0	94.59	359.44	9,619.6	661.3	-1,386.2	852.4	0.00	0.00	0.00
10,500.0	94.59	359.44	9,611.6	760.9	-1,387.2	951.2	0.00	0.00	0.00
10,600.0	94.59	359.44	9,603.6	860.6	-1,388.2	1,050.0	0.00	0.00	0.00
10,700.0	94.59	359.44	9,595.6	960.3	-1,389.1	1,148.7	0.00	0.00	0.00
10,800.0	94.59	359.44	9,587.6	1,060.0	-1,390.1	1,247.5	0.00	0.00	0.00
10,900.0	94.59	359.44	9,579.6	1,159.6	-1,391.1	1,346.3	0.00	0.00	0.00
11,000.0	94.59	359.44	9,571.6	1,259.3	-1,392.0	1,445.1	0.00	0.00	0.00
11,100.0	94.59	359.44	9,563.6	1,359.0	-1,393.0	1,543.9	0.00	0.00	0.00
11,200.0	94.59	359.44	9,555.6	1,458.7	-1,394.0	1,642.7	0.00	0.00	0.00
11,300.0	94.59	359.44	9,547.6	1,558.3	-1,395.0	1,741.5	0.00	0.00	0.00
11,400.0	94.59	359.44	9,539.6	1,658.0	-1,395.9	1,840.3	0.00	0.00	0.00
11,500.0	94.59	359.44	9,531.6	1,757.7	-1,396.9	1,939.1	0.00	0.00	0.00
11,600.0	94.59	359.44	9,523.6	1,857.4	-1,397.9	2,037.9	0.00	0.00	0.00
11,700.0	94.59	359.44	9,515.6	1,957.0	-1,398.9	2,136.7	0.00	0.00	0.00
11,800.0	94.59	359.44	9,507.6	2,056.7	-1,399.8	2,235.5	0.00	0.00	0.00
11,900.0	94.59	359.44	9,499.6	2,156.4	-1,400.8	2,334.3	0.00	0.00	0.00
12,000.0	94.59	359.44	9,491.6	2,256.0	-1,401.8	2,433.0	0.00	0.00	0.00
12,100.0	94.59	359.44	9,483.6	2,355.7	-1,402.7	2,531.8	0.00	0.00	0.00
12,200.0	94.59	359.44	9,475.6	2,455.4	-1,403.7	2,630.6	0.00	0.00	0.00
12,300.0	94.59	359.44	9,467.6	2,555.1	-1,404.7	2,729.4	0.00	0.00	0.00
12,400.0	94.59	359.44	9,459.6	2,654.7	-1,405.7	2,828.2	0.00	0.00	0.00
12,500.0	94.59	359.44	9,451.6	2,754.4	-1,406.6	2,927.0	0.00	0.00	0.00
12,600.0	94.59	359.44	9,443.6	2,854.1	-1,407.6	3,025.8	0.00	0.00	0.00
12,700.0	94.59	359.44	9,435.6	2,953.8	-1,408.6	3,124.6	0.00	0.00	0.00
12,800.0	94.59	359.44	9,427.6	3,053.4	-1,409.6	3,223.4	0.00	0.00	0.00
12,900.0	94.59	359.44	9,419.6	3,153.1	-1,410.5	3,322.2	0.00	0.00	0.00
13,000.0	94.59	359.44	9,411.6	3,252.8	-1,411.5	3,421.0	0.00	0.00	0.00
13,100.0	94.59	359.44	9,403.6	3,352.5	-1,412.5	3,519.8	0.00	0.00	0.00
13,200.0	94.59	359.44	9,395.6	3,452.1	-1,413.4	3,618.6	0.00	0.00	0.00
13,300.0	94.59	359.44	9,387.6	3,551.8	-1,414.4	3,717.4	0.00	0.00	0.00
13,400.0	94.59	359.44	9,379.6	3,651.5	-1,415.4	3,816.1	0.00	0.00	0.00
13,500.0	94.59	359.44	9,371.6	3,751.2	-1,416.4	3,914.9	0.00	0.00	0.00
13,600.0	94.59	359.44	9,363.6	3,850.8	-1,417.3	4,013.7	0.00	0.00	0.00
13,700.0	94.59	359.44	9,355.6	3,950.5	-1,418.3	4,112.5	0.00	0.00	0.00
13,800.0	94.59	359.44	9,347.6	4,050.2	-1,419.3	4,211.3	0.00	0.00	0.00
13,900.0	94.59	359.44	9,339.6	4,149.9	-1,420.3	4,310.1	0.00	0.00	0.00
ŕ									
14,000.0 14,100.0	94.59 94.59	359.44 359.44	9,331.6 9,323.6	4,249.5 4,349.2	-1,421.2 -1,422.2	4,408.9 4,507.7	0.00 0.00	0.00 0.00	0.00 0.00

Database: Hobbs

Company: Mewbourne Oil Company
Project: Lea County, New Mexico NAD 83
Site: Belgian Blue 28/21 State Com #501H

Well: Sec 28, T18S, R35E

Wellbore: BHL: 100' FNL & 500' FWL (Sec 21)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Site Belgian Blue 28/21 State Com #501H WELL @ 3939.0usft (Original Well Elev) WELL @ 3939.0usft (Original Well Elev)

Grid

Planned Survey									
Measured			Vertical			Vertical	Doglas	Build	Turn
Depth	Inclination	Azimuth	Depth	+N/-S	+E/-W	Section	Dogleg Rate	Rate	Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
14,200.0	94.59	359.44	9,315.6	4,448.9	-1,423.2	4,606.5	0.00	0.00	0.00
14,300.0	94.59	359.44	9,307.6	4,548.6	-1,424.1	4,705.3	0.00	0.00	0.00
14,400.0	94.59	359.44	9,299.6	4,648.2	-1,425.1	4,804.1	0.00	0.00	0.00
14,500.0	94.59	359.44	9,291.6	4,747.9	-1,426.1	4,902.9	0.00	0.00	0.00
14,600.0	94.59	359.44	9,283.6	4,847.6	-1,427.1	5,001.7	0.00	0.00	0.00
14,700.0	94.59	359.44	9,275.6	4,947.3	-1,428.0	5,100.5	0.00	0.00	0.00
14,800.0	94.59	359.44	9,267.5	5,046.9	-1,429.0	5,199.2	0.00	0.00	0.00
14,900.0	94.59	359.44	9,259.5	5,146.6	-1,430.0	5,298.0	0.00	0.00	0.00
15,000.0	94.59	359.44	9,251.5	5,246.3	-1,431.0	5,396.8	0.00	0.00	0.00
15,100.0	94.59	359.44	9,243.5	5,346.0	-1,431.9	5,495.6	0.00	0.00	0.00
15,200.0	94.59	359.44	9,235.5	5,445.6	-1,432.9	5,594.4	0.00	0.00	0.00
15,300.0	94.59	359.44	9,227.5	5,545.3	-1,433.9	5,693.2	0.00	0.00	0.00
15,400.0	94.59	359.44	9,219.5	5,645.0	-1,434.8	5,792.0	0.00	0.00	0.00
15,500.0	94.59	359.44	9,211.5	5,744.7	-1,435.8	5,890.8	0.00	0.00	0.00
15,600.0	94.59	359.44	9,203.5	5,844.3	-1,436.8	5,989.6	0.00	0.00	0.00
15,700.0	94.59	359.44	9,195.5	5,944.0	-1,437.8	6,088.4	0.00	0.00	0.00
15,800.0 15,900.0	94.59 94.59	359.44 359.44	9,187.5 9,179.5	6,043.7 6,143.4	-1,438.7 -1,439.7	6,187.2 6,286.0	0.00 0.00	0.00 0.00	0.00 0.00
16,000.0	94.59	359.44	9,171.5	6,243.0	-1,440.7	6,384.8	0.00	0.00	0.00
16,100.0	94.59	359.44	9,163.5	6,342.7	-1,441.7	6,483.5	0.00	0.00	0.00
16,200.0 16,300.0	94.59 94.59	359.44 359.44	9,155.5 9,147.5	6,442.4 6,542.1	-1,442.6 -1,443.6	6,582.3 6,681.1	0.00 0.00	0.00 0.00	0.00 0.00
16,400.0	94.59	359.44	9,139.5	6,641.7	-1,443.6 -1,444.6	6,779.9	0.00	0.00	0.00
16,500.0	94.59	359.44	9,131.5	6,741.4	-1,445.6	6,878.7	0.00	0.00	0.00
16,600.0 16,700.0	94.59 94.59	359.44 359.44	9,123.5 9,115.5	6,841.1 6,940.8	-1,446.5 -1,447.5	6,977.5 7,076.3	0.00 0.00	0.00 0.00	0.00 0.00
16,800.0	94.59	359.44	9,113.5	7,040.4	-1,447.5	7,076.3	0.00	0.00	0.00
16,900.0	94.59	359.44	9,099.5	7,140.1	-1,449.4	7,273.9	0.00	0.00	0.00
17,000.0	94.59	359.44	9,091.5	7,239.8	-1,450.4	7,372.7	0.00	0.00	0.00
17,000.0	94.59	359.44	9,083.5	7,339.5	-1,450.4	7,471.5	0.00	0.00	0.00
17,200.0	94.59	359.44	9,075.5	7,439.1	-1,452.4	7,570.3	0.00	0.00	0.00
17,300.0	94.59	359.44	9,067.5	7,538.8	-1,453.3	7,669.1	0.00	0.00	0.00
17,400.0	94.59	359.44	9,059.5	7,638.5	-1,454.3	7,767.9	0.00	0.00	0.00
17,500.0	94.59	359.44	9,051.5	7,738.2	-1,455.3	7,866.6	0.00	0.00	0.00
17,600.0	94.59	359.44	9,043.5	7,837.8	-1,456.3	7,965.4	0.00	0.00	0.00
17,700.0	94.59	359.44	9,035.5	7,937.5	-1,457.2	8,064.2	0.00	0.00	0.00
17,800.0	94.59	359.44	9,027.5	8,037.2	-1,458.2	8,163.0	0.00	0.00	0.00
17,900.0	94.59	359.44	9,019.5	8,136.9	-1,459.2	8,261.8	0.00	0.00	0.00
18,000.0	94.59	359.44	9,011.5	8,236.5	-1,460.1	8,360.6	0.00	0.00	0.00
18,100.0	94.59	359.44	9,003.5	8,336.2	-1,461.1	8,459.4	0.00	0.00	0.00
18,200.0	94.59	359.44	8,995.5	8,435.9	-1,462.1	8,558.2	0.00	0.00	0.00
18,300.0	94.59	359.44	8,987.5	8,535.6	-1,463.1	8,657.0	0.00	0.00	0.00
18,400.0	94.59	359.44	8,979.5	8,635.2	-1,464.0	8,755.8	0.00	0.00	0.00
18,500.0	94.59	359.44	8,971.5	8,734.9	-1,465.0	8,854.6	0.00	0.00	0.00
18,600.0	94.59	359.44	8,963.5	8,834.6	-1,466.0	8,953.4	0.00	0.00	0.00
18,700.0	94.59	359.44	8,955.5	8,934.2	-1,467.0	9,052.2	0.00	0.00	0.00
18,800.0	94.59	359.44	8,947.5	9,033.9	-1,467.9	9,151.0	0.00	0.00	0.00
18,900.0	94.59	359.44	8,939.5	9,133.6	-1,468.9	9,249.7	0.00	0.00	0.00
19,000.0	94.59	359.44	8,931.5	9,233.3	-1,469.9	9,348.5	0.00	0.00	0.00
19,100.0	94.59	359.44	8,923.5	9,332.9	-1,470.8	9,447.3	0.00	0.00	0.00
19,200.0	94.59	359.44	8,915.5	9,432.6	-1,471.8	9,546.1	0.00	0.00	0.00
19,300.0	94.59	359.44	8,907.5	9,532.3	-1,472.8	9,644.9	0.00	0.00	0.00
19,400.0	94.59	359.44	8,899.5	9,632.0	-1,473.8	9,743.7	0.00	0.00	0.00
19,500.0	94.59	359.44	8,891.5	9,731.6	-1,474.7	9,842.5	0.00	0.00	0.00

Database: Hobbs

Company: Mewbourne Oil Company
Project: Lea County, New Mexico NAD 83

Site: Belgian Blue 28/21 State Com #501H

Well: Sec 28, T18S, R35E

Wellbore: BHL: 100' FNL & 500' FWL (Sec 21)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Site Belgian Blue 28/21 State Com #501H WELL @ 3939.0usft (Original Well Elev) WELL @ 3939.0usft (Original Well Elev)

Grid

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
19,600.0	94.59	359.44	8,883.5	9,831.3	-1,475.7	9,941.3	0.00	0.00	0.00
19,700.0	94.59	359.44	8,875.5	9,931.0	-1,476.7	10,040.1	0.00	0.00	0.00
19,800.0	94.59	359.44	8,867.5	10,030.7	-1,477.7	10,138.9	0.00	0.00	0.00
19,900.0	94.59	359.44	8,859.5	10,130.3	-1,478.6	10,237.7	0.00	0.00	0.00
20,000.0	94.59	359.44	8,851.5	10,230.0	-1,479.6	10,336.5	0.00	0.00	0.00
20.030.9	94.59	359.44	8.849.0	10.260.8	-1,479.9	10.367.0	0.00	0.00	0.00

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
SHL: 205' FSL & 1880' - plan hits target c - Point		0.00	0.0	0.0	0.0	623,831.50	808,447.50	32.7119463	-103.4648914
BHL: 100' FNL & 500' l - plan hits target c - Point		0.00	8,849.0	10,260.8	-1,479.9	634,092.30	806,967.60	32.7401801	-103.4694305
KOP: 10' FSL & 500' F - plan hits target c - Point		0.00	9,066.0	-201.0	-1,377.8	623,630.49	807,069.71	32.7114248	-103.4693758
FTP: 100' FSL & 500' F - plan hits target c - Point		0.00	9,374.8	-111.0	-1,378.7	623,720.49	807,068.83	32.7116722	-103.4693763
LP: 583' FSL & 500' F\ - plan hits target c - Point		0.00	9,640.8	372.0	-1,383.4	624,203.48	807,064.11	32.7129997	-103.4693788

Page 5

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Electronically Via E-permitting

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

	Section 1 — Plan Description Effective May 25, 2021							
I. Operator: Mev	wbourne C	Oil Co.	OGRID:	14744		_ Date: _	5/2/2	22
II. Type: X Original	☐ Amendment	due to □ 19.15.27.9	9.D(6)(a) NMA(C □ 19.15.27.9.D(6)(b) NI	мас 🗆 С	Other.	
If Other, please describe	e:							
III. Well(s): Provide the be recompleted from a s	e following info single well pad	ormation for each r	new or recomple entral delivery p	ted well or set of voint.	vells pro	posed to	be drill	ed or proposed to
Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D		ripated MCF/D		Anticipated oduced Water BBL/D
BELGIN BLUE 28/21 STATE COM S	501H	N 28 18S 35E	205' FSL x 1880' FV	L 1500	150	00		4000
IV. Central Delivery P V. Anticipated Schedu proposed to be recomple	le: Provide the	following informat	sion for each new	or recompleted w	ell or se	7.		.9(D)(1) NMAC] ed to be drilled or
Well Name	API	Spud Date	TD Reached Date	Completion Commencement		Initial F Back D		First Production Date
BELGIN BLUE 28/21 STATE COM	501H	7/2/22	8/2/22	9/2/22		9/17/22	2	9/17/22
VI. Separation Equipm VII. Operational Prac Subsection A through F VIII. Best Manageme during active and plann	etices: 🖾 Attac of 19.15.27.8 I	h a complete descr NMAC. Attach a complet	ription of the act	ions Operator wil	l take to	comply	with the	e requirements of

Section 2 – Enhanced Plan EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

N Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

- XI. Map. ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.
- XII. Line Capacity. The natural gas gathering system \square will \square will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.
- **XIII.** Line Pressure. Operator \Box does \Box does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).
- ☐ Attach Operator's plan to manage production in response to the increased line pressure.
- XIV. Confidentiality:
 Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

⚠ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices

- 1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:
- (a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or
- (b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.
- 2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

Page 8

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	Bradley Bishop
Printed Name:	BRADLEY BISHOP
Title:	REGULATORY MANAGER
E-mail Address:	PRICHOD ONE APOLIDATE COM
Date:	5/2/22
Phone:	575-393-5905
	OIL CONSERVATION DIVISION (Only applicable when submitted as a standalone form)
Approved By:	
Title:	
Approval Date:	
Conditions of A	pproval:

Mewbourne Oil Company

Natural Gas Management Plan – Attachment

- VI. Separation equipment will be sized by construction engineering staff based on stated manufacturer daily throughput capacities and anticipated daily production rates to ensure adequate capacity. Closed vent system piping, compression needs, and VRUs will be sized utilizing ProMax modelling software to ensure adequate capacity for anticipated production volumes and conditions.
- VII. Mewbourne Oil Company (MOC) will take following actions to comply with the regulations listed in 19.15.27.8:
 - A. MOC will maximize the recovery of natural gas by minimizing the waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. MOC will ensure that well(s) will be connected to a natural gas gathering system with sufficient capacity to transport natural gas. If there is no adequate takeaway for the gas, well(s) will be shut in until the natural gas gathering system is available.
 - B. All drilling operations will be equipped with a rig flare located at least 100 ft from the nearest surface hole. Rig flare will be utilized to combust any natural gas that is brought to surface during normal drilling operations. In the case of emergency venting or flaring the volumes will be estimated and reported appropriately.
 - C. During completion operations any natural gas brought to surface will be flared. Immediately following the finish of completion operations, all well flow will be directed to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. It is not anticipated that gas will not meet pipeline standards. However, if natural gas does not meet gathering pipeline quality specifications, MOC will flare the natural gas for 60 days or until the natural gas meets the pipeline quality specifications, whichever is sooner. MOC will ensure that the flare is sized properly and is equipped with automatic igniter or continuous pilot. The gas sample will analyzed twice per week and the gas will be routed into a gathering system as soon as pipeline specifications are met.
 - D. Natural gas will not be flared with the exceptions and provisions listed in the 19.15.27.8 D.(1) through (4). If there is no adequate takeaway for the separator gas, well(s) will be shut in until the natural gas gathering system is available with exception of emergency or malfunction situations. Venting and/or flaring volumes will be estimated and reported appropriately.
 - E. MOC will comply with the performance standards requirements and provisions listed in 19.15.27.8 E.(1) through (8). All equipment will be designed and sized to handle maximum anticipated pressures and throughputs in order to minimize the waste. Production storage tanks constructed after May 25, 2021 will be equipped with automatic gauging system. Flares constructed after May 25, 2021 will be equipped with automatic igniter or continuous pilot. Flares will be located at least 100' from the well and storage tanks unless otherwise approved by the division. MOC will conduct AVO inspections as described in 19.15.27.8 E (5) (a) with frequencies specified in 19.15.27.8 E (5) (b) and (c). All emergencies will be resolved as quickly and safely as feasible to minimize waste.
 - F. The volume of natural gas that is vented or flared as the result of malfunction or emergency during drilling and completions operations will be estimated. The volume of natural gas that is vented, flared or beneficially used during production operations, will be measured or estimated. MOC will install equipment to measure

the volume of natural gas flared from existing process piping or a flowline piped from equipment such as high pressure separators, heater treaters, or vapor recovery units associated with a well or facility associated with a well authorized by an APD issued after May 25, 2021 that has an average daily production greater than 60 Mcf/day. If metering is not practicable due to circumstances such as low flow rate or low pressure venting and flaring, MOC will estimate the volume of vented or flared natural gas. Measuring equipment will conform to industry standards and will not be designed or equipped with a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing the measurement equipment.

VIII. For maintenance activities involving production equipment and compression, venting will be limited to the depressurization of the subject equipment to ensure safe working conditions. For maintenance of production and compression equipment the associated producing wells will be shut in to eliminate venting. For maintenance of VRUs all gas normally routed to the VRU will be routed to flare to eliminate venting.