Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 330290 District II 811 S. First St., Artesia, NM 88210 WELL APINIMBER Oil Conservation Division Phone:(575) 748-1283 Fax:(575) 748-9720 30-015-49939 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 State Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS LE MANS 2419 STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number Oil 304H 2. Name of Operator 9. OGRID Number Tascosa Energy Partners, L.L.C 329748 3. Address of Operator 10. Pool name or Wildcat 901 W. Missouri Ave, Midland, TX 79701 4. Well Location Unit Letter \underline{M} : $\underline{1137}$ feet from the \underline{S} line and feet 297 from the W Township 20S Range 26E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3292 GR Pit or Below-grade Tank Application or Closure __ Depth to Groundwater___ ___ Distance from nearest fresh water well _ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume_ Pit Liner Thickness: bbls: Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See Attached 10/31/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Est Dpth Yield Open Size Size lb/ft TOC Dpth Held Drop Hole 11/01/22 Surf FreshWater 17.5 13.375 48 H40 0 375 550 1.34 С 0 500 0 Ν 11/08/22 Int1 CutBrine 12.25 9.625 36 J55 0 2605 605 2.16 С 0 1500 0 Ν 12/05/22 20 YP110 Prod OilBasedMud 5.5 0 17815 2810 2.91 0 Ν 8.5 Н I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square TITLE SIGNATURE DATE Electronically Signed Land Manager 12/12/2022 Type or print name Kelly M Hardy E-mail address Telephone No. 432-695-6970 khardy@tascosaep.com

DATE

8/16/2023 1:48:00 PM

TITLE

For State Use Only:
APPROVED BY:

Patricia L Martinez

LeMans 24 19 State Com #304H

API# 30-015-49939

C103 Work Summary – Drilling/Cement Report

10/31/22: MIRU. PU 17-1/2" bit & BHA. **Spud LeMans 24 19 St Com #304H at 9:00 hrs MST.** Drill 17-1/2" surface hole from 120' to 335'.

11/1/22: Drill surface hole to 403'. TOH to RIH w/ 13-3/8" csg. RIH w/ 9 jts. of 13-3/8" surface csing. **Cmt surface csg w/ 550 sx of Class C. Circulate 50 bbls of cement to surface.** WOC. Walk rig to next well.

11/6/22: Walk rig back to #304H. NU BOP and test. PU intermediate BHA. TIH w/ 12-1/4" bit to 326'. **Test surface casing to 500 psi for 30 minutes. Casing held.** Drill plug & float collar.

11/7/22: Drill intermediate hole from 375' – 2605'. Circ. TOH.

11/8/22: RIH w/ 61 jts. 9-5/8" csg to 2605'. **Cmt intermediate csg w/ 405 sx lead, 200 sx tail. Circulate 30 bbls of cmt to surface.** Move rig to next well.

11/10/22: Walk rig back to #304H. NU BOP. **Test int. casing to 1,500 psi for 30 minutes. Casing held.** TIH w/8-3/4" bit.

11/11/22: TIH, displace w/ OBM. Tag float collar @ 2660'. Drill vertical production hole to 4794'.

11/12/22-11/13/22: Drill production hole to KOP @ 7158'. POOH to PU curve BHA.

11/14/22-11/15/22: RIH w/ curve BHA. Drill curve and 200' of lateral, POOH @ 8261'.

11/16/22: LD curve BHA. PU lateral BHA w/ 8-1/2" bit. Log well. TIH.

11/17/22/- 12/3/22: Drill lateral from 8261' – 17,815' w/ 8-1/2" bit. TD wellbore.

12/4/22: LD DP. RIH w/ 335 jts RYP-110 DWC 20# production casing.

12/5/22: Finish RIH w/ csg, land @ 17815'. Cmt production csg w/ 695 sx of lead, 2115 sx tail cmt. Circulate 70 bbls of cmt to surface. Prod csg will be tested prior to frac job, scheduled for 3/1/23. Rig Released at 18:00 hrs MST on 12/5/22.