

1625 N. French Dr., Hobbs, NM 88240

State of New Mexico
Energy, Minerals & Natural Resources

Form C-104

Revised August 1, 2011

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division

1220 South St. Francis Dr.

Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address OXY USA INC. P.O. BOX 50250 MIDLAND, TX 79710		² OGRID Number: 16696
		³ Reason for Filing Code/ Effective Date: NW- 10/24/2022
⁴ API Number 30 – 015-47587	⁵ Pool Name PURPLE SAGE WOLFCAMP *NSL-8389	⁶ Pool Code 98220
⁷ Property Code: 328290	⁸ Property Name: HEADS CC 9-4 FEDERAL COM	⁹ Well Number: 38H

II. ¹⁰ Surface Location

Ul or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
B	16	24S	29E		960	NORTH	1680	EAST	EDDY

¹¹ Bottom Hole Location

FTP- 344' FSL 1490' FEL LTP- 196' FNL 1511' FEL

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L2	4	24S	29E		63	NORTH	1505	EAST	EDDY
¹² Lse Code F	¹³ Producing Method Code : P		¹⁴ Gas Connection Date: 10/26/22		¹⁵ C-129 Permit Number		¹⁶ C-129 Effective Date		¹⁷ C-129 Expiration Date

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
214754	LPC CRUDE OIL, INC.	O
151618	ENTERPRISE FIELD SERVICES LLC	G

IV. Well Completion Data

²¹ Spud Date 06/18/22	²² Ready Date 10/24/2022	²³ TD 20872'M 10141'V	²⁴ PBTD 20829'M 10140'V	²⁵ Perforations 10666-20739'	²⁶ DHC, MC
²⁷ Hole Size		²⁸ Casing & Tubing Size		²⁹ Depth Set	³⁰ Sacks Cement
17-1/2"		13-3/8"		593'	2095
12-1/4"		9-5/8"		9719'	3600
8-3/4" X 8-1/2"		7" X 5-1/2"		20850'	877
		2-7/8" TBG		9696'	NA

V. Well Test Data

³¹ Date New Oil 10/27/22	³² Gas Delivery Date 10/26/22	³³ Test Date 12/09/22	³⁴ Test Length 24 HRS	³⁵ Tbg. Pressure	³⁶ Csg. Pressure 673
³⁷ Choke Size 128/128	³⁸ Oil 3537	³⁹ Water 5897	⁴⁰ Gas 5061		⁴¹ Test Method F

⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief.



Signature:

Printed name: JANA MENDIOLA

Title: SR. REGULATORY ANALYST

E-mail Address:

Janalyn_mendiola@oxy.com

Date:

02/08/2023

Phone:

432-685-5936

OIL CONSERVATION DIVISION

Approved by:

PATRICIA MARTINEZ

Title: PETROLEUM SPECIALIST

Approval Date: 8/17/2023

1625 N. French Dr., Hobbs, NM 88240
 Phone: (575) 393-6161 Fax: (575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone: (505) 748-1283 Fax: (505) 748-9720
District III
 1000 Rio Brazos Road, Aztec, NM 87410
 Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505
 Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
 Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Revised August 1, 2011
 Submit one copy to appropriate
 District Office

☒ AMENDED REPORT


WELL LOCATION AND ACREAGE DEDICATION AS-DRILLED PLAT

¹ API Number 30-015-47587	² Pool Code 98220	³ Pool Name PURPLE SAGE WOLFCAMP
⁴ Property Code 328290	Property Name HEADS CC 9_4 FEDERAL COM	⁶ Well Number 38H
⁷ OGRID No. 16696	⁸ Operator Name OXY USA INC.	⁹ Elevation 2927'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	16	24S	29E		960	NORTH	1680	EAST	EDDY
¹¹ Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L 2	4	24S	29E		63	NORTH	1505	EAST	EDDY
¹² Dedicated Acres 1278.94	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No. NSL-8389						

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



Distances/areas relative to NAD 83 Combined Scale Factor: 0.99982819 Convergence Angle: 00°26'57.22001"

Schlumberger

OXY




Borehole:	Well:	Field:	Structure:
Heads CC 9_4 Fed Com 38H	Heads CC 9_4 Fed Com 38H	NM Eddy County (NAD 83)	Oxy Heads CC 9_4 Federal Com Pad (Citadel 2)

Gravity & Magnetic Parameters	Surface Location	NAD83 New Mexico State Plane, Eastern Zone, US Feet	Miscellaneous
Model: IFR1 MagDec: 6.78° Dip: 59.934° FS: 47563.6NT Date: 26-Aug-2022 Gravity FS: 998.471mgn (9.80665 Based)	Lat: N 32 13 20.05 Lon: W 103 59 10.86	Northing: 444756.4HUS Easting: 648638.6HUS Grid Conv: 0.185° Scale Fact: 0.99992228	Slot: Heads CC 9_4 Fed Com 38H TVD Ref: RKB(2950.8ft above MSL) Plan: Oxy Heads CC 9_4 Fed Com 38H Gyro/MWD 0' to 20872MD

Critical Points

Critical Point	MD	INCL	AZIM	TVD	VSEC	N(+)S(-)	E(+)/W(-)	DLS
WRP	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
SHL	24.00	0.00	0.00	24.00	0.00	0.00	0.00	
First Gyro Survey	95.27	0.21	305.25	95.27	0.07	0.08	-0.11	0.29
Last Gyro Survey	555.10	1.80	7.41	555.00	9.13	9.13	0.40	0.30
First SLB Survey	637.00	1.19	6.87	636.87	11.26	11.25	0.67	0.75
Actual KOP	9789.00	14.44	6.95	9723.12	626.33	624.25	149.90	13.23
Wolfcamp A Intersection	10255.23	61.58	3.75	10072.80	916.35	914.00	170.98	10.22
330° FSL Crossing	10639.00	89.82	2.97	10176.17	1281.78	1279.34	180.03	1.52
Exit Target Box	18884.00	91.51	355.87	10156.84	9520.34	9519.53	124.59	0.14
Enter Target Box	19760.00	90.20	1.53	10141.56	10395.13	10394.50	118.69	0.21
Exit Target Box	20328.00	90.03	358.13	10138.77	10962.94	10962.37	117.88	0.15
Enter Target Box	20718.00	89.70	1.74	10139.88	11352.72	11352.26	113.37	1.15
100° FNL Crossing	20834.00	89.53	2.76	10140.78	11468.67	11468.16	118.02	0.72
Final MWD Survey	20841.00	89.53	2.81	10140.84	11475.67	11475.15	118.36	0.72
Proj to TD	20872.00	89.53	2.81	10141.09	11506.65	11506.11	119.88	0.00





Oxy Heads CC 9_4 Fed Com 38H Gyro+MWD 0' to 20872'MD Survey Geodetic Report (Def Survey)



Report Date:	September 09, 2022 - 10:19 AM	Survey / DLS Computation:	Minimum Curvature / Lubinski
Client:	OXY	Vertical Section Azimuth:	0.818 ° (Grid North)
Field:	NM Eddy County (NAD 83)	Vertical Section Origin:	0.000 ft, 0.000 ft
Structure / Slot:	Oxy Heads CC 9_4 Federal Com Pad (Citadel 2) / Heads CC 9_4 Fed Com 38H	TVD Reference Datum:	RKB
Well:	Heads CC 9_4 Fed Com 38H	TVD Reference Elevation:	2950.800 ft above MSL
Borehole:	Heads CC 9_4 Fed Com 38H	Seabed / Ground Elevation:	2926.800 ft above MSL
UWI / API#:	Unknown / Unknown	Magnetic Declination:	6.780 °
Survey Name:	Oxy Heads CC 9_4 Fed Com 38H Gyro+MWD 0' to 20872MD	Total Gravity Field Strength:	59.934 °
Survey Date:	June 16, 2022	Gravity Model:	GARM
Tort / AHD / DDI / ERD Ratio:	231.437 ° / 11544.047 ft / 6.739 / 1.134	Total Magnetic Field Strength:	47563.600 nT
Coordinate Reference System:	NAD83 New Mexico State Plane, Eastern Zone, US Feet	Magnetic Dip Angle:	59.934 °
Location Lat / Long:	N 32° 13' 20.04806", W 103° 59' 10.85569"	Declination Date:	August 26, 2022
Location Grid N/E Y/X:	N 444756.400 RUS, E 648638.600 ftUS	Magnetic Declination Model:	IFR1
CRS Grid Convergence Angle:	0.1850 °	North Reference:	Grid North
Grid Scale Factor:	0.99992228	Grid Convergence Used:	0.1800 °
Version / Patch:	2.10.829.1	Total Corr Mag North->Grid North:	6.6000 °
		Local Coord Referenced To:	Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Closure (ft)	Closure Azimuth (°)	Northing (ftUS)	Easting (ftUS)	Latitude (N/S ° ' ")	Longitude (E/W ° ' ")
WRP	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	0.00	0.00	444756.40	648638.60	N 32 13 20.05	W 103 59 10.86
SHL	24.00	0.00	0.00	24.00	0.00	0.00	0.00	0.00	0.00	0.00	444756.40	648638.60	N 32 13 20.05	W 103 59 10.86
First Gyro Survey	95.27	0.21	305.25	95.27	0.07	0.08	-0.11	0.29	0.13	305.25	444756.48	648638.49	N 32 13 20.05	W 103 59 10.86
	183.58	1.01	359.19	183.57	0.94	0.95	-0.25	1.02	0.98	345.22	444757.35	648638.35	N 32 13 20.06	W 103 59 10.86
	272.15	1.01	5.72	272.13	2.50	2.50	-0.18	0.13	2.51	355.82	444758.90	648638.42	N 32 13 20.07	W 103 59 10.86
	366.39	1.12	0.34	366.35	4.25	4.25	-0.09	0.16	4.25	358.72	444760.65	648638.51	N 32 13 20.09	W 103 59 10.86
	460.73	1.52	6.94	460.67	6.42	6.42	0.06	0.45	6.42	0.55	444762.82	648638.66	N 32 13 20.11	W 103 59 10.85
Last Gyro Survey	555.10	1.80	7.41	555.00	9.13	9.13	0.40	0.30	9.14	2.54	444765.53	648639.00	N 32 13 20.14	W 103 59 10.85
First SLB Survey	637.00	1.19	6.87	636.87	11.26	11.25	0.67	0.75	11.27	3.42	444767.85	648639.27	N 32 13 20.16	W 103 59 10.85
	726.00	0.25	5.50	725.86	12.37	12.36	0.80	1.06	12.38	3.71	444768.76	648639.40	N 32 13 20.17	W 103 59 10.85
	816.00	0.14	83.06	815.86	12.58	12.57	0.93	0.29	12.60	4.23	444768.97	648639.53	N 32 13 20.17	W 103 59 10.84
	904.00	0.07	183.61	903.86	12.54	12.53	1.03	0.19	12.57	4.71	444768.93	648639.63	N 32 13 20.17	W 103 59 10.84
	992.00	0.18	22.07	991.86	12.62	12.60	1.08	0.28	12.65	4.90	444769.00	648639.68	N 32 13 20.17	W 103 59 10.84
	1181.00	0.17	140.59	1180.86	12.68	12.66	1.37	0.16	12.73	6.18	444769.06	648639.97	N 32 13 20.17	W 103 59 10.84
	1274.00	0.12	347.77	1273.86	12.67	12.65	1.44	0.30	12.73	6.48	444769.05	648640.04	N 32 13 20.17	W 103 59 10.84
	1368.00	0.21	254.94	1367.86	12.72	12.70	1.25	0.26	12.76	5.62	444769.10	648639.85	N 32 13 20.17	W 103 59 10.84
	1462.00	0.15	174.48	1461.86	12.55	12.53	1.10	0.25	12.58	5.00	444768.93	648639.70	N 32 13 20.17	W 103 59 10.84
	1554.00	0.05	300.51	1553.86	12.45	12.43	1.07	0.20	12.48	4.93	444768.83	648639.67	N 32 13 20.17	W 103 59 10.84
	1649.00	0.16	211.37	1648.86	12.35	12.34	0.97	0.18	12.38	4.48	444768.74	648639.57	N 32 13 20.17	W 103 59 10.84
	1743.00	0.15	60.00	1742.86	12.30	12.29	1.01	0.32	12.33	4.68	444768.69	648639.61	N 32 13 20.17	W 103 59 10.84
	1837.00	0.17	302.11	1836.86	12.44	12.43	0.99	0.29	12.47	4.58	444768.82	648639.59	N 32 13 20.17	W 103 59 10.84
	1931.00	0.12	333.82	1930.86	12.60	12.59	0.83	0.10	12.62	3.79	444768.99	648639.43	N 32 13 20.17	W 103 59 10.85
	2025.00	0.13	328.03	2024.86	12.78	12.77	0.73	0.02	12.79	3.29	444769.17	648639.33	N 32 13 20.17	W 103 59 10.85
	2118.00	0.13	54.68	2117.86	12.93	12.92	0.76	0.19	12.94	3.38	444769.32	648639.36	N 32 13 20.18	W 103 59 10.85
	2212.00	0.17	124.13	2211.86	12.91	12.90	0.97	0.19	12.94	4.28	444769.30	648639.57	N 32 13 20.18	W 103 59 10.84
	2306.00	0.09	333.58	2305.86	12.90	12.89	1.05	0.27	12.93	4.65	444769.29	648639.65	N 32 13 20.18	W 103 59 10.84
	2400.00	0.19	180.49	2399.86	12.81	12.80	1.01	0.29	12.84	4.53	444769.20	648639.61	N 32 13 20.17	W 103 59 10.84
	2494.00	0.21	144.61	2493.86	12.52	12.50	1.11	0.13	12.55	5.09	444768.90	648639.71	N 32 13 20.17	W 103 59 10.84
	2682.00	0.06	267.61	2681.86	12.23	12.22	1.21	0.13	12.28	5.67	444768.62	648639.81	N 32 13 20.17	W 103 59 10.84
	2777.00	0.18	164.33	2776.86	12.09	12.07	1.20	0.21	12.13	5.70	444768.47	648639.80	N 32 13 20.17	W 103 59 10.84
	2872.00	0.14	87.74	2871.86	11.95	11.93	1.36	0.21	12.01	6.51	444768.33	648639.96	N 32 13 20.17	W 103 59 10.84
	2966.00	0.08	104.30	2965.86	11.94	11.92	1.54	0.07	12.02	7.36	444768.32	648640.14	N 32 13 20.17	W 103 59 10.84
	3060.00	0.10	261.77	3059.86	11.91	11.89	1.52	0.19	11.99	7.29	444768.29	648640.12	N 32 13 20.17	W 103 59 10.84
	3248.00	0.17	317.55	3247.86	12.08	12.07	1.17	0.07	12.13	5.54	444768.47	648639.77	N 32 13 20.17	W 103 59 10.84
	3341.00	0.13	342.43	3340.86	12.29	12.28	1.05	0.08	12.32	4.87	444768.68	648639.65	N 32 13 20.17	W 103 59 10.84
	3436.00	0.15	289.98	3435.86	12.43	12.42	0.90	0.13	12.46	4.13	444768.82	648639.50	N 32 13 20.17	W 103 59 10.84
	3530.00	0.16	77.46	3529.86	12.51	12.49	0.91	0.32	12.53	4.16	444768.89	648639.51	N 32 13 20.17	W 103 59 10.84
	3624.00	0.14	206.62	3623.86	12.43	12.42	0.99	0.29	12.46	4.54	444768.82	648639.59	N 32 13 20.17	W 103 59 10.84
	3718.00	0.17	83.59	3717.86	12.35	12.33	1.07	0.29	12.38	4.97	444768.73	648639.67	N 32 13 20.17	W 103 59 10.84
	3812.00	0.13	111.39	3811.86	12.33	12.31	1.31	0.09	12.38	6.08	444768.71	648639.91	N 32 13 20.17	W 103 59 10.84
	3907.00	0.14	346.82	3906.86	12.40	12.38	1.39	0.25	12.46	6.40	444768.78	648639.98	N 32 13 20.17	W 103 59 10.84
	4001.00	0.16	332.51	4000.86	12.63	12.61	1.31	0.05	12.68	5.91	444769.01	648639.91	N 32 13 20.17	W 103 59 10.84
	4096.00	0.14	180.16	4095.86	12.63	12.61	1.24	0.31	12.68	5.63	444769.01	648639.84	N 32 13 20.17	W 103 59 10.84
	4190.00	0.13	97.76	4189.86	12.50	12.49	1.35	0.19	12.56	6.17	444768.88	648639.95	N 32 13 20.17	W 103 59 10.84
	4284.00	0.11	229.52	4283.86	12.43	12.41	1.39	0.23	12.49	6.37	444768.81	648639.99	N 32 13 20.17	W 103 59 10.84
	4379.00	0.15	25.20	4378.86	12.48	12.47	1.37	0.27	12.54	6.27	444768.86	648639.97	N 32 13 20.17	W 103 59 10.84
	4473.00	0.13	338.58	4472.86	12.69	12.68	1.38	0.12	12.75	6.42	444769.08	648639.98	N 32 13 20.17	W 103 59 10.84
	4568.00	0.15	138.48	4567.86	12.70	12.68	1.43	0.29	12.76	6.42	444769.08	648640.03	N 32 13 20.17	W 103 59 10.84
	4662.00	0.15	337.41	4661.86	12.72	12.71	1.46	0.31	12.79	6.56	444769.10	648640.06	N 32 13 20.17	W 103 59 10.84
	4756.00	0.15	189.01	4755.85	12.72	12.70	1.39	0.31	12.77	6.27	444769.10	648639.99	N 32 13 20.17	W 103 59 10.84
	4850.00	0.16	282.68	4849.85	12.62	12.60	1.25	0.24	12.67	5.65	444769.00	648639.85	N 32 13 20.17	W 103 59 10.84
	4944.00	0.18	15.45	4943.85	12.79	12.78	1.16	0.26	12.83	5.18	444769.17	648639.76	N 32 13 20.17	W 103 59 10.84
	5037.00	0.11	341.09	5036.85	13.02	13.00	1.17	0.13	13.05	5.43	444769.40	648639.77	N 32 13 20.18	W 103 59 10.84
	5132.00	0.17	138.19	5131.85	13.00	12.98	1.23	0.29	13.04	5.42	444769.38	648639.83	N 32 13 20.18	W 103 59 10.84
	5226.00	0.15	94.72	5225.85	12.89	12.87	1.45	0.13	12.95	6.42	444769.27	648640.05	N 32 13 20.18	W 103 59 10.84
	5321.00	0.20	240.78	5320.85	12.80	12.78	1.43	0.35	12.86	6.37	444769.18	648640.03	N 32 13 20.17	W 103 59 10.84
	5415.00	0.21	210.25	5414.85	12.56	12.55	1.20	0.12	12.60	5.45	444768.95	648639.80	N 32 13 20.17	W 103 59 10.84
	5509.00	0.10	100.00	5508.85	12.49	12.48	1.13	0.33	12.53	5.18	444768.88	648639.73	N 32 13 20.17	W 103 59 10.84
	5603.00	0.24	139.24	5602.85	12.43	12.41	1.28	0.23	12.47	5.88	444768.81	648639.88	N 32 13 20.17	W 103 59 10.84
	5697.00	0.25	102.06	5696.85	12.22	12.22	1.61	0.17	12.24	7.49	444768.61	648640.21	N 32 13 20.17	W 103 59 10.84
	5791.00	0.20	26.80	5790.85	12.34	12.32	1.88	0.30	12.46	8.68	444768.72	648640.48	N 32 13 20.17	W 103 59 10.83
	5885.00	0.26	143.11	5884.85	12.32	12.29	2.08	0.42	12.47	9.61	444768.69	648640.68	N 32 13 20.17	W 103 59 10.83
	5978.00	0.24	80.59	5977.85	12.19	12.16	2.40	0.28	12.39	11.17	444768.56	648641.00	N 32 13 20.17	W 103 59 10.83
	6073.00	0.26	81.41	6072.85	12.26	12.22	2.81	0.02	12.54	12.95	444768.62	648641.41	N 32 13 20.17	W 103 59 10.82
	6167.00	0.40	11.60	6166.85	12.62	12.58	3.09	0.42	12.95	13.79	444768.97	648641.69	N 32 13 20.17	W 103 59 10.82
	6262.00	1.09	18.71	6261.84	13.76	13.70	3.40	0.73	14.18	14.05	444770.15	648642.07	N 32 13 20.18	W

Comments	MD (ft)	Incl (°)	Azim (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100R)	Closure (ft)	Closure Azimuth (°)	Northing (ftUS)	Easting (ftUS)	Latitude (N ° '")	Longitude (E W ° '")
Actual KOP	9647.00	13.92	11.10	9585.36	592.27	590.28	144.17	0.26	607.63	13.73	445346.63	648782.76	N 32 13 25.88	W 103 59 9.16
	9705.00	13.94	10.51	9641.66	606.03	603.99	146.79	0.25	621.57	13.66	445360.34	648785.38	N 32 13 26.02	W 103 59 9.12
	9788.00	14.31	7.01	9722.15	626.08	624.00	149.87	1.12	641.75	13.50	445380.35	648788.45	N 32 13 26.22	W 103 59 9.09
	9789.00	14.44	6.95	9723.12	626.33	624.25	149.90	13.23	641.99	13.50	445380.60	648788.48	N 32 13 26.22	W 103 59 9.09
	9882.00	26.70	3.82	9810.02	658.85	656.73	152.70	13.23	674.25	13.09	445413.08	648791.29	N 32 13 26.54	W 103 59 9.05
	9975.00	37.66	5.00	9888.62	708.20	706.03	156.58	11.80	723.19	12.50	445462.38	648795.17	N 32 13 27.03	W 103 59 9.01
	10068.00	43.94	4.03	9958.98	766.81	766.58	161.33	6.79	783.38	11.88	445522.92	648799.92	N 32 13 27.63	W 103 59 8.95
	10163.00	52.15	3.62	10022.44	839.30	837.01	166.02	8.65	853.32	11.22	445593.35	648804.61	N 32 13 28.33	W 103 59 8.89
	10255.23	61.58	3.75	10072.80	916.35	914.00	170.98	10.22	929.86	10.60	445670.33	648809.57	N 32 13 29.09	W 103 59 8.83
	10257.00	61.76	3.75	10073.64	917.90	915.55	171.09	10.22	931.40	10.58	445671.88	648809.67	N 32 13 29.10	W 103 59 8.83
Wolfcamp A Intersection	10351.00	67.92	2.33	10113.59	1002.88	1000.47	175.57	6.69	1015.76	9.95	445756.79	648814.16	N 32 13 29.94	W 103 59 8.77
	10446.00	71.56	359.88	10146.48	1091.98	1089.56	177.26	4.53	1103.88	9.24	445845.87	648815.85	N 32 13 30.82	W 103 59 8.75
	10539.00	80.95	0.02	10168.55	1182.20	1179.79	177.19	10.10	1193.02	8.54	445936.10	648815.77	N 32 13 31.72	W 103 59 8.75
	10633.00	89.78	3.05	10176.14	1259.78	1257.35	179.71	9.93	1285.97	8.03	446029.65	648818.30	N 32 13 32.64	W 103 59 8.72
	10639.00	89.82	2.97	10176.17	1281.78	1279.34	180.03	1.52	1291.94	8.01	446035.64	648818.61	N 32 13 32.70	W 103 59 8.71
	10727.00	90.43	1.78	10175.97	1369.74	1367.26	183.67	1.52	1379.54	7.65	446123.55	648822.26	N 32 13 33.57	W 103 59 8.67
	10791.00	91.05	1.27	10175.15	1433.73	1431.23	185.37	1.25	1443.19	7.38	446187.52	648823.96	N 32 13 34.20	W 103 59 8.64
	10884.00	91.61	1.63	10172.99	1526.70	1524.18	187.73	0.72	1535.69	7.02	446280.96	648826.31	N 32 13 35.12	W 103 59 8.61
	10979.00	91.29	1.38	10170.58	1621.86	1619.11	190.22	0.43	1630.25	6.70	446375.38	648828.81	N 32 13 36.08	W 103 59 8.58
	11072.00	90.68	1.24	10168.98	1714.65	1712.08	192.35	0.67	1722.85	6.41	446468.34	648830.93	N 32 13 36.98	W 103 59 8.55
330° FSL Crossing	11167.00	89.82	0.58	10168.57	1809.64	1807.06	193.86	1.14	1817.43	6.12	446563.32	648832.44	N 32 13 37.92	W 103 59 8.53
	11261.00	90.29	1.28	10168.48	1903.64	1901.05	195.38	0.90	1911.06	5.87	446657.30	648833.97	N 32 13 38.85	W 103 59 8.51
	11354.00	90.23	1.32	10168.06	1996.64	1994.02	197.49	0.08	2003.78	5.66	446750.26	648836.08	N 32 13 39.77	W 103 59 8.48
	11448.00	89.78	1.35	10168.05	2090.63	2088.00	199.68	0.48	2097.52	5.46	446844.23	648838.27	N 32 13 40.70	W 103 59 8.45
	11541.00	90.25	1.09	10168.02	2183.63	2180.98	201.66	0.58	2190.28	5.28	446937.20	648840.25	N 32 13 41.62	W 103 59 8.43
	11636.00	90.72	2.21	10167.22	2276.62	2275.93	204.40	1.28	2285.09	5.13	447032.15	648842.98	N 32 13 42.56	W 103 59 8.39
	11729.00	88.96	1.00	10167.60	2371.60	2368.89	207.00	2.28	2377.92	4.99	447125.10	648845.59	N 32 13 43.48	W 103 59 8.36
	11824.00	90.68	1.01	10167.75	2466.60	2463.87	208.67	1.79	2472.69	4.84	447220.07	648847.25	N 32 13 44.42	W 103 59 8.33
	11917.00	90.36	359.85	10166.90	2559.59	2556.86	209.37	1.29	2565.42	4.68	447313.06	648847.95	N 32 13 45.34	W 103 59 8.32
	12012.00	89.92	359.28	10166.67	2654.57	2651.86	208.64	0.76	2660.05	4.50	447408.05	648847.23	N 32 13 46.28	W 103 59 8.33
100° FNL Crossing	12107.00	90.28	359.59	10166.50	2749.51	2746.84	206.88	0.82	2754.62	4.31	447503.02	648845.46	N 32 13 47.22	W 103 59 8.34
	12201.00	89.67	0.29	10165.81	2843.48	2840.83	205.96	1.83	2848.29	4.15	447597.00	648844.54	N 32 13 48.15	W 103 59 8.35
	12295.00	89.61	358.37	10165.66	2937.44	2934.82	204.86	2.28	2941.96	3.99	447690.98	648843.45	N 32 13 49.08	W 103 59 8.36
	12389.00	89.56	358.64	10166.34	3031.36	3028.78	202.41	0.29	3035.54	3.82	447784.94	648840.99	N 32 13 50.01	W 103 59 8.39
	12483.00	89.90	358.74	10166.78	3125.30	3122.76	200.26	0.38	3129.17	3.67	447878.91	648838.84	N 32 13 50.94	W 103 59 8.41
	12577.00	90.63	358.97	10166.35	3219.24	3216.74	198.38	0.81	3222.85	3.53	447972.88	648836.97	N 32 13 51.87	W 103 59 8.43
	12671.00	90.33	359.37	10165.56	3313.20	3310.72	197.02	0.33	3316.58	3.41	448066.86	648835.60	N 32 13 52.80	W 103 59 8.44
	12765.00	91.01	0.27	10164.64	3407.18	3404.72	196.72	1.20	3410.39	3.31	448160.84	648835.31	N 32 13 53.73	W 103 59 8.44
	12859.00	90.17	0.05	10163.49	3501.17	3498.71	196.99	0.92	3504.25	3.22	448254.83	648835.57	N 32 13 54.66	W 103 59 8.43
	12954.00	91.01	0.55	10162.52	3596.16	3593.70	197.48	1.03	3599.12	3.15	448349.82	648836.07	N 32 13 55.60	W 103 59 8.42
100° FNL Crossing	13047.00	91.20	0.09	10160.72	3689.13	3686.68	198.00	0.54	3692.00	3.07	448442.79	648836.59	N 32 13 56.52	W 103 59 8.41
	13142.00	89.88	359.08	10159.83	3784.10	3781.67	197.32	1.75	3786.82	2.99	448537.77	648835.90	N 32 13 57.46	W 103 59 8.42
	13236.00	90.19	359.05	10159.77	3878.06	3875.66	195.78	0.33	3880.60	2.89	448631.75	648834.37	N 32 13 58.39	W 103 59 8.43
	13331.00	89.90	358.73	10159.69	3973.01	3970.64	193.94	0.45	3975.38	2.80	448726.73	648832.23	N 32 13 59.33	W 103 59 8.45
	13319.00	90.59	0.08	10158.89	4160.94	4158.62	191.99	0.81	4163.05	2.64	448914.69	648830.51	N 32 14 00.28	W 103 59 8.46
	13614.00	90.82	0.22	10157.72	4255.93	4253.62	192.24	0.28	4257.96	2.59	449009.68	648830.82	N 32 14 01.23	W 103 59 8.46
	13708.00	89.84	358.62	10157.18	4349.89	4347.61	191.29	2.00	4351.81	2.52	449103.66	648829.87	N 32 14 03.06	W 103 59 8.47
	13802.00	89.65	358.43	10157.60	4443.82	4441.57	188.87	0.29	4445.59	2.43	449197.62	648827.45	N 32 14 03.99	W 103 59 8.49
	13897.00	87.89	358.42	10159.64	4538.71	4536.51	186.26	1.85	4540.34	2.35	449292.55	648824.84	N 32 14 04.93	W 103 59 8.52
	13991.00	88.61	359.05	10162.51	4632.60	4630.45	184.18	1.02	4634.11	2.28	449398.48	648822.77	N 32 14 05.86	W 103 59 8.54
100° FNL Crossing	14086.00	89.23	359.19	10164.30	4727.54	4725.42	182.72	0.67	4728.95	2.21	449491.41	648821.31	N 32 14 06.80	W 103 59 8.55
	14179.00	91.70	0.63	10163.54	4820.52	4818.40	182.58	3.07	4821.86	2.17	449574.42	648821.16	N 32 14 07.72	W 103 59 8.55
	14274.00	89.52	0.27	10162.53	4915.51	4913.39	183.32	2.33	4916.81	2.14	449669.40	648821.91	N 32 14 08.66	W 103 59 8.54
	14367.00	89.64	0.24	10163.21	5008.50	5006.39	183.74	0.13	5009.76	2.10	449762.39	648822.32	N 32 14 09.58	W 103 59 8.53
	14462.00	90.86	0.50	10162.80	5103.49	5101.38	184.35	1.31	5104.71	2.07	449857.37	648822.94	N 32 14 10.52	W 103 59 8.52
	14556.00	89.33	0.37	10162.64	5197.49	5195.38	185.06	1.63	5198.67	2.04	449951.36	648823.65	N 32 14 11.45	W 103 59 8.51
	14650.00	90.35	0.57	10162.91	5291.48	5289.33								

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Closure (ft)	Closure Azimuth (°)	Northing (ftUS)	Easting (ftUS)	Latitude (N/S ° ' ")	Longitude (E/W ° ' ")
Survey Type:	Def Survey													
Survey Error Model:	ISCWSA Rev 3 *** 3-D 95.000% Confidence 2.7955 sigma													
Survey Program:														
Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size (in)	Casing Diameter (in)	Survey Tool Type	Borehole / Survey						
	1	0.000	24.000	1/98.425	26.400	26.400	GYD_GC+DROP+OH-Depth Only	Heads CC 9_4 Fed Com 38H / Oxy Heads CC 9_4 Fed Com 38H Gyro+MWD 0' to 20872MD						
	1	24.000	24.000	Act Stns	26.400	26.400	GYD_GC+DROP+OH-Depth Only	Heads CC 9_4 Fed Com 38H / Oxy Heads CC 9_4 Fed Com 38H Gyro+MWD 0' to 20872MD						
	1	24.000	555.100	Act Stns	26.400	26.400	GYD_GC+DROP+OH	Heads CC 9_4 Fed Com 38H / Oxy Heads CC 9_4 Fed Com 38H Gyro+MWD 0' to 20872MD						
	1	555.100	20872.000	Act Stns	26.400	26.400	A010Mb_MWD+IFR1+SAG+MS	Heads CC 9_4 Fed Com 38H / Oxy Heads CC 9_4 Fed Com 38H Gyro+MWD 0' to 20872MD						

Intent ☐ As Drilled ☐

API #		
Operator Name:	Property Name:	Well Number

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018

Well Name: HEADS CC 9-4 FEDERAL COM	Well Location: T24S / R29E / SEC 16 / NWNE / 32.222236 / -103.986351	County or Parish/State: EDDY / NM
Well Number: 38H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM99034	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001547587	Well Status: Producing Oil Well	Operator: OXY USA INCORPORATED

Subsequent Report

Sundry ID: 2713681	
Type of Submission: Subsequent Report	Type of Action: Workover Operations
Date Sundry Submitted: 02/01/2023	Time Sundry Submitted: 06:49
Date Operation Actually Began: 09/29/2022	

Actual Procedure: RUPU 09/29/22, RIH & clean out to PBTD @ 20829', pressure test casing to 6000# for 30 min, good test. RIH & perf @ 10666-20739' Total 1230 holes. Frac in 41 stages w/ 278849BBL Produced Water + 179132BBL Brackish Water (> 1,000 mg/I TDS and 10,000 mg/I TDS) w/ 25700000# sand, RD NexTier 10/17/22. Well ready to produce 10/24/22. 01/14/23 RIH with 2-7/8" L80 tbg & gas lift set @ 9696', RD 01/15/23. Formation Tops for this completion are as follows: RUSTLER 245'M 245'V SALADO 629'M 629'V CASTILE 1329'M 1329'V DELAWARE 2927'M 2927'V BELL CANYON 2958'M 2958'V CHERRY CANYON 3805'M 3805'V BRUSHY CANYON 5038'M 5038'V BONE SPRING 6630'M 6630'V 1ST BONE SPRING 7643'M 7643'V 2ND BONE SPRING 8464'M 8441'V 3RD BONE SPRING 9630'M 9569'V WOLFCAMP 10005'M 9912'V

Received by OCD: 6/4/2023 10:03:55 PM

Page 9 of 14

Well Name: HEADS CC 9-4 FEDERAL COM	Well Location: T24S / R29E / SEC 16 / NWNE / 32.222236 / -103.986351	County or Parish/State: EDDY / NM
Well Number: 38H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM99034	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001547587	Well Status: Producing Oil Well	Operator: OXY USA INCORPORATED

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a


Operator Electronic Signature: JANA MENDIOLA	Signed on: FEB 01, 2023 06:48 PM
Name: OXY USA INCORPORATED	
Title: Regulatory Coordinator	
Street Address: PO BOX 50250	
City: Midland	State: TX
Phone: (432) 685-5936	
Email address: Janalyn_mendiola@oxy.com	

Field

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: JONATHON W SHEPARD	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5752345972	BLM POC Email Address: jshepard@blm.gov
Disposition: Accepted	Disposition Date: 03/16/2023
Signature: Jonathon Shepard	

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised April 3, 2017					
WELL COMPLETION OR RECOMPLETION REPORT AND LOG								1. WELL API NO. 30-015-47587		
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name HEADS CC 9-4 FEDERAL COM		
								6. Well Number: 38H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator: OXY USA INC.						9. OGRID: 16696				
10. Address of Operator: P.O. BOX 50250 MIDLAND, TX 79710						11. Pool name or Wildcat PURPLE SAGE WOLFCAMP				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	B	16	24S	29E		960	NORTH	1680	EAST	EDDY
BH:	B	4	24S	29E	L2	63	NORTH	1505	EAST	EDDY
13. Date Spudded 06/18/2022	14. Date T.D. Reached 09/08/2022		15. Date Rig Released 09/10/2022			16. Date Completed (Ready to Produce) 10/24/2022		17. Elevations (DF and RKB, RT, GR, etc.) 2927' GL		
18. Total Measured Depth of Well 20872'M 10141'V			19. Plug Back Measured Depth 20829'M 10140'V			20. Was Directional Survey Made? YES		21. Type Electric and Other Logs Run CBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 10666-20739' WOLFCAMP										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
13.375" J55		54.5		593'		17.5"		2095sx-surf circ		
9.625" HCL80		40		9719'		12.25"		3600sx-surf circ		
7" x 5.5" P110		32#, 20#		20850'		8.75" x 8.5"		877sx-TOC@5483'		
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET	PACKER SET		
						2.875"	9696'			
26. Perforation record (interval, size, and number) Perf @ 10666-20739' Total 1230 holes, Hole Size=0.42						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						10666-20739'		278849BBL Produced Water + 179132BBL Brackish Water (> 1,000 mg/l TDS and < 10,000 mg/l TDS) w/ 25700000# sand		
28. PRODUCTION										
Date First Production 10/27/2022		Production Method (Flowing, gas lift, pumping - Size and type pump) Gas Lift				Well Status (Prod. or Shut-in) Prod.				
Date of Test 12/09/2022	Hours Tested 24 hrs.	Choke Size 128/128	Prod'n For Test Period	Oil - Bbl 3537	Gas - MCF 5061	Water - Bbl. 5897	Gas - Oil Ratio 1431			
Flow Tubing Press.	Casing Pressure 673	Calculated 24- Hour Rate	Oil - Bbl. 3537	Gas - MCF 5061	Water - Bbl. 5897	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD								30. Test Witnessed By		
31. List Attachments WBD										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:		
34. If an on-site burial was used at the well, report the exact location of the on-site burial: Latitude _____ Longitude _____ NAD83										
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Printed										
Signature: 		Name: <u>Jana Mendiola</u>			Title: <u>Sr. Regulatory Analyst</u>			Date: <u>02/08/2023</u>		
E-mail Address: <u>janalyn_mendiola@oxy.com</u>										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Rustler 245'	T. Bell Canyon 2958'	T. Ojo Alamo	T. Penn A"
T. Salado 629'	T. Strawn	T. Kirtland	T. Penn. "B"
T. Castile 1329'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Delaware 2927'	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. Cherry Canyon 3805'	T. Devonian	T. Cliff House	T. Leadville
T. Brushy Canyon 5038'	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Spring 6630'	T. Todilto	
T. Abo	T. 1 st Bone Spring 7643'	T. Entrada	
T. Wolfcamp 10005'	T. 2 nd Bone Spring 8464'	T. Wingate	
T. Penn	T. 3 rd Bone Spring 9630'	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.


No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

OXY USA Inc.
Heads CC 9-4 Federal Com 38H
API No. 30-015-47587



District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 223587

ACKNOWLEDGMENTS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 223587
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 223587

CONDITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 223587
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	File 3160-4 Completion Report within 10 days to NMOCD after BLM approval.	8/17/2023