State of New Mexico	Form C-Roge 1 of 5
Office District I – (575) 393-6161 Energy, Minerals and Natural Resources	Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
District II – (575) 748-1283 OIL CONSERVATION DIVISION	30-025-27505
811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Dietrict IV - (505) 476-3460 Santa Fe, NM 87505	STATE X FEE
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	6. State Oil & Gas Lease No.
87505	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	IIId Cdada
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Harton State 8. Well Number 002
1. Type of Well: Oil Well X Gas Well Other	
2. Name of Operator	9. OGRID Number
John R. Stearns dba Stearns	330352 10. Pool name or Wildcat
3. Address of Operator	West Sawyer; San Andres
HC65 Box 988, Crossroads, NM 88114	1,000
4. Well Location Unit Letter N : 660 feet from the South line and	1980 feet from theWestline
Omt Dettol 1	NMPM Lea County
Section 32 Township 9S Range 37E 11. Elevation (Show whether DR, RKB, RT, GR, etc.,	
11. Elevation (Snow whether DR, RRB, RT, OR, etc.)	
· ·	
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTERNIOR FOR	SEQUENT REPORT OF: K □ ALTERING CASING □
PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WOR	
TEMPOTATION CONTROL CO	ELINO OF NO.
POLE ON ALTER OAGING	1 000
DOWNHOLE COMMINGLE	
OTHER: OTHER:	
12. Describe proposed or completed operations. (Clearly state all pertinent details, an	d give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Co.	mpletions: Attach wellbore diagram of
proposed completion or recompletion.	
SEE ATTACHED	
I hereby certify that the information above is true and complete to the best of my knowledge	ge and belief.
Thereby certify that the information decrease in the same in the s	
11 AA Ph. i. Co.	DATE 8/20/2 3
Type or print name Bobby Steams E-mail address: bobysteams	DATE 8/20/20
Robber Steam & Emoil address Laborateras	1= 46 has com PHONE: 575-760-2482
Type or print name Pobly Steams E-mail address: 6080y31eams	74.00.00
roi state use univ	_
APPROVED BY: Accepted for record –NMOCD gc9/6/2023	DATE
Conditions of Approval (if any):	_

Plugging Report Harton State #2 30-025-27505

5/3/2023 Rig up, unseat pump and POOH with rods. 33 triples, backoff tool, pump and 8' gas anchor. Pump stuck open.

5/4/2023 Install BOP. POOH with tubing. Tubing was in bad shape from microbe contamination. Laid down tubing and RIH with rods from the derrick and left swinging in the hole. Wrote procedures, uploaded and notified NMOCD of plans to plug and abandon.

5/5/2023 Laid down rods. Moved rods and tubing off location. Removed fence from the west side of location to make room for plugging equipment.

5/8/2023 Got approved NOI for plugging. Made gauge ring run and set 4 ½" CIBP at 4815'. Tagged with tubing. Circulated MLF and tested casing to 550#. Casing good. Spot 25 sx Class C cement on top of CIBP. POOH to 3108' and spot 25 sx cement. POOH and SION.

Tagged cement at 2741'. Perforated at 485'. Pressured up on perforations to 750# and held. There was existing cement in both surface connections of the wellhead. RIH with tubing to 539' and circulated cement to surface with 35 sx cement. Rigged down and removed the wellhead. Good cement to surface in both strings of casing. Installed below ground marker. Removed the anchors and cleaned the pit.

Harton State #2 API 30-025-27505 WBD After PA 8 5/8" 32# casing set at 435" Cemented w/300 sx TOC @ Surface Perforate at 485'. Could not pump into perfortions. Circulated cement to surface with 35 sx cement from 539' Yates 2893' Spot 25 sx cement across DV Tool and top of Yates from 3100' DV Tool at 3050' Tagged at 2741' 4.5" CIBP at 4815' with 25 sx cement on top 4 1/2" 11.6# casing at 4895' Cemented w/1315 sx cement Open hole 4895' to 5052'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 261558

COMMENTS

Operator:	OGRID:
STEARNS	21566
HC 65 Box 900	Action Number:
Crossroads, NM 88114	261558
	Action Type:
	[C-103] Sub. Plugging (C-103P)

COMMENTS

Created By		Comment Date
plmartinez	DATA ENTRY PM	9/6/2023

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 261558

CONDITIONS

Operator:	OGRID:
STEARNS	21566
HC 65 Box 900	Action Number:
Crossroads, NM 88114	261558
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By		Condition Date
gcordero	None	9/6/2023