

Submit Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-22647
5. Indicate Type of Lease
STATE [] FEE [x]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name
Pardue Farms '26'
8. Well Number
2
9. OGRID Number
241333
10. Pool name or Wildcat
S. Culebra Bluff Bone Spring
11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,022.5' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)
1. Type of Well: Oil Well [x] Gas Well [] Other []
2. Name of Operator
Chevron Midcontinent, L.P.
3. Address of Operator
6301 Deauville Blvd Midland, Texas 79706
4. Well Location
Unit Letter D : 760 feet from the North line and 990 feet from the West line
Section 26 Township 23-S Range 28-E NMPM County Eddy
11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,022.5' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON [x]
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []
OTHER: []
Notify OCD 24 hrs. prior to any work done

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Run CBL

Please see attached procedure for well abandonment details.

SEE CHANGES TO PROCEDURE

Spud Date: 8/9/1978

Rig Release Date:

SEE ATTACHED COA's

MUST BE PLUGGED BY 6/1/24

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Torres TITLE P&A Engineer DATE 8/24/2023

Type or print name Mark Torres E-mail address: marktorres@chevron.com PHONE: 989-264-2525

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 9/12/23

Conditions of Approval (if any):

Plugging Plan

- 1 MIRU, pull rods and tubing. A. Set CIBP @6350' w 25 sx cmt - WOC & tag - T BS
- 2 Set CIBP within 100' of top perf at 5,916'
- 3 Spot 25 sx Class C f/ 5,916' - 5,556' (WOC/tag, pressure test barrier)
- 4 Spot 25 sx Class C f/ 4,725' - 4,365' (Brushy Canyon)
- 5 Perf & Squeeze 50 sx Class C f/ 3,463' - 3,258' (Cherry Canyon)
Pressure test barrier
- 6 Perf & Squeeze 150 sx Class C f/ 2,647' - 2,027' (Bell Canyon, Base of Salt, 8-5/8" shoe)
Pressure test barrier
- 7 Cut and pull 4-1/2" production casing from 1,500'
- 8 Spot 58 sx Class C f/ 1,550' - 1,300'
WOC, tag, pressure test barrier - min. plug length 50' above and below casing stub
- 9 Bubble test 8-5/8" and all annuli. Notify NMOCD of any fails and address as needed.
- 10 Spot 136 sx Class C f/ 500' - 0'
Confirm cement to surface in all annuli
- 11 RDMO

CURRENT WELLBORE DIAGRAM

FIELD: Culebra Bluff, Bone Spring, South
 LEASE/UNIT: Pardue Farms '26'
 WELL NO.: 2
 COUNTY: Eddy ST: New Mexico
 LOCATION: 760' FNL & 990' FWL, Sec. 26, T-23S, R-28E

API NO.: 30-015-22647
 CHEVNO:
 PROD FORMATION:
 STATUS: SI Oil Well

Spud Date: 8/9/1978
 TD Date: 10/17/1980
 Comp Date:
 GL: 3,022.5'
 KB:

Base of Fresh Water: 100'
POTASH: NO

Surface Casing


Size: 13-3/8"
 Wt., Grd.: 48# H40 ST&C
 Depth: 370'
 Sxs Cmt: 425
 Circulate: Yes, 40 sx
 TOC: Surf
 Hole Size: 17-1/2"

Intermediate Casing

Size: 8-5/8"
 Wt., Grd.: 24# K-55 ST&C
 Depth: 2,599'
 Sxs Cmt: 1000 sx
 Circulate: Yes, 50 sx
 TOC: Surf
 Hole Size: 11"

Production Casing

Size: 4-1/2"
 Wt., Grd.: 10.5# & 11.6#
 Depth: 6,855'
 Sxs Cmt: 850 sx
 Circulate: No
 TOC: 4,290' via TS
 Hole Size: 7-7/8"



TOC @ 4,290' via Temp Survey

Formation	Top (MD)
Top of Salt	Surface
Base of Salt	2,611'
Lamar Limestone	2,611'
Bell Canyon	2,647'
Cherry Canyon	3,463'
Brushy Canyon	4,725'
Bone Spring	6,256'
Avalon	6,303'

Tubing Components							
Item Des	Jts	OD (in)	ID (in)	Wt (lb/ft)	Grade	Len (ft)	Btm (ftKB)
TBG J-55 6.5#	181	2 7/8	2.441	6.50	J-55	5,780.08	5,791.1
MARKER SUB	1	2 7/8	2.441	6.50	J-55	4.10	5,795.2
TBG J-55 6.5#	2	2 7/8	2.441	6.50	J-55	64.28	5,859.5
TAC	1	2 7/8	2.441			2.70	5,862.2
TBG J-55 6.5#	17	2 7/8	2.441	6.50	J-55	540.60	6,402.8
ENDURO	1	2 7/8	2.441	6.50	J-55	31.34	6,434.2
MSN	1	2 7/8	2.441			1.10	6,435.3
TBG SUB J-55 6.5#	1	2 7/8	2.441	6.50	J-55	4.10	6,439.4
CAVINS DESANDER (D2301-G)	1	2 7/8	2.441			19.28	6,458.6
MUD JOINT	1	2 7/8	2.441			32.27	6,490.9
DUMP VALVE	1	2 7/8	2.441			0.50	6,491.4

Rod Strings: Rods, Run Date: 6/3/2016				
Rod Description	Run Date	Set Depth (ftKB)	Pull Date	Len (ft)
Rods	6/3/2016	6,425.0		6,425.00

Rod Components					
Item Des	OD (in)	Wt (lb/ft)	Grade	Len (ft)	Btm (ftKB)
POLISH ROD	1 1/2		C	26.00	26.0
RODS	7/8		KD	2,350.00	2,376.0
RODS	3/4		KD	3,725.00	6,101.0
C-BARS	1 1/2		KD	300.00	6,401.0
GUIDED SUB	3/4		KD	4.00	6,405.0
20-125-RHBM-4-20-16	2			20.00	6,425.0

Perforations

Brushy Canyon Perfs
6,016' - 6,232'

Bone Springs Perfs
6,406' - 6,676'

6,790' PBDT
7,063' TD

H2S Concentration >100 PPM? YES
NORM Present in Area? NO

PROPOSED WELLBORE DIAGRAM

FIELD: Culebra Bluff, Bone Spring, South
 LEASE/UNIT: Pardue Farms '26'
 WELL NO.: 2
 COUNTY: Eddy ST: New Mexico
 LOCATION: 760' FNL & 990' FWL, Sec. 26, T-23S, R-28E

API NO.: 30-015-22647
 CHEVNO:
 PROD FORMATION:
 STATUS: SI Oil Well
 Spud Date: 8/9/1978
 TD Date: 10/17/1980
 Comp Date:
 GL: 3,022.5'
 KB:

Base of Fresh Water: 100'
POTASH: NO

Surface Casing

Size: 13-3/8"
 Wt., Grd.: 48# H40 ST&C
 Depth: 370'
 Sxs Cmt: 425
 Circulate: Yes, 40 sx
 TOC: Surf
 Hole Size: 17-1/2"

Isolate 13-3/8" shoe, Base of Fresh Water (WSEA 10-E)
 6 Spot 136 sx Class C f/ 500' - 0'
 Verify cement to surface

Intermediate Casing

Size: 8-5/8"
 Wt., Grd.: 24# K-55 ST&C
 Depth: 2,599'
 Sxs Cmt: 1000 sx
 Circulate: Yes, 50 sx
 TOC: Surf
 Hole Size: 11"

Cut/Pull 4-1/2" f/ 1,500' (WSEA 10-D)
 5 Spot 58 sx Class C f/ 1,550' - 1,300'
 WOC/tag and pressure test barrier (min. 50' above cut depth)

Production Casing

Size: 4-1/2"
 Wt., Grd.: 10.5# & 11.6#
 Depth: 6,855'
 Sxs Cmt: 850 sx
 Circulate: No
 TOC: 4,290' via TS
 Hole Size: 7-7/8"

Isolate Bell Canyon, Base of Salt, 8-5/8" shoe (WSEA 10-C)
 4 Perf & Squeeze 150 sx Class C f/ 2,647' - 2,027'
 WOC/tag and pressure test barrier (min. 100' above 8-5/8" shoe)

Isolate Cherry Canyon
 3 Perf & Squeeze 50 sx Class C f/ 3,463' - 3,258'
 Pressure test

TOC @ 4,290' via Temp Survey

Isolate Brushy Canyon
 2 Spot 25 sx Class C f/ 4,725' - 4,365'

Formation	Top (MD)
Top of Salt	Surface
Base of Salt	2,611'
Lamar Limestone	2,611'
Bell Canyon	2,647'
Cherry Canyon	3,463'
Brushy Canyon	4,725'
Bone Spring	6,256'
Avalon	6,303'

Isolate Perfs (WSEA 10-B)
 1 Set CIBP at 5,916' and spot 25 sx Class C f/ 5,916' - 5,556'
 WOC/tag and pressure test barrier (min. 100' plug length)

Brushy Canyon Perfs
 6,016' - 6,232'

Bone Springs Perfs
 6,406' - 6,676'

6,790' PBTD
 7,063' TD

**H2S Concentration >100 PPM? YES
 NORM Present in Area? NO**

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD at 575-626-0830 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Cherry Canyon - Eddy County
 - L) **Potash**---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3.API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 257326

CONDITIONS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 257326
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	9/12/2023