Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 327674 District II 811 S. First St., Artesia, NM 88210 WELL APLNIIMBER Oil Conservation Division Phone:(575) 748-1283 Fax:(575) 748-9720 30-015-48982 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Private Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS PLINY THE ELDER FEE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number Gas 232H 9. OGRID Number 2. Name of Operator TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location Unit Letter  $\,D\,$  : 1027  $\,$  feet from the  $\,$ N line and feet 355 from the W Township 23S Range 27E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3148 GR Pit or Below-grade Tank Application or Closure \_\_ Depth to Groundwater\_\_\_ \_\_\_ Distance from nearest fresh water well \_ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume\_ Pit Liner Thickness: bbls: Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 9/9/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Dpth Yield Open Size Туре Size lb/ft TOC Held Drop Hole 09/10/22 Surf FreshWater 17.5 13.375 54.5 J55 0 601 620 1.34 С 1500 0 Ν 09/21/22 Int1 Brine 9.875 7.625 27.9 P110 0 9071 965 1.67 С 2000 0 Ν 10/02/22 P110 Prod OilBasedMud 6.75 5.5 20 5600 19811 1205 1.23 С Ν I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines  $\square$ , a general permit  $\square$  or an (attached) alternative OCD-approved plan  $\square$ SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 10/19/2022 Type or print name Christian Combs E-mail address Telephone No. 720-360-4028 ccombs@taprk.com For State Use Only:

TITLE

DATE

9/14/2023 10:29:00 AM

Patricia L Martinez

APPROVED BY:

Pliny the Elder Fee 232H Intermediate and Production Casing

9/17/2022: Test BOPS. Drill 9.875 intermediate hole to 9128 ft.

9/21/2022: Run 7.625 inch 29.7 lb P-110 intermediate casing to 9071 ft. Pump 25 bbls fresh water, followed by 725 sks of 10.5 ppg lead cmt, 240 sks of 13.2 ppg tail cmt. Drop plug and displace with 414 bbls fresh water. 160 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 2000 for 30 minutes, good test.

9/21/2022: Drill 6.75 inch production hole to 19830 ft.

10/2/2022: Run 5.5 inch 20 lb P-110 production casing to 19811 ft MD. Pump 40 bbls fresh water spacer, then 1205 sks of 14.5 ppg tail cmt. Drop plug and displace with 20 bbls sugar water, 390 bbls brine and 28 bbls fresh water. 0 bbls returned to surface. Est TOC at 5600 ft.

Intermediate Casing Details: Casing ran: 9/21/2022, Fluid Type Brine, Hole 9.875 inch to 9128 ft, Csg Size 7.625 inch, Weight 29.7 lbs, Grade P-110, Est TOC 0 ft, Depth set 9071 ft, Cement 965 sks, Yield 4.33 lead/1.67 tail, Class C, Pressure Held 2000 psi, Pres Drop 0.

Production Casing details: Casing Date: 10/2/2022, Fluid Type Oil Based Mud, Hole 6.75 inch to 19830 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 19811 ft, EST TOC 5600 ft, Cement 1205 sacks, yield 1.23 tail, Class C.

10/1/2022: TD Reached at 19830 ft MD, 9294 ft TVD. Plug Back Measured depth at 19765 ft MD, 9296 ft TVD. Rig Release on 10/4/2022 at 13:30.