Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 327636 District II 811 S. First St., Artesia, NM 88210 WELL APLNIIMBER Oil Conservation Division Phone:(575) 748-1283 Fax:(575) 748-9720 30-025-50363 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 State Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS HYPERION STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number Oil 154H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location <u>A</u> : <u>599</u> feet from the N Unit Letter A line and feet 727 from the E 33E NMPM Section Township 24S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3562 GR Pit or Below-grade Tank Application or Closure \_\_\_ Distance from nearest fresh water well\_\_ \_\_ Depth to Groundwater\_\_\_ \_ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume\_ Pit Liner Thickness: bbls: Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 9/18/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Dpth Yield Open Size Туре Size lb/ft TOC Held Drop Hole 09/20/22 Surf FreshWater 17.5 13.375 54.5 J55 0 1322 995 1.36 С 1500 0 Ν 10/06/22 Int1 Brine 12.25 9.625 40 J55 0 5247 1145 1.33 С 1600 0 Ν 10/15/22 20 P110 Prod OilBasedMud 6.75 5.5 1946 16493 1245 1.47 С Ν I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines  $\square$ , a general permit  $\square$  or an (attached) alternative OCD-approved plan  $\square$ SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 11/16/2022 Type or print name Christian Combs E-mail address Telephone No. 720-360-4028 ccombs@taprk.com

TITLE

DATE

9/14/2023 12:02:06 PM

Patricia L Martinez

For State Use Only:

APPROVED BY:

Hyperion State Com 154H Intermediate and Production Casing

10/5/2022: Test BOPS. Drill 12.25 intermediate hole to 5262 ft.

10/6/2022: Run 9.625 inch 40 lb J-55 intermediate casing to 5247 ft. Pump 20 bbls fresh water, followed by 825 sks of 11.0 ppg lead cmt, 320 sks of 14.8 ppg tail cmt. Drop plug and displace with 394 bbls fresh water. 84 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1600 for 30 minutes, good test.

10/8/2022: Drill 8.75 inch production hole to 10965 ft then switch to 6.75 in hole to 16508 ft.

10/15/2022: Run 5.5 inch 20 lb P-110 production casing to 16493 ft MD. Pump 20 bbls gel spacer, then 505 sks of 10.5 lead cmt, 740 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls sugar water and 343 bbls fresh water. 0 bbls returned to surface. Est TOC at 1946 ft.

Intermediate Casing Details: Casing ran: 10/6/2022, Fluid Type Brine, Hole 12.25 inch to 5262 ft, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 5247 ft, Cement 1145 sks, Yield 2.50 lead/1.33 tail, Class C, Pressure Held 1600 psi, Pres Drop 0.

Production Casing details: Casing Date: 10/15/2022, Fluid Type Oil Based Mud, Hole 8.75 inch to 10965, 6.75 inch to 16508 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 16493 ft, EST TOC 1946 ft, Cement 1245 sacks, yield 3.35 lead/1.47 tail, Class C.

10/14/2022: TD Reached at 16508 ft MD, 11513 ft TVD. Plug Back Measured depth at 16444 ft MD, 11511 ft TVD. Rig Release on 10/15/2022 at 22:00.