

Form 3160-3
(June 2015)

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		5. Lease Serial No. 6. If Indian, Allottee or Tribe Name 7. If Unit or CA Agreement, Name and No. 8. Lease Name and Well No.
2. Name of Operator		9. API Well No. 30-025-52502
3a. Address	3b. Phone No. (include area code)	10. Field and Pool, or Exploratory
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface At proposed prod. zone		11. Sec., T. R. M. or Blk. and Survey or Area
14. Distance in miles and direction from nearest town or post office*		12. County or Parish 13. State
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No of acres in lease	17. Spacing Unit dedicated to this well
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth	20. BLM/BIA Bond No. in file
21. Elevations (Show whether DF, KDB, RT, GL, etc.)	22. Approximate date work will start*	23. Estimated duration
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|---|---|
| 1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification.
6. Such other site specific information and/or plans as may be requested by the BLM. |
|---|---|

25. Signature	Name (Printed/Typed)	Date
Title		
Approved by (Signature)	Name (Printed/Typed)	Date
Title		Office

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
 Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



(Continued on page 2)

*(Instructions on page 2)

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (505) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-025-52502		² Pool Code 50461		³ Pool Name QUAIL RIDGE; BONE SPRING, SOUTH	
⁴ Property Code 335232		⁵ Property Name LOOSEY GOOSEY 4-9 FED COM		⁶ Well Number 302H	
⁷ OGRID No. 215099		⁸ Operator Name CIMAREX ENERGY CO.		⁹ Elevation 3659.8'	

¹⁰ Surface Location


UL or lot no. N	Section 33	Township 19S	Range 34E	Lot Idn	Feet from the 1189	North/South line SOUTH	Feet from the 1484	East/West line WEST	County LEA
--------------------	---------------	-----------------	--------------	---------	-----------------------	---------------------------	-----------------------	------------------------	---------------

¹¹ Bottom Hole Location If Different From Surface

UL or lot no. N	Section 9	Township 20S	Range 34E	Lot Idn	Feet from the 100	North/South line SOUTH	Feet from the 2120	East/West line WEST	County LEA
--------------------	--------------	-----------------	--------------	---------	----------------------	---------------------------	-----------------------	------------------------	---------------

¹² Dedicated Acres 320.44	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
---	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



¹⁷ OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Brittany Gordon 7/28/2023
Signature Date
Brittany Gordon
Printed Name
brittany.gordon@coterra.com
E-mail Address

¹⁸ SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

November 02, 2021
Date of Survey
Signature and Seal of Professional Surveyor:



Certificate Number:

State of New Mexico
Energy, Minerals and Natural Resources Department

Submit Electronically
Via E-permitting

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description Effective May 25, 2021

I. Operator: Cimarex Energy Company **OGRID:** 215099 **Date:** 1/29/24

II. Type: Original Amendment due to 19.15.27.9.D(6)(a) NMAC 19.15.27.9.D(6)(b) NMAC Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Loosey Goosey 4-9 Fed Com	302H	N, Sec 33 T19S, R34E	1189 FSL/ 1484	FWL 1589	1455	2845

IV. Central Delivery Point Name: Loosey Goosey CTB [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Loosey Goosey 4-9 Fed Com	302H	11/10/2024	1/14/2025	1/20/2025	3/1/2025	3/1/2025

VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: Attach a complete description of Operator’s best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan
EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system will will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator does does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

Attach Operator’s plan to manage production in response to the increased line pressure.

XIV. Confidentiality: Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	<i>Sarah Jordan</i>
Printed Name:	Sarah Jordan
Title:	Regulatory Analyst
E-mail Address:	sarah.jordan@coterra.com
Date:	1/29/24
Phone:	432/620-1909

OIL CONSERVATION DIVISION
(Only applicable when submitted as a standalone form)

Approved By:
Title:
Approval Date:
Conditions of Approval:

From State of New Mexico, Natural Gas Management Plan

VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.

XEC Standard Response

Standard facility gas process flow begins at the inlet separator. These vessels are designed based off of forecasted rates and residence times in accordance with, and often greater than, API 12J. The separated gas is then routed to an additional separation vessel (ie sales scrubber) in order to extract liquids that may have carried over or developed due to the decrease in pressure. The sales scrubber is sized based on API 521. From the sales scrubber, the gas leaves the facility and enters the gas midstream gathering network.

Cimarex

VII. Operational Practices

Cimarex values the sustainable development of New Mexico's natural resources. Venting and flaring of natural gas is a source of waste in the industry, and Cimarex will ensure that its values are aligned with those of NMOCD. As such, Cimarex plans to take pointed steps to ensure compliance with Subsection A through F of 19.15.27.8 NMAC.

Specifically, below are the steps Cimarex will plan to follow under routine well commissioning and operations.

1. Capture or combust natural gas during drilling operations where technically feasible, using the best industry practices and control technologies.
 - a. All flares during these operations will be a minimum of 100ft away from the nearest surface-hole location.
2. All gas present during post-completion drill-out and flow back will be routed through separation equipment, and, if technically feasible, flare unsellable vapors rather than vent. Lastly, formal sales separator commissioning to process well-stream fluids and send gas to a gas flow line/collection system or use the gas for on-site fuel or beneficial usage, gas as soon as is safe and technically feasible.
3. Cimarex will ensure the flare or combustion equipment is properly sized to handle expected flow rates, ensure this equipment is equipped with an automatic or continuous ignition source, and ensure this equipment is designed for proper combustion efficiency.
4. If Cimarex must flare because gas is not meeting pipeline specifications, Cimarex will limit flaring to <60 days, analyze gas composition at least twice per week, and route gas into a gathering pipeline as soon as pipeline specifications are met.
5. Under routine production operations, Cimarex will not flare/vent unless:
 - a. Venting or flaring occurs due to an emergency or equipment malfunction.
 - b. Venting or flaring occurs as a result of unloading practices, and an operator is onsite (or within 30 minutes of drive time and posts contact information at the wellsite) until the end of unloading practice.
 - c. The venting or flaring occurs during automated plungerlift operations, in which case the Cimarex operator will work to optimize the plungerlift system to minimize venting/flaring.
 - d. The venting or flaring occurs during downhole well maintenance, in which case Cimarex will work to minimize venting or flaring operations to the extent that it does not pose a risk to safe operations.
 - e. The well is an exploratory well, the division has approved the well as an exploratory well, venting or flaring is limited to 12 months, as approved by the division, and venting/flaring does not cause Cimarex to breach its State-wide 98% gas capture requirement.
 - f. Venting or flaring occurs because the stock tanks or other low-pressure vessels are being gauged, sampled, or liquids are being loaded out.
 - g. The venting or flaring occurs because pressurized vessels are being maintained and are being blown-down or depressurized.
 - h. Venting or flaring occurs as a result of normal dehydration unit operations.

- i. Venting or flaring occurs as a result of bradenhead testing.
 - j. Venting or flaring occurs as a result of normal compressor operations, including general compressor operations, compressor engines and turbines.
 - k. Venting or flaring occurs as a result of a packer leakage test.
 - l. Venting or flaring occurs as a result of a production test lasting less than 24 hours unless otherwise approved by the division.
 - m. Venting or flaring occurs as a result of new equipment commissioning and is necessary to purge impurities from the pipeline or production equipment.
6. Cimarex will maintain its equipment in accordance with its Operations and Maintenance Program, to ensure venting or flaring events are minimized and that equipment is properly functioning.
7. Cimarex will install automatic tank gauging equipment on all production facilities constructed after May 25, 2021, to ensure minimal emissions from tank gauging practices.
8. By November 25, 2022, all Cimarex facilities equipped with flares or combustors will be equipped with continuous pilots or automatic igniters, and technology to ensure proper function, i.e. thermocouple, fire-eye, etc...
9. Cimarex will perform AVO (audio, visual, olfactory) facility inspections in accordance with NMOCD requirements. Specifically, Cimarex will:
 - a. Perform weekly inspections during the first year of production, and so long as production is greater than 60 MCFD.
 - b. If production is less than 60 MCFD, Cimarex will perform weekly AVO inspections when an operator is present on location, and inspections at least once per calendar month with at least 20 calendar days between inspections.
10. Cimarex will measure or estimate the volume of vented, flared or beneficially used natural gas, regardless of the reason or authorization for such venting or flaring.
11. On all facilities constructed after May 25, 2021, Cimarex will install metering where feasible and in accordance with available technology and best engineering practices, in an effort to measure how much gas could have been vented or flared.
 - a. In areas where metering is not technically feasible, such as low-pressure/low volume venting or flaring applications, engineering estimates will be used such that the methodology could be independently verified.
12. Cimarex will fulfill the division's requirements for reporting and filing of venting or flaring that exceeds 50 MCF in volume or last eight hours or more cumulatively within any 24-hour period.

VIII. Best Management Practices to minimize venting during active and planned maintenance

Cimarex strives to ensure minimal venting occurs during active and planned maintenance activities. Below is a description of common maintenance practices, and the steps Cimarex takes to limit venting exposure.

- **Workovers:**
 - Always strive to kill well when performing downhole maintenance.
 - If vapors or trapped pressure is present and must be relieved then:
 - Initial blowdown to production facility:
 - Route vapors to LP flare if possible/applicable
 - Blowdown to portable gas buster tank:
 - Vent to existing or portable flare if applicable.

- **Stock tank servicing:**
 - Minimize time spent with thief hatches open.
 - When cleaning or servicing via manway, suck tank bottoms to ensure minimal volatiles exposed to atmosphere.
 - Connect vacuum truck to low pressure flare while cleaning bottoms to limit venting.
 - Isolate the vent lines and overflows on the tank being serviced from other tanks.

- **Pressure vessel/compressor servicing and associated blowdowns:**
 - Route to flare where possible.
 - Blow vessel down to minimum available pressure via pipeline, prior to venting vessel.
 - Preemptively changing anodes to reduce failures and extended corrosion related servicing.
 - When cleaning or servicing via manway, suck vessel bottoms to ensure minimal volatiles exposed to atmosphere.

- **Flare/combustor maintenance:**
 - Minimize downtime by coordinating with vendor and Cimarex staff travel logistics.
 - Utilizing preventative and predictive maintenance programs to replace high wear components before failure.
 - Because the flare/combustor is the primary equipment used to limit venting practices, ensure flare/combustor is properly maintained and fully operational at all times via routine maintenance, temperature telemetry, onsite visual inspections.

The Cimarex expectation is to limit all venting exposure. Equipment that may not be listed on this document is still expected to be maintained and associated venting during such maintenance minimized.

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Cimarex
LEASE NO.:	NMLC065607
LOCATION:	Section 33, T.19 S, R.34 E., NMPM
COUNTY:	Lea County, New Mexico
WELL NAME & NO.:	Loosey Goosey 4-9 Fed Com 302H
SURFACE HOLE FOOTAGE:	1189'/S & 1448'/W
BOTTOM HOLE FOOTAGE:	100'/S & 2120'/W

COA

H₂S	<input checked="" type="radio"/> Yes	<input type="radio"/> No		
Potash / WIPP	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P	<input type="checkbox"/> WIPP
Cave / Karst	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High	<input type="radio"/> Critical
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both	<input type="radio"/> Diverter
Cementing	<input type="checkbox"/> Primary Squeeze	<input type="checkbox"/> Cont. Squeeze	<input type="checkbox"/> EchoMeter	<input type="checkbox"/> DV Tool
Special Req	<input type="checkbox"/> Break Testing	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit
Variance	<input checked="" type="checkbox"/> Flex Hose	<input type="checkbox"/> Casing Clearance	<input type="checkbox"/> Pilot Hole	<input checked="" type="checkbox"/> Capitan Reef
Variance	<input type="checkbox"/> Four-String	<input checked="" type="checkbox"/> Offline Cementing	<input checked="" type="checkbox"/> Fluid-Filled	<input type="checkbox"/> Open Annulus
<input type="checkbox"/> Batch APD / Sundry				

A. HYDROGEN SULFIDE

A Hydrogen Sulfide (H₂S) Drilling Plan shall be activated 500 feet prior to drilling into the **Delaware Group and Morrow** formation. As a result, the Hydrogen Sulfide area must meet all requirements from **43 CFR 3176**, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

B. CASING

Surface casings must be kept fluid filled to meet BLM minimum collapse requirement.

1. The **13-3/8** inch surface casing shall be set at approximately **1820** feet (a minimum of **25 feet (Lea County)** into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

2. The minimum required fill of cement behind the **9-5/8** inch intermediate casing shall be set at **5600ft**:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Excess calculates to 12%. Additional cement may be required.**
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, and Capitan Reef.

 - ❖ In Capitan Reef Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.

 - ❖ **Special Capitan Reef requirements.** If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following:
(Use this for 3 string wells in the Capitan Reef, if 4 string well ensure FW based mud used across the Capitan interval)

 - Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.

 - Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.

3. The minimum required fill of cement behind the **7** inch production casing is:
 - Cement should tie-back at least **50 feet(4950ft)** on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, and Capitan Reef.

4. The minimum required fill of cement behind the **4-1/2** inch production liner is:
 - Cement should tie-back **100 feet** into the previous casing. Operator shall provide method of verification. **Excess calculates to 9%. Additional cement maybe required.**

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).
 2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one-inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172 must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- The operator will submit an as-drilled survey well plat of the well completion, but are not limited to, those specified in 43 CFR 3171 and 3172.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

Offline Cementing

Contact the BLM prior to the commencement of any offline cementing procedure.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Email **or** call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, BLM_NM_CFO_DrillingNotifications@BLM.GOV
(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,
(575) 689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per **43 CFR part 3170 Subpart 3172** as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a

digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR part 3170 Subpart 3172** and **API STD 53 Sec. 5.3**.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in **43 CFR part 3170 Subpart 3172** must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after

installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR part 3170 Subpart 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR**

part 3170 Subpart 3172.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

ZS 9/14/2023



Operator Certification Data Report

01/25/2024

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: AMITHY CRAWFORD

Signed on: 03/15/2022

Title: Regulatory Analyst

Street Address: 600 N MARIENFELD STE 600

City: MIDLAND

State: TX

Zip: 79701

Phone: (432)620-1909

Email address: AMITHY.CRAWFORD@COTERRA.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data

01/25/2024

APD ID: 10400083756

Submission Date: 03/17/2022

Highlighted data reflects the most recent changes
[Show Final Text](#)

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400083756

Tie to previous NOS? N

Submission Date: 03/17/2022

BLM Office: Carlsbad

User: AMITHY CRAWFORD

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM065607

Lease Acres:

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? Y

Permitting Agent? NO

APD Operator: CIMAREX ENERGY COMPANY

Operator letter of

Operator Info

Operator Organization Name: CIMAREX ENERGY COMPANY

Operator Address: 6001 DEAUVILLE BLVD STE 300N

Zip: 79706

Operator PO Box:

Operator City: MIDLAND

State: TX

Operator Phone: (303)295-3995

Operator Internet Address: hknaults@cimarex.com

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: Quail Ridge

Pool Name: Bone Spring

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Is the proposed well in an area containing other mineral resources? USEABLE WATER,NATURAL GAS,OIL

Is the proposed well in a Helium production area? N **Use Existing Well Pad?** N **New surface disturbance?**

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name: Loosey **Number:** E2W2

Goosey 4-9 Fed Com

Well Class: HORIZONTAL

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: 26 Miles

Distance to nearest well: 20 FT

Distance to lease line: 1189 FT

Reservoir well spacing assigned acres Measurement: 320 Acres

Well plat: Loosey_Goosey_4_9_Fed_Com_302H_C102_20230814_20230814141952.pdf

Well work start Date: 10/31/2022

Duration: 30 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number:

Reference Datum: GROUND LEVEL

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this
SHL Leg #1	1189	FSL	1484	FWL	19S	34E	33	Aliquot SESW	32.612713	-103.568946	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 94622	3659	0	0	N
KOP Leg #1	1189	FSL	1484	FWL	19S	34E	33	Aliquot SESW	32.612713	-103.568946	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 94622	-6578	10401	10237	N
PPP Leg #1-1	100	FNL	2120	FWL	20S	34E	4	Aliquot NENW	32.609173	-103.566869	LEA	NEW MEXICO	NEW MEXICO	F	NMLC0 65607	-7171	11451	10830	Y

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this
PPP Leg #1-2	264 4	FNL	213 4	FW L	20S	34E	4	Aliquot NESW	32.60218 2	- 103.5668 98	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0 64194	- 717 1	132 73	108 30	Y
EXIT Leg #1	264 4	FNL	213 4	FW L	20S	34E	4	Aliquot NESW	32.60218 2	- 103.5668 98	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0 64194	- 717 1	132 73	108 30	Y
BHL Leg #1	100	FSL	212 0	FW L	20S	34E	4	Aliquot NESW	32.60218 2	- 103.5668 98	LEA	NEW MEXI CO	NEW MEXI CO	F	NMLC0 64194	- 717 1	211 00	108 30	Y

Intent As Drilled

API #									
Operator Name:					Property Name:				Well Number

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Is this well the defining well for the Horizontal Spacing Unit?

Is this well an infill well?

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #									
Operator Name:					Property Name:				Well Number

Estimated Formation Tops

Formation:	Top:	Formation:	Top:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

01/25/2024

APD ID: 10400083756

Submission Date: 03/17/2022

Highlighted data reflects the most recent changes

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well Type: OIL WELL

Well Work Type: Drill

Show Final Text

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical	Measured Depth	Lithologies	Mineral Resources	Producing Formatio
12144260	RUSTLER	0	1543	1543	ANHYDRITE, SANDSTONE	USEABLE WATER	N
12144261	TOP SALT	-1632	1632	1632	ANHYDRITE	NONE	N
12144262	BASE OF SALT	-3225	3225	3225	ANHYDRITE	NONE	N
12144263	LAMAR	-5214	5214	5214	SANDSTONE	NONE	N
12144264	BELL CANYON	-5286	5286	5286	SANDSTONE	NONE	N
12144265	CHERRY CANYON	-5740	5740	5740	SANDSTONE	NONE	N
12144266	BRUSHY CANYON	-6672	6672	6672	SANDSTONE	NATURAL GAS, OIL	N
12144267	BONE SPRING	-8200	8200	8200	LIMESTONE	NATURAL GAS, OIL	N
12144268	BONE SPRING 1ST	-9376	9376	9376	SHALE	NATURAL GAS, OIL	N
12144269	BONE SPRING 2ND	-9928	9928	9928	SANDSTONE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Pressure Rating (PSI): 2M

Rating Depth: 5236

Equipment: A BOP consisting of three rams, including one blind ram and two pipe rams and one annular preventer. An accumulator that meets the requirements in Onshore Order #2 for the pressure rating of the BOP stack. A rotating head may be installed as needed. A Kelly clock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

Requesting Variance? YES

Variance request: Co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used. Variance to include Hammer Union connections on lines downstream of the buffer tank only.

Testing Procedure: A multi-bowl wellhead system will be utilized. After running the 13 3/8" surface casing, a 13 3/8" BOP/BOPE system with a minimum working pressure of 2000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 2000 psi test. Annular will be tested to 100%

Operator Name: CIMAREX ENERGY COMPANY**Well Name:** LOOSEY GOOSEY 4-9 FED COM**Well Number:** 302H

of working pressure. The pressure test will be repeated at least every 30 days, as per Onshore Order No. 2. The multi-bowl wellhead will be installed by vendors representative. A copy of the installation instructions has been sent to the BLM field office. The wellhead will be installed by a third-party welder, monitored by the wellhead vendor representative. All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type. A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 2000 psi. The surface casing string will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1500 psi, whichever is greater. The casing strings utilizing steel body pack-off will be tested to 70% of casing burst. If well conditions dictate conventional slips will be set and BOPE will be tested to appropriate pressures based on permitted pressure requirements.

Choke Diagram Attachment:

Loosey_Goosey_4_9_Fed_Com_302H_Choke_2M_3M_20220317084231.pdf

BOP Diagram Attachment:

Loosey_Goosey_4_9_Fed_Com_302H_BOP_2M_20220317084239.pdf

Pressure Rating (PSI): 3M**Rating Depth:** 11152

Equipment: A BOP consisting of three rams, including one blind ram and two pipe rams and one annular preventer. An accumulator that meets the requirements in Onshore Order #2 for the pressure rating of the BOP stack. A rotating head may be installed as needed. A Kelly clock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

Requesting Variance? YES

Variance request: Co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used. Variance to include Hammer Union connections on lines downstream of the buffer tank only.

Testing Procedure: A multi-bowl wellhead system will be utilized. After running the 13 3/8" surface casing, a 13 3/8 BOP/BOPE system with a minimum working pressure of 3000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 3000 psi test. Annular will be tested to 100% of working pressure. The pressure test will be repeated at least every 30 days, as per Onshore Order No. 2. The multi-bowl wellhead will be installed by vendors representative. A copy of the installation instructions has been sent to the BLM field office. The wellhead will be installed by a third-party welder, monitored by the wellhead vendor representative. All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type. A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 3000 psi. Slips will be utilized after running and cementing the production casing. After installation of the slips and wellhead on the production casing, a 13 5/8 BOP/BOPE system with a minimum working pressure of 3000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 3000 psi test. Annular will be tested to 100% of working pressure. The pressure test will be repeated at least every 30 days, as per Onshore Order No. 2. The surface casing string will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1500 psi, whichever is greater. The casing string utilizing steel body pack-off will be tested to 70% of casing burst. If well conditions dictate conventional slips will be set and BOPE will be tested to appropriate pressures based on permitted pressure requirements.

Choke Diagram Attachment:

Loosey_Goosey_4_9_Fed_Com_302H_Choke_2M_3M_20220317084254.pdf

BOP Diagram Attachment:

Loosey_Goosey_4_9_Fed_Com_BOP_3M_20220317084306.pdf

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Pressure Rating (PSI): 5M

Rating Depth: 21100

Equipment: A BOP consisting of three rams, including one blind ram and two pipe rams and one annular preventer. An accumulator that meets the requirements in Onshore Order #2 for the pressure rating of the BOP stack. A rotating head may be installed as needed. A Kelly clock will be installed and maintained in operable condition and a drill string safety valve in the open position will be available on the rig floor.

Requesting Variance? YES

Variance request: Co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. In the event the specific hose is not available, one of equal or higher rating will be used. Variance to include Hammer Union connections on lines downstream of the buffer tank only.

Testing Procedure: A multi-bowl wellhead system will be utilized. After running the 13 3/8" surface casing, a 13 3/8 BOP/BOPE system with a minimum working pressure of 5000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 5000 psi test. Annular will be tested to 100% of working pressure. The pressure test will be repeated at least every 30 days, as per Onshore Order No. 2. The multi-bowl wellhead will be installed by vendors representative. A copy of the installation instructions has been sent to the BLM field office. The wellhead will be installed by a third-party welder, monitored by the wellhead vendor representative. All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type. A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi. Slips will be utilized after running and cementing the production casing. After installation of the slips and wellhead on the production casing, a 13 5/8 BOP/BOPE system with a minimum working pressure of 5000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 5000 psi test. Annular will be tested to 100% of working pressure. The pressure test will be repeated at least every 30 days, as per Onshore Order No. 2. The surface casing string will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1500 psi, whichever is greater. The casing string utilizing steel body pack-off will be tested to 70% of casing burst. If well conditions dictate conventional slips will be set and BOPE will be tested to appropriate pressures based on permitted pressure requirements.

Choke Diagram Attachment:

Loosey_Goosey_4_9_Fed_Com_302H_Choke_5M_20220317084329.pdf

BOP Diagram Attachment:

Loosey_Goosey_4_9_Fed_Com_302H_BOP_5M_20220317084335.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1593	0	1593	3659	2066	1593	H-40	48	ST&C	1.12	2.51	BUOY	4.21	BUOY	4.21
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	5236	0	5236	3750	-1577	5236	HCK-55	40	LT&C	1.36	1.41	BUOY	2.68	BUOY	2.68
3	PRODUCTION	8.75	7.0	NEW	API	N	0	10402	0	10402	3750	-6743	10402	L-80	29	LT&C	1.44	1.68	BUOY	1.88	BUOY	1.88

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
4	PRODUCTION	8.75	7.0	NEW	API	N	10402	11152	10402	10791	-6743	-7132	750	P-110	29	BUTT	1.69	2.22	BUOY	82.35	BUOY	82.35
5	COMPLETION SYSTEM	6	4.5	NEW	API	N	9402	21100	9402	10830	-5743	-7171	11698	P-110	11.6	BUTT	1.5	2.11	BUOY	22.16	BUOY	22.16

Casing Attachments

Casing ID: 1 **String** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Loosey_Goosey_4_9_Fed_Com_302H_Casing_Assumptions_20220317084402.pdf

Casing ID: 2 **String** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Loosey_Goosey_4_9_Fed_Com_302H_Casing_Assumptions_20220317084459.pdf

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Casing Attachments

Casing ID: 3 **String** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Loosey_Goosey_4_9_Fed_Com_302H_Casing_Assumptions_20220317084420.pdf

Casing ID: 4 **String** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Loosey_Goosey_4_9_Fed_Com_302H_Casing_Assumptions_20220317084438.pdf

Casing ID: 5 **String** COMPLETION SYSTEM

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Loosey_Goosey_4_9_Fed_Com_302H_Casing_Assumptions_20220317084536.pdf

Section 4 - Cement

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
PRODUCTION	Lead		0	0	0	0	0	0	0	0	0

SURFACE	Lead		0	1593	772	1.72	13.5	1327	45	Class C	Bentonite
SURFACE	Tail		0	1593	207	1.34	14.8	277	45	Class C	LCM
INTERMEDIATE	Lead		0	5236	980	1.88	12.9	1842	53	35:65 (Poz:C)	Salt, Bentonite
INTERMEDIATE	Tail		0	5236	292	1.34	14.8	391	53	Class C	LCM
PRODUCTION	Lead		0	1115 2	327	3.64	10.3	1070	25	Tuned Light	LCM
PRODUCTION	Tail		0	1115 2	127	1.34	14.8	170	25	Class C	LCM
COMPLETION SYSTEM	Lead		9402	2110 0	723	1.3	14.2	939	10	50:50 (Poz:H)	Salt + Bentonite + Fluid Loss + Dispersant + SMS

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials will be kept on location at all times in order to combat lost circulation or unexpected kicks. In order to run DSTs, open hole logs, and casing, the viscosity and water loss may have to be adjusted in order to meet these needs.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1593	OTHER : Fresh Water	7.83	8.33							
1593	5236	SALT SATURATED	9.8	10.3							
5236	1115 2	OTHER : Cut Brine or OBM	8.5	9							
1115 2	2110 0	OIL-BASED MUD	8.5	9							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

No DST Planned

List of open and cased hole logs run in the well:

COMPENSATED NEUTRON LOG,DIRECTIONAL SURVEY,GAMMA RAY LOG,

Coring operation description for the well:

N/A

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 5068

Anticipated Surface Pressure: 2685

Anticipated Bottom Hole Temperature(F): 177

Anticipated abnormal pressures, temperatures, or potential geologic hazards? YES

Describe:

Lost circulation may be encountered in the Delaware mountain group. Abnormal pressure as well as hole stability issues may be encountered in the Wolfcamp.

Contingency Plans geohazards description:

Lost circulation material will be available, as well as additional drilling fluid along with the fluid volume in the drilling rig pit system. Drilling fluid can be mixed on location or mixed in vendor mud plant and trucked to location if needed. Sufficient barite will be available to maintain appropriate mud weight for the Wolfcamp interval.

Contingency Plans geohazards

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations

Loosey_Goosey_4_9_Fed_Com_302H_H2S_Plan_20220317084654.pdf

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Loosey_Goosey_4_9_Fed_Com_302H_Prelim_Directional___AC_Report_20220317084711.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

Loosey_Goosey_4_9_Fed_Com_302H_Drilling_Plan_20220317084720.pdf


Other Variance attachment:

Offline_Cement_Procedure_20220126145421.pdf

Loosey_Goosey_4_9_Fed_Com_302H_Flex_Hose_20220317084741.pdf

Loosey_Goosey_4_9_Fed_Com_302H_Multibowl_20220317084748.pdf

CONFIDENTIAL





Choke Line:
 2M System: 2" Minimum
 3M System: 3" Minimum
 OPTIONAL: 4" Flex Hose may be used if approved in APD

2M: 1 Valve Minimum
 3M: 2 Valves Minimum
 HCR Valve is optional

Choke Manifold Diagram
 Loosey Goosey 4-9 Fed Com 302H


**Drilling Operations
 Choke Manifold
 2M/3M Service**

Choke Line:
5M System: 3" Minimum
OPTIONAL: 4" Flex Hose may be
used if approved in APD



Drilling Operations Choke Manifold 5M Service

Choke Manifold Diagram
Loosey Goosey 4-9 Fed Com
302H Cimarex Energy Co.




Choke Manifold Diagram
 Loosey Goosey 4-9 Fed Com 302H

Choke Line:
 2M System: 2" Minimum
 3M System: 3" Minimum
 OPTIONAL: 4" Flex Hose may be used if approved in APD

BOP Outlet
 HCR (Optional)
 2M: 1 Valve Minimum
 3M: 2 Valves Minimum
 HCR Valve is optional

**Drilling Operations
 Choke Manifold
 2M/3M Service**

Drilling 8-3/4" hole
below 9 5/8" Casing



SRR & A

Drilling 6" hole
below 7" Casing

Fill Line

Flowline

5000# (5M)
BOP

Annular Preventer

SRR & A

Pipe Rams

Blind Rams

2" Minimum Kill Line

Kill Line

Drilling
Spool

3" minimum choke line

Choke Line

2 Valves Minimum
(HCR Required)

2 Valves and a check valve

Wellhead
Assembly

11" 5000 psi x 7-1/16" 10,000 psi
Wellhead Assembly

Wellhead
Assembly

13-5/8" 3000 psi x 11" 5000 psi
Wellhead Assembly


13-5/8" 3000# psi x 13-3/8" SOW Casing Head

5000# BOP
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.

Drilling 12 1/4" hole
below 13 3/8"
Casing

Fill Line

Flowline



SRR & A

2000# BOP
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.

Loosey Goosey 4-9 Fed Com 302H Casing Assumptions

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet

Loosey Goosey 4-9 Fed Com 302H Casing Assumptions

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet

Loosey Goosey 4-9 Fed Com 302H Casing Assumptions

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet

Loosey Goosey 4-9 Fed Com 302H Casing Assumptions

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet

Loosey Goosey 4-9 Fed Com 302H Casing Assumptions

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet

Loosey Goosey 4-9 Fed Com 302H

Cimarex Energy Co.

Lea Co., NM

- 1 All Company and Contract personnel admitted on location must be trained by a qualified H2S safety instructor to the following:
 - A. Characteristics of H₂S
 - B. Physical effects and hazards
 - C. Principal and operation of H₂S detectors, warning system and briefing areas.
 - D. Evacuation procedure, routes and first aid.
 - E. Proper use of safety equipment & life support systems
 - F. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.

H₂S Detection and Alarm Systems:

 - A. H₂S sensors/detectors to be located on the drilling rig floor, in the base of the sub structure/cellar area, on the mud pits in the shale shaker area. Additional H₂S detectors may play placed as deemed necessary.
 - B. An audio alarm system will be installed on the derrick floor and in the top doghouse.
- 3 Windsock and/or wind streamers:
 - A. Windsock at mudpit area should be high enough to be visible.
 - B. Windsock on the rig floor and / or top doghouse should be high enough to be visible.
- 4 Condition Flags and Signs
 - A. Warning sign on access road to location.
 - B. Flags to be displayed on sign at entrance to location. Green flag indicates normal safe condition. Yellow flag indicates potential pressure and danger. Red flag indicates danger (H₂S present in dangerous concentration). Only H₂S trained and certified personnel admitted to location.
- 5 Well control equipment:
 - A. See exhibit "E-1"
- 6 Communication:
 - A. While working under masks chalkboards will be used for communication.
 - B. Hand signals will be used where chalk board is inappropriate.
 - C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.
- 7 Drillstem Testing:

No DSTs r cores are planned at this time.
- 8 Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.
- 9 If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

H₂S Contingency Plan
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.
Lea Co., NM

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must:

- « Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- « Evacuate any public places encompassed by the 100 ppm ROE.
- « Be equipped with H₂S monitors and air packs in order to control the release.
- « Use the "buddy system" to ensure no injuries occur during the 432-620-1975
- « Take precautions to avoid personal injury during this operation.
- « Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- « Have received training in the:
 - Detection of H₂S, and
 - Measures for protection against the gas,
 - Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Please see attached International Chemical Safety Cards.

Contacting Authorities

Cimarex Energy Co. of Colorado's personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. Cimarex Energy Co. of Colorado's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

H₂S Contingency Plan Emergency Contacts
Loosey Goosey 4-9 Fed Com 302H
 Cimarex Energy Co.
 Lea Co., NM

<u>Company Office</u>			
Cimarex Energy Co. of Colorado		800-969-4789	
Co. Office and After-Hours Menu			
<u>Key Personnel</u>			
Name	Title	Office	Mobile
Larry Seigrist	Drilling Manager	432-620-1934	580-243-8485
Charlie Pritchard	Drilling Superintendent	432-620-1975	432-238-7084
Roy Shirley	Construction Superintendent		432-634-2136
<u>Artesia</u>			
Ambulance		911	
State Police		575-746-2703	
City Police		575-746-2703	
Sheriff's Office		575-746-9888	
Fire Department		575-746-2701	
Local Emergency Planning Committee		575-746-2122	
New Mexico Oil Conservation Division		575-748-1283	
<u>Carlsbad</u>			
Ambulance		911	
State Police		575-885-3137	
City Police		575-885-2111	
Sheriff's Office		575-887-7551	
Fire Department		575-887-3798	
Local Emergency Planning Committee		575-887-6544	
US Bureau of Land Management		575-887-6544	
<u>Santa Fe</u>			
New Mexico Emergency Response Commission (Santa Fe)		505-476-9600	
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs		505-827-9126	
New Mexico State Emergency Operations Center		505-476-9635	
<u>National</u>			
National Emergency Response Center (Washington, D.C.)		800-424-8802	
<u>Medical</u>			
Flight for Life - 4000 24th St.; Lubbock, TX		806-743-9911	
Aerocare - R3, Box 49F; Lubbock, TX		806-747-8923	
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM		505-842-4433	
SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM		505-842-4949	
<u>Other</u>			
Boots & Coots IWC		800-256-9688	or 281-931-8884
Cudd Pressure Control		432-699-0139	or 432-563-3356
Halliburton		575-746-2757	
B.J. Services		575-746-3569	



Coterra Loosey Goosey 4-9 Fed Com 302H Rev1 kFc 10Mar22 Proposal Geodetic Report (Def Plan)



Report Date:	March 10, 2022 - 10:01 AM	Survey / DLS Computation:	Minimum Curvature / Lubinski
Client:	COTERRA	Vertical Section Azimuth:	179.790 ° (Grid North)
Field:	NM Lea County (NAD 83)	Vertical Section Origin:	0.000 ft, 0.000 ft
Structure / Slot:	Coterra Loosey Goosey 4-9 Pad (west) / 302H	TVD Reference Datum:	RKB = 22ft
Well:	Loosey Goosey 4-9 Fed Com 302H	TVD Reference Elevation:	3681.800 ft above MSL
Borehole:	Loosey Goosey 4-9 Fed Com 302H	Seabed / Ground Elevation:	3659.800 ft above MSL
UWI / API#:	Unknown / Unknown	Magnetic Declination:	6.357 °
Survey Name:	Coterra Loosey Goosey 4-9 Fed Com 302H Rev1 kFc 10Mar22	Total Gravity Field Strength:	998.5086mgn (9.80665 Based)
Survey Date:	February 04, 2022	Gravity Model:	GARM
Tort / AHD / DDI / ERD Ratio:	117.001 ° / 11808.103 ft / 6.430 / 1.090	Total Magnetic Field Strength:	47846.542 nT
Coordinate Reference System:	NAD83 New Mexico State Plane, Eastern Zone, US Feet	Magnetic Dip Angle:	60.458 °
Location Lat / Long:	N 32° 36' 45.76642", W 103° 34' 8.20512"	Declination Date:	March 10, 2022
Location Grid N/E Y/X:	N 587481.930 ftUS, E 776702.180 ftUS	Magnetic Declination Model:	HDGM 2022
CRS Grid Convergence Angle:	0.4120 °	North Reference:	Grid North
Grid Scale Factor:	0.99997253	Grid Convergence Used:	0.4120 °
Version / Patch:	2.10.829.1	Total Corr Mag North->Grid North:	5.9452 °
		Local Coord Referenced To:	Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (NS °)	Longitude (EW °)
SHL [1189' FSL, 1484' FWL]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	587481.93	776702.18	N 32.612713	W 103.568946
	100.00	0.00	153.18	100.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	200.00	0.00	153.18	200.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	300.00	0.00	153.18	300.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	400.00	0.00	153.18	400.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	500.00	0.00	153.18	500.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	600.00	0.00	153.18	600.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	700.00	0.00	153.18	700.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	800.00	0.00	153.18	800.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	900.00	0.00	153.18	900.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	1000.00	0.00	153.18	1000.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	1100.00	0.00	153.18	1100.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	1200.00	0.00	153.18	1200.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	1300.00	0.00	153.18	1300.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
Nudge, Build 2"/100ft	1350.00	0.00	153.18	1350.00	0.00	0.00	0.00	0.00	587481.93	776702.18	N 32.612713	W 103.568946
	1400.00	1.00	153.18	1400.00	0.39	-0.39	0.20	2.00	587481.54	776702.38	N 32.612712	W 103.568945
	1500.00	3.00	153.18	1499.93	3.51	-3.50	1.77	2.00	587478.43	776703.95	N 32.612703	W 103.568940
Rustler	1543.75	3.87	153.18	1543.60	5.86	-5.84	2.96	2.00	587476.09	776705.14	N 32.612697	W 103.568936
Top Salt	1600.00	5.00	153.18	1599.68	9.75	-9.73	4.92	2.00	587472.20	776707.10	N 32.612686	W 103.568930
	1633.06	5.66	153.18	1632.60	12.49	-12.47	6.31	2.00	587469.46	776708.49	N 32.612678	W 103.568926
	1700.00	7.00	153.18	1699.13	19.09	-19.06	9.64	2.00	587462.87	776711.82	N 32.612660	W 103.568915
	1800.00	9.00	153.18	1798.15	31.53	-31.48	15.92	2.00	587450.46	776718.10	N 32.612626	W 103.568895
	1900.00	11.00	153.18	1896.63	47.06	-46.97	23.75	2.00	587434.96	776725.93	N 32.612583	W 103.568870
	2000.00	13.00	153.18	1994.44	65.64	-65.52	33.13	2.00	587416.41	776735.31	N 32.612532	W 103.568840
Hold	2025.02	13.50	153.18	2018.80	70.77	-70.64	35.72	2.00	587411.29	776737.90	N 32.612518	W 103.568832
	2100.00	13.50	153.18	2091.70	86.42	-86.26	43.62	2.00	587395.67	776745.80	N 32.612475	W 103.568806
	2200.00	13.50	153.18	2188.94	107.29	-107.10	54.15	0.00	587374.84	776756.33	N 32.612417	W 103.568773
	2300.00	13.50	153.18	2286.17	128.17	-127.93	64.69	0.00	587354.00	776766.87	N 32.612360	W 103.568739
	2400.00	13.50	153.18	2383.41	149.04	-148.76	75.22	0.00	587333.17	776777.40	N 32.612303	W 103.568705
	2500.00	13.50	153.18	2480.65	169.91	-169.60	85.76	0.00	587312.34	776787.94	N 32.612245	W 103.568671
	2600.00	13.50	153.18	2577.88	190.78	-190.43	96.29	0.00	587291.51	776798.47	N 32.612188	W 103.568638
	2700.00	13.50	153.18	2675.12	211.65	-211.26	106.83	0.00	587270.67	776809.00	N 32.612130	W 103.568604
	2800.00	13.50	153.18	2772.36	232.52	-232.10	117.36	0.00	587249.84	776819.54	N 32.612073	W 103.568570
	2900.00	13.50	153.18	2869.59	253.40	-252.93	127.90	0.00	587229.01	776830.07	N 32.612015	W 103.568536
	3000.00	13.50	153.18	2966.83	274.27	-273.76	138.43	0.00	587208.18	776840.61	N 32.611958	W 103.568503
	3100.00	13.50	153.18	3064.07	295.14	-294.60	148.97	0.00	587187.34	776851.14	N 32.611900	W 103.568469
	3200.00	13.50	153.18	3161.30	316.01	-315.43	159.50	0.00	587166.51	776861.68	N 32.611843	W 103.568435
Base Salt (Tansil)	3266.12	13.50	153.18	3225.60	329.81	-329.20	166.47	0.00	587152.73	776868.64	N 32.611805	W 103.568413
	3300.00	13.50	153.18	3328.54	336.88	-336.26	170.03	0.00	587145.68	776872.21	N 32.611785	W 103.568402
	3400.00	13.50	153.18	3355.78	357.76	-357.10	180.57	0.00	587124.84	776882.74	N 32.611728	W 103.568368
	3500.00	13.50	153.18	3453.01	378.63	-377.93	191.10	0.00	587104.01	776893.28	N 32.611670	W 103.568334
	3600.00	13.50	153.18	3550.25	399.50	-398.76	201.64	0.00	587083.18	776903.81	N 32.611613	W 103.568300
	3700.00	13.50	153.18	3647.49	420.37	-419.60	212.17	0.00	587062.35	776914.35	N 32.611555	W 103.568267
	3800.00	13.50	153.18	3744.72	441.24	-440.43	222.71	0.00	587041.51	776924.88	N 32.611498	W 103.568233
	3900.00	13.50	153.18	3841.96	462.11	-461.26	233.24	0.00	587020.68	776935.42	N 32.611441	W 103.568199
	4000.00	13.50	153.18	3939.20	482.99	-482.10	243.78	0.00	586999.85	776945.95	N 32.611383	W 103.568166
	4100.00	13.50	153.18	4036.44	503.86	-502.93	254.31	0.00	586979.02	776956.48	N 32.611326	W 103.568132
	4200.00	13.50	153.18	4133.67	524.73	-523.76	264.85	0.00	586958.18	776967.02	N 32.611268	W 103.568098
	4300.00	13.50	153.18	4230.91	545.60	-544.60	275.38	0.00	586937.35	776977.55	N 32.611211	W 103.568064
	4400.00	13.50	153.18	4328.15	566.47	-565.43	285.92	0.00	586916.52	776988.09	N 32.611153	W 103.568031
	4500.00	13.50	153.18	4425.38	587.35	-586.26	296.45	0.00	586895.68	776998.62	N 32.611096	W 103.567997
	4600.00	13.50	153.18	4522.62	608.22	-607.10	306.98	0.00	586874.85	777009.16	N 32.611038	W 103.567963
	4700.00	13.50	153.18	4619.86	629.09	-627.93	317.52	0.00	586854.02	777019.69	N 32.610981	W 103.567929
	4800.00	13.50	153.18	4717.09	649.96	-648.76	328.05	0.00	586833.19	777030.22	N 32.610923	W 103.567896
	4900.00	13.50	153.18	4814.33	670.83	-669.60	338.59	0.00	586812.35	777040.76	N 32.610866	W 103.567862
Capitan	4924.96	13.50	153.18	4838.60	676.04	-674.80	341.22	0.00	586800.75	777043.39	N 32.610852	W 103.567854
	5000.00	13.50	153.18	4911.57	691.70	-690.43	349.12	0.00	586791.52	777051.29	N 32.610808	W 103.567828
	5100.00	13.50	153.18	5008.80	712.58	-711.26	359.66	0.00	586770.69	777061.83	N 32.610751	W 103.567795
	5200.00	13.50	153.18	5106.04	733.45	-732.10	370.19	0.00	586749.86	777072.36	N 32.610693	W 103.567761
	5300.00	13.50	153.18	5203.28	754.32	-752.93	380.73	0.00	586729.02	777082.90	N 32.610636	W 103.567727
Lamar	5311.65	13.50	153.18	5214.60	756.75	-755.36	381.95	0.00	586726.60	777084.12	N 32.610629	W 103.567723
Bell Canyon	5385.69	13.50	153.18	5286.60	772.21	-770.78	389.75	0.00	586707.11	777091.92	N 32.610587	W 103.567698
	5400.00	13.50	153.18	5300.51	775.19	-773.76	391.26	0.00	586708.19	777093.43	N 32.610579	W 103.567693
	5500.00	13.50	153.18	5397.75	796.06	-794.60	401.80	0.00	586687.36	777103.96	N 32.610521	W 103.567660
	5600.00	13.50	153.18	5494.99	816.94	-815.43	412.33	0.00	586666.52	777114.50	N 32.610464	W 103.567626
	5700.00											

Comments	MD (ft)	Incl (°)	Azim (°)	Grid (ft)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (N/S °)	Longitude (E/W °)
Brushy Canyon	6500.00	13.50	153.18	6370.12	1004.78	-1002.93	507.14	0.00	586479.03	777209.31	N 32.609946	W 103.567322	
	6600.00	13.50	153.18	6467.35	1025.65	-1023.76	517.68	0.00	586458.20	777219.84	N 32.609889	W 103.567289	
	6700.00	13.50	153.18	6564.59	1046.53	-1044.60	528.21	0.00	586437.36	777230.38	N 32.609831	W 103.567255	
	6800.00	13.50	153.18	6661.83	1067.40	-1065.43	538.75	0.00	586416.53	777240.91	N 32.609774	W 103.567221	
	6811.08	13.50	153.18	6672.60	1069.71	-1067.74	539.91	0.00	586414.22	777242.08	N 32.609768	W 103.567218	
	6900.00	13.50	153.18	6759.07	1088.27	-1086.26	549.28	0.00	586395.70	777251.44	N 32.609717	W 103.567188	
	7000.00	13.50	153.18	6856.30	1109.14	-1107.10	559.82	0.00	586374.87	777261.98	N 32.609659	W 103.567154	
	7100.00	13.50	153.18	6953.54	1130.01	-1127.93	570.35	0.00	586354.03	777272.51	N 32.609602	W 103.567120	
	7200.00	13.50	153.18	7050.78	1150.88	-1148.76	580.89	0.00	586333.20	777283.05	N 32.609544	W 103.567086	
	7300.00	13.50	153.18	7148.01	1171.76	-1169.60	591.42	0.00	586312.37	777293.58	N 32.609487	W 103.567053	
Section 33-4 Line NMLC0065607 Lease Crossing	7368.03	13.50	153.18	7214.16	1185.96	-1183.77	598.59	0.00	586298.19	777300.75	N 32.609448	W 103.567030	
Drop 2"/100ft	7400.00	13.50	153.18	7245.25	1192.63	-1190.43	601.95	0.00	586291.54	777304.12	N 32.609429	W 103.567019	
	7500.00	13.50	153.18	7342.49	1213.50	-1211.26	612.49	0.00	586270.70	777314.65	N 32.609372	W 103.566985	
	7506.83	13.50	153.18	7349.12	1214.92	-1212.69	613.21	0.00	586269.28	777315.37	N 32.609368	W 103.566983	
	7600.00	11.64	153.18	7440.06	1233.05	-1230.78	622.36	2.00	586251.19	777324.52	N 32.609318	W 103.566954	
	7700.00	9.64	153.18	7538.34	1249.55	-1247.25	630.69	2.00	586234.72	777332.85	N 32.609272	W 103.566927	
	7800.00	7.64	153.18	7637.20	1262.98	-1260.65	637.46	2.00	586221.32	777339.82	N 32.609235	W 103.566905	
	7900.00	5.64	153.18	7736.52	1273.31	-1270.96	642.68	2.00	586211.00	777344.84	N 32.609207	W 103.566889	
	8000.00	3.64	153.18	7836.19	1280.54	-1278.18	648.33	2.00	586203.79	777348.49	N 32.609187	W 103.566877	
	8100.00	1.64	153.18	7936.08	1284.65	-1282.28	648.40	2.00	586199.68	777350.56	N 32.609176	W 103.566870	
	8181.85	0.00	153.18	8017.92	1285.70	-1283.33	648.93	2.00	586198.64	777351.09	N 32.609173	W 103.566869	
Hold	8200.00	0.00	153.18	8036.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8300.00	0.00	153.18	8136.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8364.53	0.00	153.18	8200.60	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8400.00	0.00	153.18	8236.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8500.00	0.00	153.18	8336.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8600.00	0.00	153.18	8436.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8700.00	0.00	153.18	8536.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8800.00	0.00	153.18	8636.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	8900.00	0.00	153.18	8736.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9000.00	0.00	153.18	8836.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
1st BS Sand	9100.00	0.00	153.18	8936.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9200.00	0.00	153.18	9036.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9300.00	0.00	153.18	9136.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9400.00	0.00	153.18	9236.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9500.00	0.00	153.18	9336.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9540.53	0.00	153.18	9376.60	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9600.00	0.00	153.18	9436.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9700.00	0.00	153.18	9536.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9800.00	0.00	153.18	9636.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	9900.00	0.00	153.18	9736.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
2nd BS Sand	10000.00	0.00	153.18	9836.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	10092.53	0.00	153.18	9928.60	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	10100.00	0.00	153.18	9936.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	10200.00	0.00	153.18	10036.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	10300.00	0.00	153.18	10136.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	10400.00	0.00	153.18	10236.07	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869	
	KOP, Build 10"/100ft	10401.45	0.00	153.18	10237.52	1285.70	-1283.33	648.93	0.00	586198.64	777351.09	N 32.609173	W 103.566869
	10500.00	9.85	179.79	10335.58	1294.15	-1291.78	648.96	10.00	586190.19	777351.12	N 32.609150	W 103.566869	
	10600.00	19.85	179.79	10432.12	1319.76	-1317.39	649.05	10.00	586164.58	777351.21	N 32.609079	W 103.566869	
	10700.00	29.85	179.79	10522.74	1361.74	-1359.36	649.21	10.00	586122.61	777351.37	N 32.608964	W 103.566870	
3rd BS Sand	10765.55	36.41	179.79	10577.60	1397.57	-1395.17	649.34	10.00	586086.80	777351.50	N 32.608866	W 103.566870	
	10800.00	39.85	179.79	10604.70	1418.81	-1416.44	649.42	10.00	586065.53	777351.58	N 32.608807	W 103.566870	
	10900.00	49.85	179.79	10675.50	1489.25	-1486.88	649.68	10.00	585995.09	777351.84	N 32.608613	W 103.566871	
	11000.00	59.85	179.79	10732.99	1570.92	-1568.55	649.97	10.00	585913.43	777352.14	N 32.608389	W 103.566872	
	11100.00	69.85	179.79	10775.43	1661.33	-1658.96	650.31	10.00	585823.02	777352.47	N 32.608141	W 103.566873	
	11151.45	75.00	179.79	10790.95	1710.36	-1707.99	650.49	10.00	585773.99	777352.65	N 32.608006	W 103.566874	
	11200.00	77.43	179.79	10802.52	1757.51	-1755.14	650.66	5.00	585726.85	777352.82	N 32.607876	W 103.566874	
	11300.00	82.43	179.79	10820.01	1855.94	-1853.56	651.02	5.00	585628.42	777353.18	N 32.607606	W 103.566875	
	11400.00	87.43	179.79	10828.85	1955.51	-1953.14	651.38	5.00	585528.85	777353.54	N 32.607332	W 103.566876	
	Landing Point	11451.45	90.00	179.79	10830.00	2006.95	-2004.57	651.57	5.00	585477.42	777353.73	N 32.607191	W 103.566877
11500.00		90.00	179.79	10830.00	2055.50	-2053.12	651.75	0.00	585428.87	777353.91	N 32.607057	W 103.566877	
11600.00		90.00	179.79	10830.00	2155.50	-2153.12	652.12	0.00	585328.87	777354.28	N 32.606782	W 103.566879	
11700.00		90.00	179.79	10830.00	2255.50	-2253.12	652.48	0.00	585228.88	777354.64	N 32.606507	W 103.566880	
11800.00		90.00	179.79	10830.00	2355.50	-2353.12	652.85	0.00	585128.88	777355.01	N 32.606233	W 103.566881	
11900.00		90.00	179.79	10830.00	2455.50	-2453.12	653.21	0.00	585028.88	777355.37	N 32.605958	W 103.566882	
12000.00		90.00	179.79	10830.00	2555.50	-2553.12	653.58	0.00	584928.89	777355.74	N 32.605683	W 103.566883	
12100.00		90.00	179.79	10830.00	2655.50	-2653.12	653.94	0.00	584828.89	777356.10	N 32.605408	W 103.566884	
12200.00		90.00	179.79	10830.00	2755.50	-2753.12	654.31	0.00	584728.89	777356.47	N 32.605133	W 103.566886	
12300.00		90.00	179.79	10830.00	2855.50	-2853.12	654.68	0.00	584628.90	777356.84	N 32.604858	W 103.566887	
NMLC0065607 to NMLC0064194 Lease Crossing	12400.00	90.00	179.79	10830.00	2955.50	-2953.12	655.04</						

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (N/S °)	Longitude (E/W °)
	15500.00	90.00	179.79	10830.00	6055.50	-6053.09	666.38	0.00	581429.01	777368.54	N 32.596063	W 103.566924
	15600.00	90.00	179.79	10830.00	6155.50	-6153.09	666.75	0.00	581329.02	777368.91	N 32.595788	W 103.566925
	15700.00	90.00	179.79	10830.00	6255.50	-6253.09	667.11	0.00	581229.02	777369.27	N 32.595514	W 103.566926
	15800.00	90.00	179.79	10830.00	6355.50	-6353.09	667.48	0.00	581129.02	777369.64	N 32.595239	W 103.566927
	15900.00	90.00	179.79	10830.00	6455.50	-6453.09	667.85	0.00	581029.03	777370.01	N 32.594964	W 103.566928
Section 4-9 Line Crossing	15917.64	90.00	179.79	10830.00	6473.13	-6470.73	667.91	0.00	581011.39	777370.07	N 32.594915	W 103.566928
	16000.00	90.00	179.79	10830.00	6555.50	-6553.09	668.21	0.00	580929.03	777370.37	N 32.594689	W 103.566929
	16100.00	90.00	179.79	10830.00	6655.50	-6653.09	668.58	0.00	580829.04	777370.74	N 32.594414	W 103.566931
	16200.00	90.00	179.79	10830.00	6755.50	-6753.09	668.94	0.00	580729.04	777371.10	N 32.594139	W 103.566932
	16300.00	90.00	179.79	10830.00	6855.50	-6853.09	669.31	0.00	580629.04	777371.47	N 32.593865	W 103.566933
	16400.00	90.00	179.79	10830.00	6955.50	-6953.09	669.68	0.00	580529.05	777371.84	N 32.593590	W 103.566934
	16500.00	90.00	179.79	10830.00	7055.50	-7053.09	670.04	0.00	580429.05	777372.20	N 32.593315	W 103.566935
	16600.00	90.00	179.79	10830.00	7155.50	-7153.09	670.41	0.00	580329.05	777372.57	N 32.593040	W 103.566936
	16700.00	90.00	179.79	10830.00	7255.50	-7253.09	670.77	0.00	580229.06	777372.93	N 32.592765	W 103.566937
	16800.00	90.00	179.79	10830.00	7355.50	-7353.09	671.14	0.00	580129.06	777373.30	N 32.592490	W 103.566939
	16900.00	90.00	179.79	10830.00	7455.50	-7453.09	671.50	0.00	580029.06	777373.66	N 32.592215	W 103.566940
	17000.00	90.00	179.79	10830.00	7555.50	-7553.09	671.87	0.00	579929.07	777374.03	N 32.591941	W 103.566941
	17100.00	90.00	179.79	10830.00	7655.50	-7653.09	672.24	0.00	579829.07	777374.40	N 32.591666	W 103.566942
	17200.00	90.00	179.79	10830.00	7755.50	-7753.09	672.60	0.00	579729.08	777374.76	N 32.591391	W 103.566943
	17300.00	90.00	179.79	10830.00	7855.50	-7853.09	672.97	0.00	579629.08	777375.13	N 32.591116	W 103.566944
	17400.00	90.00	179.79	10830.00	7955.50	-7953.09	673.33	0.00	579529.08	777375.49	N 32.590841	W 103.566945
	17500.00	90.00	179.79	10830.00	8055.50	-8053.09	673.70	0.00	579429.09	777375.86	N 32.590566	W 103.566947
	17600.00	90.00	179.79	10830.00	8155.50	-8153.09	674.07	0.00	579329.09	777376.23	N 32.590292	W 103.566948
	17700.00	90.00	179.79	10830.00	8255.50	-8253.09	674.43	0.00	579229.09	777376.59	N 32.590017	W 103.566949
	17800.00	90.00	179.79	10830.00	8355.50	-8353.09	674.80	0.00	579129.10	777376.96	N 32.589742	W 103.566950
	17900.00	90.00	179.79	10830.00	8455.50	-8453.09	675.16	0.00	579029.10	777377.32	N 32.589467	W 103.566951
	18000.00	90.00	179.79	10830.00	8555.50	-8553.09	675.53	0.00	578929.10	777377.69	N 32.589192	W 103.566952
	18100.00	90.00	179.79	10830.00	8655.50	-8653.09	675.89	0.00	578829.11	777378.05	N 32.588917	W 103.566954
	18200.00	90.00	179.79	10830.00	8755.50	-8753.09	676.26	0.00	578729.11	777378.42	N 32.588642	W 103.566955
	18300.00	90.00	179.79	10830.00	8855.50	-8853.09	676.63	0.00	578629.12	777378.79	N 32.588368	W 103.566956
	18400.00	90.00	179.79	10830.00	8955.50	-8953.09	676.99	0.00	578529.12	777379.15	N 32.588093	W 103.566957
	18500.00	90.00	179.79	10830.00	9055.50	-9053.09	677.36	0.00	578429.12	777379.52	N 32.587818	W 103.566958
	18600.00	90.00	179.79	10830.00	9155.50	-9153.09	677.72	0.00	578329.13	777379.88	N 32.587543	W 103.566959
	18700.00	90.00	179.79	10830.00	9255.50	-9253.09	678.09	0.00	578229.13	777380.25	N 32.587268	W 103.566960
	18800.00	90.00	179.79	10830.00	9355.50	-9353.09	678.46	0.00	578129.13	777380.62	N 32.586993	W 103.566962
	18900.00	90.00	179.79	10830.00	9455.50	-9453.09	678.82	0.00	578029.14	777380.98	N 32.586718	W 103.566963
	19000.00	90.00	179.79	10830.00	9555.50	-9553.09	679.19	0.00	577929.14	777381.35	N 32.586444	W 103.566964
	19100.00	90.00	179.79	10830.00	9655.50	-9653.09	679.55	0.00	577829.14	777381.71	N 32.586169	W 103.566965
	19200.00	90.00	179.79	10830.00	9755.50	-9753.09	679.92	0.00	577729.15	777382.08	N 32.585894	W 103.566966
	19300.00	90.00	179.79	10830.00	9855.50	-9853.09	680.28	0.00	577629.15	777382.44	N 32.585619	W 103.566967
	19400.00	90.00	179.79	10830.00	9955.50	-9953.09	680.65	0.00	577529.16	777382.81	N 32.585344	W 103.566968
	19500.00	90.00	179.79	10830.00	10055.50	-10053.07	681.02	0.00	577429.16	777383.18	N 32.585069	W 103.566970
	19600.00	90.00	179.79	10830.00	10155.50	-10153.07	681.38	0.00	577329.16	777383.54	N 32.584795	W 103.566971
	19700.00	90.00	179.79	10830.00	10255.50	-10253.07	681.75	0.00	577229.17	777383.91	N 32.584520	W 103.566972
	19800.00	90.00	179.79	10830.00	10355.50	-10353.07	682.11	0.00	577129.17	777384.27	N 32.584245	W 103.566973
	19900.00	90.00	179.79	10830.00	10455.50	-10453.06	682.48	0.00	577029.17	777384.64	N 32.583970	W 103.566974
	20000.00	90.00	179.79	10830.00	10555.50	-10553.06	682.85	0.00	576929.18	777385.01	N 32.583695	W 103.566975
	20100.00	90.00	179.79	10830.00	10655.50	-10653.06	683.21	0.00	576829.18	777385.37	N 32.583420	W 103.566977
	20200.00	90.00	179.79	10830.00	10755.50	-10753.06	683.58	0.00	576729.18	777385.74	N 32.583145	W 103.566978
	20300.00	90.00	179.79	10830.00	10855.50	-10853.06	683.94	0.00	576629.19	777386.10	N 32.582871	W 103.566979
	20400.00	90.00	179.79	10830.00	10955.50	-10953.06	684.31	0.00	576529.19	777386.47	N 32.582596	W 103.566980
	20500.00	90.00	179.79	10830.00	11055.50	-11053.06	684.67	0.00	576429.19	777386.83	N 32.582321	W 103.566981
	20600.00	90.00	179.79	10830.00	11155.50	-11153.06	685.04	0.00	576329.20	777387.20	N 32.582046	W 103.566982
	20700.00	90.00	179.79	10830.00	11255.50	-11253.06	685.41	0.00	576229.20	777387.57	N 32.581771	W 103.566983
	20800.00	90.00	179.79	10830.00	11355.50	-11353.06	685.77	0.00	576129.21	777387.93	N 32.581496	W 103.566985
	20900.00	90.00	179.79	10830.00	11455.50	-11453.06	686.14	0.00	576029.21	777388.30	N 32.581222	W 103.566986
	21000.00	90.00	179.79	10830.00	11555.50	-11553.06	686.50	0.00	575929.21	777388.66	N 32.580947	W 103.566987
	21100.00	90.00	179.79	10830.00	11655.50	-11653.06	686.87	0.00	575829.22	777389.03	N 32.580672	W 103.566988

Loosey Goosey
4-9 Fed Com
302H - BHL
[100' FSL, 2120'
FWL]

21100.24	90.00	179.79	10830.00	11655.73	-11653.29	686.87	0.00	575828.98	777389.03	N 32.580671	W 103.566988
----------	-------	--------	----------	----------	-----------	--------	------	-----------	-----------	-------------	--------------

Survey Type: Def Plan

Survey Error Model: ISCWSA Rev 3 *** 3-D 95.000% Confidence 2.7955 sigma




Survey Program:

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size (in)	Casing Diameter (in)	Expected Max Inclination (deg)	Survey Tool Type	Borehole / Survey
	1	0.000	22.000	1/100.000	30.000	30.000		A001Mb_MWD-Depth Only	Loosey Goosey 4-9 Fed Com 302H / Coterra Loosey Goosey 4-9
	1	22.000	21100.237	1/100.000	30.000	30.000		A001Mb_MWD	Loosey Goosey 4-9 Fed Com 302H / Coterra Loosey Goosey 4-9

Borehole: Loosey Goosey 4-9 Fed Com 302H	Well: Loosey Goosey 4-9 Fed Com 302H	Field: NM Lea County (NAD 83)	Structure: Coterra Loosey Goosey 4-9 Pad (west)
--	--	---	---

Gravity & Magnetic Parameters		Surface Location			NAD83 New Mexico State Plane, Eastern Zone, US Feet		Miscellaneous	
Model: HDGM 2022	Dip: 60.458°	Date: 10-Mar-2022	Lat: N 32 36 45.77	Northing: 587481.93ftUS	Grid Conv: 0.412°	Slot: 302H	TVD Ref: RKB = 22ft (3681.8ft above MSL)	
MagDec: 6.357°	FS: 47846.542nT	Gravity FS: 998.509mgn (9.80665 Based)	Lon: W 103 34 8.21	Easting: 776702.18ftUS	Scale Fact: 0.99997253	Plan: Coterra Loosey Goosey 4-9 Fed Com 302H Rev1 kFc 10Mar22		

Critical Point	MD	INCL	AZIM	TVD	VSEC	N(+)/S(-)	E(+)/W(-)	DLS
SHL [1189' FSL, 1484' FWL]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
Nudge, Build 2'*/100ft	1350.00	0.00	153.18	1350.00	0.00	0.00	0.00	
Rustler	1543.75	3.87	153.18	1543.60	5.86	-5.84	2.96	2.00
Top Salt	1633.06	5.66	153.18	1632.60	12.49	-12.47	6.31	2.00
Hold	2025.02	13.50	153.18	2018.80	70.77	-70.64	35.72	2.00
Base Salt (Tansil)	3266.12	13.50	153.18	3225.60	329.81	-329.20	166.47	0.00
Capitan	4924.96	13.50	153.18	4838.60	676.04	-674.80	341.22	0.00
Lamar	5311.65	13.50	153.18	5214.60	756.75	-755.36	381.95	0.00
Bell Canyon	5385.69	13.50	153.18	5286.60	772.21	-770.78	389.75	0.00
Cherry Canyon	5852.59	13.50	153.18	5740.60	869.66	-868.05	438.94	0.00
Brushy Canyon	6811.08	13.50	153.18	6672.60	1069.71	-1067.74	539.91	0.00
Section 33-4 Line NMLC0065607 Lease Crossing	7368.03	13.50	153.18	7214.16	1185.96	-1183.77	598.59	0.00
Drop 2'*/100ft	7506.83	13.50	153.18	7349.12	1214.92	-1212.69	613.21	0.00
Hold	8181.85	0.00	153.18	8017.92	1285.70	-1283.33	648.93	2.00
Bone Spring	8364.53	0.00	153.18	8200.60	1285.70	-1283.33	648.93	0.00
1st BS Sand	9540.53	0.00	153.18	9376.60	1285.70	-1283.33	648.93	0.00
2nd BS Sand	10092.53	0.00	153.18	9928.60	1285.70	-1283.33	648.93	0.00
KOP, Build 10'*/100ft	10401.45	0.00	153.18	10237.52	1285.70	-1283.33	648.93	0.00
3rd BS Sand	10765.55	36.41	179.79	10577.60	1397.54	-1395.17	649.34	10.00
Build 5'*/100ft	11151.45	75.00	179.79	10790.95	1710.36	-1707.99	650.49	10.00
Landing Point	11451.45	90.00	179.79	10830.00	2006.95	-2004.57	651.57	5.00
NMLC0065607 to NMLC0064194 Lease Crossing	13273.93	90.00	179.79	10830.00	3829.43	-3827.04	658.24	0.00
Section 4-9 Line Crossing	15917.64	90.00	179.79	10830.00	6473.13	-6470.73	667.91	0.00
Loosey Goosey 4-9 Fed Com 302H - BHL [100' FSL, 2120' FWL]	21100.24	90.00	179.79	10830.00	11655.73	-11653.29	686.87	0.00
Wolfcamp	NaN			10850.60				



0
-500
-1000
-1500
-2000
-2500
-3000
-3500
-4000
-4500
-5000
-5500
-6000
-6500
-7000
-7500
-8000
-8500
-9000
-9500
-10000
-10500
-11000
-11500
-12000
-12500
 NS (ft) Scale = 1:200.00(ft)
 EW (ft) Scale = 1:500.00(ft)



Coterra Loosey Goosey 4-9 Fed Com 302H Rev1 kFc 10Mar22 Anti-Collision Summary Report

Analysis Date-24hr Time: March 10, 2022 - 10:02
Client: COTERRA
Field: NM Lea County (NAD 83)
Structure: Coterra Loosey Goosey 4-9 Pad (west)
Slot: 302H
Well: Loosey Goosey 4-9 Fed Com 302H
Borehole: Loosey Goosey 4-9 Fed Com 302H
Scan MD Range: 0.00ft ~ 21100.24ft

Analysis Method: 3D Least Distance
Reference Trajectory: Coterra Loosey Goosey 4-9 Fed Com 302H Rev1 kFc 10Mar22 (Def Plan)
Depth Interval: Every 10.00 Measured Depth (ft)
Rule Set: NAL Procedure; D&M AntiCollision Standard S002
Min Pts: All local minima indicated.
Version / Patch: 2.10.829.1
Database \ Project: localhost/drilling-Project

Trajectory Error Model: ISCWSA0 3-D 95.000% Confidence 2.7955 sigma

Offset Trajectories Summary

Offset Selection Criteria

Wellhead distance scan: Not performed!
 Selection filters: Definitive Surveys - Definitive Plans - Definitive surveys exclude definitive plans
 - All Non-Def Surveys when no Def-Survey is set in a borehole - All Non-Def Plans when no Def-Plan is set in a borehole

Offset Trajectory	Separation			Allow Dev. (ft)	Sep. Fact.	Controlling Rule	Reference Trajectory		Risk Level			Alert	Status
	Ct-Ct (ft)	MAS (ft)	EOU (ft)				MD (ft)	TVD (ft)	Alert	Minor	Major		
Coterra Loosey Goosey 4-9 Fed Com 301H Rev1 kFc 10Mar22 (Def Plan)													
	20.00	16.49	17.50	3.50	N/A	MAS = 5.03 (m)	0.00	0.00	CtCt<=15m<15.00				Fail Minor
	19.99	16.49	17.49	3.50	N/A	MAS = 5.03 (m)	22.00	22.00					Enter Alert
	19.99	20.07	5.78	-0.08	1.49	OSF1.50	1230.00	1230.00		OSF<1.50			WRP
	19.99	21.87	4.58	-1.88	1.35	OSF1.50	1350.00	1350.00					Enter Minor
	20.28	22.76	4.28	-2.47	1.32	OSF1.50	1410.00	1410.00					MinPt-CiCt
	20.39	22.89	4.29	-2.51	1.32	OSF1.50	1420.00	1419.99					MINPT-O-EOU
	20.51	23.04	4.32	-2.53	1.32	OSF1.50	1430.00	1429.99					MinPt-O-SF
	24.56	24.89	7.14	-0.33	1.48	OSF1.50	1560.00	1559.81		OSF>1.50			MinPt-O-ADP
	103.90	32.98	81.08	70.92	4.99	OSF1.50	2120.00	2111.15		OSF>5.00			Exit Minor
	1413.84	426.18	1128.89	987.66	5.00	OSF1.50	15120.00	10830.00		OSF<5.00			Exit Alert
	1413.82	825.31	862.78	588.51	2.57	OSF1.50	21090.00	10830.00					Enter Alert
	1413.82	825.99	862.37	587.89	2.51	OSF1.50	21100.24	10830.00					MinPt-CiCt
													MinPts
Coterra Chapadoniz 33-28 Fed Com 1H Rev1 kFc 10Mar22 (Def Plan)													
	40.00	32.49	37.50	7.50	N/A	MAS = 9.90 (m)	0.00	0.00	CtCt<=15m<15.00				Warning Alert
	39.99	32.49	37.49	7.50	N/A	MAS = 9.90 (m)	22.00	22.00					Enter Alert
	39.99	32.49	24.58	7.50	2.90	MAS = 9.90 (m)	1350.00	1350.00					WRP
	40.15	32.49	24.45	7.66	2.85	MAS = 9.90 (m)	1380.00	1380.00					MinPts
	40.86	32.49	24.79	8.36	2.83	MAS = 9.90 (m)	1420.00	1419.99					MINPT-O-EOU
	91.65	32.49	71.22	59.16	4.97	MAS = 9.90 (m)	1890.00	1886.81		OSF>5.00			MinPt-O-SF
	1472.84	174.98	1355.38	1297.85	12.79	OSF1.50	10420.00	10256.07					Exit Alert
	1472.93	175.10	1355.37	1297.84	12.78	OSF1.50	10430.00	10286.06					MINPT-O-EOU
	1479.69	176.74	1361.02	1302.94	12.72	OSF1.50	10580.00	10413.19					MinPt-O-ADP
	10678.92	185.26	10554.58	10493.66	87.63	OSF1.50	21100.24	10830.00					MinPt-O-SF
													TD
30-025-34119 - Pearl '33' Federal 1 INC Only to 10250ft - A (Def Survey)													
	1217.46	32.81	1214.96	1184.65	N/A	MAS = 10.00 (m)	0.00	0.00					Warning Alert
	1217.33	32.81	1214.75	1184.52	15466.65	MAS = 10.00 (m)	22.00	22.00					Surface
	1216.08	32.81	1201.36	1183.27	99.37	MAS = 10.00 (m)	490.00	490.00					WRP
	729.71	220.81	581.67	508.90	5.00	OSF1.50	4280.00	4211.46		OSF<5.00			MinPts
	548.71	337.09	323.15	211.63	2.45	OSF1.50	6490.00	6360.39					Enter Alert
	552.66	348.72	319.35	203.95	2.38	OSF1.50	6730.00	6593.76					MinPt-CiCt
	558.25	355.31	320.54	202.93	2.36	OSF1.50	6860.00	6720.17					MINPT-O-EOU
	576.36	369.06	329.49	207.31	2.35	OSF1.50	7120.00	6972.99					MinPt-O-ADP
	643.95	455.63	339.36	188.32	2.12	OSF1.50	8810.00	8646.07					MinPt-O-SF
	645.82	540.54	284.63	105.28	1.79	OSF1.50	10420.00	10256.07					MinPt-CiCt
	1698.94	512.17	1356.66	1186.77	4.99	OSF1.50	11740.00	10830.00		OSF>5.00			MinPts
	10949.58	544.56	10585.71	10405.02	30.29	OSF1.50	21100.24	10830.00					Exit Alert
													TD
30-025-33017 - Hudson Federal 3 INC Only to 8350ft - A (Def Survey)													
	2120.66	32.81	2118.16	2087.85	N/A	MAS = 10.00 (m)	0.00	0.00					Warning Alert
	2120.58	32.81	2118.01	2087.77	27651.78	MAS = 10.00 (m)	22.00	22.00					Surface
	2108.90	66.80	2063.53	2042.10	49.14	OSF1.50	1120.00	1120.00					WRP
	2111.19	74.73	2060.53	2036.45	43.79	OSF1.50	1310.00	1310.00					MinPt-CiCt
	1062.05	321.50	846.88	740.55	4.98	OSF1.50	6150.00	6029.79		OSF<5.00			Enter Alert
	866.52	425.06	382.32	241.47	2.36	OSF1.50	8150.00	7986.07					MinPt-CiCt
	670.92	444.38	373.83	226.54	2.27	OSF1.50	8530.00	8366.07					MinPts
	1009.03	307.21	803.39	701.82	4.85	OSF1.50	9280.00	9116.07		OSF>5.00			Exit Alert
	3390.37	321.96	3174.89	3068.41	15.91	OSF1.50	13640.00	10830.00					MinPt-O-SF
	10077.81	445.59	9779.92	9632.22	34.11	OSF1.50	21100.24	10830.00					TD
30-025-33325 - Hudson Federal 6 INC Only to 8330ft - P (Def Survey)													
	1930.28	32.81	1927.78	1897.47	N/A	MAS = 10.00 (m)	0.00	0.00					Warning Alert
	1930.18	32.81	1927.67	1897.37	130655.47	MAS = 10.00 (m)	10.00	10.00					Surface
	1930.14	32.81	1927.63	1897.33	237231.62	MAS = 10.00 (m)	20.00	20.00					MinPt-O-SF
	1930.13	32.81	1927.63	1897.33	455291.63	MAS = 10.00 (m)	22.00	22.00					MINPT-O-EOU
	1926.13	35.08	1901.91	1891.05	88.57	OSF1.50	650.00	650.00					WRP
	1213.62	365.89	968.86	847.73	5.00	OSF1.50	6900.00	6759.07		OSF<5.00			MinPt-CiCt
	1170.90	418.60	891.00	752.30	4.21	OSF1.50	7890.00	7726.57					Enter Alert
	1181.14	451.51	879.29	729.62	3.94	OSF1.50	8530.00	8366.07					MinPt-CiCt
	1336.63	403.52	1066.78	933.10	4.99	OSF1.50	9140.00	8976.07		OSF>5.00			MinPts
	3386.48	323.37	3170.07	3063.11	15.87	OSF1.50	13380.00	10830.00					Exit Alert
	10146.91	446.99	9848.08	9699.92	34.23	OSF1.50	21100.24	10830.00					MinPt-O-SF
													TD
Coterra Loosey Goosey 4-9 Fed Com 303H Rev0 kFc 04Feb22 (Def Plan)													
	2551.50	32.81	2549.00	2518.69	N/A	MAS = 10.00 (m)	0.00	0.00					Warning Alert
													Surface

Offset Trajectory	Separation			Allow Dev. (ft)	Sep. Fact.	Controlling Rule	Reference Trajectory		Risk Level			Alert	Status	
	Ct-Ct (ft)	MAS (ft)	EOU (ft)				MD (ft)	TVD (ft)	Alert	Minor	Major			
	2551.50	32.81	2549.00	2518.69	N/A	MAS = 10.00 (m)	22.00	22.00				WRP		
	1416.34	166.37	1304.59	1249.97	12.94	OSF1.50	10401.45	10237.52				MinPt-CtCt		
	1426.29	430.13	1138.70	996.15	4.99	OSF1.50	15650.00	10830.00		OSF-5.00		Enter Alert		
	1437.32	793.77	907.31	643.55	2.72	OSF1.50	21100.24	10830.00				MinPts		
30-025-41879 - Chaparral '33'														
Federal Com 5H MWD to 15130ft (Def Survey)													Pass	
	3778.93	32.81	3776.41	3746.12	239041.43	MAS = 10.00 (m)	0.00	0.00				Surface		
	3778.92	32.81	3776.32	3746.11	38313.22	MAS = 10.00 (m)	22.00	22.00				WRP		
	3778.37	32.81	3773.17	3745.56	1399.67	MAS = 10.00 (m)	330.00	330.00				MinPts		
	3774.97	32.81	3758.93	3742.17	278.56	MAS = 10.00 (m)	1390.00	1390.00				MinPts		
	3775.14	32.81	3758.70	3742.33	270.64	MAS = 10.00 (m)	1430.00	1429.99				MINPT-O-EOU		
	549.20	161.90	440.44	387.30	5.14	OSF1.50	10710.00	10531.37				MinPt-CtCt		
	549.32	162.32	440.27	386.99	5.13	OSF1.50	10720.00	10539.91				MinPts		
	551.79	163.52	441.95	388.27	5.12	OSF1.50	10750.00	10564.96				MinPt-O-SF		
	10758.37	181.89	10636.28	10576.48	89.94	OSF1.50	21100.24	10830.00				TD		
Coterra Loosey Goosey 4-9 Fed Com 204H Rev0 kFc 04Feb22 (Def Plan)													Pass	
	2569.93	32.81	2567.43	2537.12	N/A	MAS = 10.00 (m)	0.00	0.00				Surface		
	2569.93	32.81	2567.43	2537.12	N/A	MAS = 10.00 (m)	22.00	22.00				WRP		
	2519.24	34.68	2495.28	2484.55	117.29	OSF1.50	2440.00	2422.30				MinPt-CtCt		
	2519.40	35.17	2495.12	2484.23	115.56	OSF1.50	2480.00	2461.20				MINPT-O-EOU		
	2519.60	35.41	2495.16	2484.19	114.72	OSF1.50	2500.00	2480.65				MinPt-O-ADP		
	2679.14	160.59	2571.25	2518.56	25.40	OSF1.50	9850.00	9686.07				MinPt-CtCt		
	2679.25	161.05	2571.05	2518.21	25.32	OSF1.50	9890.00	9726.07				MINPT-O-EOU		
	2679.42	161.27	2571.08	2518.15	25.29	OSF1.50	9910.00	9746.07				MinPt-O-ADP		
	2899.96	785.26	2375.62	2114.70	5.55	OSF1.50	21100.24	10830.00				MinPts		
Coterra Loosey Goosey 4-9 Fed Com 304H Rev0 kFc 04Feb22 (Def Plan)													Pass	
	2588.37	32.81	2585.87	2555.56	N/A	MAS = 10.00 (m)	0.00	0.00				Surface		
	2588.37	32.81	2585.87	2555.56	N/A	MAS = 10.00 (m)	22.00	22.00				WRP		
	2588.37	32.81	2573.45	2555.56	208.29	MAS = 10.00 (m)	1300.00	1300.00				MinPts		
	2588.51	32.81	2573.29	2555.70	203.32	MAS = 10.00 (m)	1340.00	1340.00				MINPT-O-EOU		
	2571.88	32.81	2549.94	2539.07	132.22	MAS = 10.00 (m)	2250.00	2237.55				MinPts		
	2572.01	32.81	2549.77	2539.21	130.12	MAS = 10.00 (m)	2290.00	2276.45				MINPT-O-EOU		
	2830.14	168.01	2717.30	2662.13	25.63	OSF1.50	10401.45	10237.52				MinPt-CtCt		
	2851.12	793.52	2321.27	2057.60	5.40	OSF1.50	21100.24	10830.00				MinPts		

1. Geological Formations

TVD of target 10,830
MD at TD 21,100

Pilot Hole TD N/A
Deepest expected fresh water

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone	Hazards
Rustler	1543	Useable Water	
Top salt	1632	N/A	
Base Salt	3225	N/A	
Capitan	4838	N/A	
Lamar	5214	N/A	
Bell Canyon	5286	Hydrocarbons	
Cherry Canyon	5740	Hydrocarbons	
Brushy Canyon	6672	Hydrocarbons	
Bone Spring	8200	Hydrocarbons	
1st Bone Spring	9376	Hydrocarbons	
2nd Bone Spring	9928	Hydrocarbons	
3rd Bone Sping	10577	Hydrocarbons	

2. Casing Program

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet

TVD was used on all calculations.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Cimarex Energy Co., Loosey Goosey 4-9 Fed Com 302H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	N
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3rd string cement tied back 500' into previous casing?	N
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	N
Is 2nd string set 100' to 600' below the base of salt?	N
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	N
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	N
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	N
Is AC Report included?	Y

3. Cementing Program

Casing	# Sks	Wt. lb/gal	Yld ft3/sack	H2O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surface	772	13.50	1.72	9.15	15.5	Lead: Class C + Bentonite
	207	14.80	1.34	6.32	9.5	Tail: Class C + LCM
Intermediate	980	12.90	1.88	9.65	12	Lead: 35:65 (Poz:C) + Salt + Bentonite
	292	14.80	1.34	6.32	9.5	Tail: Class C + LCM
Production	327	10.30	3.64	22.18		Lead: Tuned Light + LCM
	127	14.80	1.34	6.32	9.5	Tail: Class C + LCM
Completion System	723	14.20	1.30	5.86	14:30	Tail: 50:50 (Poz:H) + Salt + Bentonite + Fluid Loss + Dispersant + SMS

Casing String	TOC	% Excess
Surface	0	45
Intermediate	0	53
Production	4980	25
Completion System	11152	10

Cimarex request the ability to perform casing integrity tests after plug bump of cement job.

4. Pressure Control Equipment

	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
--	--

BOP installed and tested before drilling which hole?	Size	Min Required WP	Type		Tested To
12 1/4	13 5/8	2M	Annular	X	2M
			Blind Ram		
			Pipe Ram		
			Double Ram	X	
			Other		
8 3/4		3M	Annular	X	3M
			Blind Ram		
			Pipe Ram		
			Double Ram	X	
			Other		
6	13 5/8	5M	Annular	X	5M
			Blind Ram		
			Pipe Ram		
			Double Ram	X	
			Other		

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

X	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
X	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
Y	Are anchors required by manufacturer?

5. Mud Program

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0' to 1593'	Fresh Water	7.83 - 8.33	28	N/C
1593' to 5236'	Brine Water	9.80 - 10.30	30-32	N/C
5236' to 11152'	Cut Brine or OBM	8.50 - 9.00	27-70	N/C
11152' to 21100'	OBM	8.50 - 9.00	50-70	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test?
	Coring?

Additional Logs Planned	Interval

7. Drilling Conditions

Condition	
BH Pressure at deepest TVD	5068 psi
Abnormal Temperature	No

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
X	H2S is present
X	H2S plan is attached

8. Other Facets of Operation

9. Wellhead

A multi-bowl wellhead system will be utilized.

After running the 13-3/8" surface casing, a 13 5/8" BOP/BOPE system with a minimum working pressure of 5000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 5000 psi test. Annular will be tested to working pressure, or a maximum test pressure of 5000 psi. The pressure test will be repeated at least every 30 days, as per Onshore Order No. 2.

The multi-bowl wellhead will be installed by vendor's representative. A copy of the installation instructions has been sent to the BLM field office.

The wellhead will be installed by a third-party welder while being monitored by the wellhead vendor representative.

All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type.

A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi.

A solid steel body pack-off will be utilized after running and cementing the production casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi.

All casing strings will be tested as per Onshore Order No.2 to atleast 0.22 psi/ft or 1,500 whichever is greater and not to exceed 70% of casing burst.

If well conditions dictate conventional slips will be set and BOPE will be tested to appropriate pressures based on permitted pressure requirements.

10. Other Variances

Cimarex requests to perform offline cementing. OLC procedure as follows: 1. Land casing on solid body mandrel hanger. Engage packoff and lockring 2. Install BPV 3. Skid rig 4. Check for pressure and remove BPV 5. Circulate down casing, taking returns through casing valves 6. Pump lead and tail cement 7. Displace cement and bump the plug 8. Ensure floats are holding pressure 9. RD cement crew 10. Install BPV and TA cap.

Cimarex requests permission to skid the rig to the next well on the pad to begin operations instead of waiting 8 hours for surface cement to harden on this 302H well. Surface cement will be pumped, we will ensure floats hold, do a green cement test and then Skid to the next well on pad. We will not perform any operations on this 302H well until at least 8 hours and when both tail and lead slurry reach 500psi. The mandrel hanger is made up on the last joint of 13 3/8" casing and then lowered down with and landing joint. It is then lowered down until the mandrel contacts the landing ring which is prewelded to the conductor pipe. At this point the 13 3/8" casing is entirely supported by the conductor pipe via the landing ring / mandrel and is independent from the rig. This allows us to walk the rig away from the 302H well and begin work on the next well while the cement is hardening. There is no way for the casing to be moved or knocked off center since it is hanging from the landing ring.

Cementing Operational Workflow

Conventional Cementing


1. Land casing on fluted mandrel hanger
2. Circulate down casing, taking returns through BOP stack
3. Pump lead and tail cement
4. Displace cement and bump the plug
5. Ensure floats are holding pressure
6. RD cement crew
7. Install packoff to isolate pressure
8. Install BPV and skid rig

Offline Cementing

1. Land casing on **solid body** mandrel hanger
 - a) Engage packoff and lockring
2. Install BPV
3. Skid rig
4. Check for pressure and remove BPV
5. Circulate down casing, taking returns through casing valves
6. Pump lead and tail cement
7. Displace cement and bump the plug
8. Ensure floats are holding pressure
9. RD cement crew
10. Install BPV and TA cap


Conventional Cementing Equipment-Fluted Mandrel

- Fluted Hanger allows returns up past the hanger body
- Returns throughout cement job flow up through BOP stack and into flowline
- Packoff is installed **after** cement job to isolate pressure above and below hanger
- Lockring engaged during packoff installation




Offline Cementing Equipment-Solid Body Mandrel Hanger


- Solid Body Mandrel Hanger allows for casing to be landed and pressure isolated in one step, **prior** to cementing
- Lockring is engaged to lock casing in place
- Casing is isolated and returns throughout cement job flow through the casing valves and through flowback iron independent of rig




Conventional Cementing Flow Diagram




Conventional Cementing Flow Diagram



Offline Cementing -- Intermediate Casing




Offline Cementing -- Intermediate Casing




Offline Cementing Progression

- Run 7" casing
- Land 11" nominal x 7" hanger
- Test casing hanger
- Energize 11" nom x 7" hanger lock ring and pull test
- Re-test casing hanger
- Barriers & Procedures after landing casing before setting packoff
 - 10K BOP & 5K Annular-Internal and Annular barrier
 - Kill Weight Fluid in annulus and casing (ensure well is static before setting solid body packoff) Internal and Annular barrier
 - **If well is not static we WILL NOT set solid body packoff.**
 - 10K float collar-Internal Barrier
 - 10k float Shoe-Internal Barrier
 - **After circulating a 1.5 casing capacities to ensure full column of mud and no entrained gas pumps will be shut off and floats checked for flow**




Offline Cementing Progression

- Pick up running tool with 6-1/2" nominal Back Pressure valve run into well and set
- Barriers and procedures **BEFORE** removing BOP's
 - Kill weight Fluid in annulus-Annular Barrier
 - Solid Body Packoff-Annular Barrier
 - 10K Float Equipment-Internal Barrier
 - 10K Back pressure valve installed with BOP still on well-Internal Barrier
 - BPV will be tested before it arrives on location by Cactus




Offline Cementing Progression

- Nipple down BOP
- Nipple up TA Cap and test
- Skid Drilling Rig
- Barriers and procedures **AFTER** removing BOP's
 - Kill weight Fluid in annulus-Annular Barrier
 - Solid Body Packoff-Annular Barrier
 - 10K Float Equipment-Internal Barrier
 - 10K Back pressure valve-Internal Barrier
 - 10K rated TA cap with Valve-Internal Barrier



Offline Cementing Progression


- Check Pressure on TA Cap and remove
- Install adaptor with Gate valve for off line cementing and test
- Rig up flowback iron independent of rig
- Retrieve Back Pressure Valve
- Shut in well
- Rig up to cement and pump job
- NU 10K TA cap after cement job
- Barriers and procedures before **rigging up cementing equipment**
 - **Address well and ensure no pressure on TA cap**
 - **Ability to pump into well through casing valves on backside to kill if needed**
 - Kill weight Fluid in annulus-Annular barrier
 - Solid Body Packoff-Annular barrier
 - 10K Float Equipment-Internal Barrier
 - 10K Back pressure valve-Internal Barrier



Offline Cementing Risk and COA Compliance

- All testing and breaks tested in accordance with Onshore Order # 2 and COA's
- If no cement to surface, bradenhead squeeze still possible with offline cementing equipment
- Time from skid rig to offline cementing ops typically 24 hours
- **Conditions where we would not Offline Cement**
 - Well is flowing
- All wellhead equipment rated to 10K maintaining APD compliant
 - 10K flowback iron independent of rig circulating system
 - 10K Back Pressure Valve
 - 10K Gate Valve & TA combo for second barrier during operations
 - 10K 1-13/16 Valve coming off TA cap
 - 10K TA Cap

Co-Flex Hose
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.





Co-Flex Hose Hydrostatic Test
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.

Midwest Hose & Specialty, Inc.

INTERNAL HYDROSTATIC TEST REPORT			
Customer:		P.O. Number:	
Oderco Inc		odyd-271	
HOSE SPECIFICATIONS			
Type: Stainless Steel Armor Choke & Kill Hose		Hose Length: 45'ft.	
I.D.	4 INCHES	O.D.	9 INCHES
WORKING PRESSURE	TEST PRESSURE	BURST PRESSURE	
10,000 PSI	15,000 PSI	0 PSI	
COUPLINGS			
Stem Part No.		Ferrule No.	
OKC OKC		OKC OKC	
Type of Coupling:			
Swage-It			
PROCEDURE			
<i>Hose assembly pressure tested with water at ambient temperature.</i>			
TIME HELD AT TEST PRESSURE		ACTUAL BURST PRESSURE:	
15 MIN.		0 PSI	
Hose Assembly Serial Number:		Hose Serial Number:	
79793		OKC	
Comments:			
Date:	Tested:	Approved:	
3/8/2011	<i>A. Joins</i>	<i>[Signature]</i>	



Midwest Hose & Specialty, Inc.

Internal Hydrostatic Test Graph

March 3, 2011

Customer: Houston


Pick Ticket #: 94260

Hose Specifications

<u>Hose Type</u>	<u>Length</u>
C & K	45'
<u>I.D.</u>	<u>O.D.</u>
4"	6.09"
<u>Working Pressure</u>	<u>Burst Pressure</u>
10000 PSI	Standard Safety Multiplier Applies

Verification

<u>Type of Fitting</u>	<u>Coupling Method</u>
41/16 10K	Swage
<u>Die Size</u>	<u>Final O.D.</u>
6.38"	6.25"
<u>Hose Serial #</u>	<u>Hose Assembly Serial #</u>
5544	79793



<u>Test Pressure</u>	<u>Time Held at Test Pressure</u>	<u>Actual Burst Pressure</u>	<u>Peak Pressure</u>
15000 PSI	11 Minutes		15483 PSI


Comments: Hose assembly pressure tested with water at ambient temperature.

Tested By: Zac McConnell

Approved By: Kim Thomas

Co-Flex Hose Hydrostatic Test
 Loosey Goosey 4-9 Fed Com 302H
 Cimarex Energy Co.

Co-Flex Hose
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.



Midwest Hose & Specialty, Inc.

Certificate of Conformity

Customer:	DEM	PO	ODYD-271
------------------	-----	-----------	----------

SPECIFICATIONS

Sales Order	79793	Dated:	3/8/2011
--------------------	-------	---------------	----------

We hereby certify that the material supplied for the referenced purchase order to be true according to the requirements of the purchase order and current industry standards

Supplier:
Midwest Hose & Specialty, Inc.
10640 Tanner Road
Houston, Texas 77041

Comments:

Approved:	<i>Jamal Garcia</i>	Date:	3/8/2011
------------------	---------------------	--------------	----------



Midwest Hose
& Specialty, Inc.

Co-Flex Hose
Loosey Goosey 4-9 Fed Com 302H
Cimarex Energy Co.

Specification Sheet Choke & Kill Hose

The Midwest Hose & Specialty Choke & Kill hose is manufactured with only premium components. The reinforcement cables, inner liner and cover are made of the highest quality material to handle the tough drilling applications of today's industry. The end connections are available with API flanges, API male threads, hubs, hammer unions or other special fittings upon request. Hose assembly is manufactured to API 7K. This assembly is wrapped with fire resistant vermiculite coated fiberglass insulation, rated at 2000 degrees with stainless steel armor cover.

Working Pressure:	5,000 or 10,000 psi working pressure
Test Pressure:	10,000 or 15,000 psi test pressure
Reinforcement:	Multiple steel cables
Cover:	Stainless Steel Armor
Inner Tube:	Petroleum resistant, Abrasion resistant
End Fitting:	API flanges, API male threads, threaded or butt weld hammer unions, unbolt and other special connections
Maximum Length:	110 Feet
ID:	2-1/2", 3", 3-1/2", 4"
Operating Temperature:	-22 deg F to +180 deg F (-30 deg C to +82 deg C)

P.O. Box 96558 – 1421 S.E. 29th St. Oklahoma City, OK 73143 * (405) 670-6718 * Fax: (405) 670-6816




CACTUS FOR SERVICE
WEARBUSHING
IN CASING HEAD &
CASING SPOOL

LEA CO., NM

Loosey Goosey 4-9 Fed com 302H

Hole Size	Casing Depth From	Casing Depth To	Setting Depth TVD	Casing Size	Weight (lb/ft)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
17 1/2	0	1593	1593	13-3/8"	48.00	H-40	ST&C	1.12	2.51	4.21
12 1/4	0	5236	5236	9-5/8"	40.00	HCK-55	LT&C	1.36	1.41	2.68
8 3/4	0	10402	10402	7"	29.00	L-80	LT&C	1.44	1.68	1.88
8 3/4	10402	11152	10791	7"	29.00	P-110	BT&C	1.69	2.22	82.35
6	9402	21100	10830	4-1/2"	11.60	P-110	BT&C	1.50	2.11	22.16
BLM Minimum Safety Factor								1.125	1	1.6 Dry 1.8 Wet



PREPARED ON 04/22/21



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

SUPO Data Report

01/25/2024

APD ID: 10400083756

Submission Date: 03/17/2022

Highlighted data reflects the most recent changes

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

Chapadoniz_and_Loosey_Goosey_E2W2_Pad_Existing_Access_Road_20220309153233.pdf

Existing Road Purpose: ACCESS,FLUID TRANSPORT

Row(s) Exist? NO

ROW ID(s)

ID: NM137119

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

Chapadoniz_and_Loosey_Goosey_E2W2_New_Access_Road_ROW_20220309153251.pdf

New road type: COLLECTOR

Length: 1524 Feet

Width (ft.): 30

Max slope (%): 2

Max grade (%): 6

Army Corp of Engineers (ACOE) permit required? N

ACOE Permit Number(s):

New road travel width: 18

New road access erosion control: Water will be diverted where necessary to avoid ponding, prevent erosion, maintain good drainage, and to be consistent with local drainage patterns.

New road access plan or profile prepared? N

New road access plan

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Access road engineering design? N

Access road engineering design

Turnout? N

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: Push off and stockpile alongside the location

Access other construction information: The operator will prevent and abate fugitive dust as needed created by vehicular traffic, equipment operations or other events.

Access miscellaneous information: N/a

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: CULVERT,LOW WATER

Drainage Control comments: To control and prevent potentially contaminated precipitation from leaving the pad site, a perimeter berm and settlement pond will be installed. Contaminated water will be removed from pond, stored in waste tanks, and disposed of at a state approved facility. Standing water or puddles will not be allowed. Drainage ditches would be established and maintained on the pad and along access roads to divert water away from operations. Natural drainage areas disturbed during construction would be re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured, and reclaimed to near original condition to re-establish natural drainage.

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

Chapadoniz_and_Loosey_Goosey_E2W2_Pad_One_Mile_Radius_20220309153522.pdf

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Production from this well pad will be routed to the on pad battery. Flowline/Bulklines will be on pad.1524' of new access road will be built. 9460' of offlease 3phase 4wire 40v overhead powerline will be built. 1- 12" temporary layflat poly fresh water line. 5 miles in length.

Production Facilities map:

Loosey_Goosey_4_9_Fed_Com_E2W2_Temp_Water_Route_20220309154332.pdf

Mighty_Loosey_Chap_Power_ROW_20220301143624.pdf

Loosey_Goosey_4_9_Fed_Com_E2W2_SUPO_20220317084125.pdf

Mighty_Chapadoniz_and_Loosey_Goosey_E2W2_On_Pad_Battery_20220317084132.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Water source type: MUNICIPAL

Water source use type: SURFACE CASING

INTERMEDIATE/PRODUCTION CASING

Source latitude:

Source longitude:

Source datum:

Water source permit type: WATER RIGHT

Permit Number:

Water source transport method: TRUCKING

Source land ownership: FEDERAL

Source transportation land ownership: FEDERAL

Water source volume (barrels): 5000

Source volume (acre-feet): 0.64446548

Source volume (gal): 210000

Water source and transportation

Loosey_Goosey_4_9_Drilling_Water_Route_20220309154538.pdf

Water source comments:

New water well? N

New Water Well Info

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Using any construction materials: YES

Construction Materials description: Caliche will be obtained from the actual well site if available. If not available onsite caliche will be obtained for a pit located in SESW SWSE of Sec. 25 19S 33E & SW of Sec 13 19S 33E

Construction Materials source location

Section 7 - Methods for Handling

Waste type: DRILLING

Waste content description: Drilling Fluids, drill cuttings, water and other waste produced from the well during drilling operations.

Amount of waste: 15000 barrels

Waste disposal frequency : Weekly

Safe containment description: N/A

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: Haul to R360 Environmental Solutions, 4507 Carlsbad Hwy, Hobbs, NM 88240

Operator Name: CIMAREX ENERGY COMPANY	
Well Name: LOOSEY GOOSEY 4-9 FED COM	Well Number: 302H

Waste type: SEWAGE

Waste content description: Human Waste

Amount of waste: 300 gallons

Waste disposal frequency : Weekly

Safe containment description: Waste will be properly contained and disposed of properly at a state approved disposal facility.

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: A licensed 3rd party contractor will be used to haul and dispose human waste to City of Toyah TX waste water facility.

Waste type: GARBAGE

Waste content description: Garbage and trash produced during drilling and completion operations

Amount of waste: 32500 pounds

Waste disposal frequency : Weekly

Safe containment description: N/A

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: A licensed 3rd party hauls trash to Lea County Landfill

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit? NO

Reserve pit length (ft.) **Reserve pit width (ft.)**

Reserve pit depth (ft.) **Reserve pit volume (cu. yd.)**

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? N

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Description of cuttings location

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary

Are you requesting any Ancillary Facilities?: N

Ancillary Facilities

Comments:

Section 9 - Well Site

Well Site Layout Diagram:

Loosey_Goosey_4_9_E2W2_Well_List_20220309155135.docx

Loosey_Goosey_4_9_Fed_Com_302H_Wellsite_Layout_20220315151053.pdf

Comments:

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: Loosey Goosey 4-9 Fed Com

Multiple Well Pad Number: E2W2

Recontouring

Chapadoniz_and_Loosey_Goosey_E2W2_Interim_Reclaim_20220309155155.pdf

Drainage/Erosion control construction: To control and prevent potentially contaminated precipitation from leaving the pad site, a perimeter berm and settlement pond will be installed. Contaminated water will be removed from pond, stored in waste tanks, and disposed of at a state approved facility. Standing water or puddles will not be allowed. Drainage ditches would be established and maintained on the pad and along access roads to divert water away from operations. Natural drainage areas disturbed during construction would be re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured to near original condition prior to construction. Erosion Control Best Management Practices would be used where necessary and consist of seeding, fiber rolls, water bars, silt fences, and temporary diversion dikes. Areas disturbed during construction that are no longer needed for operations would be obliterated, re-contoured, and reclaimed to near original condition to re-establish natural drainage.

Drainage/Erosion control reclamation: All disturbed and re-contoured areas would be reseeded according to specifications. Approved seed mixtures would be certified weed free and consist of grasses, forbs, or shrubs similar to the surrounding area. Compacted soil areas may need to be obliterated and reclaimed to near natural conditions by re-contouring all slopes to facilitate and re-establish natural drainage.

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well pad proposed disturbance (acres): 12.861	Well pad interim reclamation (acres): 3.335	Well pad long term disturbance (acres): 9.526
Road proposed disturbance (acres): 1.05	Road interim reclamation (acres): 0	Road long term disturbance (acres): 1.05
Powerline proposed disturbance (acres): 6.512	Powerline interim reclamation (acres): 0	Powerline long term disturbance (acres): 6.512
Pipeline proposed disturbance (acres): 0	Pipeline interim reclamation (acres): 0	Pipeline long term disturbance (acres): 0
Other proposed disturbance (acres): 0	Other interim reclamation (acres): 0	Other long term disturbance (acres): 0
Total proposed disturbance: 20.423000000000002	Total interim reclamation: 3.335	Total long term disturbance: 17.088

Disturbance Comments:

Reconstruction method: After well plugging, all disturbed areas would be returned to the original contour or a contour that blends with the surrounding landform including roads unless the surface owner requests that they be left intact. In consultation with the surface owners it will be determined if any gravel or similar materials used to reinforce an area are to be removed, buried, or left in place during final reclamation. Salvaged topsoil, if any, would be re-spread evenly over the surfaces to be re-vegetated. As necessary, the soil surface would be prepared to provide a seedbed for re-establishment of desirable vegetation. Site preparation may include gouging, scarifying, dozer track-walking, mulching, or fertilizing. Reclamation, Re-vegetation, and Drainage: All disturbed and re-contoured areas would be reseeded using techniques outlined under Phase I and II of this plan or as specified by the land owner. Approved seed mixtures would be certified weed free and consist of grasses, forbs, or shrubs similar to the surrounding area. Compacted soil areas may need to be obliterated and reclaimed to near natural conditions by re-contouring all slopes to facilitate and re-establish natural drainage.

Topsoil redistribution: The original stock piled topsoil, if any, will be spread evenly over the areas being reclaimed and the original landform will be restored for all disturbed areas including well pad, production facilities, roads, pipelines, and power line corridors as close as possible to the original topography. The location will then be seeded

Soil treatment: The soil surface would be prepared to provide a seedbed for reestablishment of desirable vegetation. Establish control of erosion and invasion of non-native plants to reestablish plant community.

Existing Vegetation at the well pad: N/A

Existing Vegetation at the well pad

Existing Vegetation Community at the road: N/A

Existing Vegetation Community at the road

Existing Vegetation Community at the pipeline: N/A

Existing Vegetation Community at the pipeline

Existing Vegetation Community at other disturbances: N/A

Existing Vegetation Community at other disturbances

Non native seed used? N

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? N

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Seedling transplant description

Will seed be harvested for use in site reclamation? N

Seed harvest description:

Seed harvest description attachment:

Seed

Seed Table

Seed Summary	
Seed Type	Pounds/Acre

Total pounds/Acre:

Seed reclamation

Operator Contact/Responsible Official

First Name: amithy

Last Name: Crawford

Phone: (432)620-1909

Email: amithy.crawford@coterra.com

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? N

Existing invasive species treatment description:

Existing invasive species treatment

Weed treatment plan description: N/A

Weed treatment plan

Monitoring plan description: N/A

Monitoring plan

Success standards: N/A

Pit closure description: N/A

Pit closure attachment:

Section 11 - Surface Ownership

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Disturbance type: TRANSMISSION LINE

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT, STATE GOVERNMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office: NMSLO

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Disturbance type: NEW ACCESS ROAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Section 12 - Other

Right of Way needed? Y

Use APD as ROW? Y

ROW Type(s): 281001 ROW - ROADS,289001 ROW- O&G Well Pad,FLPMA (Powerline)

ROW

SUPO Additional Information:

Use a previously conducted onsite? N

Previous Onsite information:

Other SUPO

Cimarex Loosey Goosey 4-9 Fed Com E2W2 Surface Use Plan

Upon approval of the Application for Permit to Drill (APD) the following surface use plan of operations will be followed and carried out. The surface use plan outlines the proposed surface disturbance. If any other disturbance is needed after the APD is approved, a BLM sundry notice or right of way application will be submitted for approval prior to any additional surface disturbance.

Existing Roads

- Directions to location - Exhibit A.
- Public access route - Exhibit B.
- Existing access road for the proposed project. Please see Exhibit B and C.
- Cimarex Energy will:
 - Improve and/or maintain existing road(s) condition the same as or better than before the operations began.
 - Provide plans for improvement and /or maintenance of existing roads if requested.
 - Repair or replace damaged or deteriorated structures as needed. Including cattle guards and culverts.
 - Prevent and abate fugitive dust as needed, whether created by vehicular traffic, equipment operations, or other events.
 - Obtain written BLM approval prior to the application of surfactants, binding agents, or other dust suppression chemicals on the roadways.
- The maximum width of the driving surface will be 18'. The road will be crowned and ditched with a 2% slope from the tip of the crown to the edge of the driving surface. The ditches will be 1' deep with 3:1 slopes. The driving surface will be made of 6" rolled and compacted caliche.

New or Reconstructed Access Roads

Cimarex Energy plans to construct a new off-lease access road

- Length: 1524'
- Width: 30'
- Road Plat - Exhibit D.
- A ROW will be submitted to the BLM for approval.
- Cimarex Energy will complete improvements to the driving surface as needed.
- The maximum width of the driving surface for all roads above will be 18'.
- The road will be crowned and ditched with a 2% slope from the tip of the crown to the edge of the driving surface.
- The ditches will be 1' deep with 3:1 slopes.
- The driving surface will be made of 6" rolled and compacted caliche.
- Cimarex Energy will prevent and abate fugitive dust as needed, whether created by vehicular traffic, equipment operations, or other events.

Well Radius Map

Please see Exhibit E for wells within one mile or proposed well SHL and BHL.

Proposed or Existing Production Facility

A new facility will be constructed for this project if the well is productive.

- Loosey Goosey 4-9 E2W2 CTB - Exhibit F
 - Direction to facility
 - Facility pad location layout and cut and fill
 - Facility pad archeological boundary
 - Facility pad flowline corridor
 - Facility pad access road

Gas Pipeline Specifications

- No new gas pipelines are required for this project.

Salt Water Disposal Specifications

- No new SWD pipelines are required for this project.

Power Lines

Cimarex Loosey Goosey 4-9 Fed Com E2W2 Surface Use Plan

- Cimarex plans to construct an off-lease power line to service the Mighty Pheasant wells.
- Overhead power line from an existing power source located in the .
- Length: 9,460'.
- Poles: 34
- Specifications: 480 volt, 4 wire, 3 phase.
- Please see Exhibit I for proposed route.
- A ROW application will be submitted to the BLM for the proposed route.

Well Site Location

- Proposed well pad/location layout - Exhibit J.
- Proposed Rig layout - Exhibit K
 - The rig layout, including V-door and flare line may change depending on rig availability. The pad dimensions and orientation will remain the same. No additional disturbance is anticipated if a rig layout change is necessary to accommodate the drilling rig. If additional disturbance is required a sundry notice will be submitted to the BLM for approval.
 - Mud pits in the closed circulation system will be steel pits and the cuttings will be stored in the steel containment pits.
 - Cuttings will be stored in steel pits until they are hauled to a state-approved disposal facility.
- Archeological boundary - Exhibit L
- Multi well pad: 301H 302H 202H 102H 201H 101H & Chapadoniz 33-28 Fed Com 1H
- Pad Size: 500 x 560
- Construction Material
 - If possible, native caliche will be obtained from the excavation of drill site. The primary way of obtaining caliche will be by "turning over" the location. This means caliche will be obtained from the actual well site. A caliche permit will be obtained from BLM prior to pushing up any caliche. 2,400 cu yds is the max amount of caliche needed for pad and roads. Amount will vary for each pad. The procedure below has been approved by BLM personnel:
 - The top 6 inches of topsoil is pushed off and stockpiled along the side of the location.
 - An approximate 120' x 120' area is used within the proposed well site to remove caliche.
 - Subsoil is removed and piled alongside the 120' x 120' area within the pad site.
 - When caliche is found, material will be stockpiled within the pad site to build the location and road.
 - Then subsoil is pushed back in the hole and caliche is spread accordingly across entire location and road.
 - Once well is drilled, the stockpiled top soil will be used for interim reclamation and spread along areas where caliche is picked up and the location size is reduced. Neither caliche nor subsoil will be stockpiled outside of the well pad. Topsoil will be stockpiled along the edge of the pad as depicted in Exhibit J - Layout Diagram.
 - Caliche will be obtained from the actual well site if available. If not available onsite caliche will be obtained for a pit located in SESW SWSE of Sec. 25 19S 33E & SW of Sec 13 19S 33E
 - Mud pits in the closed circulation system will be steel pits and the cuttings will be stored in steel containment pits.
- Cuttings will be stored in steel pits until they are hauled to a state-approved disposal facility.
- If the well is a producer, those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements. Exhibit P: Interim Reclamation Diagram.
- There are no known dwellings within 1.5 miles of this location.

Bulkline Pipelines

All proposed pipelines will be constructed on-Pad

Water Resources

1- 12" temporary layflat poly fresh water line. 5 miles in length.

Methods of Handling Waste

Cimarex Loosey Goosey 4-9 Fed Com E2W2 Surface Use Plan

- Drilling fluids, produced oil, and water from the well during drilling and completion operations will be stored safely and disposed of properly in a NMOCD approved disposal facility.
- Garbage and trash produced during drilling and completion operations will be collected in a trash container and disposed of properly at a state approved disposal facility. All trash on and around well site will be collected for disposal.
- Human waste and grey water will be contained and disposed of properly at a state approved disposal site.
- After drilling and completion operations, trash, chemicals, salts, frac sand and other waste will be removed and disposed of properly at a state approved disposal site.
- The well will be drilled utilizing a closed loop system. Drill cuttings will be properly disposed of into steel tanks and taken to an NMOCD approved disposal facility.

Ancillary Facilities

No camps or airstrips to be constructed.

Interim and Final Reclamation

- Rehabilitation of the location will start in a timely manner after all proposed drilling wells have been drilled from the pad or if drilling operations have ceased as outlined below:
 - No approved or pending drill permits for wells located on the drill pad
 - No drilling activity for 5 years from the drill pad
- Surfacing materials will be removed and returned to a mineral pit or recycled to repair or build roads and well pads.
- Drainage systems, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location's pad and surface facilities. After the area has been shaped and contoured, topsoil from the spoil pile will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.
- Exhibit P illustrates the proposed Surface Reclamation plans after cessation of drilling operations as outlined above.
 - The areas of the location not essential to production facilities and operations will be reclaimed and seeded per BLM requirements.
- Operator will amend the surface reclamation plan if well is a dry hole and/or a single well pad.

Surface Ownership

- The wellsite is on surface owned by NMSLO.
- A copy of Surface Use Agreement has been given to the surface owner.
- The land is used mainly for farming, cattle ranching, recreational use, and oil and gas production.

Cultural Resource Survey - Archeology

- Cultural Resources Survey will be conducted for the entire project as proposed in the APD and submitted to the BLM for review and approval.

On Site Notes and Information:

Location was droned



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

PWD Data Report

01/25/2024

APD ID: 10400083756

Submission Date: 03/17/2022

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined

Would you like to utilize Lined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit

Pit liner description:

Pit liner manufacturers

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule

Lined pit reclamation description:

Lined pit reclamation

Leak detection system description:

Leak detection system

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Lined pit Monitor description:

Lined pit Monitor

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information

Section 3 - Unlined

Would you like to utilize Unlined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD disturbance (acres):

PWD surface owner:

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule

Unlined pit reclamation description:

Unlined pit reclamation

Unlined pit Monitor description:

Unlined pit Monitor

Do you propose to put the produced water to beneficial use?

Beneficial use user

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic

State

Unlined Produced Water Pit Estimated

Unlined pit: do you have a reclamation bond for the pit?

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information

Section 4 -

Would you like to utilize Injection PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Injection well name:

Assigned injection well API number?

Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection

Underground Injection Control (UIC) Permit?

UIC Permit

Section 5 - Surface

Would you like to utilize Surface Discharge PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 -

Would you like to utilize Other PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Other PWD type description:

Other PWD type

Have other regulatory requirements been met?

Other regulatory requirements



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data

01/25/2024

APD ID: 10400083756

Submission Date: 03/17/2022

Highlighted data reflects the most recent changes
[Show Final Text](#)

Operator Name: CIMAREX ENERGY COMPANY

Well Name: LOOSEY GOOSEY 4-9 FED COM

Well Number: 302H

Well Type: OIL WELL

Well Work Type: Drill

Bond

Federal/Indian APD: FED

BLM Bond number: NMB001188

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 308842

CONDITIONS

Operator: CIMAREX ENERGY CO. 6001 Deauville Blvd Midland, TX 79706	OGRID: 215099
	Action Number: 308842
	Action Type: [C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104	2/6/2024
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	2/6/2024
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system	2/6/2024
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing	2/6/2024
pkautz	If cement does not circulate on any string, a CBL is required for that string of casing	2/6/2024