Distant - (-37) 98-80. Miss Miss Distant Company Com	Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103 Revised July 18, 2013
SILS FIRST St. Amesia, NM 8210 DERICHLE OSSI 334-678 DERICH CORNS AS 4-708 DERICH CORNS		Energy, Minerals and Natural Resources	
District Gots 334-6178 1220 South St. Francis Dr. Statt Gots		OIL CONSERVATION DIVISION	
Santa Fe, NM 87505 6. State Oil & Gas Leuse No. 1220 S. Flames D. Santa Fe, NM 87505 6. State Oil & Gas Leuse No. 1220 S. Flames D. Santa Fe, NM 87505 7. Lease Name or Unit Agreement Name Carlsbad *1.3** Carlsb	<u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESKNORL (SE-7PMLK ATTOR FOR PERMIT (FORM C-101) FOR SLICH 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator RAYBAW Operating, LLC 3. Address of Operator 26.26 Cole Ave, Ste 300, Dallas, TX 75204 4. Well Location Unit Letter G		Santa Fe, NM 87505	
SUNDRY NOTICES AND REPORTS ON WELLS T. Lease Name or Unit Agreement Name CONDITION STEMS FORM FOR PROPOSALS 170 BMLOR TO DEPERSON RESERVOR. USE: "APPLICATION FOR PERMIT GORM C-101) FOR SUCH S. Well Number #1			
1. Type of Well: Oil Well	SUNDRY NOTICE (DO NOT USE THIS FORM FOR PROPOSAL	S TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Carlsbad "13" Com
2. Name of Operator RAYBAW Operating, LLC 3. Address of Operator 2.626 Cole Ave, Ste 300, Dallas, TX 75204 4. Well Location Unit Letter G: 2.040 feet from the E line and 1650 feet from the N line Section 13 Township 22S Range 26E NMPM County Eddy 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PAND A DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM ULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM ULTIPLE COMPL CHANGE PLANS COMMENCE DRILLING OPNS PAND A DOWNHOLE COMMINGLE OTHER 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 30.718/24 M1RU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string, 03/20/24 RIH w/ guage ring to 11,021'. Set 5 ½" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg. held 500 PSI. 03/21/24 Spotted 30 sx class C cmt @ 1809.8300'. Port @ 8230'. Established an injection rate @ 300 PSI @ 1BPM. Sqz'd 50 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd@ 8420'. Established an injection rate @ 300 PSI @ 1BPM. Sqz'd 50 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd@ 8420'. Established an injection rate @ 300 PSI @ 1BPM. Sqz'd 50 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd@ 8420'. Established an injection rate @ 300 PSI @ 1BPM. Sqz'd 50 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd@ 8420'. Established an injection rate @ 300 PSI @ 1BPM. Sqz'd 50 sx class C cmt @ 980'. Sqz'd		a Wall 🖂 Other	8. Well Number #1
RAYBAW Operating, LLC 330220 3. Address of Operator 10, Pool name or Wildcat 2626 Cole Ave, Ste 300, Dallas, TX 75204 Carlsbad Morrow, South		s well 🔼 Other	9 OGRID Number
4. Well Location Unit Letter G			
Well Location			1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
Unit Letter G: 2040 feet from the E line and 1650 feet from the N line Section 13 Township 228 Range 26E NMPM County Eddy 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,144° GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS DULTIPLE COMPL PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PAND A CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSSED-LOOP SYSTEM DTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 03/18/24 MIRU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string, 03/20/24 RIH w/ guage ring to 11,021°. Set 5 ½" CIBP @ 11,021°. Tagged CIBP @ 11,021°. Mixed hole w/ MLF. Pressure tested esg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 9609-9480°. Spotted 40 sx class C cmt @ 11,021°. Set 360°. 32/00°. Set 360°.		5204	Carlsbad Morrow, South
Section 13 Township 228 Range 26E NMPM County Eddy		1040 fort from the F	1650 6 46 4 24
11. Elevation (Show whether DR. RKB, RT, GR. etc.) 3,144 ° GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:			
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM THE PROPERTY STATE AND A CASING/CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 03/18/24 MIRU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string. 03/20/24 RIH w/ guage ring to 11,021'. Set 5 ½" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 9680-9480'. Spotted 30 sx class C cmt @ 8780-8430'. 03/27/24 Perf 1 @ 8420'. Established an injection rate @ 18 PBM. Sqz' d 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 2555'. Perf d @ 5270'. Established injection rate of 1 BPM & 250 PSI. Sqz' d 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag@ 5035'. Perf d @ 3500'. Sqz' d 50 sx class C cmt @ 300 PSI. @ 1 BPM. Sqz' d 50 PSI. Sqz' d 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf d @ 1600''. Sqz' d 50 sx class C cmt @ 1600-1400''. WOC. 04/01/24 Tagged plug @ 3135'. Perf d @ 450''. N BOP. Sqz' d 200 sx class C cmt @ 4600-1400''. WOC chapped plug @ 1345'. Perf d @ 450''. N BOP. Sqz' d 200 sx class C cmt @ 460''. Alternative to surface of the property of the string of the property of the property of the string of the property of the proper			
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM THE PROPERTY STATE AND A CASING/CEMENT JOB DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A CASING/CEMENT JOB P AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A CASING/CEMENT JOB P AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A DOWNHOLE COMMINGLE THE PROPERTY STATE AND A DOWNHOLE DOWNHOLE COMMINGLE CASH THE PAND A DOWNHOLE COMMINGLE CASH THE PAND A DOWNHOLE COMMINGLE CASH THE PAND A DOWNHOLE			
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ALTERING CASING DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A DULT OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CASI	12. Check App	propriate Box to Indicate Nature of Noti	ce, Report or Other Data
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ALTERING CASING DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB PAND A DULT OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CASI	NOTICE OF INTE	NTION TO:	LIBSECLIENT REPORT OF:
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CIOSED-LOOP SYSTEM OTHER:	attraction of the attention is a second to be a second and the sec		
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER: OTHER:	TEMPORARILY ABANDON C		DRILLING OPNS. ☐ P AND A 🖂
CLOSED-LOOP SYSTEM OTHER: OT		IULTIPLE COMPL CASING/CEN	MENT JOB
OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 03/18/24 MIRU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string. 03/20/24 RIH w/ guage ring to 11,021'. Set 5 ½" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 11,021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class H cmt @ 9880-9480'. Spotted 40 sx class C cmt @ 8780-8430'. 30;26/24 Perfd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 8255'. Perf'd @ 5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Avarado w/ OCO verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Signature Alacca dead of the best of my knowledge and belief. Signature Alacca dead of the best of my knowledge and belief. Phone: 281-793-5452 Title Regulatory Analyst Date Phone: 281-793-5452			
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10.3/18/24 MIRU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string. 03/20/24 RIH w/ guage ring to 11,021'. Set 5 ½" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 11,021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class H cmt @ 9680-9480'. Spotted 40 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 8255'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653'-32453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024 TITLE Regulatory Analyst DATE 04/30/2024 Rype or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452		□ OTHER:	П
proposed completion or recompletion. 03/18/24 MIRU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string. 03/20/24 RIH w/ guage ring to 11,021'. Set 5 ½" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 11,021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class H cmt @ 11,021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd @ 8250'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC. & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024 Title Regulatory Analyst DATE DATE DATE DATE	13. Describe proposed or complete	d operations. (Clearly state all pertinent details	
03/18/24 MIRU plugging equipment. Dug out cellar. 03/19/24 Killed well, ND wellhead, NU BOP. POH w/ tbg & packer. RIH w/ kill string. 03/20/24 RIH w/ guage ring to 11.021'. Set 5 ½" CIBP @ 11.021'. Tagged CIBP @ 11.021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 11.021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class H cmt @ 9680-9480'. Spotted 40 sx class C cmt @ 8780-8430'. 03/26/24 Perfd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 8255'. Perf'd @ 5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500'. Sqz'd 50 sx class C cmt @ 3500'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perfd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024 Title Regulatory Analyst DATE 04/30/2024 Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 For State Use Only APPROVED BY: TITLE DATE			Completions: Attach wellbore diagram of
kill string. 03/20/24 RIH w/ guage ring to 11,021'. Set 5 ½" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 11,021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class H cmt @ 9680-9480'. Spotted 40 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 8255'. Perf'd @ 5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024 Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 For State Use Only APPROVED BY: TITLE DATE DATE	proposed completion or recomp	oletion.	
Pressure tested csg, held 500 PSI. 03/21/24 Spotted 30 sx class H cmt @ 11,021-10,777'. Ran CBL & tagged TOC @ 10,660'. 03/22/24 Spotted 30 sx class H cmt @ 9680-9480'. Spotted 40 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 8255'. Perf'd @ 5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024 Title Regulatory Analyst DATE 04/30/2024 Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 For State Use Only APPROVED BY: TITLE DATE	03/18/24 MIRU plugging equipment.	Dug out cellar. 03/19/24 Killed well, ND well	lhead, NU BOP. POH w/ tbg & packer. RIH w/
03/22/24 Spotted 30 sx class H cmt @ 9680-9480'. Spotted 40 sx class C cmt @ 8780-8430'. 03/26/24 Perf'd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC. 03/27/24 Tagged plug @ 8255'. Perf'd @ 5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024 Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: _281-793-5452 Title DATE DATE	Pressure tested csg. held 500 PSL 03/	3 to 11,021'. Set 5 ½' CIBP @ 11,021'. 1agge 21/24 Spotted 30 sx class H cmt @ 11,021-10	ed CIBP @ 11,021'. Mixed hole w/ MLF.
5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: Signature			
Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC. 03/28/24 Tagged plug @ 3300'. Perf'd @ 2653'. Sqz'd 50 sx class C cmt w/2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: Signature	an injection rate @ 300 PSI @ 1 BPM	l. Sqz'd 50 sx class C cmt @ 8420-8270'. WO	C. 03/27/24 Tagged plug @ 8255'. Perf'd @
cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'. Perf'd @ 1600'. Sqz'd 50 sx class C cmt @ 1600-1400'. WOC. 04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: Spud Date: 3/18/2024 Rig Release Date: 4/2/2024			
04/01/24 Tagged plug @ 1345'. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface. 04/02/24 Rigged down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024			
down & moved off. Moved in backhoe and welder. Cut off well head & anchors. David Alvarado w/ OCD verified cmt @ surface via picture text message. Welded on "Above Ground Dry Hole Marker". Installed 2' concrete form w/ 6 sx cmt. Backfilled cellar, cut off deadmen, cleaned location, and moved off. Spud Date: 3/18/2024 Rig Release Date: 4/2/2024			
Spud Date: Spud Date: 3/18/2024 Rig Release Date: 4/2/2024	down & moved off. Moved in backhoo	e and welder. Cut off well head & anchors. D	Pavid Alvarado w/ OCD verified cmt @ surface
Spud Date: 3/18/2024 Rig Release Date: 4/2/2024			d 2' concrete form w/ 6 sx cmt. Backfilled
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Regulatory Analyst Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 APPROVED BY: TITLE DATE	cenar, cut on deadmen, cleaned locati	on, and moved on.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Regulatory Analyst Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 APPROVED BY: TITLE DATE	0.440,600.4		11010001
SIGNATURE TITLE Regulatory Analyst Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 APPROVED BY: DATE	Spud Date: 3/18/2024	Rig Release Date:	4/2/2024
SIGNATURE TITLE Regulatory Analyst Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 APPROVED BY: DATE			
SIGNATURE TITLE Regulatory Analyst Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 APPROVED BY: DATE	I hereby certify that the information abo	we is true and complete to the best of my knowle	ledge and helief
Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 For State Use Only APPROVED BY: DATE	Thereby certify that the information abo	ve is true and complete to the best of my knowl	leage and benef.
Type or print name Nancy J. Winn E-mail address: nwinn@sbcglobal.net PHONE: 281-793-5452 For State Use Only APPROVED BY: DATE	W/ Cks	Dogwilaton, Anglias	04/20/2024
For State Use Only APPROVED BY:	SIGNATURE (any fr)	TITLE Regulatory Analysi	DATE_04/30/2024
For State Use Only APPROVED BY:	Type or print name Nancy J. Winn	E-mail address: nwinn@sbo	eglobal.net PHONE: 281-793-5452
		2	11101121
	A DDD OVED DV	THE P	D.A.TE
		IIILE	DATE

Rawbaw O	perating, LLC		PLUGGED
Author:	Abby @ BCM		
Well Name	Carlsbad 13 Com	Well No.	#1
Field/Pool	Sth Carlsbad(Morrow)	API#:	30-015-21999
County	Eddy	Location:	Sec 13, T22S, R26E
State	NM	•	2040 FEL & 1650 FNL
Spud Date	1/16/1977	GL:	3144

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surface Csg	16	H40	65#	400	20	600	Circ
Inter Csg	10 3/4		45.5#	2,603	14 3/4	1,400	Circ
Prod Csg	5 1/2	N80	17&20#	11,700	7 7/8	800	8430 TS

Formation

Bone Springs

Wolfcamp

Cisco

Strawn

Atoka Morrow

T/Salt

B/Salt

Anhy Del Sand Top

250

1828

5220


8728 9680

10182 10538

10923

400 +/-

1500 +/-



16 65# CSG @ 400

10. Perf'd @ 450'. ND BOP. Sqz'd 200 sx class C cmt @ 450' & circulated to surface.

9. Perf'd @ 1600'. Sqz'd 50 sx class C cmt 1600-1400'. WOC & Tagged plug @ 1345'.

10 3/4 45.5# CSG @ 2,603

8. Perf'd @ 2653'. Sqz'd 50 sx class C cmt w/ 2% CACL @ 2653-2453'. WOC & tagged @ 2416'.

7. Perf'd @ 3500'. Sqz'd 50 sx class C cmt @ 3500-3300'. WOC & Tagged plug @ 3300'.

6. Perf'd @ 5270'. Established injection rate of 1 BPM @ 250 PSI. Sqz'd 50 sx class C cmt w/ 2% CACL @ 5270-5070'. WOC & tag @ 5035'.

- 5. Perf'd @ 8420'. Established an injection rate @ 300 PSI @ 1 BPM. Sqz'd 50 sx class C cmt @ 8420-8270'. WOC & Tagged plug @ 8255'.
- 4. Spotted 40 sx class C cmt @ 8780-8430'.
- 3. Spotted 30 sx class H cmt @ 9680-9480'.
- 2. Spotted 30 sx class H cmt @ 11,021-10,777'. WOC & tagged TOC @ 10,660'.
- 1. Set 5 1/2" CIBP @ 11,021'. Tagged CIBP @ 11,021'. Mixed hole w/ MLF. Pressure tested csg, held 500 PSI.

Perfs @ 11,121-11,459'

03/11/77 Set DR plug in pkr w/ 1 bailer cement on top Perfs @ 11,541-11,642

5 1/2 17&20# CSG @ 11,700

32.3953781

-104.244194

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 339184

CONDITIONS

Operator:	OGRID:
RAYBAW Operating, LLC	330220
2626 Cole Avenue	Action Number:
Dallas, TX 75204	339184
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By		Condition Date
gcordero	well head cut off 4/2/24. CBL in Well File	5/31/2024