

Form 3160-3
(June 2015)

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No.
1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No.
2. Name of Operator		8. Lease Name and Well No.
3a. Address		9. API Well No. 30-025-53037
3b. Phone No. (include area code)		10. Field and Pool, or Exploratory
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface At proposed prod. zone		11. Sec., T. R. M. or Blk. and Survey or Area
14. Distance in miles and direction from nearest town or post office*		12. County or Parish
		13. State
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No of acres in lease	17. Spacing Unit dedicated to this well
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth	20. BLM/BIA Bond No. in file
21. Elevations (Show whether DF, KDB, RT, GL, etc.)	22. Approximate date work will start*	23. Estimated duration
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM. |

25. Signature	Name (Printed/Typed)	Date
Title		
Approved by (Signature)	Name (Printed/Typed)	Date
Title	Office	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



(Continued on page 2)

*(Instructions on page 2)

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM I: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to a new evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

0. SHL: SENW / 2500 FNL / 1620 FWL / TWSP: 26S / RANGE: 32E / SECTION: 7 / LAT: 32.058008 / LONG: -103.7178411 (TVD: 0 feet, MD: 0 feet)

PPP: NENW / 1334 FNL / 2220 FWL / TWSP: 26S / RANGE: 32E / SECTION: 6 / LAT: 32.0758901 / LONG: -103.7159008 (TVD: 10945 feet, MD: 17902 feet)

PPP: SENW / 2569 FNL / 2220 FWL / TWSP: 26S / RANGE: 32E / SECTION: 7 / LAT: 32.0578183 / LONG: -103.7159029 (TVD: 10958 feet, MD: 11327 feet)

BHL: NENW / 100 FNL / 2220 FWL / TWSP: 26S / RANGE: 32E / SECTION: 6 / LAT: 32.0792815 / LONG: -103.7159002 (TVD: 10943 feet, MD: 19135 feet)

BLM Point of Contact

Name: TENILLE C MOLINA

Title: Land Law Examiner

Phone: (575) 234-2224

Email: TCMOLINA@BLM.GOV

CONFIDENTIAL

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

CONFIDENTIAL

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

**Mewbourne Oil Company
Lease Serial Number: NMNM128929
Lea County, N.M.**

Well Pad 1

PADUCA 7/6 A3ED FED COM 1H:

Surface Hole Location: 2500' FNL & 1240' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 330' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 B1ED FED COM 1H:

Surface Hole Location: 2500' FNL & 1260' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 495' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 B2ED FED COM 1H:

Surface Hole Location: 2500' FNL & 1320' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 660' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 H3ED FED COM 1H:

Surface Hole Location: 2500' FNL & 1280' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 400' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 H3ED FED COM 2H:

Surface Hole Location: 2500' FNL & 1340' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 1310' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 W2ED FED COM 1H:

Surface Hole Location: 2500' FNL & 1300' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 500' FWL, Section 6, T. 26 S, R 32 E.

Well Pad 2

PADUCA 7/6 A3FC FED COM 1H:

Surface Hole Location: 2500' FNL & 1560' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 1665' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 B2FC FED COM 1H:

Surface Hole Location: 2500' FNL & 1600' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 2000' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 B2FC FED COM 2H:

Surface Hole Location: 2500' FNL & 1640' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 2320' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 H3FC FED COM 1H:

Surface Hole Location: 2500' FNL & 1620' FWL, Section 7, T. 26 S., R. 32 E.
Bottom Hole Location: 100' FNL & 2220' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 W2FC FED COM 1H:

Surface Hole Location: 2500' FNL & 1540' FWL, Section 7, T. 26 S., R. 32 E.

Bottom Hole Location: 100' FNL & 1410' FWL, Section 6, T. 26 S, R 32 E.

PADUCA 7/6 W2FC FED COM 2H:

Surface Hole Location: 2500' FNL & 1640' FWL, Section 7, T. 26 S., R. 32 E.

Bottom Hole Location: 100' FNL & 2320' FWL, Section 6, T. 26 S, R 32 E.

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
 - Cave/Karst
 - Hydrology
- Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- Road Section Diagram**
- Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
- Interim Reclamation**
- Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for

acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Cave/Karst Surface Mitigation

The following stipulations will be applied to minimize impacts during construction, drilling and production:

Construction:

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

No Blasting:

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

Pad Berming:

- The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.
- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g., caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)
- Following a rain event, all fluids will vacuumed off of the pad and hauled off-site and disposed at a proper disposal facility.

Tank Battery Liners and Berms:

Tank battery locations and all facilities will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing, or equivalent, to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

Leak Detection System:

A method of detecting leaks is required. The method could incorporate gauges to measure loss, situating valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

Automatic Shut-off Systems:

Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Cave/Karst Subsurface Mitigation

The following stipulations will be applied to protect cave/karst and ground water concerns:

Rotary Drilling with Fresh Water:

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

Directional Drilling:

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

Lost Circulation:

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

Abandonment Cementing:

Upon well abandonment in cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Pressure Testing:

The operator will perform annual pressure monitoring on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

FLOWLINES (SURFACE):

- Flowlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize the possibility of leaks and spills from entering karst systems.

- If a void is encountered alignments may be rerouted to avoid the karst feature and lessen; the potential of subsidence or collapse of karst features, buildup of toxic or combustible gas, or other possible impacts to cave and karst resources from the buried pipeline.
- Regular monitoring is required to quickly identify leaks for their immediate and proper treatment.
- All spills or leaks will be reported to the BLM immediately for their immediate and proper treatment.

Hydrology

The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed. Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.

Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank or 24 hour production, whichever is greater. Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.

A leak detection plan will be submitted to the BLM Carlsbad Field Office for approval prior to pipeline installation. The method could incorporate gauges to detect pressure drops, siting valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out-sloping and in-sloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production

equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the Grant and attachments, including stipulations, survey plat(s) and/or map(s), shall be on location during construction. BLM personnel may request to review a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, Holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC § 2601 *et seq.* (1982) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant (see 40 CFR, Part 702-799 and in particular, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193). Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. Holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms

are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. § 9601, *et seq.* or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, *et seq.*) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way Holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way Holder on the Right-of-Way. This provision applies without regard to whether a release is caused by Holder, its agent, or unrelated third parties.

4. Holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. Holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:

- a. Activities of Holder including, but not limited to: construction, operation, maintenance, and termination of the facility;
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing
 - (2) Earth-disturbing and earth-moving work
 - (3) Blasting
 - (4) Vandalism and sabotage;

c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of Holder, regardless of fault. Upon failure of Holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he/she deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of Holder. Such action by the Authorized Officer shall not relieve Holder of any responsibility as provided herein.

6. All construction and maintenance activity shall be confined to the authorized

right-of-way width of **20** feet. If the pipeline route follows an existing road or buried pipeline right-of-way, the surface pipeline shall be installed no farther than 10 feet from the edge of the road or buried pipeline right-of-way. If existing surface pipelines prevent this distance, the proposed surface pipeline shall be installed immediately adjacent to the outer surface pipeline. All construction and maintenance activity shall be confined to existing roads or right-of-ways.

7. No blading or clearing of any vegetation shall be allowed unless approved in writing by the Authorized Officer.

8. Holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky or dune areas, the pipeline shall be "snaked" around hummocks and dunes rather than suspended across these features.

9. The pipeline shall be buried with a minimum of **24** inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.

10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.

13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.

14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway.

15. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

16. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, powerline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

17. Surface pipelines shall be less than or equal to 4 inches and a working pressure below 125 psi.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Sand dropseed (Sporobolus cryptandrus)	1.0
Sand love grass (Eragrostis trichodes)	1.0
Plains bristlegrass (Setaria macrostachya)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	MEWBOURNE OIL COMPANY
LEASE NO.:	NMNM128929
LOCATION:	Section 07, T.26 S., R.32 E., NMPM
COUNTY:	LEA County, New Mexico

WELL NAME & NO.:	PADUCA 7-6 H3FC FED COM 1H
SURFACE HOLE FOOTAGE:	2500'/N & 1620'/W
BOTTOM HOLE FOOTAGE:	100'/N & 2220'/W
ATS/API ID:	ATS-23-259
APD ID:	10400087453
Sundry ID:	

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Wellhead Variance	<input type="radio"/> Diverter		
Other	<input type="checkbox"/> 4 String	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Pilot Hole	<input type="checkbox"/> Open Annulus
Cementing	<input type="checkbox"/> Contingency Cement Squeeze	<input type="checkbox"/> EchoMeter	<input type="checkbox"/> Primary Cement Squeeze
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit
Special Requirements	<input type="checkbox"/> Batch Sundry		
Special Requirements Variance	<input type="checkbox"/> Break Testing	<input type="checkbox"/> Offline Cementing	<input type="checkbox"/> Casing Clearance

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Casing Design:

1. The **13-3/8** inch surface casing shall be set at approximately **1,075** feet (a minimum of **25 feet (Lea County)** into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface. The surface hole shall be **17 1/2** inch in diameter.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **24 hours in the Potash Area** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash. Cement excess is less than 25%, more cement is required if washout occurs. Adjust cement volume and excess based on a fluid caliper or similar method that reflects the as-drilled size of the wellbore.**
 - ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
3. The minimum required fill of cement behind the **7** inch production casing is:

Option 1 (Single Stage):

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification. **Excess cement calculates to -1%, additional cement might be required.**

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification. **Excess cement calculates to 24%, additional cement might be required.**
4. The minimum required fill of cement behind the **4-1/2** inch production liner is:
- Cement should tie-back **100 feet** into the previous casing. Operator shall provide method of verification.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the **13-3/8** inch surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR part 3172 must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- The operator will submit an as-drilled survey well plat of the well completion, but are not limited to, those specified in 43 CFR part 3171 and 3172.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County
 Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
 (575) 361-2822

Lea County
 Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
 689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure

- rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
- b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per 43 CFR part 3172 (Drilling Operations on Federal and Indian Oil and Gas Leases) as soon as 2nd Rig is rigged up on well.
 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the doghouse or stairway area.
 3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for

details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.

4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hard band drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in 43 CFR part 3172 (Drilling Operations on Federal and Indian Oil and Gas Leases) and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:

- a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR part 3172 must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
 - c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to 43 CFR part 3172 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
 - d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE.

If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.

- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per 43 CFR part 3172.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

OTA 7/5/2023



Operator Certification Data Report

05/20/2024

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Bradley Bishop

Signed on: 11/14/2022

Title: Regulatory

Street Address: PO Box 5270

City: Hobbs

State: NM

Zip: 88260

Phone: (575)393-5905

Email address: bbishop@mewbourne.com

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data

05/20/2024

APD ID: 10400087453	Submission Date: 11/14/2022	Highlighted data reflects the most recent changes Show Final Text
Operator Name: MEWBOURNE OIL COMPANY		
Well Name: PADUCA 7/6 H3FC FED COM	Well Number: 1H	
Well Type: OTHER	Well Work Type: Drill	

Section 1 - General

APD ID: 10400087453	Tie to previous NOS? N	Submission Date: 11/14/2022
BLM Office: Carlsbad	User: Bradley Bishop	Title: Regulatory
Federal/Indian APD: FED	Is the first lease penetrated for production Federal or Indian? FED	
Lease number: NMNM128929	Lease Acres:	
Surface access agreement in place?	Allotted?	Reservation:
Agreement in place? NO	Federal or Indian agreement:	
Agreement number:		
Agreement name:		
Keep application confidential? Y		
Permitting Agent? NO	APD Operator: MEWBOURNE OIL COMPANY	
Operator letter of		

Operator Info

Operator Organization Name: MEWBOURNE OIL COMPANY		
Operator Address: P O BOX 5270		Zip: 88241
Operator PO Box:		
Operator City: HOBBS	State: NM	
Operator Phone: (575)393-5905		
Operator Internet Address:		

Section 2 - Well Information

Well in Master Development Plan? NO	Master Development Plan name:	
Well in Master SUPO? NO	Master SUPO name:	
Well in Master Drilling Plan? NO	Master Drilling Plan name:	
Well Name: PADUCA 7/6 H3FC FED COM	Well Number: 1H	Well API Number:
Field/Pool or Exploratory? Field and Pool	Field Name: Jennings	Pool Name: Bone Spring West

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Is the proposed well in an area containing other mineral resources? POTASH

Is the proposed well in a Helium production area? N **Use Existing Well Pad?** N **New surface disturbance?**

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:

Number: 6

Paduca ED well pad

Well Class: HORIZONTAL

Number of Legs: 1

Well Work Type: Drill

Well Type: OTHER

Describe Well Type: gas

Well sub-Type: APPRAISAL

Describe sub-type:

Distance to town: 10 Miles

Distance to nearest well: 20 FT

Distance to lease line: 330 FT

Reservoir well spacing assigned acres Measurement: 240 Acres

Well plat: Paduca_7_6_H3FC_Fed_Com_1H_WellPlat_20220922110751.pdf

Well work start Date: 05/25/2022

Duration: 60 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number:

Reference Datum: KELLY BUSHING

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this
SHL Leg #1	2500	FNL	1620	FWL	26S	32E	7	Aliquot SENW	32.058008	-103.7178411	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 128929	3278	0	0	Y
KOP Leg #1	2195	FSL	2220	FWL	26S	32E	7	Aliquot NESW	32.0562433	-103.7159031	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 140480	-7107	10427	10385	N
PPP Leg #1-1	2569	FNL	2220	FWL	26S	32E	7	Aliquot SENW	32.0578183	-103.7159029	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 128929	-7680	11327	10958	Y

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this
PPP Leg #1-2	1334	FNL	2220	FWL	26S	32E	6	Aliquot NENW	32.0758901	-103.7159008	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 120910	-7667	17902	10945	Y
EXIT Leg #1	100	FNL	2220	FWL	26S	32E	6	Aliquot NENW	32.0792815	-103.7159002	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 120910	-7665	19135	10943	Y
BHL Leg #1	100	FNL	2220	FWL	26S	32E	6	Aliquot NENW	32.0792815	-103.7159002	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 120910	-7665	19135	10943	Y

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number		² Pool Code		³ Pool Name	
		97860		JENNINGS; BONE SPRING WEST	
⁴ Property Code		⁵ Property Name			⁶ Well Number
		PADUCA 7/6 H3FC FED COM			1H
⁷ OGRID NO.		⁸ Operator Name			⁹ Elevation
14744		MEWBOURNE OIL COMPANY			3250'

¹⁰ Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet From the	East/West line	County
F	7	26S	32E		2500	NORTH	1620	WEST	LEA

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
C	6	26S	32E		100	NORTH	2220	WEST	LEA

¹² Dedicated Acres	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
240			

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.



¹⁷ OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature: *Bradley C. Bishop* Date: 9/21/22
Printed Name: BRADLEY BISHOP
E-mail Address: BBISHOP@MEWBOURNE.COM

¹⁸ SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

05/25/2022
Date of Survey

Signature and Seal of Professional Surveyor



19680
Certificate Number

Job No.: LS22050641



Drilling Plan Data Report

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

05/20/2024

APD ID: 10400087453

Submission Date: 11/14/2022

Highlighted data reflects the most recent changes

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Well Type: OTHER

Well Work Type: Drill

Show Final Text

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical	Measured Depth	Lithologies	Mineral Resources	Producing Formatio
13409582	UNKNOWN	3278	28	28	OTHER : Topsoil	NONE	N
13409583	RUSTLER	2279	999	999	ANHYDRITE, DOLOMITE	USEABLE WATER	N
13409593	TOP SALT	1946	1332	1332	SALT	NONE	N
13409594	BASE OF SALT	-834	4112	4112	SALT	NONE	N
13409596	LAMAR	-1047	4325	4325	LIMESTONE	NATURAL GAS, OIL	N
13409597	BELL CANYON	-1070	4348	4348	SANDSTONE	NATURAL GAS, OIL	N
13409598	CHERRY CANYON	-2081	5359	5359	SANDSTONE	NATURAL GAS, OIL	N
13409599	MANZANITA	-2208	5486	5486	LIMESTONE	NATURAL GAS, OIL	N
13409590	BONE SPRING	-5068	8346	8346	LIMESTONE, SHALE	NATURAL GAS, OIL	N
13409591	BONE SPRING 1ST	-6084	9362	9362	SANDSTONE	NATURAL GAS, OIL	N
13409601	BONE SPRING 2ND	-6649	9927	9927	SANDSTONE	NATURAL GAS, OIL	Y
13409602	BONE SPRING 3RD	-7891	11169	11169	SANDSTONE	NATURAL GAS, OIL	N

Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M

Rating Depth: 19135

Equipment: Annular Pipe Rams Blind Rams Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for hydrostatic test chart. Anchors are not required by manufacturer. A variance is requested to use a multi-bowl wellhead.

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Testing Procedure: BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

Choke Diagram Attachment:

Paduca_7_6_H3FC_Fed_Com_1H_Flex_Line_Specs_API_16C_20220817092228.pdf

Paduca_7_6_H3FC_Fed_Com_1H_5M_BOPE_Choke_Diagram_20220817092228.pdf

Paduca_7_6_H3FC_Fed_Com_1H_Flex_Line_Specs_20220817092228.pdf

BOP Diagram Attachment:

Paduca_7_6_H3FC_Fed_Com_1H_5M_BOPE_Schematic_20220817092249.pdf

Paduca_7_6_H3FC_Fed_Com_1H_5M_Mutli_Bowl_WH_20220817092249.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1075	0	1075	3278	2203	1075	H-40	48	ST&C	1.57	3.52	DRY	6.24	DRY	10.48
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	3453	0	3453		-175	3453	J-55	36	LT&C	1.13	1.96	DRY	2.9	DRY	3.61
3	INTERMEDIATE	12.25	9.625	NEW	API	N	3453	4250	3453	4250	-174	-972	797	J-55	40	LT&C	1.16	1.79	DRY	16.31	DRY	19.76
4	PRODUCTION	8.75	7.0	NEW	API	N	0	10360	0	10317		-7039	10360	P-110	26	LT&C	1.2	1.91	DRY	2.37	DRY	3.08
5	LINER	6.125	4.5	NEW	API	N	10160	19135	10119	10943	-6841	-7665	8975	P-110	13.5	LT&C	1.56	1.81	DRY	2.79	DRY	3.48

Casing Attachments

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Casing Attachments

Casing ID: 1 **String** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092414.pdf

Casing ID: 2 **String** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092541.pdf

Casing ID: 3 **String** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092949.pdf

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Casing Attachments

Casing ID: 4 **String** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092508.pdf

Casing ID: 5 **String** LINER

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092908.pdf

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	883	580	2.12	12.5	1230	100	Class C	Salt, Gel, Extender, LCM
SURFACE	Tail		883	1075	200	1.34	14.8	268	100	Class C	Retarder
INTERMEDIATE	Lead		0	3567	660	2.12	12.5	1399	25	Class C	Salt, Gel, Extender, LCM
INTERMEDIATE	Tail		3567	4250	200	1.34	14.8	268	25	Class C	Retarder
PRODUCTION	Lead	5460	4050	4835	70	2.12	12.5	148	25	Class C	Salt, Gel, Extender, LCM, Defoamer

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
PRODUCTION	Tail		4835	5460	100	1.18	15.6	118	25	Class H	Retarder
PRODUCTION	Lead	5460	5460	7895	220	2.12	12.5	466	25	Class C	Salt, Gel, Extender, LCM Defoamer
PRODUCTION	Tail		7895	10360	400	1.18	15.6	472	25	Class H	Retarder, Fluid Loss, Defoamer
LINER	Lead		10160	19135	570	1.85	13.5	1055	25	Class H	Salt, Gel, Fluid Loss, Retarder, Dispersant, Defoamer, Anti-settling Agent

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Lost circulation material, sweeps, mud scavengers

Describe the mud monitoring system utilized: Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1075	SPUD MUD	8.4	8.8							
1075	4250	SALT SATURATED	10	10							
4250	10360	WATER-BASED MUD	8.6	9.7							

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
1036 0	1913 5	OIL-BASED MUD	8.6	12							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will run GR/CNL logs from KOP to surface.

List of open and cased hole logs run in the well:

DIRECTIONAL SURVEY, MEASUREMENT WHILE DRILLING, MUD LOG/GEOLOGIC LITHOLOGY LOG, GAMMA RAY LOG, COMPENSATED NEUTRON LOG,

Coring operation description for the well:

None

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 6828

Anticipated Surface Pressure: 4417

Anticipated Bottom Hole Temperature(F): 195

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations

Paduca_7_6_H3FC_Fed_Com_1H_H2S_Plan_20220817093536.pdf

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Paduca_7_6_H3FC_Fed_Com_1H_MOC_DIR_PLOT_20220817093559.pdf

Paduca_7_6_H3FC_Fed_Com_1H_MOC_DIR_PLAN_20220817093559.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

Paduca_7_6_H3FC_Fed_Com_1H_Additional_Information___Permitting_20220817093606.pdf

Other Variance attachment:

CONFIDENTIAL



GATES ENGINEERING & SERVICES NORTH AMERICA
7603 Prairie Oak Dr.
Houston, TX 77086

PHONE: (281) 602 - 4119
FAX:
EMAIL: Troy.Schmidt@gates.com
WEB: www.gates.com

10K CHOKE & KILL ASSEMBLY PRESSURE TEST CERTIFICATE

Customer:	A-7 AUSTIN INC DBA AUSTIN HOSE	Test Date:	8/20/2018
Customer Ref.:	4101901	Hose Serial No.:	H-082018-10
Invoice No.:	511956	Created By:	Moosa Naqvi
Product Description:	10KF3.035.0CK41/1610KFLGFXDxFLT L/E		
End Fitting 1:	4 1/16 in. Fixed Flange	End Fitting 2:	4 1/16 in. Float Flange
Gates Part No.:	68503010-9721632	Assembly Code:	L40695052218H-082018-10
Working Pressure:	10,000 psi.	Test Pressure:	15,000 psi.

Gates Engineering & Services North America certifies that the following hose assembly has successfully passed all pressure testing requirements set forth in Gates specifications: GTS-04-052 (for 5K assemblies) or GTS-04-053 (10K assemblies), which include reference to Specification API 16C (2nd Edition); sections 7.5.4, 7.5.9, and 10.8.7. A test graph will accompany this test certificate to illustrate conformity to test requirements.


Quality:	QUALITY
Date :	8/20/2018
Signature :	<i>Moosa Naqvi</i>

Production:	PRODUCTION
Date :	8/20/2018
Signature :	<i>[Signature]</i>

Form PTC - 01 Rev.0 2



5M BOPE & Closed Loop Equipment Schematic



Drawing not to scale



GATES E & S NORTH AMERICA, INC.
134 44TH STREET
CORPUS CHRISTI, TEXAS 78405

PHONE: 361-887-9807
FAX: 361-887-0812
EMAIL: Tim.Cantu@gates.com
WEB: www.gates.com

10K CEMENTING ASSEMBLY PRESSURE TEST CERTIFICATE

Customer :	AUSTIN DISTRIBUTING	Test Date:	4/30/2015
Customer Ref. :	4060578	Hose Serial No.:	D-043015-7
Invoice No. :	500506	Created By:	JUSTIN CROPPER

Product Description: 10K3.548.0CK4.1/1610KFLGE/E LE


End Fitting 1 :	4 1/16 10K FLG	End Fitting 2 :	4 1/16 10K FLG
Gates Part No. :	4773-6290	Assembly Code :	L36554102914D-043015-7
Working Pressure :	10,000 PSI	Test Pressure :	15,000 PSI

Gates E & S North America, Inc. certifies that the following hose assembly has been tested to the Gates Oilfield Roughneck Agreement/Specification requirements and passed the 15 minute hydrostatic test per API Spec 7K/Q1, Fifth Edition, June 2010, Test pressure 9.6.7 and per Table 9 to 15,000 psi in accordance with this product number. Hose burst pressure 9.6.7.2 exceeds the minimum of 2.5 times the working pressure per Table 9.

Quality Manager :	QUALITY	Production:	PRODUCTION
Date :	4/30/2015	Date :	4/30/2015
Signature :	<i>Justin Cropper</i>	Signature :	<i>[Signature]</i>

Form PTC - 01 Rev.02







Hydril "GK"
13 5/8" 5M




Hydril "GK"


Cameron Type U
13 5/8" 5M



4 1/2" x 5 7/8" VBR




BLIND RAMS



MUD CROSS

H.C.R.




7" RAMS

13 5/8" 5M


13 5/8" 5M

13 5/8" 5M





13-5/8" MN-DS Wellhead System



MEMBOURNE
OIL COMPANY

Log Pressure Change 579' conductor cut-off 79

NOTE: All dimensions on this drawing are estimated measurements and should be evaluated by engineering.

C7585
Rev. 02

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Hydrogen Sulfide Drilling Operations Plan
Mewbourne Oil Company

1. General Requirements

Rule 118 does not apply to this well because MOC has researched this area and no high concentrations of H₂S were found. MOC will have on location and working all H₂S safety equipment before the Delaware formation for purposes of safety and insurance requirements.

2. Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will have received training from a qualified instructor in the following areas prior to entering the drilling pad area of the well:

1. The hazards and characteristics of hydrogen sulfide gas.
2. The proper use of personal protective equipment and life support systems.
3. The proper use of hydrogen sulfide detectors, alarms, warning systems, briefing areas, evacuation procedures.
4. The proper techniques for first aid and rescue operations.

Additionally, supervisory personnel will be trained in the following areas:

- 1 The effects of hydrogen sulfide on metal components. If high tensile tubular systems are utilized, supervisory personnel will be trained in their special maintenance requirements.
- 2 Corrective action and shut in procedures, blowout prevention, and well control procedures while drilling a well.
- 3 The contents of the Hydrogen Sulfide Drilling Operations Plan.

There will be an initial training session prior to encountering a known hydrogen sulfide source. The initial training session shall include a review of the site specific Hydrogen Sulfide Drilling Operations Plan.

3. Hydrogen Sulfide Safety Equipment and Systems

All hydrogen sulfide safety equipment and systems will be installed, tested, and operational prior to drilling below the 9 5/8" intermediate casing.

1. Well Control Equipment
 - A. Choke manifold with minimum of one adjustable choke/remote choke.
 - B. Blowout preventers equipped with blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
 - C. Auxiliary equipment including annular type blowout preventer.
2. Protective Equipment for Essential Personnel

Thirty minute self contained work unit located in the dog house and at briefing areas.

Additionally: If H₂S is encountered in concentrations less than 10 ppm, fans will be placed in work areas to prevent the accumulation of hazardous amounts of poisonous gas. If higher concentrations of H₂S are detected the well will be shut in and a rotating head, mud/gas separator, remote choke and flare line with igniter will be installed.

3. Hydrogen Sulfide Protection and Monitoring Equipment
 Two portable hydrogen sulfide monitors positioned on location for optimum coverage and detection. The units shall have audible sirens to notify personnel when hydrogen sulfide levels exceed 20 PPM.

4. Visual Warning Systems
 A. Wind direction indicators as indicated on the wellsite diagram.
 B. Caution signs shall be posted on roads providing access to location. Signs shall be painted a high visibility color with lettering of sufficient size to be readable at reasonable distances from potentially contaminated areas.

4. Mud Program

The mud program has been designed to minimize the amount of hydrogen sulfide entrained in the mud system. Proper mud weight, safe drilling practices, and the use of hydrogen sulfide scavengers will minimize hazards while drilling the well.

5. Metallurgy

All tubular systems, wellheads, blowout preventers, drilling spools, kill lines, choke manifolds, and valves shall be suitable for service in a hydrogen sulfide environment when chemically treated.

6. Communications

State & County Officials phone numbers are posted on rig floor and supervisors trailer. Communications in company vehicles and toolpushers are either two way radios or cellular phones.

7. Well Testing

Drill stem testing is not an anticipated requirement for evaluation of this well. If a drill stem test is required, it will be conducted with a minimum number of personnel in the immediate vicinity. The test will be conducted during daylight hours only.



8. Emergency Phone Numbers

Eddy County Sheriff's Office	911 or 575-887-7551
Ambulance Service	911 or 575-885-2111
Carlsbad Fire Dept	911 or 575-885-2111
Loco Hills Volunteer Fire Dept.	911 or 575-677-3266
Closest Medical Facility - Columbia Medical Center of Carlsbad	575-492-5000

Mewbourne Oil Company	Hobbs District Office	575-393-5905
	Fax	575-397-6252
	2nd Fax	575-393-7259

District Manager	Robin Terrell	575-390-4816
Drilling Superintendent	Frosty Lathan	575-390-4103
	Bradley Bishop	575-390-6838
Drilling Foreman	Wesley Noseff	575-441-0729

Paduca 7/6 H3FC Fed Com #1H



Mewbourne Oil Company

Lea County, New Mexico NAD 83

Paduca 7/6 H3FC Fed Com #1H

Sec 7, T26S, R32E

SHL: 2500' FNL & 1620' FWL (Sec 7)

BHL: 100' FNL & 2220' FWL (Sec 6)

Plan: Design #1

Standard Planning Report

16 August, 2022

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Project	Lea County, New Mexico NAD 83		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Paduca 7/6 H3FC Fed Com #1H				
Site Position:		Northing:	385,384.70 usft	Latitude:	32.0580080
From:	Map	Easting:	732,014.10 usft	Longitude:	-103.7178412
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "		

Well	Sec 7, T26S, R32E					
Well Position	+N-S	0.0 usft	Northing:	385,384.70 usft	Latitude:	32.0580080
	+E-W	0.0 usft	Easting:	732,014.10 usft	Longitude:	-103.7178412
Position Uncertainty		0.0 usft	Wellhead Elevation:	3,278.0 usft	Ground Level:	3,250.0 usft
Grid Convergence:	0.33 °					

Wellbore	BHL: 100' FNL & 2220' FWL (Sec 6)				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	12/31/2014	7.21	59.92	48,147.93093291

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N-S (usft)	+E-W (usft)	Direction (°)
	0.0	0.0	0.0	4.11

Plan Survey Tool Program	Date	8/9/2022		
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks
1	0.0	19,135.4	Design #1 (BHL: 100' FNL & 2220	

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,275.0	0.00	0.00	1,275.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,275.0	5.51	136.59	1,275.0	0.0	0.0	0.00	0.00	0.00	0.00	
10,427.4	5.51	136.59	10,385.0	-638.6	604.1	0.00	0.00	0.00	0.00	
10,427.4	0.00	0.00	10,385.0	-638.6	604.1	614,546,543	614,546,543	0.00	180.00	KOP: 2195' FSL & 22:
11,328.5	90.11	359.68	10,958.0	-64.5	600.9	10.00	10.00	0.00	-0.32	
19,135.4	90.11	359.68	10,943.0	7,742.3	557.0	0.00	0.00	0.00	0.00	BHL: 100' FNL & 2220

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	
SHL: 2500' FNL & 1620' FWL (Sec 7)										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00	
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00	
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00	
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00	
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,275.0	5.51	136.59	1,275.0	0.0	0.0	0.0	7.35	7.35	0.00	
1,300.0	5.51	136.59	1,299.9	-1.7	1.7	-1.6	0.00	0.00	0.00	
1,400.0	5.51	136.59	1,399.4	-8.7	8.3	-8.1	0.00	0.00	0.00	
1,500.0	5.51	136.59	1,499.0	-15.7	14.9	-14.6	0.00	0.00	0.00	
1,600.0	5.51	136.59	1,598.5	-22.7	21.5	-21.1	0.00	0.00	0.00	
1,700.0	5.51	136.59	1,698.0	-29.7	28.1	-27.6	0.00	0.00	0.00	
1,800.0	5.51	136.59	1,797.6	-36.6	34.7	-34.0	0.00	0.00	0.00	
1,900.0	5.51	136.59	1,897.1	-43.6	41.3	-40.5	0.00	0.00	0.00	
2,000.0	5.51	136.59	1,996.6	-50.6	47.9	-47.0	0.00	0.00	0.00	
2,100.0	5.51	136.59	2,096.2	-57.6	54.5	-53.5	0.00	0.00	0.00	
2,200.0	5.51	136.59	2,195.7	-64.5	61.1	-60.0	0.00	0.00	0.00	
2,300.0	5.51	136.59	2,295.3	-71.5	67.7	-66.5	0.00	0.00	0.00	
2,400.0	5.51	136.59	2,394.8	-78.5	74.3	-73.0	0.00	0.00	0.00	
2,500.0	5.51	136.59	2,494.3	-85.5	80.9	-79.4	0.00	0.00	0.00	
2,600.0	5.51	136.59	2,593.9	-92.4	87.5	-85.9	0.00	0.00	0.00	
2,700.0	5.51	136.59	2,693.4	-99.4	94.1	-92.4	0.00	0.00	0.00	
2,800.0	5.51	136.59	2,792.9	-106.4	100.7	-98.9	0.00	0.00	0.00	
2,900.0	5.51	136.59	2,892.5	-113.4	107.3	-105.4	0.00	0.00	0.00	
3,000.0	5.51	136.59	2,992.0	-120.4	113.9	-111.9	0.00	0.00	0.00	
3,100.0	5.51	136.59	3,091.6	-127.3	120.5	-118.4	0.00	0.00	0.00	
3,200.0	5.51	136.59	3,191.1	-134.3	127.1	-124.8	0.00	0.00	0.00	
3,300.0	5.51	136.59	3,290.6	-141.3	133.7	-131.3	0.00	0.00	0.00	
3,400.0	5.51	136.59	3,390.2	-148.3	140.3	-137.8	0.00	0.00	0.00	
3,500.0	5.51	136.59	3,489.7	-155.2	146.9	-144.3	0.00	0.00	0.00	
3,600.0	5.51	136.59	3,589.3	-162.2	153.5	-150.8	0.00	0.00	0.00	
3,700.0	5.51	136.59	3,688.8	-169.2	160.1	-157.3	0.00	0.00	0.00	
3,800.0	5.51	136.59	3,788.3	-176.2	166.7	-163.8	0.00	0.00	0.00	
3,900.0	5.51	136.59	3,887.9	-183.1	173.3	-170.2	0.00	0.00	0.00	
4,000.0	5.51	136.59	3,987.4	-190.1	179.9	-176.7	0.00	0.00	0.00	
4,100.0	5.51	136.59	4,086.9	-197.1	186.5	-183.2	0.00	0.00	0.00	
4,200.0	5.51	136.59	4,186.5	-204.1	193.1	-189.7	0.00	0.00	0.00	
4,300.0	5.51	136.59	4,286.0	-211.1	199.7	-196.2	0.00	0.00	0.00	
4,400.0	5.51	136.59	4,385.6	-218.0	206.3	-202.7	0.00	0.00	0.00	
4,500.0	5.51	136.59	4,485.1	-225.0	212.9	-209.2	0.00	0.00	0.00	
4,600.0	5.51	136.59	4,584.6	-232.0	219.5	-215.6	0.00	0.00	0.00	
4,700.0	5.51	136.59	4,684.2	-239.0	226.1	-222.1	0.00	0.00	0.00	
4,800.0	5.51	136.59	4,783.7	-245.9	232.7	-228.6	0.00	0.00	0.00	
4,900.0	5.51	136.59	4,883.2	-252.9	239.3	-235.1	0.00	0.00	0.00	
5,000.0	5.51	136.59	4,982.8	-259.9	245.9	-241.6	0.00	0.00	0.00	
5,100.0	5.51	136.59	5,082.3	-266.9	252.5	-248.1	0.00	0.00	0.00	

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
5,200.0	5.51	136.59	5,181.9	-273.8	259.1	-254.5	0.00	0.00	0.00	
5,300.0	5.51	136.59	5,281.4	-280.8	265.7	-261.0	0.00	0.00	0.00	
5,400.0	5.51	136.59	5,380.9	-287.8	272.3	-267.5	0.00	0.00	0.00	
5,500.0	5.51	136.59	5,480.5	-294.8	278.9	-274.0	0.00	0.00	0.00	
5,600.0	5.51	136.59	5,580.0	-301.8	285.5	-280.5	0.00	0.00	0.00	
5,700.0	5.51	136.59	5,679.5	-308.7	292.1	-287.0	0.00	0.00	0.00	
5,800.0	5.51	136.59	5,779.1	-315.7	298.7	-293.5	0.00	0.00	0.00	
5,900.0	5.51	136.59	5,878.6	-322.7	305.3	-299.9	0.00	0.00	0.00	
6,000.0	5.51	136.59	5,978.2	-329.7	311.9	-306.4	0.00	0.00	0.00	
6,100.0	5.51	136.59	6,077.7	-336.6	318.5	-312.9	0.00	0.00	0.00	
6,200.0	5.51	136.59	6,177.2	-343.6	325.1	-319.4	0.00	0.00	0.00	
6,300.0	5.51	136.59	6,276.8	-350.6	331.7	-325.9	0.00	0.00	0.00	
6,400.0	5.51	136.59	6,376.3	-357.6	338.3	-332.4	0.00	0.00	0.00	
6,500.0	5.51	136.59	6,475.8	-364.5	344.9	-338.9	0.00	0.00	0.00	
6,600.0	5.51	136.59	6,575.4	-371.5	351.5	-345.3	0.00	0.00	0.00	
6,700.0	5.51	136.59	6,674.9	-378.5	358.1	-351.8	0.00	0.00	0.00	
6,800.0	5.51	136.59	6,774.5	-385.5	364.7	-358.3	0.00	0.00	0.00	
6,900.0	5.51	136.59	6,874.0	-392.5	371.3	-364.8	0.00	0.00	0.00	
7,000.0	5.51	136.59	6,973.5	-399.4	377.9	-371.3	0.00	0.00	0.00	
7,100.0	5.51	136.59	7,073.1	-406.4	384.5	-377.8	0.00	0.00	0.00	
7,200.0	5.51	136.59	7,172.6	-413.4	391.1	-384.3	0.00	0.00	0.00	
7,300.0	5.51	136.59	7,272.1	-420.4	397.7	-390.7	0.00	0.00	0.00	
7,400.0	5.51	136.59	7,371.7	-427.3	404.3	-397.2	0.00	0.00	0.00	
7,500.0	5.51	136.59	7,471.2	-434.3	410.9	-403.7	0.00	0.00	0.00	
7,600.0	5.51	136.59	7,570.8	-441.3	417.5	-410.2	0.00	0.00	0.00	
7,700.0	5.51	136.59	7,670.3	-448.3	424.1	-416.7	0.00	0.00	0.00	
7,800.0	5.51	136.59	7,769.8	-455.2	430.7	-423.2	0.00	0.00	0.00	
7,900.0	5.51	136.59	7,869.4	-462.2	437.3	-429.7	0.00	0.00	0.00	
8,000.0	5.51	136.59	7,968.9	-469.2	443.9	-436.1	0.00	0.00	0.00	
8,100.0	5.51	136.59	8,068.4	-476.2	450.5	-442.6	0.00	0.00	0.00	
8,200.0	5.51	136.59	8,168.0	-483.2	457.1	-449.1	0.00	0.00	0.00	
8,300.0	5.51	136.59	8,267.5	-490.1	463.7	-455.6	0.00	0.00	0.00	
8,400.0	5.51	136.59	8,367.1	-497.1	470.3	-462.1	0.00	0.00	0.00	
8,500.0	5.51	136.59	8,466.6	-504.1	476.9	-468.6	0.00	0.00	0.00	
8,600.0	5.51	136.59	8,566.1	-511.1	483.5	-475.1	0.00	0.00	0.00	
8,700.0	5.51	136.59	8,665.7	-518.0	490.1	-481.5	0.00	0.00	0.00	
8,800.0	5.51	136.59	8,765.2	-525.0	496.7	-488.0	0.00	0.00	0.00	
8,900.0	5.51	136.59	8,864.7	-532.0	503.3	-494.5	0.00	0.00	0.00	
9,000.0	5.51	136.59	8,964.3	-539.0	509.9	-501.0	0.00	0.00	0.00	
9,100.0	5.51	136.59	9,063.8	-545.9	516.5	-507.5	0.00	0.00	0.00	
9,200.0	5.51	136.59	9,163.4	-552.9	523.1	-514.0	0.00	0.00	0.00	
9,300.0	5.51	136.59	9,262.9	-559.9	529.7	-520.4	0.00	0.00	0.00	
9,400.0	5.51	136.59	9,362.4	-566.9	536.3	-526.9	0.00	0.00	0.00	
9,500.0	5.51	136.59	9,462.0	-573.9	542.9	-533.4	0.00	0.00	0.00	
9,600.0	5.51	136.59	9,561.5	-580.8	549.5	-539.9	0.00	0.00	0.00	
9,700.0	5.51	136.59	9,661.1	-587.8	556.1	-546.4	0.00	0.00	0.00	
9,800.0	5.51	136.59	9,760.6	-594.8	562.7	-552.9	0.00	0.00	0.00	
9,900.0	5.51	136.59	9,860.1	-601.8	569.3	-559.4	0.00	0.00	0.00	
10,000.0	5.51	136.59	9,959.7	-608.7	575.9	-565.8	0.00	0.00	0.00	
10,100.0	5.51	136.59	10,059.2	-615.7	582.5	-572.3	0.00	0.00	0.00	
10,200.0	5.51	136.59	10,158.7	-622.7	589.1	-578.8	0.00	0.00	0.00	
10,300.0	5.51	136.59	10,258.3	-629.7	595.7	-585.3	0.00	0.00	0.00	
10,400.0	5.51	136.59	10,357.8	-636.6	602.3	-591.8	0.00	0.00	0.00	
10,427.4	0.00	0.00	10,385.0	-638.6	604.1	-593.6	20.15	-20.15	0.00	

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
KOP: 2195' FSL & 2220' FWL (Sec 7)									
10,500.0	7.26	359.68	10,457.5	-634.0	604.1	-589.0	10.00	10.00	0.00
10,600.0	17.26	359.68	10,555.1	-612.7	604.0	-567.8	10.00	10.00	0.00
10,700.0	27.26	359.68	10,647.5	-574.9	603.8	-530.1	10.00	10.00	0.00
10,800.0	37.26	359.68	10,732.0	-521.6	603.5	-476.9	10.00	10.00	0.00
10,900.0	47.26	359.68	10,805.9	-454.4	603.1	-410.0	10.00	10.00	0.00
11,000.0	57.26	359.68	10,867.0	-375.4	602.6	-331.2	10.00	10.00	0.00
11,100.0	67.26	359.68	10,913.5	-287.0	602.1	-243.1	10.00	10.00	0.00
11,200.0	77.26	359.68	10,943.9	-191.9	601.6	-148.2	10.00	10.00	0.00
11,300.0	87.26	359.68	10,957.3	-92.9	601.0	-49.6	10.00	10.00	0.00
11,327.4	90.00	359.68	10,958.0	-65.6	600.9	-22.3	10.00	10.00	0.00
FTP/LP: 2569' FNL & 2220' FWL (Sec 7) - FTP/LP: 2569' FNL & 2220' FWL (Sec 7)									
11,328.5	90.11	359.68	10,958.0	-64.5	600.9	-21.2	10.00	10.00	0.00
11,400.0	90.11	359.68	10,957.9	7.0	600.5	50.1	0.00	0.00	0.00
11,500.0	90.11	359.68	10,957.7	107.0	599.9	149.8	0.00	0.00	0.00
11,600.0	90.11	359.68	10,957.5	207.0	599.4	249.5	0.00	0.00	0.00
11,700.0	90.11	359.68	10,957.3	307.0	598.8	349.2	0.00	0.00	0.00
11,800.0	90.11	359.68	10,957.1	407.0	598.2	448.9	0.00	0.00	0.00
11,900.0	90.11	359.68	10,956.9	507.0	597.7	548.6	0.00	0.00	0.00
12,000.0	90.11	359.68	10,956.7	607.0	597.1	648.3	0.00	0.00	0.00
12,100.0	90.11	359.68	10,956.5	707.0	596.5	748.0	0.00	0.00	0.00
12,200.0	90.11	359.68	10,956.3	807.0	596.0	847.7	0.00	0.00	0.00
12,300.0	90.11	359.68	10,956.1	907.0	595.4	947.4	0.00	0.00	0.00
12,400.0	90.11	359.68	10,955.9	1,007.0	594.9	1,047.1	0.00	0.00	0.00
12,500.0	90.11	359.68	10,955.7	1,107.0	594.3	1,146.8	0.00	0.00	0.00
12,600.0	90.11	359.68	10,955.6	1,207.0	593.7	1,246.5	0.00	0.00	0.00
12,700.0	90.11	359.68	10,955.4	1,307.0	593.2	1,346.2	0.00	0.00	0.00
12,800.0	90.11	359.68	10,955.2	1,407.0	592.6	1,445.9	0.00	0.00	0.00
12,900.0	90.11	359.68	10,955.0	1,507.0	592.0	1,545.6	0.00	0.00	0.00
13,000.0	90.11	359.68	10,954.8	1,607.0	591.5	1,645.3	0.00	0.00	0.00
13,100.0	90.11	359.68	10,954.6	1,707.0	590.9	1,745.0	0.00	0.00	0.00
13,200.0	90.11	359.68	10,954.4	1,807.0	590.4	1,844.7	0.00	0.00	0.00
13,300.0	90.11	359.68	10,954.2	1,907.0	589.8	1,944.4	0.00	0.00	0.00
13,400.0	90.11	359.68	10,954.0	2,007.0	589.2	2,044.1	0.00	0.00	0.00
13,500.0	90.11	359.68	10,953.8	2,107.0	588.7	2,143.8	0.00	0.00	0.00
13,600.0	90.11	359.68	10,953.6	2,207.0	588.1	2,243.5	0.00	0.00	0.00
13,700.0	90.11	359.68	10,953.4	2,307.0	587.6	2,343.2	0.00	0.00	0.00
13,800.0	90.11	359.68	10,953.3	2,407.0	587.0	2,442.9	0.00	0.00	0.00
13,900.0	90.11	359.68	10,953.1	2,507.0	586.4	2,542.6	0.00	0.00	0.00
14,000.0	90.11	359.68	10,952.9	2,607.0	585.9	2,642.3	0.00	0.00	0.00
14,100.0	90.11	359.68	10,952.7	2,707.0	585.3	2,742.0	0.00	0.00	0.00
14,200.0	90.11	359.68	10,952.5	2,807.0	584.7	2,841.7	0.00	0.00	0.00
14,300.0	90.11	359.68	10,952.3	2,907.0	584.2	2,941.4	0.00	0.00	0.00
14,400.0	90.11	359.68	10,952.1	3,007.0	583.6	3,041.1	0.00	0.00	0.00
14,500.0	90.11	359.68	10,951.9	3,107.0	583.1	3,140.8	0.00	0.00	0.00
14,600.0	90.11	359.68	10,951.7	3,207.0	582.5	3,240.5	0.00	0.00	0.00
14,700.0	90.11	359.68	10,951.5	3,307.0	581.9	3,340.2	0.00	0.00	0.00
14,800.0	90.11	359.68	10,951.3	3,407.0	581.4	3,439.9	0.00	0.00	0.00
14,900.0	90.11	359.68	10,951.1	3,507.0	580.8	3,539.6	0.00	0.00	0.00
15,000.0	90.11	359.68	10,950.9	3,607.0	580.2	3,639.3	0.00	0.00	0.00
15,100.0	90.11	359.68	10,950.8	3,707.0	579.7	3,739.0	0.00	0.00	0.00
15,200.0	90.11	359.68	10,950.6	3,807.0	579.1	3,838.7	0.00	0.00	0.00
15,300.0	90.11	359.68	10,950.4	3,907.0	578.6	3,938.4	0.00	0.00	0.00
15,400.0	90.11	359.68	10,950.2	4,007.0	578.0	4,038.1	0.00	0.00	0.00

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,500.0	90.11	359.68	10,950.0	4,107.0	577.4	4,137.8	0.00	0.00	0.00
15,600.0	90.11	359.68	10,949.8	4,207.0	576.9	4,237.5	0.00	0.00	0.00
15,700.0	90.11	359.68	10,949.6	4,307.0	576.3	4,337.2	0.00	0.00	0.00
15,800.0	90.11	359.68	10,949.4	4,407.0	575.7	4,436.9	0.00	0.00	0.00
15,900.0	90.11	359.68	10,949.2	4,507.0	575.2	4,536.6	0.00	0.00	0.00
16,000.0	90.11	359.68	10,949.0	4,607.0	574.6	4,636.3	0.00	0.00	0.00
16,100.0	90.11	359.68	10,948.8	4,707.0	574.1	4,736.0	0.00	0.00	0.00
16,200.0	90.11	359.68	10,948.6	4,807.0	573.5	4,835.7	0.00	0.00	0.00
16,300.0	90.11	359.68	10,948.4	4,907.0	572.9	4,935.4	0.00	0.00	0.00
16,400.0	90.11	359.68	10,948.3	5,007.0	572.4	5,035.1	0.00	0.00	0.00
16,500.0	90.11	359.68	10,948.1	5,106.9	571.8	5,134.8	0.00	0.00	0.00
16,600.0	90.11	359.68	10,947.9	5,206.9	571.3	5,234.5	0.00	0.00	0.00
16,700.0	90.11	359.68	10,947.7	5,306.9	570.7	5,334.2	0.00	0.00	0.00
16,800.0	90.11	359.68	10,947.5	5,406.9	570.1	5,433.9	0.00	0.00	0.00
16,900.0	90.11	359.68	10,947.3	5,506.9	569.6	5,533.6	0.00	0.00	0.00
17,000.0	90.11	359.68	10,947.1	5,606.9	569.0	5,633.3	0.00	0.00	0.00
17,100.0	90.11	359.68	10,946.9	5,706.9	568.4	5,733.0	0.00	0.00	0.00
17,200.0	90.11	359.68	10,946.7	5,806.9	567.9	5,832.7	0.00	0.00	0.00
17,300.0	90.11	359.68	10,946.5	5,906.9	567.3	5,932.4	0.00	0.00	0.00
17,400.0	90.11	359.68	10,946.3	6,006.9	566.8	6,032.1	0.00	0.00	0.00
17,500.0	90.11	359.68	10,946.1	6,106.9	566.2	6,131.8	0.00	0.00	0.00
17,600.0	90.11	359.68	10,945.9	6,206.9	565.6	6,231.5	0.00	0.00	0.00
17,700.0	90.11	359.68	10,945.8	6,306.9	565.1	6,331.2	0.00	0.00	0.00
17,800.0	90.11	359.68	10,945.6	6,406.9	564.5	6,430.9	0.00	0.00	0.00
17,900.0	90.11	359.68	10,945.4	6,506.9	563.9	6,530.6	0.00	0.00	0.00
17,901.7	90.11	359.68	10,945.4	6,508.6	563.9	6,532.3	0.00	0.00	0.00
PPP2: 1234' FNL & 2220' FWL (Sec 6) - PPP2: 1334' FNL & 2220' FWL (Sec 6)									
18,000.0	90.11	359.68	10,945.2	6,606.9	563.4	6,630.3	0.00	0.00	0.00
18,100.0	90.11	359.68	10,945.0	6,706.9	562.8	6,730.0	0.00	0.00	0.00
18,200.0	90.11	359.68	10,944.8	6,806.9	562.3	6,829.7	0.00	0.00	0.00
18,300.0	90.11	359.68	10,944.6	6,906.9	561.7	6,929.4	0.00	0.00	0.00
18,400.0	90.11	359.68	10,944.4	7,006.9	561.1	7,029.1	0.00	0.00	0.00
18,500.0	90.11	359.68	10,944.2	7,106.9	560.6	7,128.8	0.00	0.00	0.00
18,600.0	90.11	359.68	10,944.0	7,206.9	560.0	7,228.5	0.00	0.00	0.00
18,700.0	90.11	359.68	10,943.8	7,306.9	559.4	7,328.2	0.00	0.00	0.00
18,800.0	90.11	359.68	10,943.6	7,406.9	558.9	7,427.9	0.00	0.00	0.00
18,900.0	90.11	359.68	10,943.5	7,506.9	558.3	7,527.6	0.00	0.00	0.00
19,000.0	90.11	359.68	10,943.3	7,606.9	557.8	7,627.3	0.00	0.00	0.00
19,100.0	90.11	359.68	10,943.1	7,706.9	557.2	7,727.0	0.00	0.00	0.00
19,135.4	90.11	359.68	10,943.0	7,742.3	557.0	7,762.3	0.00	0.00	0.00
BHL: 100' FNL & 2220' FWL (Sec 6)									

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Design Targets										
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
SHL: 2500' FNL & 1620' - plan hits target center - Point	0.00	0.00	0.0	0.0	0.0	385,384.70	732,014.10	32.0580080	-103.7178412	
KOP: 2195' FSL & 2220' - plan hits target center - Point	0.00	0.00	10,385.0	-638.6	604.1	384,746.14	732,618.21	32.0562433	-103.7159031	
BHL: 100' FNL & 2220' F - plan hits target center - Point	0.00	0.01	10,943.0	7,742.3	557.0	393,127.00	732,571.10	32.0792814	-103.7159004	
PPP2: 1334' FNL & 2220' - plan hits target center - Point	0.00	0.00	10,945.4	6,508.6	563.9	391,893.30	732,578.03	32.0758901	-103.7159008	
FTP/LP: 2569' FNL & 2220' - plan hits target center - Point	0.00	0.00	10,958.0	-65.6	600.9	385,319.10	732,614.99	32.0578183	-103.7159029	

Operator Name:	Property Name:	Well Number
----------------	----------------	-------------

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Is this well the defining well for the Horizontal Spacing Unit?

Is this well an infill well?

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

SUPO Data Report

05/20/2024

APD ID: 10400087453

Submission Date: 11/14/2022

Highlighted data reflects the most recent changes

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

[Show Final Text](#)

Well Type: OTHER

Well Work Type: Drill

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

Paduca_7_6_H3FC_Fed_Com_1H_ExistingRoadMap_20220922110954.pdf

Existing Road Purpose: ACCESS,FLUID TRANSPORT

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? NO

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Paduca_7_6_H3FC_Fed_Com_1H_ExistingWellMap_20220922110814.pdf

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Production facility is onsite on the west edge of the existing pad.

Production Facilities map:

Paduca_7_6_H3FC_Fed_Com_1H_ProductionFacilitymap_20220922110820.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Water source type: IRRIGATION

Water source use type: DUST CONTROL
CAMP USE
SURFACE CASING
INTERMEDIATE/PRODUCTION CASING
STIMULATION

Source latitude: 32.093172

Source longitude: -103.736026

Source datum: NAD83

Water source permit type: WATER WELL

Water source transport method: TRUCKING

Source land ownership: PRIVATE

Source transportation land ownership: STATE

Water source volume (barrels): 1940

Source volume (acre-feet): 0.2500526

Source volume (gal): 81480

Water source and transportation

Paduca_7_6_H3FC_Fed_Com_1H_WaterSourceTransmap_20220922110829.jpg

Water source comments: BOTH SOURCES SHOWN ON ONE MAP

New water well? N

New Water Well Info

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Using any construction materials: YES

Construction Materials description: Caliche

Construction Materials source location

Paduca_7_6_H3FC_Fed_Com_1H_CalicheSourceTransmap_20220922110836.jpg

Section 7 - Methods for Handling

Waste type: DRILLING

Waste content description: DRILL CUTTINGS

Amount of waste: 940 barrels

Waste disposal frequency : One Time Only

Safe containment description: DRILL CUTTINGS WILL BE PROPERLY CONTAINED IN STEEL TANKS (20 YARD ROLL OFF BINS.)

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: NMOCD approved waste disposal locations are CRI or Lea Land, both facilities are located on HWY 62/180, Sec 27, T20S, R32E

Operator Name: MEWBOURNE OIL COMPANY	
Well Name: PADUCA 7/6 H3FC FED COM	Well Number: 1H

Waste type: SEWAGE

Waste content description: Human waste & grey water

Amount of waste: 1500 gallons

Waste disposal frequency : Weekly

Safe containment description: 2,000 gallon plastic container

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: City of Carlsbad Water Treatment facility

Waste type: GARBAGE

Waste content description: Garbage & Trash

Amount of waste: 1500 pounds

Waste disposal frequency : One Time Only

Safe containment description: Enclosed trash trailer

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: Waste Management facility in Carlsbad.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit? NO

Reserve pit length (ft.) **Reserve pit width (ft.)**

Reserve pit depth (ft.) **Reserve pit volume (cu. yd.)**

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? N

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Description of cuttings location

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary

Are you requesting any Ancillary Facilities?: N

Ancillary Facilities

Comments:

Section 9 - Well Site

Well Site Layout Diagram:

Paduca_7_6_H3FC_Fed_Com_1H_WellSiteLayout_20220922110853.pdf

Comments: NONE

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: Paduca ED well pad

Multiple Well Pad Number: 6

Recontouring

Drainage/Erosion control construction: NONE

Drainage/Erosion control reclamation: NONE

Well pad proposed disturbance (acres): 4.59

Well pad interim reclamation (acres): 0.68

Well pad long term disturbance (acres): 3.91

Road proposed disturbance (acres): 0

Road interim reclamation (acres): 0

Road long term disturbance (acres): 0

Powerline proposed disturbance (acres): 0

Powerline interim reclamation (acres): 0

Powerline long term disturbance (acres): 0

Pipeline proposed disturbance (acres): 0

Pipeline interim reclamation (acres): 0

Pipeline long term disturbance (acres): 0

Other proposed disturbance (acres): 0

Other interim reclamation (acres): 0

Other long term disturbance (acres): 0

Total proposed disturbance: 4.59

Total interim reclamation: 0.68

Total long term disturbance: 3.91

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Disturbance Comments: In areas to be heavily disturbed, the top 6 inches of soil material, will be stripped and stockpiled on the perimeter of the well location to keep topsoil viable, and to make redistribution of topsoil more efficient during interim reclamation. Stockpiled topsoil should include vegetative material. Topsoil will be clearly segregated and stored separately from subsoils. Contaminated soil will not be stockpiled, but properly treated and handled prior to topsoil salvaging.

Reconstruction method: The areas planned for interim reclamation will then be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ration, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.

Topsoil redistribution: Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations including cuts & fills. To see the area, the proper BLM seed mixture, free of noxious weeds, will be used.

Soil treatment: N/A

Existing Vegetation at the well pad: VARIOUS BRUSH & GRASSES

Existing Vegetation at the well pad

Existing Vegetation Community at the road: VARIOUS BRUSH & GRASSES

Existing Vegetation Community at the road

Existing Vegetation Community at the pipeline: none

Existing Vegetation Community at the pipeline

Existing Vegetation Community at other disturbances: none

Existing Vegetation Community at other disturbances

Non native seed used? N

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? N

Seedling transplant description

Will seed be harvested for use in site reclamation? N

Seed harvest description:

Seed harvest description attachment:

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Seed

Seed Table

Seed Summary

Total pounds/Acre:

Seed Type

Pounds/Acre

Seed reclamation

Operator Contact/Responsible Official

First Name:

Last Name:

Phone:

Email:

Seedbed prep: Final seedbed preparation will consist of contour cultivating to the depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.

Seed BMP: To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used.

Seed method: Drilling or broadcasting seed over entire reclaimed area.

Existing invasive species? N

Existing invasive species treatment description:

Existing invasive species treatment

Weed treatment plan description: N/A

Weed treatment plan

Monitoring plan description: vii. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, and that erosion and invasive/noxious weeds are controlled.

Monitoring plan

Success standards: regrowth within 1 full growing season of reclamation.

Pit closure description: NA

Pit closure attachment:

Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Disturbance type: EXISTING ACCESS ROAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Section 12 - Other

Right of Way needed? N

Use APD as ROW?

ROW Type(s):

ROW

SUPO Additional Information: MAY 26 2022 Met w/RRC Surveying & staked location @ 2500' FNL & 1620' FWL, Sec 7, T26S, R32E, Lea, Co., NM. (Elevation @ 3250'). Pad is 500' x 400'. Topsoil staked 30 wide to the S. Reclaim 60' S. No road needed. Pad overlaps existing Paduca 7/6 W1FC pad to the E & proposed Paduca 7/6 ED wells to the W. Will need to move existing compressors & lines for E & W half of pad. Pad will be built over existing MOC SWD & flow lines to the S. Will require onsite w/BLM. Lat. 32.0580081 N, Long. -103.71784104 W NAD83. (BPS)

Use a previously conducted onsite? N

Previous Onsite information:


Other SUPO

Paudca_7_6_H3FC_Fed_Com_1H_NGMP_20220922110921.pdf

Paduca_7_6_H3FC_Fed_Com_1H_InterimReclamationMap_20220922110926.pdf

VICINITY MAP

NOT TO SCALE



PADUCA 7/6 H3FC FED COM #1H

*SECTION 7, TWP. 26 SOUTH, RGE. 32 EAST,
N. M. P. M., LEA CO., NEW MEXICO*

OPERATOR: Mewbourne Oil Company
 LEASE: Paduca 7/6 H3FC Fed Com
 WELL NO.: 1H

LOCATION: 2500' FNL & 1620' FWL
 ELEVATION: 3250'

Copyright 2016 - All Rights Reserved


NO.	REVISION	DATE
JOB NO.: LS22050641		
DWG. NO.: 22050641-3		



ENERGY SERVICES LLC.
 701 S. CECIL ST., HOBBS, NM 88240 (575) 964-8200


SCALE: N. T. S.
DATE: 05/25/2022
SURVEYED BY: ML/AB/JM
DRAWN BY: RQ
APPROVED BY: RMH
SHEET: 1 OF 1

OCD Well Locations



9/19/2022, 11:04:38 AM


- | | | | |
|------------|---------------------|----------------|----------------------------|
| Areas | Wells - Large Scale | Gas, New | Oil, New |
| Override 1 | Miscellaneous | Oil, Active | Oil, Plugged |
| Override 2 | Gas, Active | Oil, Cancelled | Oil, Temporarily Abandoned |



Esri, NASA, NGA, USGS, FEMA, Oil Conservation Division of the New Mexico Energy, Minerals and Natural Resources Department, Texas Parks &


New Mexico Oil Conservation Division

**MEWBOURNE OIL COMPANY
 PADUCA 7/6 H3FC FED COM #1H
 (2500' FNL & 1620' FWL)
 SECTION 7, T26S, R32E
 N. M. P. M., LEA CO., NEW MEXICO**



DIRECTIONS TO LOCATION

*From the intersection of CR #2 (Battle Axe Rd.) & CR #1 (Orla Hwy);
 Go North on CR #1 approx. 3.1 miles to a Pipeline Rd. on the left;
 Turn left and go West approx. 2.5 miles to a lease road on the left;
 Turn left and go South approx. 0.4 miles to a lease road on the right;
 Turn right and go West approx. 0.1 miles to location on the left.*



I, R. M. Howett, a N. M. Professional Surveyor, hereby certify that I prepared this unclassified survey of a well location from an actual survey made on the ground under my direct supervision, said survey and plat meet the Min. Stds. for Land Surveying in the State of N. M. and are true and correct to the best of my knowledge and belief.

Robert M. Howett
 Robert M. Howett NM PS 19680



Copyright 2016 - All Rights Reserved


NO.	REVISION	DATE
JOB NO.: LS22050641		
DWG. NO.: 22050641-4		



ENERGY SERVICES LLC.
 701 S. CECIL ST., HOBBS, NM 88240 (575) 964-8200


SCALE: 1" = 100'
DATE: 05/25/2022
SURVEYED BY: ML/AB/JM
DRAWN BY: RQ
APPROVED BY: RMH
SHEET: 1 OF 1

**MEWBOURNE OIL COMPANY
 PADUCA 7/6 H3FC FED COM #1H
 (2500' FNL & 1620' FWL)
 SECTION 7, T26S, R32E
 N. M. P. M., LEA CO., NEW MEXICO**



DIRECTIONS TO LOCATION

*From the intersection of CR #2 (Battle Axe Rd.) & CR #1 (Orla Hwy);
 Go North on CR #1 approx. 3.1 miles to a Pipeline Rd. on the left;
 Turn left and go West approx. 2.5 miles to a lease road on the left;
 Turn left and go South approx. 0.4 miles to a lease road on the right;
 Turn right and go West approx. 0.1 miles to location on the left.*



I, R. M. Howett, a N. M. Professional Surveyor, hereby certify that I prepared this unclassified survey of a well location from an actual survey made on the ground under my direct supervision, said survey and plat meet the Min. Stds. for Land Surveying in the State of N. M. and are true and correct to the best of my knowledge and belief.

Robert M. Howett
 Robert M. Howett NM PS 19680



Copyright 2016 - All Rights Reserved

			RRC ENERGY SERVICES LLC. 701 S. CECIL ST., HOBBS, NM 88240 (575) 964-8200	SCALE: 1" = 100'
				DATE: 05/25/2022
NO.	REVISION	DATE		SURVEYED BY: ML/AB/JM
JOB NO.: LS22050641				DRAWN BY: RQ
DWG. NO.: 22050641-4				APPROVED BY: RMH
				SHEET: 1 OF 1

State of New Mexico
Energy, Minerals and Natural Resources Department

Submit Electronically
Via E-permitting

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description

Effective May 25, 2021

I. Operator: Mewbourne Oil Co. **OGRID:** 14744 **Date:** 5/2/22

II. Type: Original Amendment due to 19.15.27.9.D(6)(a) NMAC 19.15.27.9.D(6)(b) NMAC Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Paduca 7/6 H3FC Fed Com 1H		F 7 26S 32E	2500' FNL x 1620' FWL	1500	3000	2500

IV. Central Delivery Point Name: Paduca 7/6 H3FC Fed Com 1H [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Paduca 7/6 H3FC Fed Com 1H		7/2/22	8/2/22	9/2/22	9/17/22	9/17/22

VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan
EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system will will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator does does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

Attach Operator’s plan to manage production in response to the increased line pressure.

XIV. Confidentiality: Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

Page 8

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	<i>Bradley Bishop</i>
Printed Name:	BRADLEY BISHOP
Title:	REGULATORY MANAGER
E-mail Address:	BBISHOP@MEWBOURNE.COM
Date:	5/2/22
Phone:	575-393-5905
OIL CONSERVATION DIVISION (Only applicable when submitted as a standalone form)	
Approved By:	
Title:	
Approval Date:	
Conditions of Approval:	

Mewbourne Oil Company


Natural Gas Management Plan – Attachment

- VI. Separation equipment will be sized by construction engineering staff based on stated manufacturer daily throughput capacities and anticipated daily production rates to ensure adequate capacity. Closed vent system piping, compression needs, and VRUs will be sized utilizing ProMax modelling software to ensure adequate capacity for anticipated production volumes and conditions.
- VII. Mewbourne Oil Company (MOC) will take following actions to comply with the regulations listed in 19.15.27.8 :
- A. MOC will maximize the recovery of natural gas by minimizing the waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. MOC will ensure that well(s) will be connected to a natural gas gathering system with sufficient capacity to transport natural gas. If there is no adequate takeaway for the gas, well(s) will be shut in until the natural gas gathering system is available.
 - B. All drilling operations will be equipped with a rig flare located at least 100 ft from the nearest surface hole. Rig flare will be utilized to combust any natural gas that is brought to surface during normal drilling operations. In the case of emergency venting or flaring the volumes will be estimated and reported appropriately.
 - C. During completion operations any natural gas brought to surface will be flared. Immediately following the finish of completion operations, all well flow will be directed to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. It is not anticipated that gas will not meet pipeline standards. However, if natural gas does not meet gathering pipeline quality specifications, MOC will flare the natural gas for 60 days or until the natural gas meets the pipeline quality specifications, whichever is sooner. MOC will ensure that the flare is sized properly and is equipped with automatic igniter or continuous pilot. The gas sample will analyzed twice per week and the gas will be routed into a gathering system as soon as pipeline specifications are met.
 - D. Natural gas will not be flared with the exceptions and provisions listed in the 19.15.27.8 D.(1) through (4). If there is no adequate takeaway for the separator gas, well(s) will be shut in until the natural gas gathering system is available with exception of emergency or malfunction situations. Venting and/or flaring volumes will be estimated and reported appropriately.
 - E. MOC will comply with the performance standards requirements and provisions listed in 19.15.27.8 E.(1) through (8). All equipment will be designed and sized to handle maximum anticipated pressures and throughputs in order to minimize the waste. Production storage tanks constructed after May 25, 2021 will be equipped with automatic gauging system. Flares constructed after May 25, 2021 will be equipped with automatic igniter or continuous pilot. Flares will be located at least 100' from the well and storage tanks unless otherwise approved by the division. MOC will conduct AVO inspections as described in 19.15.27.8 E (5) (a) with frequencies specified in 19.15.27.8 E (5) (b) and (c). All emergencies will be resolved as quickly and safely as feasible to minimize waste.
 - F. The volume of natural gas that is vented or flared as the result of malfunction or emergency during drilling and completions operations will be estimated. The volume of natural gas that is vented, flared or beneficially used during production operations, will be measured or estimated. MOC will install equipment to measure

the volume of natural gas flared from existing process piping or a flowline piped from equipment such as high pressure separators, heater treaters, or vapor recovery units associated with a well or facility associated with a well authorized by an APD issued after May 25, 2021 that has an average daily production greater than 60 Mcf/day. If metering is not practicable due to circumstances such as low flow rate or low pressure venting and flaring, MOC will estimate the volume of vented or flared natural gas. Measuring equipment will conform to industry standards and will not be designed or equipped with a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing the measurement equipment.


- VIII. For maintenance activities involving production equipment and compression, venting will be limited to the depressurization of the subject equipment to ensure safe working conditions. For maintenance of production and compression equipment the associated producing wells will be shut in to eliminate venting. For maintenance of VRUs all gas normally routed to the VRU will be routed to flare to eliminate venting.

**MEWBOURNE OIL COMPANY
 PADUCA 7/6 H3FC FED COM #1H
 (2500' FNL & 1620' FWL)
 SECTION 7, T26S, R32E
 N. M. P. M., LEA CO., NEW MEXICO**




DIRECTIONS TO LOCATION

*From the intersection of CR #2 (Battle Axe Rd.) & CR #1 (Orla Hwy);
 Go North on CR #1 approx. 3.1 miles to a Pipeline Rd. on the left;
 Turn left and go West approx. 2.5 miles to a lease road on the left;
 Turn left and go South approx. 0.4 miles to a lease road on the right;
 Turn right and go West approx. 0.1 miles to location on the left.*



I, R. M. Howett, a N. M. Professional Surveyor, hereby certify that I prepared this unclassified survey of a well location from an actual survey made on the ground under my direct supervision, said survey and plat meet the Min. Stds. for Land Surveying in the State of N. M. and are true and correct to the best of my knowledge and belief.

Robert M. Howett
 Robert M. Howett NM PS 19680



Copyright 2016 - All Rights Reserved

			RRC ENERGY SERVICES LLC. 701 S. CECIL ST., HOBBS, NM 88240 (575) 964-8200	SCALE: 1" = 100'
				DATE: 05/25/2022
NO.	REVISION	DATE		SURVEYED BY: ML/AB/JM
JOB NO.: LS22050641				DRAWN BY: RQ
DWG. NO.: 22050641-4				APPROVED BY: RMH
				SHEET: 1 OF 1



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

PWD Data Report

05/20/2024

APD ID: 10400087453

Submission Date: 11/14/2022

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Well Type: OTHER

Well Work Type: Drill

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined

Would you like to utilize Lined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit

Pit liner description:

Pit liner manufacturers

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule

Lined pit reclamation description:

Lined pit reclamation

Leak detection system description:

Leak detection system

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Lined pit Monitor description:

Lined pit Monitor

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information

Section 3 - Unlined

Would you like to utilize Unlined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD disturbance (acres):

PWD surface owner:

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule

Unlined pit reclamation description:

Unlined pit reclamation

Unlined pit Monitor description:

Unlined pit Monitor

Do you propose to put the produced water to beneficial use?

Beneficial use user

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic

State

Unlined Produced Water Pit Estimated

Unlined pit: do you have a reclamation bond for the pit?

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information

Section 4 -

Would you like to utilize Injection PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Injection well name:

Assigned injection well API number?

Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection

Underground Injection Control (UIC) Permit?

UIC Permit

Section 5 - Surface

Would you like to utilize Surface Discharge PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 -

Would you like to utilize Other PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Other PWD type description:

Other PWD type

Have other regulatory requirements been met?

Other regulatory requirements



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data

05/20/2024

APD ID: 10400087453

Submission Date: 11/14/2022

Operator Name: MEWBOURNE OIL COMPANY

Highlighted data reflects the most recent changes

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

[Show Final Text](#)

Well Type: OTHER

Well Work Type: Drill

Bond

Federal/Indian APD: FED

BLM Bond number: NM 1693

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

AMENDED REPORT

WC-025 G-08
S253235G;LOWER

WELL LOCATION AND ACREAGE DEDICATION PLAT

Table with 3 columns: 1 API Number (30-025-53037), 2 Pool Code (97903), 3 Pool Name (BONE SPRING), 4 Property Code (335966), 5 Property Name (PADUCA 7/6 H3FC FED COM), 6 Well Number (1H), 7 OGRID NO. (14744), 8 Operator Name (MEWBOURNE OIL COMPANY), 9 Elevation (3250')

10 Surface Location


Table with 10 columns: UL or lot no. (F), Section (7), Township (26S), Range (32E), Lot Idn, Feet from the (2500), North/South line (NORTH), Feet From the (1620), East/West line (WEST), County (LEA)

11 Bottom Hole Location If Different From Surface

Table with 10 columns: UL or lot no. (C), Section (6), Township (26S), Range (32E), Lot Idn, Feet from the (100), North/South line (NORTH), Feet from the (2220), East/West line (WEST), County (LEA)

Table with 4 columns: 12 Dedicated Acres (240), 13 Joint or Infill, 14 Consolidation Code, 15 Order No.

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.



17 OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.
Signature: Bradley C Bishop
Date: 9/21/22
Printed Name: BRADLEY BISHOP
E-mail Address: BBISHOP@MEWBOURNE.COM

18 SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.
Date of Survey: 05/25/2022
Signature and Seal of Professional Surveyor: Robert M. Howett
Certificate Number: 19680

Job No.:LS22050641

State of New Mexico
Energy, Minerals and Natural Resources Department

Submit Electronically
Via E-permitting

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description

Effective May 25, 2021

I. Operator: Mewbourne Oil Co. **OGRID:** 14744 **Date:** 5/2/22

II. Type: Original Amendment due to 19.15.27.9.D(6)(a) NMAC 19.15.27.9.D(6)(b) NMAC Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Paduca 7/6 H3FC Fed Com 1H		F 7 26S 32E	2500' FNL x 1620' FWL	1500	3000	2500

IV. Central Delivery Point Name: Paduca 7/6 H3FC Fed Com 1H [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Paduca 7/6 H3FC Fed Com 1H		7/2/22	8/2/22	9/2/22	9/17/22	9/17/22

VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan
EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system will will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator does does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

Attach Operator’s plan to manage production in response to the increased line pressure.

XIV. Confidentiality: Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

Page 8

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	<i>Bradley Bishop</i>
Printed Name:	BRADLEY BISHOP
Title:	REGULATORY MANAGER
E-mail Address:	BBISHOP@MEWBOURNE.COM
Date:	5/2/22
Phone:	575-393-5905
OIL CONSERVATION DIVISION (Only applicable when submitted as a standalone form)	
Approved By:	
Title:	
Approval Date:	
Conditions of Approval:	

Mewbourne Oil Company

Natural Gas Management Plan – Attachment

- VI. Separation equipment will be sized by construction engineering staff based on stated manufacturer daily throughput capacities and anticipated daily production rates to ensure adequate capacity. Closed vent system piping, compression needs, and VRUs will be sized utilizing ProMax modelling software to ensure adequate capacity for anticipated production volumes and conditions.
- VII. Mewbourne Oil Company (MOC) will take following actions to comply with the regulations listed in 19.15.27.8 :
- A. MOC will maximize the recovery of natural gas by minimizing the waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. MOC will ensure that well(s) will be connected to a natural gas gathering system with sufficient capacity to transport natural gas. If there is no adequate takeaway for the gas, well(s) will be shut in until the natural gas gathering system is available.
 - B. All drilling operations will be equipped with a rig flare located at least 100 ft from the nearest surface hole. Rig flare will be utilized to combust any natural gas that is brought to surface during normal drilling operations. In the case of emergency venting or flaring the volumes will be estimated and reported appropriately.
 - C. During completion operations any natural gas brought to surface will be flared. Immediately following the finish of completion operations, all well flow will be directed to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. It is not anticipated that gas will not meet pipeline standards. However, if natural gas does not meet gathering pipeline quality specifications, MOC will flare the natural gas for 60 days or until the natural gas meets the pipeline quality specifications, whichever is sooner. MOC will ensure that the flare is sized properly and is equipped with automatic igniter or continuous pilot. The gas sample will analyzed twice per week and the gas will be routed into a gathering system as soon as pipeline specifications are met.
 - D. Natural gas will not be flared with the exceptions and provisions listed in the 19.15.27.8 D.(1) through (4). If there is no adequate takeaway for the separator gas, well(s) will be shut in until the natural gas gathering system is available with exception of emergency or malfunction situations. Venting and/or flaring volumes will be estimated and reported appropriately.
 - E. MOC will comply with the performance standards requirements and provisions listed in 19.15.27.8 E.(1) through (8). All equipment will be designed and sized to handle maximum anticipated pressures and throughputs in order to minimize the waste. Production storage tanks constructed after May 25, 2021 will be equipped with automatic gauging system. Flares constructed after May 25, 2021 will be equipped with automatic igniter or continuous pilot. Flares will be located at least 100' from the well and storage tanks unless otherwise approved by the division. MOC will conduct AVO inspections as described in 19.15.27.8 E (5) (a) with frequencies specified in 19.15.27.8 E (5) (b) and (c). All emergencies will be resolved as quickly and safely as feasible to minimize waste.
 - F. The volume of natural gas that is vented or flared as the result of malfunction or emergency during drilling and completions operations will be estimated. The volume of natural gas that is vented, flared or beneficially used during production operations, will be measured or estimated. MOC will install equipment to measure

the volume of natural gas flared from existing process piping or a flowline piped from equipment such as high pressure separators, heater treaters, or vapor recovery units associated with a well or facility associated with a well authorized by an APD issued after May 25, 2021 that has an average daily production greater than 60 Mcf/day. If metering is not practicable due to circumstances such as low flow rate or low pressure venting and flaring, MOC will estimate the volume of vented or flared natural gas. Measuring equipment will conform to industry standards and will not be designed or equipped with a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing the measurement equipment.

- VIII. For maintenance activities involving production equipment and compression, venting will be limited to the depressurization of the subject equipment to ensure safe working conditions. For maintenance of production and compression equipment the associated producing wells will be shut in to eliminate venting. For maintenance of VRUs all gas normally routed to the VRU will be routed to flare to eliminate venting.



Drilling Plan Data Report

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

05/20/2024

APD ID: 10400087453

Submission Date: 11/14/2022

Highlighted data
reflects the most
recent changes

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Well Type: OTHER

Well Work Type: Drill

[Show Final Text](#)

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical	Measured Depth	Lithologies	Mineral Resources	Producing Formatio
13409582	UNKNOWN	3278	28	28	OTHER : Topsoil	NONE	N
13409583	RUSTLER	2279	999	999	ANHYDRITE, DOLOMITE	USEABLE WATER	N
13409593	TOP SALT	1946	1332	1332	SALT	NONE	N
13409594	BASE OF SALT	-834	4112	4112	SALT	NONE	N
13409596	LAMAR	-1047	4325	4325	LIMESTONE	NATURAL GAS, OIL	N
13409597	BELL CANYON	-1070	4348	4348	SANDSTONE	NATURAL GAS, OIL	N
13409598	CHERRY CANYON	-2081	5359	5359	SANDSTONE	NATURAL GAS, OIL	N
13409599	MANZANITA	-2208	5486	5486	LIMESTONE	NATURAL GAS, OIL	N
13409590	BONE SPRING	-5068	8346	8346	LIMESTONE, SHALE	NATURAL GAS, OIL	N
13409591	BONE SPRING 1ST	-6084	9362	9362	SANDSTONE	NATURAL GAS, OIL	N
13409601	BONE SPRING 2ND	-6649	9927	9927	SANDSTONE	NATURAL GAS, OIL	Y
13409602	BONE SPRING 3RD	-7891	11169	11169	SANDSTONE	NATURAL GAS, OIL	N

Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M

Rating Depth: 19135

Equipment: Annular Pipe Rams Blind Rams Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for hydrostatic test chart. Anchors are not required by manufacturer. A variance is requested to use a multi-bowl wellhead.

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Testing Procedure: BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

Choke Diagram Attachment:

Paduca_7_6_H3FC_Fed_Com_1H_Flex_Line_Specs_API_16C_20220817092228.pdf

Paduca_7_6_H3FC_Fed_Com_1H_5M_BOPE_Choke_Diagram_20220817092228.pdf

Paduca_7_6_H3FC_Fed_Com_1H_Flex_Line_Specs_20220817092228.pdf

BOP Diagram Attachment:

Paduca_7_6_H3FC_Fed_Com_1H_5M_BOPE_Schematic_20220817092249.pdf

Paduca_7_6_H3FC_Fed_Com_1H_5M_Mutli_Bowl_WH_20220817092249.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1075	0	1075	3278	2203	1075	H-40	48	ST&C	1.57	3.52	DRY	6.24	DRY	10.48
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	3453	0	3453		-175	3453	J-55	36	LT&C	1.13	1.96	DRY	2.9	DRY	3.61
3	INTERMEDIATE	12.25	9.625	NEW	API	N	3453	4250	3453	4250	-174	-972	797	J-55	40	LT&C	1.16	1.79	DRY	16.31	DRY	19.76
4	PRODUCTION	8.75	7.0	NEW	API	N	0	10360	0	10317		-7039	10360	P-110	26	LT&C	1.2	1.91	DRY	2.37	DRY	3.08
5	LINER	6.125	4.5	NEW	API	N	10160	19135	10119	10943	-6841	-7665	8975	P-110	13.5	LT&C	1.56	1.81	DRY	2.79	DRY	3.48

Casing Attachments

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Casing Attachments

Casing ID: 1 **String** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092414.pdf

Casing ID: 2 **String** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092541.pdf

Casing ID: 3 **String** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092949.pdf

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Casing Attachments

Casing ID: 4 **String** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092508.pdf

Casing ID: 5 **String** LINER

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Paduca_7_6_H3FC_Fed_Com_1H_Csg_Assumptions_20220817092908.pdf

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	883	580	2.12	12.5	1230	100	Class C	Salt, Gel, Extender, LCM
SURFACE	Tail		883	1075	200	1.34	14.8	268	100	Class C	Retarder
INTERMEDIATE	Lead		0	3567	660	2.12	12.5	1399	25	Class C	Salt, Gel, Extender, LCM
INTERMEDIATE	Tail		3567	4250	200	1.34	14.8	268	25	Class C	Retarder
PRODUCTION	Lead	5460	4050	4835	70	2.12	12.5	148	25	Class C	Salt, Gel, Extender, LCM, Defoamer

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
PRODUCTION	Tail		4835	5460	100	1.18	15.6	118	25	Class H	Retarder
PRODUCTION	Lead	5460	5460	7895	220	2.12	12.5	466	25	Class C	Salt, Gel, Extender, LCM Defoamer
PRODUCTION	Tail		7895	10360	400	1.18	15.6	472	25	Class H	Retarder, Fluid Loss, Defoamer
LINER	Lead		10160	19135	570	1.85	13.5	1055	25	Class H	Salt, Gel, Fluid Loss, Retarder, Dispersant, Defoamer, Anti-settling Agent

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Lost circulation material, sweeps, mud scavengers

Describe the mud monitoring system utilized: Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1075	SPUD MUD	8.4	8.8							
1075	4250	SALT SATURATED	10	10							
4250	10360	WATER-BASED MUD	8.6	9.7							

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
1036 0	1913 5	OIL-BASED MUD	8.6	12							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will run GR/CNL logs from KOP to surface.

List of open and cased hole logs run in the well:

DIRECTIONAL SURVEY, MEASUREMENT WHILE DRILLING, MUD LOG/GEOLOGIC LITHOLOGY LOG, GAMMA RAY LOG, COMPENSATED NEUTRON LOG,

Coring operation description for the well:

None

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 6828

Anticipated Surface Pressure: 4417

Anticipated Bottom Hole Temperature(F): 195

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations

Paduca_7_6_H3FC_Fed_Com_1H_H2S_Plan_20220817093536.pdf

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Paduca_7_6_H3FC_Fed_Com_1H_MOC_DIR_PLOT_20220817093559.pdf

Paduca_7_6_H3FC_Fed_Com_1H_MOC_DIR_PLAN_20220817093559.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

Paduca_7_6_H3FC_Fed_Com_1H_Additional_Information___Permitting_20220817093606.pdf

Other Variance attachment:

CONFIDENTIAL



GATES ENGINEERING & SERVICES NORTH AMERICA
7603 Prairie Oak Dr.
Houston, TX 77086

PHONE: (281) 602 - 4119
FAX:
EMAIL: Troy.Schmidt@gates.com
WEB: www.gates.com

10K CHOKE & KILL ASSEMBLY PRESSURE TEST CERTIFICATE

Customer:	A-7 AUSTIN INC DBA AUSTIN HOSE	Test Date:	8/20/2018
Customer Ref.:	4101901	Hose Serial No.:	H-082018-10
Invoice No.:	511956	Created By:	Moosa Naqvi
Product Description:	10KF3.035.0CK41/1610KFLGFXDxFLT L/E		
End Fitting 1:	4 1/16 in. Fixed Flange	End Fitting 2:	4 1/16 in. Float Flange
Gates Part No.:	68503010-9721632	Assembly Code:	L40695052218H-082018-10
Working Pressure:	10,000 psi.	Test Pressure:	15,000 psi.

Gates Engineering & Services North America certifies that the following hose assembly has successfully passed all pressure testing requirements set forth in Gates specifications: GTS-04-052 (for 5K assemblies) or GTS-04-053 (10K assemblies), which include reference to Specification API 16C (2nd Edition); sections 7.5.4, 7.5.9, and 10.8.7. A test graph will accompany this test certificate to illustrate conformity to test requirements.


Quality:	QUALITY
Date :	8/20/2018
Signature :	<i>Moosa Naqvi</i>

Production:	PRODUCTION
Date :	8/20/2018
Signature :	<i>[Signature]</i>

Form PTC - 01 Rev.02



5M BOPE & Closed Loop Equipment Schematic



Note: All valves & lines on choke manifold are 4" unless otherwise noted. Exact manifold configuration may vary.

Drawing not to scale



GATES E & S NORTH AMERICA, INC.
134 44TH STREET
CORPUS CHRISTI, TEXAS 78405

PHONE: 361-887-9807
FAX: 361-887-0812
EMAIL: Tim.Cantu@gates.com
WEB: www.gates.com

10K CEMENTING ASSEMBLY PRESSURE TEST CERTIFICATE

Customer :	AUSTIN DISTRIBUTING	Test Date:	4/30/2015
Customer Ref. :	4060578	Hose Serial No.:	D-043015-7
Invoice No. :	500506	Created By:	JUSTIN CROPPER

Product Description: 10K3.548.0CK4.1/1610KFLGE/E LE


End Fitting 1 :	4 1/16 10K FLG	End Fitting 2 :	4 1/16 10K FLG
Gates Part No. :	4773-6290	Assembly Code :	L36554102914D-043015-7
Working Pressure :	10,000 PSI	Test Pressure :	15,000 PSI

Gates E & S North America, Inc. certifies that the following hose assembly has been tested to the Gates Oilfield Roughneck Agreement/Specification requirements and passed the 15 minute hydrostatic test per API Spec 7K/Q1, Fifth Edition, June 2010, Test pressure 9.6.7 and per Table 9 to 15,000 psi in accordance with this product number. Hose burst pressure 9.6.7.2 exceeds the minimum of 2.5 times the working pressure per Table 9.


Quality Manager :	QUALITY	Production:	PRODUCTION
Date :	4/30/2015	Date :	4/30/2015
Signature :	<i>Justin Cropper</i>	Signature :	<i>[Signature]</i>

Form PTC - 01 Rev.02







Hydril "GK"
13 5/8" 5M





Cameron Type U
13 5/8" 5M




4 1/2" x 5 7/8" VBR



BLIND RAMS




7" RAMS





13-5/8" MN-DS Wellhead System



C7585
Rev. 02

NOTE: All dimensions on this drawing are estimated measurements and should be evaluated by engineering.

Cuffing Height 57" conductor cut-off

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Paduca 7/6 H3FC Fed Com #1H
Sec 7, T26S, R32E
SHL: 2500' FNL & 1620' FWL, Sec 7
BHL: 100' FNL & 2220' FWL, Sec 6

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1075'	13.375"	48	H40	STC	1.57	3.52	6.24	10.48
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.90	3.61
12.25"	3453'	4250'	9.625"	40	J55	LTC	1.16	1.79	16.31	19.76
8.75"	0'	10360'	7"	26	P110	LTC	1.2	1.91	2.37	3.08
6.125"	10160'	19135'	4.5"	13.5	P110	LTC	1.56	1.81	2.79	3.48
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	Y
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company

Lea County, New Mexico NAD 83

Paduca 7/6 H3FC Fed Com #1H

Sec 7, T26S, R32E

SHL: 2500' FNL & 1620' FWL (Sec 7)

BHL: 100' FNL & 2220' FWL (Sec 6)

Plan: Design #1

Standard Planning Report

16 August, 2022

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Project	Lea County, New Mexico NAD 83		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Paduca 7/6 H3FC Fed Com #1H				
Site Position:		Northing:	385,384.70 usft	Latitude:	32.0580080
From:	Map	Easting:	732,014.10 usft	Longitude:	-103.7178412
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "		

Well	Sec 7, T26S, R32E					
Well Position	+N-S	0.0 usft	Northing:	385,384.70 usft	Latitude:	32.0580080
	+E-W	0.0 usft	Easting:	732,014.10 usft	Longitude:	-103.7178412
Position Uncertainty		0.0 usft	Wellhead Elevation:	3,278.0 usft	Ground Level:	3,250.0 usft
Grid Convergence:	0.33 °					

Wellbore	BHL: 100' FNL & 2220' FWL (Sec 6)				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	12/31/2014	7.21	59.92	48,147.93093291

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N-S (usft)	+E-W (usft)	Direction (°)
	0.0	0.0	0.0	4.11

Plan Survey Tool Program	Date	8/9/2022		
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks
1	0.0	19,135.4	Design #1 (BHL: 100' FNL & 2220	

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,275.0	0.00	0.00	1,275.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,275.0	5.51	136.59	1,275.0	0.0	0.0	0.00	0.00	0.00	0.00	
10,427.4	5.51	136.59	10,385.0	-638.6	604.1	0.00	0.00	0.00	0.00	
10,427.4	0.00	0.00	10,385.0	-638.6	604.1	614,546,543	614,546,543	0.00	180.00	KOP: 2195' FSL & 22'
11,328.5	90.11	359.68	10,958.0	-64.5	600.9	10.00	10.00	0.00	-0.32	
19,135.4	90.11	359.68	10,943.0	7,742.3	557.0	0.00	0.00	0.00	0.00	BHL: 100' FNL & 2220'

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	
SHL: 2500' FNL & 1620' FWL (Sec 7)										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00	
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00	
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00	
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00	
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,275.0	5.51	136.59	1,275.0	0.0	0.0	0.0	7.35	7.35	0.00	
1,300.0	5.51	136.59	1,299.9	-1.7	1.7	-1.6	0.00	0.00	0.00	
1,400.0	5.51	136.59	1,399.4	-8.7	8.3	-8.1	0.00	0.00	0.00	
1,500.0	5.51	136.59	1,499.0	-15.7	14.9	-14.6	0.00	0.00	0.00	
1,600.0	5.51	136.59	1,598.5	-22.7	21.5	-21.1	0.00	0.00	0.00	
1,700.0	5.51	136.59	1,698.0	-29.7	28.1	-27.6	0.00	0.00	0.00	
1,800.0	5.51	136.59	1,797.6	-36.6	34.7	-34.0	0.00	0.00	0.00	
1,900.0	5.51	136.59	1,897.1	-43.6	41.3	-40.5	0.00	0.00	0.00	
2,000.0	5.51	136.59	1,996.6	-50.6	47.9	-47.0	0.00	0.00	0.00	
2,100.0	5.51	136.59	2,096.2	-57.6	54.5	-53.5	0.00	0.00	0.00	
2,200.0	5.51	136.59	2,195.7	-64.5	61.1	-60.0	0.00	0.00	0.00	
2,300.0	5.51	136.59	2,295.3	-71.5	67.7	-66.5	0.00	0.00	0.00	
2,400.0	5.51	136.59	2,394.8	-78.5	74.3	-73.0	0.00	0.00	0.00	
2,500.0	5.51	136.59	2,494.3	-85.5	80.9	-79.4	0.00	0.00	0.00	
2,600.0	5.51	136.59	2,593.9	-92.4	87.5	-85.9	0.00	0.00	0.00	
2,700.0	5.51	136.59	2,693.4	-99.4	94.1	-92.4	0.00	0.00	0.00	
2,800.0	5.51	136.59	2,792.9	-106.4	100.7	-98.9	0.00	0.00	0.00	
2,900.0	5.51	136.59	2,892.5	-113.4	107.3	-105.4	0.00	0.00	0.00	
3,000.0	5.51	136.59	2,992.0	-120.4	113.9	-111.9	0.00	0.00	0.00	
3,100.0	5.51	136.59	3,091.6	-127.3	120.5	-118.4	0.00	0.00	0.00	
3,200.0	5.51	136.59	3,191.1	-134.3	127.1	-124.8	0.00	0.00	0.00	
3,300.0	5.51	136.59	3,290.6	-141.3	133.7	-131.3	0.00	0.00	0.00	
3,400.0	5.51	136.59	3,390.2	-148.3	140.3	-137.8	0.00	0.00	0.00	
3,500.0	5.51	136.59	3,489.7	-155.2	146.9	-144.3	0.00	0.00	0.00	
3,600.0	5.51	136.59	3,589.3	-162.2	153.5	-150.8	0.00	0.00	0.00	
3,700.0	5.51	136.59	3,688.8	-169.2	160.1	-157.3	0.00	0.00	0.00	
3,800.0	5.51	136.59	3,788.3	-176.2	166.7	-163.8	0.00	0.00	0.00	
3,900.0	5.51	136.59	3,887.9	-183.1	173.3	-170.2	0.00	0.00	0.00	
4,000.0	5.51	136.59	3,987.4	-190.1	179.9	-176.7	0.00	0.00	0.00	
4,100.0	5.51	136.59	4,086.9	-197.1	186.5	-183.2	0.00	0.00	0.00	
4,200.0	5.51	136.59	4,186.5	-204.1	193.1	-189.7	0.00	0.00	0.00	
4,300.0	5.51	136.59	4,286.0	-211.1	199.7	-196.2	0.00	0.00	0.00	
4,400.0	5.51	136.59	4,385.6	-218.0	206.3	-202.7	0.00	0.00	0.00	
4,500.0	5.51	136.59	4,485.1	-225.0	212.9	-209.2	0.00	0.00	0.00	
4,600.0	5.51	136.59	4,584.6	-232.0	219.5	-215.6	0.00	0.00	0.00	
4,700.0	5.51	136.59	4,684.2	-239.0	226.1	-222.1	0.00	0.00	0.00	
4,800.0	5.51	136.59	4,783.7	-245.9	232.7	-228.6	0.00	0.00	0.00	
4,900.0	5.51	136.59	4,883.2	-252.9	239.3	-235.1	0.00	0.00	0.00	
5,000.0	5.51	136.59	4,982.8	-259.9	245.9	-241.6	0.00	0.00	0.00	
5,100.0	5.51	136.59	5,082.3	-266.9	252.5	-248.1	0.00	0.00	0.00	

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
5,200.0	5.51	136.59	5,181.9	-273.8	259.1	-254.5	0.00	0.00	0.00	
5,300.0	5.51	136.59	5,281.4	-280.8	265.7	-261.0	0.00	0.00	0.00	
5,400.0	5.51	136.59	5,380.9	-287.8	272.3	-267.5	0.00	0.00	0.00	
5,500.0	5.51	136.59	5,480.5	-294.8	278.9	-274.0	0.00	0.00	0.00	
5,600.0	5.51	136.59	5,580.0	-301.8	285.5	-280.5	0.00	0.00	0.00	
5,700.0	5.51	136.59	5,679.5	-308.7	292.1	-287.0	0.00	0.00	0.00	
5,800.0	5.51	136.59	5,779.1	-315.7	298.7	-293.5	0.00	0.00	0.00	
5,900.0	5.51	136.59	5,878.6	-322.7	305.3	-299.9	0.00	0.00	0.00	
6,000.0	5.51	136.59	5,978.2	-329.7	311.9	-306.4	0.00	0.00	0.00	
6,100.0	5.51	136.59	6,077.7	-336.6	318.5	-312.9	0.00	0.00	0.00	
6,200.0	5.51	136.59	6,177.2	-343.6	325.1	-319.4	0.00	0.00	0.00	
6,300.0	5.51	136.59	6,276.8	-350.6	331.7	-325.9	0.00	0.00	0.00	
6,400.0	5.51	136.59	6,376.3	-357.6	338.3	-332.4	0.00	0.00	0.00	
6,500.0	5.51	136.59	6,475.8	-364.5	344.9	-338.9	0.00	0.00	0.00	
6,600.0	5.51	136.59	6,575.4	-371.5	351.5	-345.3	0.00	0.00	0.00	
6,700.0	5.51	136.59	6,674.9	-378.5	358.1	-351.8	0.00	0.00	0.00	
6,800.0	5.51	136.59	6,774.5	-385.5	364.7	-358.3	0.00	0.00	0.00	
6,900.0	5.51	136.59	6,874.0	-392.5	371.3	-364.8	0.00	0.00	0.00	
7,000.0	5.51	136.59	6,973.5	-399.4	377.9	-371.3	0.00	0.00	0.00	
7,100.0	5.51	136.59	7,073.1	-406.4	384.5	-377.8	0.00	0.00	0.00	
7,200.0	5.51	136.59	7,172.6	-413.4	391.1	-384.3	0.00	0.00	0.00	
7,300.0	5.51	136.59	7,272.1	-420.4	397.7	-390.7	0.00	0.00	0.00	
7,400.0	5.51	136.59	7,371.7	-427.3	404.3	-397.2	0.00	0.00	0.00	
7,500.0	5.51	136.59	7,471.2	-434.3	410.9	-403.7	0.00	0.00	0.00	
7,600.0	5.51	136.59	7,570.8	-441.3	417.5	-410.2	0.00	0.00	0.00	
7,700.0	5.51	136.59	7,670.3	-448.3	424.1	-416.7	0.00	0.00	0.00	
7,800.0	5.51	136.59	7,769.8	-455.2	430.7	-423.2	0.00	0.00	0.00	
7,900.0	5.51	136.59	7,869.4	-462.2	437.3	-429.7	0.00	0.00	0.00	
8,000.0	5.51	136.59	7,968.9	-469.2	443.9	-436.1	0.00	0.00	0.00	
8,100.0	5.51	136.59	8,068.4	-476.2	450.5	-442.6	0.00	0.00	0.00	
8,200.0	5.51	136.59	8,168.0	-483.2	457.1	-449.1	0.00	0.00	0.00	
8,300.0	5.51	136.59	8,267.5	-490.1	463.7	-455.6	0.00	0.00	0.00	
8,400.0	5.51	136.59	8,367.1	-497.1	470.3	-462.1	0.00	0.00	0.00	
8,500.0	5.51	136.59	8,466.6	-504.1	476.9	-468.6	0.00	0.00	0.00	
8,600.0	5.51	136.59	8,566.1	-511.1	483.5	-475.1	0.00	0.00	0.00	
8,700.0	5.51	136.59	8,665.7	-518.0	490.1	-481.5	0.00	0.00	0.00	
8,800.0	5.51	136.59	8,765.2	-525.0	496.7	-488.0	0.00	0.00	0.00	
8,900.0	5.51	136.59	8,864.7	-532.0	503.3	-494.5	0.00	0.00	0.00	
9,000.0	5.51	136.59	8,964.3	-539.0	509.9	-501.0	0.00	0.00	0.00	
9,100.0	5.51	136.59	9,063.8	-545.9	516.5	-507.5	0.00	0.00	0.00	
9,200.0	5.51	136.59	9,163.4	-552.9	523.1	-514.0	0.00	0.00	0.00	
9,300.0	5.51	136.59	9,262.9	-559.9	529.7	-520.4	0.00	0.00	0.00	
9,400.0	5.51	136.59	9,362.4	-566.9	536.3	-526.9	0.00	0.00	0.00	
9,500.0	5.51	136.59	9,462.0	-573.9	542.9	-533.4	0.00	0.00	0.00	
9,600.0	5.51	136.59	9,561.5	-580.8	549.5	-539.9	0.00	0.00	0.00	
9,700.0	5.51	136.59	9,661.1	-587.8	556.1	-546.4	0.00	0.00	0.00	
9,800.0	5.51	136.59	9,760.6	-594.8	562.7	-552.9	0.00	0.00	0.00	
9,900.0	5.51	136.59	9,860.1	-601.8	569.3	-559.4	0.00	0.00	0.00	
10,000.0	5.51	136.59	9,959.7	-608.7	575.9	-565.8	0.00	0.00	0.00	
10,100.0	5.51	136.59	10,059.2	-615.7	582.5	-572.3	0.00	0.00	0.00	
10,200.0	5.51	136.59	10,158.7	-622.7	589.1	-578.8	0.00	0.00	0.00	
10,300.0	5.51	136.59	10,258.3	-629.7	595.7	-585.3	0.00	0.00	0.00	
10,400.0	5.51	136.59	10,357.8	-636.6	602.3	-591.8	0.00	0.00	0.00	
10,427.4	0.00	0.00	10,385.0	-638.6	604.1	-593.6	20.15	-20.15	0.00	

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
KOP: 2195' FSL & 2220' FWL (Sec 7)										
10,500.0	7.26	359.68	10,457.5	-634.0	604.1	-589.0	10.00	10.00	0.00	
10,600.0	17.26	359.68	10,555.1	-612.7	604.0	-567.8	10.00	10.00	0.00	
10,700.0	27.26	359.68	10,647.5	-574.9	603.8	-530.1	10.00	10.00	0.00	
10,800.0	37.26	359.68	10,732.0	-521.6	603.5	-476.9	10.00	10.00	0.00	
10,900.0	47.26	359.68	10,805.9	-454.4	603.1	-410.0	10.00	10.00	0.00	
11,000.0	57.26	359.68	10,867.0	-375.4	602.6	-331.2	10.00	10.00	0.00	
11,100.0	67.26	359.68	10,913.5	-287.0	602.1	-243.1	10.00	10.00	0.00	
11,200.0	77.26	359.68	10,943.9	-191.9	601.6	-148.2	10.00	10.00	0.00	
11,300.0	87.26	359.68	10,957.3	-92.9	601.0	-49.6	10.00	10.00	0.00	
11,327.4	90.00	359.68	10,958.0	-65.6	600.9	-22.3	10.00	10.00	0.00	
FTP/LP: 2569' FNL & 2220' FWL (Sec 7) - FTP/LP: 2569' FNL & 2220' FWL (Sec 7)										
11,328.5	90.11	359.68	10,958.0	-64.5	600.9	-21.2	10.00	10.00	0.00	
11,400.0	90.11	359.68	10,957.9	7.0	600.5	50.1	0.00	0.00	0.00	
11,500.0	90.11	359.68	10,957.7	107.0	599.9	149.8	0.00	0.00	0.00	
11,600.0	90.11	359.68	10,957.5	207.0	599.4	249.5	0.00	0.00	0.00	
11,700.0	90.11	359.68	10,957.3	307.0	598.8	349.2	0.00	0.00	0.00	
11,800.0	90.11	359.68	10,957.1	407.0	598.2	448.9	0.00	0.00	0.00	
11,900.0	90.11	359.68	10,956.9	507.0	597.7	548.6	0.00	0.00	0.00	
12,000.0	90.11	359.68	10,956.7	607.0	597.1	648.3	0.00	0.00	0.00	
12,100.0	90.11	359.68	10,956.5	707.0	596.5	748.0	0.00	0.00	0.00	
12,200.0	90.11	359.68	10,956.3	807.0	596.0	847.7	0.00	0.00	0.00	
12,300.0	90.11	359.68	10,956.1	907.0	595.4	947.4	0.00	0.00	0.00	
12,400.0	90.11	359.68	10,955.9	1,007.0	594.9	1,047.1	0.00	0.00	0.00	
12,500.0	90.11	359.68	10,955.7	1,107.0	594.3	1,146.8	0.00	0.00	0.00	
12,600.0	90.11	359.68	10,955.6	1,207.0	593.7	1,246.5	0.00	0.00	0.00	
12,700.0	90.11	359.68	10,955.4	1,307.0	593.2	1,346.2	0.00	0.00	0.00	
12,800.0	90.11	359.68	10,955.2	1,407.0	592.6	1,445.9	0.00	0.00	0.00	
12,900.0	90.11	359.68	10,955.0	1,507.0	592.0	1,545.6	0.00	0.00	0.00	
13,000.0	90.11	359.68	10,954.8	1,607.0	591.5	1,645.3	0.00	0.00	0.00	
13,100.0	90.11	359.68	10,954.6	1,707.0	590.9	1,745.0	0.00	0.00	0.00	
13,200.0	90.11	359.68	10,954.4	1,807.0	590.4	1,844.7	0.00	0.00	0.00	
13,300.0	90.11	359.68	10,954.2	1,907.0	589.8	1,944.4	0.00	0.00	0.00	
13,400.0	90.11	359.68	10,954.0	2,007.0	589.2	2,044.1	0.00	0.00	0.00	
13,500.0	90.11	359.68	10,953.8	2,107.0	588.7	2,143.8	0.00	0.00	0.00	
13,600.0	90.11	359.68	10,953.6	2,207.0	588.1	2,243.5	0.00	0.00	0.00	
13,700.0	90.11	359.68	10,953.4	2,307.0	587.6	2,343.2	0.00	0.00	0.00	
13,800.0	90.11	359.68	10,953.3	2,407.0	587.0	2,442.9	0.00	0.00	0.00	
13,900.0	90.11	359.68	10,953.1	2,507.0	586.4	2,542.6	0.00	0.00	0.00	
14,000.0	90.11	359.68	10,952.9	2,607.0	585.9	2,642.3	0.00	0.00	0.00	
14,100.0	90.11	359.68	10,952.7	2,707.0	585.3	2,742.0	0.00	0.00	0.00	
14,200.0	90.11	359.68	10,952.5	2,807.0	584.7	2,841.7	0.00	0.00	0.00	
14,300.0	90.11	359.68	10,952.3	2,907.0	584.2	2,941.4	0.00	0.00	0.00	
14,400.0	90.11	359.68	10,952.1	3,007.0	583.6	3,041.1	0.00	0.00	0.00	
14,500.0	90.11	359.68	10,951.9	3,107.0	583.1	3,140.8	0.00	0.00	0.00	
14,600.0	90.11	359.68	10,951.7	3,207.0	582.5	3,240.5	0.00	0.00	0.00	
14,700.0	90.11	359.68	10,951.5	3,307.0	581.9	3,340.2	0.00	0.00	0.00	
14,800.0	90.11	359.68	10,951.3	3,407.0	581.4	3,439.9	0.00	0.00	0.00	
14,900.0	90.11	359.68	10,951.1	3,507.0	580.8	3,539.6	0.00	0.00	0.00	
15,000.0	90.11	359.68	10,950.9	3,607.0	580.2	3,639.3	0.00	0.00	0.00	
15,100.0	90.11	359.68	10,950.8	3,707.0	579.7	3,739.0	0.00	0.00	0.00	
15,200.0	90.11	359.68	10,950.6	3,807.0	579.1	3,838.7	0.00	0.00	0.00	
15,300.0	90.11	359.68	10,950.4	3,907.0	578.6	3,938.4	0.00	0.00	0.00	
15,400.0	90.11	359.68	10,950.2	4,007.0	578.0	4,038.1	0.00	0.00	0.00	

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,500.0	90.11	359.68	10,950.0	4,107.0	577.4	4,137.8	0.00	0.00	0.00
15,600.0	90.11	359.68	10,949.8	4,207.0	576.9	4,237.5	0.00	0.00	0.00
15,700.0	90.11	359.68	10,949.6	4,307.0	576.3	4,337.2	0.00	0.00	0.00
15,800.0	90.11	359.68	10,949.4	4,407.0	575.7	4,436.9	0.00	0.00	0.00
15,900.0	90.11	359.68	10,949.2	4,507.0	575.2	4,536.6	0.00	0.00	0.00
16,000.0	90.11	359.68	10,949.0	4,607.0	574.6	4,636.3	0.00	0.00	0.00
16,100.0	90.11	359.68	10,948.8	4,707.0	574.1	4,736.0	0.00	0.00	0.00
16,200.0	90.11	359.68	10,948.6	4,807.0	573.5	4,835.7	0.00	0.00	0.00
16,300.0	90.11	359.68	10,948.4	4,907.0	572.9	4,935.4	0.00	0.00	0.00
16,400.0	90.11	359.68	10,948.3	5,007.0	572.4	5,035.1	0.00	0.00	0.00
16,500.0	90.11	359.68	10,948.1	5,106.9	571.8	5,134.8	0.00	0.00	0.00
16,600.0	90.11	359.68	10,947.9	5,206.9	571.3	5,234.5	0.00	0.00	0.00
16,700.0	90.11	359.68	10,947.7	5,306.9	570.7	5,334.2	0.00	0.00	0.00
16,800.0	90.11	359.68	10,947.5	5,406.9	570.1	5,433.9	0.00	0.00	0.00
16,900.0	90.11	359.68	10,947.3	5,506.9	569.6	5,533.6	0.00	0.00	0.00
17,000.0	90.11	359.68	10,947.1	5,606.9	569.0	5,633.3	0.00	0.00	0.00
17,100.0	90.11	359.68	10,946.9	5,706.9	568.4	5,733.0	0.00	0.00	0.00
17,200.0	90.11	359.68	10,946.7	5,806.9	567.9	5,832.7	0.00	0.00	0.00
17,300.0	90.11	359.68	10,946.5	5,906.9	567.3	5,932.4	0.00	0.00	0.00
17,400.0	90.11	359.68	10,946.3	6,006.9	566.8	6,032.1	0.00	0.00	0.00
17,500.0	90.11	359.68	10,946.1	6,106.9	566.2	6,131.8	0.00	0.00	0.00
17,600.0	90.11	359.68	10,945.9	6,206.9	565.6	6,231.5	0.00	0.00	0.00
17,700.0	90.11	359.68	10,945.8	6,306.9	565.1	6,331.2	0.00	0.00	0.00
17,800.0	90.11	359.68	10,945.6	6,406.9	564.5	6,430.9	0.00	0.00	0.00
17,900.0	90.11	359.68	10,945.4	6,506.9	563.9	6,530.6	0.00	0.00	0.00
17,901.7	90.11	359.68	10,945.4	6,508.6	563.9	6,532.3	0.00	0.00	0.00
PPP2: 1234' FNL & 2220' FWL (Sec 6) - PPP2: 1334' FNL & 2220' FWL (Sec 6)									
18,000.0	90.11	359.68	10,945.2	6,606.9	563.4	6,630.3	0.00	0.00	0.00
18,100.0	90.11	359.68	10,945.0	6,706.9	562.8	6,730.0	0.00	0.00	0.00
18,200.0	90.11	359.68	10,944.8	6,806.9	562.3	6,829.7	0.00	0.00	0.00
18,300.0	90.11	359.68	10,944.6	6,906.9	561.7	6,929.4	0.00	0.00	0.00
18,400.0	90.11	359.68	10,944.4	7,006.9	561.1	7,029.1	0.00	0.00	0.00
18,500.0	90.11	359.68	10,944.2	7,106.9	560.6	7,128.8	0.00	0.00	0.00
18,600.0	90.11	359.68	10,944.0	7,206.9	560.0	7,228.5	0.00	0.00	0.00
18,700.0	90.11	359.68	10,943.8	7,306.9	559.4	7,328.2	0.00	0.00	0.00
18,800.0	90.11	359.68	10,943.6	7,406.9	558.9	7,427.9	0.00	0.00	0.00
18,900.0	90.11	359.68	10,943.5	7,506.9	558.3	7,527.6	0.00	0.00	0.00
19,000.0	90.11	359.68	10,943.3	7,606.9	557.8	7,627.3	0.00	0.00	0.00
19,100.0	90.11	359.68	10,943.1	7,706.9	557.2	7,727.0	0.00	0.00	0.00
19,135.4	90.11	359.68	10,943.0	7,742.3	557.0	7,762.3	0.00	0.00	0.00
BHL: 100' FNL & 2220' FWL (Sec 6)									

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Paduca 7/6 H3FC Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 3278.0usft (Original Well Elev)
Project:	Lea County, New Mexico NAD 83	MD Reference:	WELL @ 3278.0usft (Original Well Elev)
Site:	Paduca 7/6 H3FC Fed Com #1H	North Reference:	Grid
Well:	Sec 7, T26S, R32E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 100' FNL & 2220' FWL (Sec 6)		
Design:	Design #1		

Design Targets										
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
SHL: 2500' FNL & 1620' - plan hits target center - Point	0.00	0.00	0.0	0.0	0.0	385,384.70	732,014.10	32.0580080	-103.7178412	
KOP: 2195' FSL & 2220' - plan hits target center - Point	0.00	0.00	10,385.0	-638.6	604.1	384,746.14	732,618.21	32.0562433	-103.7159031	
BHL: 100' FNL & 2220' F - plan hits target center - Point	0.00	0.01	10,943.0	7,742.3	557.0	393,127.00	732,571.10	32.0792814	-103.7159004	
PPP2: 1334' FNL & 2220' - plan hits target center - Point	0.00	0.00	10,945.4	6,508.6	563.9	391,893.30	732,578.03	32.0758901	-103.7159008	
FTP/LP: 2569' FNL & 2220' - plan hits target center - Point	0.00	0.00	10,958.0	-65.6	600.9	385,319.10	732,614.99	32.0578183	-103.7159029	

Operator Name: Mewbourne Oil Company	Property Name: Paduca 7/6 H3FC Fed Com	Well Number 1H
---	---	-------------------

Kick Off Point (KOP)

UL K	Section 7	Township 26S	Range 32E	Lot	Feet 2195	From N/S S	Feet 2220	From E/W W	County Lea
Latitude 32.0562433					Longitude -103.7159031				NAD 83

First Take Point (FTP)

UL F	Section 7	Township 26S	Range 32E	Lot	Feet 2569	From N/S N	Feet 2220	From E/W W	County Lea
Latitude 32.0578183					Longitude -103.7159029				NAD 83

Last Take Point (LTP)

UL C	Section 6	Township 26S	Range 32E	Lot	Feet 100	From N/S N	Feet 2220	From E/W W	County Lea
Latitude 32.0792815					Longitude -103.7159002				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?

Is this well an infill well?

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #	
Operator Name:	Property Name:
	Well Number

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	MEWBOURNE OIL COMPANY
LEASE NO.:	NMNM128929
LOCATION:	Section 07, T.26 S., R.32 E., NMPM
COUNTY:	LEA County, New Mexico

WELL NAME & NO.:	PADUCA 7-6 H3FC FED COM 1H
SURFACE HOLE FOOTAGE:	2500'/N & 1620'/W
BOTTOM HOLE FOOTAGE:	100'/N & 2220'/W
ATS/API ID:	ATS-23-259
APD ID:	10400087453
Sundry ID:	

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Wellhead Variance	<input type="radio"/> Diverter		
Other	<input type="checkbox"/> 4 String	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Pilot Hole	<input type="checkbox"/> Open Annulus
Cementing	<input type="checkbox"/> Contingency Cement Squeeze	<input type="checkbox"/> EchoMeter	<input type="checkbox"/> Primary Cement Squeeze
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit
Special Requirements	<input type="checkbox"/> Batch Sundry		
Special Requirements Variance	<input type="checkbox"/> Break Testing	<input type="checkbox"/> Offline Cementing	<input type="checkbox"/> Casing Clearance

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Casing Design:

1. The **13-3/8** inch surface casing shall be set at approximately **1,075** feet (a minimum of **25 feet (Lea County)** into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface. The surface hole shall be **17 1/2** inch in diameter.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **24 hours in the Potash Area** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash. Cement excess is less than 25%, more cement is required if washout occurs. Adjust cement volume and excess based on a fluid caliper or similar method that reflects the as-drilled size of the wellbore.**
 - ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
3. The minimum required fill of cement behind the **7** inch production casing is:

Option 1 (Single Stage):

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification. **Excess cement calculates to -1%, additional cement might be required.**

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
Excess cement calculates to 24%, additional cement might be required.
4. The minimum required fill of cement behind the **4-1/2** inch production liner is:
- Cement should tie-back **100 feet** into the previous casing. Operator shall provide method of verification.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the **13-3/8** inch surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR part 3172 must be followed.

D. SPECIAL REQUIREMENT (S)**Communitization Agreement**

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- The operator will submit an as-drilled survey well plat of the well completion, but are not limited to, those specified in 43 CFR part 3171 and 3172.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure

- rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
- b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per 43 CFR part 3172 (Drilling Operations on Federal and Indian Oil and Gas Leases) as soon as 2nd Rig is rigged up on well.
 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the doghouse or stairway area.
 3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for

details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.

4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hard band drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in 43 CFR part 3172 (Drilling Operations on Federal and Indian Oil and Gas Leases) and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:

- a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR part 3172 must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
 - c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to 43 CFR part 3172 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
 - d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE.

If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.

- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per 43 CFR part 3172.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

OTA 7/5/2023

Hydrogen Sulfide Drilling Operations Plan
Mewbourne Oil Company

1. General Requirements

Rule 118 does not apply to this well because MOC has researched this area and no high concentrations of H₂S were found. MOC will have on location and working all H₂S safety equipment before the Delaware formation for purposes of safety and insurance requirements.

2. Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will have received training from a qualified instructor in the following areas prior to entering the drilling pad area of the well:

1. The hazards and characteristics of hydrogen sulfide gas.
2. The proper use of personal protective equipment and life support systems.
3. The proper use of hydrogen sulfide detectors, alarms, warning systems, briefing areas, evacuation procedures.
4. The proper techniques for first aid and rescue operations.

Additionally, supervisory personnel will be trained in the following areas:

- 1 The effects of hydrogen sulfide on metal components. If high tensile tubular systems are utilized, supervisory personnel will be trained in their special maintenance requirements.
- 2 Corrective action and shut in procedures, blowout prevention, and well control procedures while drilling a well.
- 3 The contents of the Hydrogen Sulfide Drilling Operations Plan.

There will be an initial training session prior to encountering a known hydrogen sulfide source. The initial training session shall include a review of the site specific Hydrogen Sulfide Drilling Operations Plan.

3. Hydrogen Sulfide Safety Equipment and Systems

All hydrogen sulfide safety equipment and systems will be installed, tested, and operational prior to drilling below the 9 5/8" intermediate casing.

1. Well Control Equipment
 - A. Choke manifold with minimum of one adjustable choke/remote choke.
 - B. Blowout preventers equipped with blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
 - C. Auxiliary equipment including annular type blowout preventer.
2. Protective Equipment for Essential Personnel

Thirty minute self contained work unit located in the dog house and at briefing areas.

Additionally: If H₂S is encountered in concentrations less than 10 ppm, fans will be placed in work areas to prevent the accumulation of hazardous amounts of poisonous gas. If higher concentrations of H₂S are detected the well will be shut in and a rotating head, mud/gas separator, remote choke and flare line with igniter will be installed.

3. Hydrogen Sulfide Protection and Monitoring Equipment
 Two portable hydrogen sulfide monitors positioned on location for optimum coverage and detection. The units shall have audible sirens to notify personnel when hydrogen sulfide levels exceed 20 PPM.

4. Visual Warning Systems
 A. Wind direction indicators as indicated on the wellsite diagram.
 B. Caution signs shall be posted on roads providing access to location. Signs shall be painted a high visibility color with lettering of sufficient size to be readable at reasonable distances from potentially contaminated areas.

4. Mud Program

The mud program has been designed to minimize the amount of hydrogen sulfide entrained in the mud system. Proper mud weight, safe drilling practices, and the use of hydrogen sulfide scavengers will minimize hazards while drilling the well.

5. Metallurgy

All tubular systems, wellheads, blowout preventers, drilling spools, kill lines, choke manifolds, and valves shall be suitable for service in a hydrogen sulfide environment when chemically treated.

6. Communications

State & County Officials phone numbers are posted on rig floor and supervisors trailer. Communications in company vehicles and toolpushers are either two way radios or cellular phones.

7. Well Testing

Drill stem testing is not an anticipated requirement for evaluation of this well. If a drill stem test is required, it will be conducted with a minimum number of personnel in the immediate vicinity. The test will be conducted during daylight hours only.

8. Emergency Phone Numbers

Eddy County Sheriff's Office	911 or 575-887-7551
Ambulance Service	911 or 575-885-2111
Carlsbad Fire Dept	911 or 575-885-2111
Loco Hills Volunteer Fire Dept.	911 or 575-677-3266
Closest Medical Facility - Columbia Medical Center of Carlsbad	575-492-5000

Mewbourne Oil Company	Hobbs District Office	575-393-5905
	Fax	575-397-6252
	2nd Fax	575-393-7259

District Manager	Robin Terrell	575-390-4816
Drilling Superintendent	Frosty Lathan	575-390-4103
	Bradley Bishop	575-390-6838
Drilling Foreman	Wesley Noseff	575-441-0729

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Waste type: SEWAGE

Waste content description: Human waste & grey water

Amount of waste: 1500 gallons

Waste disposal frequency : Weekly

Safe containment description: 2,000 gallon plastic container

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: City of Carlsbad Water Treatment facility

Waste type: GARBAGE

Waste content description: Garbage & Trash

Amount of waste: 1500 pounds

Waste disposal frequency : One Time Only

Safe containment description: Enclosed trash trailer

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** PRIVATE

Disposal type description:

Disposal location description: Waste Management facility in Carlsbad.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit? NO

Reserve pit length (ft.) **Reserve pit width (ft.)**

Reserve pit depth (ft.) **Reserve pit volume (cu. yd.)**

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? N

Operator Name: MEWBOURNE OIL COMPANY

Well Name: PADUCA 7/6 H3FC FED COM

Well Number: 1H

Description of cuttings location

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary

Are you requesting any Ancillary Facilities?: N

Ancillary Facilities

Comments:

Section 9 - Well Site

Well Site Layout Diagram:

Paduca_7_6_H3FC_Fed_Com_1H_WellSiteLayout_20220922110853.pdf

Comments: NONE

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: Paduca ED well pad

Multiple Well Pad Number: 6

Recontouring

Drainage/Erosion control construction: NONE

Drainage/Erosion control reclamation: NONE

Well pad proposed disturbance (acres): 4.59

Well pad interim reclamation (acres): 0.68

Well pad long term disturbance (acres): 3.91

Road proposed disturbance (acres): 0

Road interim reclamation (acres): 0

Road long term disturbance (acres): 0

Powerline proposed disturbance (acres): 0

Powerline interim reclamation (acres): 0

Powerline long term disturbance (acres): 0

Pipeline proposed disturbance (acres): 0

Pipeline interim reclamation (acres): 0

Pipeline long term disturbance (acres): 0

Other proposed disturbance (acres): 0

Other interim reclamation (acres): 0

Other long term disturbance (acres): 0

Total proposed disturbance: 4.59

Total interim reclamation: 0.68

Total long term disturbance: 3.91

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 345904

CONDITIONS

Operator: MEWBOURNE OIL CO P.O. Box 5270 Hobbs, NM 88241	OGRID:	14744
	Action Number:	345904
	Action Type:	[C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104	6/11/2024
pkautz	WILL REQUIRE NAME CHANGE	6/11/2024
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	6/11/2024
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system	6/11/2024
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing	6/11/2024
pkautz	If cement does not circulate on any string, a CBL is required for that string of casing	6/11/2024