

Well Name: MULE 11-14 FED COM	Well Location: T25S / R31E / SEC 11 / NENE / 32.150873 / -103.743227	County or Parish/State: EDDY / NM
Well Number: 535H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM000503	Unit or CA Name:	Unit or CA Number:
US Well Number:	Operator: DEVON ENERGY PRODUCTION COMPANY LP	

Notice of Intent

Sundry ID: 2791639

Type of Submission: Notice of Intent

Type of Action: APD Change

Date Sundry Submitted: 05/21/2024

Time Sundry Submitted: 09:11

Date proposed operation will begin: 05/20/2024

Procedure Description: Devon Energy Production Co., L.P. (Devon) respectfully requests to change the well name, BHL and depth on the subject well. Devon is also requesting a variance for offline cementing and break test. Please see attached revised C102, Drill plan, directional plan, variance requests. API: 30-015-55057 Permitted Well name: MULE 11-14 FED COM 525H Proposed Well name: MULE 11-23 FED COM 304H Permitted BHL: SWSE, 20 FSL, 1350 FEL, 14-25S-31E Proposed BHL: NWNE, 1288 FNL, 2600 FEL, 14-25S-31E Permitted TVD/MD: 9140/19363 Proposed TVD/MD: 10475/22226

NOI Attachments

Procedure Description

WA018222915_MULE_11_23_FED_COM_304H_WL_R1_SIGNED_20240521091116.pdf

Offline_Cementing___Variance_Request_20240521083146.pdf

break_test_variance_BOP_1_15_24_20240521083140.pdf

10.750_45.5_J55_SEAH_20240521083140.pdf

MULE_11_23_FED_COM_304H_Directional_Plan_04_30_24_20240521083140.pdf

MULE_11_23_FED_COM_304H_20240521083140.pdf

8.625_32lb_P110_MOFXL_20240521083140.pdf

5.5_20lb_P110EC_DWC_C_IS_PLUS_20240521083140.pdf

Well Name: MULE 11-14 FED COM

Well Location: T25S / R31E / SEC 11 / NENE / 32.150873 / -103.743227

County or Parish/State: EDDY / NM

Well Number: 535H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM000503

Unit or CA Name:

Unit or CA Number:

US Well Number:

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Conditions of Approval

Specialist Review

Mule_11_14_Fed_Com_304H_Sundry_ID_2791639_20240529090125.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: CHELSEY GREEN

Signed on: MAY 21, 2024 08:31 AM

Name: DEVON ENERGY PRODUCTION COMPANY LP

Title: Regulatory Compliance Professional

Street Address: 333 West Sheridan Avenue

City: Oklahoma City

State: OK

Phone: (405) 228-8595

Email address: Chelsey.Green@dvn.com

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5759885402

BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved

Disposition Date: 05/29/2024

Signature: Long Vo

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. **NMNM0503**

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator **DEVON ENERGY PRODUCTION COMPANY LP**

3a. Address **333 WEST SHERIDAN AVE, OKLAHOMA CITY,** 3b. Phone No. (include area code)
(405) 235-3611

4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)
SEC 11/T25S/R31E/NMP

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No. **MULE 11-14 FED COM/535H**

9. API Well No.

10. Field and Pool or Exploratory Area
PADUCA/BONE SPRING

11. Country or Parish, State
EDDY/NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Devon Energy Production Co., L.P. (Devon) respectfully requests to change the well name, BHL and depth on the subject well. Devon is also requesting a variance for offline cementing and break test. Please see attached revised C102, Drill plan, directional plan, variance requests.

API: 30-015-55057

Permitted Well name: MULE 11-14 FED COM 525H
 Proposed Well name: MULE 11-23 FED COM 304H
 Permitted BHL: SWSE, 20 FSL, 1350 FEL, 14-25S-31E
 Proposed BHL: NWNE, 1288 FNL, 2600 FEL, 14-25S-31E
 Permitted TVD/MD: 9140/19363
 Proposed TVD/MD: 10475/22226

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)
CHELSEY GREEN / Ph: (405) 228-8595

Signature (Electronic Submission)

Title **Regulatory Compliance Professional**

Date **05/21/2024**

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by
LONG VO / Ph: (575) 988-5402 / Approved

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title **Petroleum Engineer**

Office **CARLSBAD**

Date **05/29/2024**

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: NENE / 450 FNL / 966 FEL / TWSP: 25S / RANGE: 31E / SECTION: 11 / LAT: 32.150873 / LONG: -103.743227 (TVD: 0 feet, MD: 0 feet)

PPP: NWNE / 100 FNL / 1350 FEL / TWSP: 25S / RANGE: 31E / SECTION: 11 / LAT: 32.151844 / LONG: -103.744466 (TVD: 8424 feet, MD: 8491 feet)

BHL: SWSE / 20 FSL / 1350 FEL / TWSP: 25S / RANGE: 31E / SECTION: 14 / LAT: 32.123097 / LONG: -103.74449 (TVD: 9140 feet, MD: 19363 feet)

CONFIDENTIAL

DISTRICT I
1625 N. FRENCH DR., HOBBS, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II
811 S. FIRST ST., ARTESIA, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III
1000 RIO BRAZOS RD., AZTEC, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DR.
Santa Fe, New Mexico 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-015-55057	Pool Code 96641	Pool Name PADUCA; BONE SPRING
Property Code 335888	Property Name MULE 11-23 FED COM	Well Number 304H
OGRID No. 6137	Operator Name DEVON ENERGY PRODUCTION COMPANY, L.P.	Elevation 3451.4'

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	11	25-S	31-E		450	NORTH	966	EAST	EDDY

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	23	25-S	31-E		1288	NORTH	2600	EAST	EDDY

Dedicated Acres 720	Joint or Infill	Consolidation Code	Order No. NSL Pending
------------------------	-----------------	--------------------	--------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

MULE 11-23 FED COM 304H
EL: 3451.4'
GEOIDETIC COORDINATES
NAD 83 NMSP EAST
SURFACE LOCATION
N:419123.43
E:723964.79
LAT:32.150873
LON:103.743227


KICK OFF POINT
CALLS: 65 FNL 2601 FEL
N: 419513
E: 722329
LAT: 32.1519
LON: 103.7486

FIRST TAKE POINT(PPP 1)
100' FNL 2600' FEL SEC. 11
N:419477.94
E:722329.35
LAT:32.151872
LON:103.748505

LAST TAKE POINT
1208' FNL 2600' FEL SEC. 23
N:407782.90
E:722383.98
LAT:32.119724
LON:103.748533

BOTTOM OF HOLE
N:407702.90
E:722384.30
LAT:32.119504
LON:103.748534

(PPP 2)
0' FSL 2603' FEL SEC. 11
N:414293.67
E:722353.57
LAT:32.137621
LON:103.748517



A=N:419597.37 E:719631.86
B=N:419578.10 E:722271.62
C=N:419570.77 E:724929.00
D=N:416925.27 E:724939.62
E=N:414282.44 E:724957.17
F=N:411638.94 E:724969.31
G=N:409003.32 E:724979.03
H=N:406364.11 E:724989.78
I=N:403723.61 E:724993.33
J=N:403715.48 E:722335.80
K=N:403707.33 E:719678.01
L=N:406360.85 E:719664.63
M=N:409003.26 E:719655.72
N=N:411652.57 E:719658.66
O=N:414305.28 E:719664.76
P=N:416942.70 E:719647.42
Q=N:408990.91 E:722330.98

OPERATOR CERTIFICATION

I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Chelsey Green 5/20/24
Signature Date


Chelsey Green
Printed Name
chelsey.green@dvn.com
E-mail Address

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

04/2024
Date of Survey

Signature & Seal of Professional Surveyor



04/10/24

Certificate No. 23261 Albert R. DeHoyos
DRAWN BY: CM

Intent As Drilled

API # 30-015-55057		
Operator Name: DEVON ENERGY PRODUCTION COMPANY, LP.	Property Name: MULE 11-23 FED COM	Well Number 304H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	11	25S	31E		65	FNL	2601	FEL	EDDY
Latitude 32.1519					Longitude 103.7486				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	11	25-S	31-E		100	NORTH	2600	EAST	EDDY
Latitude 32.151872					Longitude 103.748505				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	23	25-S	31-E		1208	NORTH	2600	EAST	EDDY
Latitude 32.119724					Longitude 103.748533				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? N

Is this well an infill well? Y

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-015-55054		
Operator Name: DEVON ENERGY PRODUCTION COMPANY, LP	Property Name: MULE 11-14 FED COM	Well Number 525H

KZ 06/29/2018

Offline Cementing

Variance Request

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements.

Section 2 - Blowout Preventer Testing Procedure

Variance Request

Devon Energy requests to only test BOP connection breaks after drilling out of surface casing and while skidding between wells which conforms to API Standard 53 and industry standards. This test will include the Top Pipe Rams, HCR, Kill Line Check Valve, QDC (quick disconnect to wellhead) and Shell of the 10M BOPE to 5M for 10 minutes. If a break to the flex hose that runs to the choke manifold is required due to repositioning from a skid, the HCR will remain open during the shell test to include that additional break. The variance only pertains to intermediate hole-sections and no deeper than the Bone Springs Formation where 5M BOP tests are required. The initial BOP test will follow 43 CFR 3172, and subsequent tests following a skid will only test connections that are broken. The annular preventer will be tested to 100% working pressure. This variance will meet or exceed 43 CFR 3172 per the following: Devon Energy will perform a full BOP test per 43 CFR 3172 before drilling out of the intermediate casing string(s) and starting the production hole, before starting any hole section that requires a 10M test, before the expiration of the allotted 14-days for 5M intermediate batch drilling or when the drilling rig is fully mobilized to a new well pad, whichever is sooner. We will utilize a 200' TVD tolerance between intermediate shoes as the cutoff for a full BOP test. The BLM will be contacted 4hrs prior to a BOPE test. The BLM will be notified if and when a well control event is encountered. Break test will be a 14 day interval and not a 30 day full BOPE test interval. If in the event break testing is not utilized, then a full BOPE test would be conducted.



1. Well Control Response:
 1. Primary barrier remains fluid
 2. In the event of an influx due to being underbalanced and after a realized gain or flow, the order of closing BOPE is as follows:
 - a) Annular first
 - b) If annular were to not hold, Upper pipe rams second (which were tested on the skid BOP test)
 - c) If the Upper Pipe Rams were to not hold, Lower Pipe Rams would be third

Cactus
Wellhead

2-9-17
E Bell

80.7 °F

15:49



50

Date 02-09-17

Tested By E.BELL

Transducer bay2

Transducer Serial 181504

Calibration Date 9/6/15

Job#	Part#	Serial#	Description	Test Pressure
1	TRJ0006341-0007 116966	TRJ6341-7-1	ADPT,DRLG,CW,MBU-3T,13-5/8 10M	15000
2				
3				
4				
5			TRANSDUCER CALIBRATION DUE 03/13/2017	
6				
7				
8				

Start Stop Zero Config Save Print EXIT



10-3/4" 45.50# 0.400" J-55

Dimensions (Nominal)

Outside Diameter	10.750	in.
Wall	0.400	in.
Inside Diameter	9.950	in.
Drift	9.875	in.
Weight, T&C	45.500	lbs/ft
Weight, PE	44.260	lbs/ft

Internal Yield Pressure at Minimum Yield

Collapse	2090	psi
----------	------	-----

Internal Yields Pressure

PE	3580	psi
STC	3580	psi
BTC	3580	psi

Yield Strength, Pipe Body	715	1000 lbs
---------------------------	-----	----------

Joint Strength, STC

STC	493	1000 lbs
BTC	796	1000 lbs


Note: SeAH Steel has produced this specification sheet for general information only. SeAH does not assume liability or responsibility for any loss or injury resulting from the use of information or data contained herein. All applications for the material described are at the customer's own risk and responsibility.



Well: MULE 11-23 FED COM 304H
 County: Eddy
 Wellbore: Permit Plan
 Design: Permit Plan #1

Geodetic System: US State Plane 1983
 Datum: North American Datum 1927
 Ellipsoid: Clarke 1866
 Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
2000.00	0.00	283.40	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2500.00	13.00	283.40	2495.72	13.09	-54.94	-5.43	1.00	Hold Tangent
9399.41	13.00	283.40	9218.30	372.77	-1564.72	-154.75	0.00	Drop to Vertical
10049.41	0.00	283.40	9862.74	389.78	-1636.15	-161.81	2.00	Hold Vertical
10088.72	0.00	179.73	9902.04	389.78	-1636.15	-161.81	0.00	KOP
10988.72	90.00	179.73	10475.00	-183.17	-1633.45	405.36	10.00	Landing Point
22226.20	90.00	179.73	10475.00	-11420.53	-1580.49	11529.37	0.00	BHL



Key Depths	MD (ft)	TVD (ft)
Rustler	0.00	0.00
Salt	1090.00	1090.00
Base of Salt	4213.19	4165.00
Delaware	4441.03	4387.00
Cherry Canyon	5444.75	5365.00
Brushy Canyon	6790.24	6676.00
1st Bone Spring Lime	8464.14	8307.00
Leonard	8584.22	8424.00
Bone Spring 1st	9515.59	9332.00
Bone Spring 2nd	9720.95	9535.00
3rd Bone Spring Lime / Point of Penetration	10767.97	10433.00
exit	22146.20	10475.01

	MD (ft)	TVD (ft)	Lat (°)	Long (°)	Section Footages
SHL	0.00	0.00	32.1508	-103.7433	450' FNL, 966' FEL of Sec 11 in T25S, R31E
KOP	10088.72	9902.04	32.1519	-103.7486	65' FNL, 2601' FEL of Sec 11 in T25S, R31E
Point of Penetration	10767.97	10433.00	32.1519	-103.7485	100' FNL, 2600' FEL of Sec 11 in T25S, R31E
Exit	22146.20	10475.01	32.1197	-103.7485	1208' FNL, 2600' FEL of Sec 23 in T25S, R31E
BHL	22226.20	10475.00	32.1194	-103.7486	1288' FNL, 2600' FEL of Sec 23 in T25S, R31E

	Y	X	MD
KOP	419513	722329	10088.72



Well: MULE 11-23 FED COM 304H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
100.00	0.00	283.40	100.00	0.00	0.00	0.00	0.00	
200.00	0.00	283.40	200.00	0.00	0.00	0.00	0.00	
300.00	0.00	283.40	300.00	0.00	0.00	0.00	0.00	
400.00	0.00	283.40	400.00	0.00	0.00	0.00	0.00	
500.00	0.00	283.40	500.00	0.00	0.00	0.00	0.00	
600.00	0.00	283.40	600.00	0.00	0.00	0.00	0.00	
665.00	0.00	283.40	665.00	0.00	0.00	0.00	0.00	Rustler
700.00	0.00	283.40	700.00	0.00	0.00	0.00	0.00	
800.00	0.00	283.40	800.00	0.00	0.00	0.00	0.00	
900.00	0.00	283.40	900.00	0.00	0.00	0.00	0.00	
1000.00	0.00	283.40	1000.00	0.00	0.00	0.00	0.00	
1090.00	0.00	283.40	1090.00	0.00	0.00	0.00	0.00	Salt
1100.00	0.00	283.40	1100.00	0.00	0.00	0.00	0.00	
1200.00	0.00	283.40	1200.00	0.00	0.00	0.00	0.00	
1300.00	0.00	283.40	1300.00	0.00	0.00	0.00	0.00	
1400.00	0.00	283.40	1400.00	0.00	0.00	0.00	0.00	
1500.00	0.00	283.40	1500.00	0.00	0.00	0.00	0.00	
1600.00	0.00	283.40	1600.00	0.00	0.00	0.00	0.00	
1700.00	0.00	283.40	1700.00	0.00	0.00	0.00	0.00	
1800.00	0.00	283.40	1800.00	0.00	0.00	0.00	0.00	
1900.00	0.00	283.40	1900.00	0.00	0.00	0.00	0.00	
2000.00	0.00	283.40	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2100.00	2.60	283.40	2099.97	0.53	-2.21	-0.22	2.60	
2200.00	5.20	283.40	2199.73	2.10	-8.82	-0.87	2.60	
2300.00	7.80	283.40	2299.07	4.72	-19.83	-1.96	2.60	
2400.00	10.40	283.40	2397.81	8.39	-35.22	-3.48	2.60	
2500.00	13.00	283.40	2495.72	13.09	-54.94	-5.43	1.00	Hold Tangent
2600.00	13.00	283.40	2593.16	18.30	-76.83	-7.60	0.00	
2700.00	13.00	283.40	2690.60	23.52	-98.71	-9.76	0.00	
2800.00	13.00	283.40	2788.03	28.73	-120.59	-11.93	0.00	
2900.00	13.00	283.40	2885.47	33.94	-142.47	-14.09	0.00	
3000.00	13.00	283.40	2982.91	39.15	-164.36	-16.25	0.00	
3100.00	13.00	283.40	3080.34	44.37	-186.24	-18.42	0.00	
3200.00	13.00	283.40	3177.78	49.58	-208.12	-20.58	0.00	
3300.00	13.00	283.40	3275.22	54.79	-230.00	-22.75	0.00	
3400.00	13.00	283.40	3372.65	60.01	-251.89	-24.91	0.00	
3500.00	13.00	283.40	3470.09	65.22	-273.77	-27.07	0.00	
3600.00	13.00	283.40	3567.53	70.43	-295.65	-29.24	0.00	
3700.00	13.00	283.40	3664.97	75.65	-317.54	-31.40	0.00	
3800.00	13.00	283.40	3762.40	80.86	-339.42	-33.57	0.00	
3900.00	13.00	283.40	3859.84	86.07	-361.30	-35.73	0.00	
4000.00	13.00	283.40	3957.28	91.29	-383.18	-37.90	0.00	
4100.00	13.00	283.40	4054.71	96.50	-405.07	-40.06	0.00	
4200.00	13.00	283.40	4152.15	101.71	-426.95	-42.22	0.00	
4213.19	13.00	283.40	4165.00	102.40	-429.83	-42.51	0.00	Base of Salt
4300.00	13.00	283.40	4249.59	106.92	-448.83	-44.39	0.00	
4400.00	13.00	283.40	4347.02	112.14	-470.71	-46.55	0.00	
4441.03	13.00	283.40	4387.00	114.28	-479.69	-47.44	0.00	Delaware
4500.00	13.00	283.40	4444.46	117.35	-492.60	-48.72	0.00	
4600.00	13.00	283.40	4541.90	122.56	-514.48	-50.88	0.00	
4700.00	13.00	283.40	4639.34	127.78	-536.36	-53.04	0.00	
4800.00	13.00	283.40	4736.77	132.99	-558.24	-55.21	0.00	
4900.00	13.00	283.40	4834.21	138.20	-580.13	-57.37	0.00	
5000.00	13.00	283.40	4931.65	143.42	-602.01	-59.54	0.00	
5100.00	13.00	283.40	5029.08	148.63	-623.89	-61.70	0.00	
5200.00	13.00	283.40	5126.52	153.84	-645.78	-63.86	0.00	
5300.00	13.00	283.40	5223.96	159.06	-667.66	-66.03	0.00	
5400.00	13.00	283.40	5321.39	164.27	-689.54	-68.19	0.00	
5444.75	13.00	283.40	5365.00	166.60	-699.33	-69.16	0.00	Cherry Canyon
5500.00	13.00	283.40	5418.83	169.48	-711.42	-70.36	0.00	
5600.00	13.00	283.40	5516.27	174.70	-733.31	-72.52	0.00	
5700.00	13.00	283.40	5613.71	179.91	-755.19	-74.68	0.00	
5800.00	13.00	283.40	5711.14	185.12	-777.07	-76.85	0.00	
5900.00	13.00	283.40	5808.58	190.33	-798.95	-79.01	0.00	
6000.00	13.00	283.40	5906.02	195.55	-820.84	-81.18	0.00	
6100.00	13.00	283.40	6003.45	200.76	-842.72	-83.34	0.00	
6200.00	13.00	283.40	6100.89	205.97	-864.60	-85.51	0.00	
6300.00	13.00	283.40	6198.33	211.19	-886.49	-87.67	0.00	
6400.00	13.00	283.40	6295.76	216.40	-908.37	-89.83	0.00	



Well: MULE 11-23 FED COM 304H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
6500.00	13.00	283.40	6393.20	221.61	-930.25	-92.00	0.00	
6600.00	13.00	283.40	6490.64	226.83	-952.13	-94.16	0.00	
6700.00	13.00	283.40	6588.08	232.04	-974.02	-96.33	0.00	
6790.24	13.00	283.40	6676.00	236.74	-993.76	-98.28	0.00	Brushy Canyon
6800.00	13.00	283.40	6685.51	237.25	-995.90	-98.49	0.00	
6900.00	13.00	283.40	6782.95	242.47	-1017.78	-100.65	0.00	
7000.00	13.00	283.40	6880.39	247.68	-1039.66	-102.82	0.00	
7100.00	13.00	283.40	6977.82	252.89	-1061.55	-104.98	0.00	
7200.00	13.00	283.40	7075.26	258.10	-1083.43	-107.15	0.00	
7300.00	13.00	283.40	7172.70	263.32	-1105.31	-109.31	0.00	
7400.00	13.00	283.40	7270.13	268.53	-1127.19	-111.47	0.00	
7500.00	13.00	283.40	7367.57	273.74	-1149.08	-113.64	0.00	
7600.00	13.00	283.40	7465.01	278.96	-1170.96	-115.80	0.00	
7700.00	13.00	283.40	7562.45	284.17	-1192.84	-117.97	0.00	
7800.00	13.00	283.40	7659.88	289.38	-1214.73	-120.13	0.00	
7900.00	13.00	283.40	7757.32	294.60	-1236.61	-122.29	0.00	
8000.00	13.00	283.40	7854.76	299.81	-1258.49	-124.46	0.00	
8100.00	13.00	283.40	7952.19	305.02	-1280.37	-126.62	0.00	
8200.00	13.00	283.40	8049.63	310.24	-1302.26	-128.79	0.00	
8300.00	13.00	283.40	8147.07	315.45	-1324.14	-130.95	0.00	
8400.00	13.00	283.40	8244.50	320.66	-1346.02	-133.12	0.00	
8464.14	13.00	283.40	8307.00	324.01	-1360.06	-134.50	0.00	1st Bone Spring Lime
8500.00	13.00	283.40	8341.94	325.88	-1367.90	-135.28	0.00	
8584.22	13.00	283.40	8424.00	330.27	-1386.33	-137.10	0.00	Leonard
8600.00	13.00	283.40	8439.38	331.09	-1389.79	-137.44	0.00	
8700.00	13.00	283.40	8536.82	336.30	-1411.67	-139.61	0.00	
8800.00	13.00	283.40	8634.25	341.51	-1433.55	-141.77	0.00	
8900.00	13.00	283.40	8731.69	346.73	-1455.44	-143.94	0.00	
9000.00	13.00	283.40	8829.13	351.94	-1477.32	-146.10	0.00	
9100.00	13.00	283.40	8926.56	357.15	-1499.20	-148.26	0.00	
9200.00	13.00	283.40	9024.00	362.37	-1521.08	-150.43	0.00	
9300.00	13.00	283.40	9121.44	367.58	-1542.97	-152.59	0.00	
9399.41	13.00	283.40	9218.30	372.77	-1564.72	-154.75	0.00	Drop to Vertical
9400.00	12.99	283.40	9218.87	372.80	-1564.85	-154.76	2.01	
9500.00	10.99	283.40	9316.69	377.61	-1585.05	-156.76	2.00	
9515.59	10.68	283.40	9332.00	378.29	-1587.90	-157.04	2.00	Bone Spring 1st
9600.00	8.99	283.40	9415.17	381.63	-1601.92	-158.43	2.00	
9700.00	6.99	283.40	9514.19	384.85	-1615.44	-159.77	2.00	
9720.95	6.57	283.40	9535.00	385.43	-1617.85	-160.00	2.00	Bone Spring 2nd
9800.00	4.99	283.40	9613.64	387.27	-1625.59	-160.77	2.00	
9900.00	2.99	283.40	9713.39	388.88	-1632.36	-161.44	2.00	
10000.00	0.99	283.40	9813.33	389.69	-1635.73	-161.77	2.00	
10049.41	0.00	283.40	9862.74	389.78	-1636.15	-161.81	2.00	Hold Vertical
10088.72	0.00	179.73	9902.04	389.78	-1636.15	-161.81	0.00	KOP
10100.00	1.13	179.73	9913.33	389.67	-1636.14	-161.70	10.00	
10200.00	11.13	179.73	10012.63	379.01	-1636.09	-151.15	10.00	
10300.00	21.13	179.73	10108.57	351.27	-1635.96	-123.69	10.00	
10400.00	31.13	179.73	10198.24	307.29	-1635.76	-80.15	10.00	
10500.00	41.13	179.73	10278.91	248.40	-1635.48	-21.86	10.00	
10600.00	51.13	179.73	10348.12	176.40	-1635.14	49.41	10.00	
10700.00	61.13	179.73	10403.78	93.48	-1634.75	131.50	10.00	
10767.97	67.93	179.73	10433.00	32.16	-1634.46	192.21	10.00	3rd Bone Spring Lime / Point of Penetration
10800.00	71.13	179.73	10444.20	2.15	-1634.32	221.91	10.00	
10900.00	81.13	179.73	10468.15	-94.81	-1633.86	317.89	10.00	
10988.72	90.00	179.73	10475.00	-183.17	-1633.45	405.36	10.00	Landing Point
11000.00	90.00	179.73	10475.00	-194.45	-1633.39	416.53	0.00	
11100.00	90.00	179.73	10475.00	-294.45	-1632.92	515.52	0.00	
11200.00	90.00	179.73	10475.00	-394.45	-1632.45	614.51	0.00	
11300.00	90.00	179.73	10475.00	-494.45	-1631.98	713.50	0.00	
11400.00	90.00	179.73	10475.00	-594.45	-1631.51	812.49	0.00	
11500.00	90.00	179.73	10475.00	-694.45	-1631.03	911.48	0.00	
11600.00	90.00	179.73	10475.00	-794.44	-1630.56	1010.47	0.00	
11700.00	90.00	179.73	10475.00	-894.44	-1630.09	1109.46	0.00	
11800.00	90.00	179.73	10475.00	-994.44	-1629.62	1208.45	0.00	
11900.00	90.00	179.73	10475.00	-1094.44	-1629.15	1307.44	0.00	
12000.00	90.00	179.73	10475.00	-1194.44	-1628.68	1406.43	0.00	
12100.00	90.00	179.73	10475.00	-1294.44	-1628.21	1505.42	0.00	
12200.00	90.00	179.73	10475.00	-1394.44	-1627.73	1604.41	0.00	
12300.00	90.00	179.73	10475.00	-1494.44	-1627.26	1703.40	0.00	
12400.00	90.00	179.73	10475.00	-1594.44	-1626.79	1802.39	0.00	



Well: MULE 11-23 FED COM 304H
 County: Eddy
 Wellbore: Permit Plan
 Design: Permit Plan #1

Geodetic System: US State Plane 1983
 Datum: North American Datum 1927
 Ellipsoid: Clarke 1866
 Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
12500.00	90.00	179.73	10475.00	-1694.43	-1626.32	1901.38	0.00	
12600.00	90.00	179.73	10475.00	-1794.43	-1625.85	2000.37	0.00	
12700.00	90.00	179.73	10475.00	-1894.43	-1625.38	2099.36	0.00	
12800.00	90.00	179.73	10475.00	-1994.43	-1624.90	2198.35	0.00	
12900.00	90.00	179.73	10475.00	-2094.43	-1624.43	2297.34	0.00	
13000.00	90.00	179.73	10475.00	-2194.43	-1623.96	2396.33	0.00	
13100.00	90.00	179.73	10475.00	-2294.43	-1623.49	2495.32	0.00	
13200.00	90.00	179.73	10475.00	-2394.43	-1623.02	2594.31	0.00	
13300.00	90.00	179.73	10475.00	-2494.43	-1622.55	2693.30	0.00	
13400.00	90.00	179.73	10475.00	-2594.42	-1622.08	2792.29	0.00	
13500.00	90.00	179.73	10475.00	-2694.42	-1621.60	2891.28	0.00	
13600.00	90.00	179.73	10475.00	-2794.42	-1621.13	2990.27	0.00	
13700.00	90.00	179.73	10475.00	-2894.42	-1620.66	3089.26	0.00	
13800.00	90.00	179.73	10475.00	-2994.42	-1620.19	3188.25	0.00	
13900.00	90.00	179.73	10475.00	-3094.42	-1619.72	3287.24	0.00	
14000.00	90.00	179.73	10475.00	-3194.42	-1619.25	3386.24	0.00	
14100.00	90.00	179.73	10475.00	-3294.42	-1618.78	3485.23	0.00	
14200.00	90.00	179.73	10475.00	-3394.42	-1618.30	3584.22	0.00	
14300.00	90.00	179.73	10475.00	-3494.41	-1617.83	3683.21	0.00	
14400.00	90.00	179.73	10475.00	-3594.41	-1617.36	3782.20	0.00	
14500.00	90.00	179.73	10475.00	-3694.41	-1616.89	3881.19	0.00	
14600.00	90.00	179.73	10475.00	-3794.41	-1616.42	3980.18	0.00	
14700.00	90.00	179.73	10475.00	-3894.41	-1615.95	4079.17	0.00	
14800.00	90.00	179.73	10475.01	-3994.41	-1615.47	4178.16	0.00	
14900.00	90.00	179.73	10475.01	-4094.41	-1615.00	4277.15	0.00	
15000.00	90.00	179.73	10475.01	-4194.41	-1614.53	4376.14	0.00	
15100.00	90.00	179.73	10475.01	-4294.41	-1614.06	4475.13	0.00	
15200.00	90.00	179.73	10475.01	-4394.40	-1613.59	4574.12	0.00	
15300.00	90.00	179.73	10475.01	-4494.40	-1613.12	4673.11	0.00	
15400.00	90.00	179.73	10475.01	-4594.40	-1612.65	4772.10	0.00	
15500.00	90.00	179.73	10475.01	-4694.40	-1612.17	4871.09	0.00	
15600.00	90.00	179.73	10475.01	-4794.40	-1611.70	4970.08	0.00	
15700.00	90.00	179.73	10475.01	-4894.40	-1611.23	5069.07	0.00	
15800.00	90.00	179.73	10475.01	-4994.40	-1610.76	5168.06	0.00	
15900.00	90.00	179.73	10475.01	-5094.40	-1610.29	5267.05	0.00	
16000.00	90.00	179.73	10475.01	-5194.40	-1609.82	5366.04	0.00	
16100.00	90.00	179.73	10475.01	-5294.39	-1609.35	5465.03	0.00	
16200.00	90.00	179.73	10475.01	-5394.39	-1608.87	5564.02	0.00	
16300.00	90.00	179.73	10475.01	-5494.39	-1608.40	5663.01	0.00	
16400.00	90.00	179.73	10475.01	-5594.39	-1607.93	5762.00	0.00	
16500.00	90.00	179.73	10475.01	-5694.39	-1607.46	5860.99	0.00	
16600.00	90.00	179.73	10475.01	-5794.39	-1606.99	5959.98	0.00	
16700.00	90.00	179.73	10475.01	-5894.39	-1606.52	6058.97	0.00	
16800.00	90.00	179.73	10475.01	-5994.39	-1606.04	6157.96	0.00	
16900.00	90.00	179.73	10475.01	-6094.39	-1605.57	6256.95	0.00	
17000.00	90.00	179.73	10475.01	-6194.38	-1605.10	6355.94	0.00	
17100.00	90.00	179.73	10475.01	-6294.38	-1604.63	6454.93	0.00	
17200.00	90.00	179.73	10475.01	-6394.38	-1604.16	6553.92	0.00	
17300.00	90.00	179.73	10475.01	-6494.38	-1603.69	6652.91	0.00	
17400.00	90.00	179.73	10475.01	-6594.38	-1603.22	6751.90	0.00	
17500.00	90.00	179.73	10475.01	-6694.38	-1602.74	6850.89	0.00	
17600.00	90.00	179.73	10475.01	-6794.38	-1602.27	6949.88	0.00	
17700.00	90.00	179.73	10475.01	-6894.38	-1601.80	7048.87	0.00	
17800.00	90.00	179.73	10475.01	-6994.38	-1601.33	7147.86	0.00	
17900.00	90.00	179.73	10475.01	-7094.37	-1600.86	7246.85	0.00	
18000.00	90.00	179.73	10475.01	-7194.37	-1600.39	7345.84	0.00	
18100.00	90.00	179.73	10475.01	-7294.37	-1599.92	7444.83	0.00	
18200.00	90.00	179.73	10475.01	-7394.37	-1599.44	7543.82	0.00	
18300.00	90.00	179.73	10475.01	-7494.37	-1598.97	7642.81	0.00	
18400.00	90.00	179.73	10475.01	-7594.37	-1598.50	7741.80	0.00	
18500.00	90.00	179.73	10475.01	-7694.37	-1598.03	7840.79	0.00	
18600.00	90.00	179.73	10475.01	-7794.37	-1597.56	7939.78	0.00	
18700.00	90.00	179.73	10475.01	-7894.37	-1597.09	8038.77	0.00	
18800.00	90.00	179.73	10475.01	-7994.36	-1596.61	8137.76	0.00	
18900.00	90.00	179.73	10475.01	-8094.36	-1596.14	8236.75	0.00	
19000.00	90.00	179.73	10475.01	-8194.36	-1595.67	8335.74	0.00	
19100.00	90.00	179.73	10475.01	-8294.36	-1595.20	8434.73	0.00	
19200.00	90.00	179.73	10475.01	-8394.36	-1594.73	8533.73	0.00	
19300.00	90.00	179.73	10475.01	-8494.36	-1594.26	8632.72	0.00	
19400.00	90.00	179.73	10475.01	-8594.36	-1593.79	8731.71	0.00	



Well: MULE 11-23 FED COM 304H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
19500.00	90.00	179.73	10475.01	-8694.36	-1593.31	8830.70	0.00	
19600.00	90.00	179.73	10475.01	-8794.36	-1592.84	8929.69	0.00	
19700.00	90.00	179.73	10475.01	-8894.35	-1592.37	9028.68	0.00	
19800.00	90.00	179.73	10475.01	-8994.35	-1591.90	9127.67	0.00	
19900.00	90.00	179.73	10475.01	-9094.35	-1591.43	9226.66	0.00	
20000.00	90.00	179.73	10475.01	-9194.35	-1590.96	9325.65	0.00	
20100.00	90.00	179.73	10475.01	-9294.35	-1590.49	9424.64	0.00	
20200.00	90.00	179.73	10475.01	-9394.35	-1590.01	9523.63	0.00	
20300.00	90.00	179.73	10475.01	-9494.35	-1589.54	9622.62	0.00	
20400.00	90.00	179.73	10475.01	-9594.35	-1589.07	9721.61	0.00	
20500.00	90.00	179.73	10475.01	-9694.35	-1588.60	9820.60	0.00	
20600.00	90.00	179.73	10475.01	-9794.34	-1588.13	9919.59	0.00	
20700.00	90.00	179.73	10475.01	-9894.34	-1587.66	10018.58	0.00	
20800.00	90.00	179.73	10475.01	-9994.34	-1587.18	10117.57	0.00	
20900.00	90.00	179.73	10475.01	-10094.34	-1586.71	10216.56	0.00	
21000.00	90.00	179.73	10475.01	-10194.34	-1586.24	10315.55	0.00	
21100.00	90.00	179.73	10475.01	-10294.34	-1585.77	10414.54	0.00	
21200.00	90.00	179.73	10475.01	-10394.34	-1585.30	10513.53	0.00	
21300.00	90.00	179.73	10475.01	-10494.34	-1584.83	10612.52	0.00	
21400.00	90.00	179.73	10475.01	-10594.34	-1584.36	10711.51	0.00	
21500.00	90.00	179.73	10475.01	-10694.33	-1583.88	10810.50	0.00	
21600.00	90.00	179.73	10475.01	-10794.33	-1583.41	10909.49	0.00	
21700.00	90.00	179.73	10475.01	-10894.33	-1582.94	11008.48	0.00	
21800.00	90.00	179.73	10475.01	-10994.33	-1582.47	11107.47	0.00	
21900.00	90.00	179.73	10475.01	-11094.33	-1582.00	11206.46	0.00	
22000.00	90.00	179.73	10475.01	-11194.33	-1581.53	11305.45	0.00	
22100.00	90.00	179.73	10475.01	-11294.33	-1581.06	11404.44	0.00	
22146.20	90.00	179.73	10475.01	-11340.53	-1580.84	11450.18	0.00	exit
22200.00	90.00	179.73	10475.01	-11394.33	-1580.58	11503.43	0.00	
22226.20	90.00	179.73	10475.00	-11420.53	-1580.49	11529.37	0.00	BHL

MULE 11-23 FED COM 304H

1. Geologic Formations

TVD of target	10475	Pilot hole depth	N/A
MD at TD:	22226	Deepest expected fresh water	

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Rustler	665		
Salt	1090		
Base of Salt	4165		
Delaware	4387		
Cherry Canyon	5365		
Brushy Canyon	6676		
1st Bone Spring Lime	8307		
Leonard	8424		
Bone Spring 1st	9332		
Bone Spring 2nd	9535		
3rd Bone Spring Lime	10433		

*H2S, water flows, loss of circulation, abnormal pressures, etc.

MULE 11-23 FED COM 304H

2. Casing Program (Primary Design)

Hole Size	Csg. Size	Wt (PPF)	Grade	Conn	Casing Interval		Casing Interval	
					From (MD)	To (MD)	From (TVD)	To (TVD)
14 3/4	10 3/4	45 1/2	J-55	BTC	0	690	0	690
9 7/8	8 5/8	32	P110HSCY	MOFXL	0	9989	0	9989
7 7/8	5 1/2	20	P110EC	DWC/C-IS PLUS	0	22226	0	10475

• All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.

3. Cementing Program (Primary Design)

Casing	# Sks	TOC	Wt. ppg	Yld (ft3/sack)	Slurry Description
Surface	423	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	332	Surf	9	3.27	Lead: Class C Cement + additives
	376	6776	13.2	1.44	Tail: Class H / C + additives
Int 1 Intermediate Squeeze	431	Surf	13.2	1.44	Squeeze Lead: Class C Cement + additives
	332	Surf	9	3.27	Lead: Class C Cement + additives
	376	6776	13.2	1.44	Tail: Class H / C + additives
Production	35	9489	9	3.27	Lead: Class H / C + additives
	1606	10089	13.2	1.44	Tail: Class H / C + additives

Assuming no returns are established while drilling, Devon requests to pump a two stage cement job on the intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. The final cement top will be verified by Echo-meter. Devon will include the Echo-meter verified fluid top and the volume of displacement fluid above the cement slurry in the annulus in all post-drill sundries on wells utilizing this cement program. Devon will report to the BLM the volume of fluid (limited to 1 bbls) used to flush intermediate casing valves following backside cementing procedures

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

4. Pressure Control Equipment (Three String Design)

BOP installed and tested before drilling which hole?		Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-58"	5M	Annular	X	50% of rated working pressure	
			Blind Ram	X		
			Pipe Ram			
			Double Ram	X		
			Other*			
Production	13-5/8"	5M	Annular (5M)	X	50% of rated working pressure	
			Blind Ram	X		
			Pipe Ram			
			Double Ram	X		
			Other*			
			Annular (5M)			
			Blind Ram			
			Pipe Ram			
			Double Ram			
			Other*			
N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.					
Y	A variance is requested to run a 5 M annular on a 10M system					

5. Mud Program (Three String Design)

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	DBE / Cut Brine	10-10.5
Production	OBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	Intermediate shoe to TD
PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH pressure at deepest TVD	4902
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H2S is present
Y	H2S plan attached.

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.,
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pa.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. A that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

- Directional Plan
- Other, describe

Metal One Corp. Metal One	MO-FXL *1 Pipe Body: BMP P110HSCY MinYS125ksi Special Drift 7.875" Connection Data Sheet	CDS#	MO-FXL 8-5/8 32.0
			P110HSCY
			MinYS125ksi
		Date	SD7.875

MO-FXL

Geometry

Imperial

S.I.

Pipe Body

Grade *1	P110HSCY		P110HSCY	
MinYS *1	125	ksi	125	ksi
Pipe OD (D)	8 5/8	in	219.08	mm
Weight	32.00	lb/ft	47.68	kg/m
Actual weight	31.10		46.34	kg/m
Wall Thickness (t)	0.352	in	8.94	mm
Pipe ID (d)	7.921	in	201.19	mm
Pipe body cross section	9.149	in ²	5,902	mm ²
Special Drift Dia. *1	7.875	in	200.03	mm
-	-	-	-	-

Connection

Box OD (W)	8.625	in	219.08	mm
PIN ID	7.921	in	201.19	mm
Make up Loss	3.847	in	97.71	mm
Box Critical Area	5.853	in ²	3686	mm ²
Joint load efficiency	69	%	69	%
Thread Taper	1 / 10 (1.2" per ft)			
Number of Threads	5 TPI			

Performance

Performance Properties for Pipe Body

S.M.Y.S. *1	1,144	kips	5,087	kN
M.I.Y.P. *1	8,930	psi	61.59	MPa
Collapse Strength *1	4,300	psi	29.66	MPa

Note S.M.Y.S.= Specified Minimum YIELD Strength of Pipe body
M.I.Y.P. = Minimum Internal Yield Pressure of Pipe body

*1: BMP P110HSCY: MinYS125ksi, SD7.875, Collapse Strength 4,300psi


Performance Properties for Connection

Tensile Yield load	789 kips (69% of S.M.Y.S.)			
Min. Compression Yield	789 kips (69% of S.M.Y.S.)			
Internal Pressure	6,250 psi (70% of M.I.Y.P.)			
External Pressure	100% of Collapse Strength			
Max. DLS (deg. /100ft)	29			

Recommended Torque

Min.	13,600	ft-lb	18,400	N-m
Opti.	14,900	ft-lb	20,200	N-m
Max.	16,200	ft-lb	21,900	N-m
Operational Max.	28,400	ft-lb	38,500	N-m

Note : Operational Max. torque can be applied for high torque application



Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Connection Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Connection Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-con/images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Connection Data Sheet.

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Well Name: MULE 11-14 FED COM	Well Location: T25S / R31E / SEC 11 / NENE / 32.150873 / -103.743227	County or Parish/State: EDDY / NM
Well Number: 535H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM000503	Unit or CA Name:	Unit or CA Number:
US Well Number:	Operator: DEVON ENERGY PRODUCTION COMPANY LP	

LONG VO Digitally signed by LONG VO
Date: 2024.05.29 09:57:46 -05'00'

Notice of Intent

Sundry ID: 2791639

Type of Submission: Notice of Intent

Type of Action: APD Change

Date Sundry Submitted: 05/21/2024

Time Sundry Submitted: 09:11

Date proposed operation will begin: 05/20/2024

Procedure Description: Devon Energy Production Co., L.P. (Devon) respectfully requests to change the well name, BHL and depth on the subject well. Devon is also requesting a variance for offline cementing and break test. Please see attached revised C102, Drill plan, directional plan, variance requests. API: 30-015-55057 Permitted Well name: MULE 11-14 FED COM 525H Proposed Well name: MULE 11-23 FED COM 304H Permitted BHL: SWSE, 20 FSL, 1350 FEL, 14-25S-31E Proposed BHL: NWNE, 1288 FNL, 2600 FEL, 14-25S-31E Permitted TVD/MD: 9140/19363 Proposed TVD/MD: 10475/22226

NOI Attachments

Procedure Description

WA018222915_MULE_11_23_FED_COM_304H_WL_R1_SIGNED_20240521091116.pdf

Offline_Cementing___Variance_Request_20240521083146.pdf

break_test_variance_BOP_1_15_24_20240521083140.pdf

10.750_45.5_J55_SEAH_20240521083140.pdf

MULE_11_23_FED_COM_304H_Directional_Plan_04_30_24_20240521083140.pdf

MULE_11_23_FED_COM_304H_20240521083140.pdf

8.625_32lb_P110_MOFXL_20240521083140.pdf

5.5_20lb_P110EC_DWC_C_IS_PLUS_20240521083140.pdf

Well Name: MULE 11-14 FED COM

Well Location: T25S / R31E / SEC 11 / NENE / 32.150873 / -103.743227

County or Parish/State: EDDY / NM

Well Number: 535H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM000503

Unit or CA Name:

Unit or CA Number:

US Well Number:

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: CHELSEY GREEN

Signed on: MAY 21, 2024 08:31 AM

Name: DEVON ENERGY PRODUCTION COMPANY LP

Title: Regulatory Compliance Professional

Street Address: 333 West Sheridan Avenue

City: Oklahoma City State: OK

Phone: (405) 228-8595

Email address: Chelsey.Green@dvn.com

Field

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Devon Energy Production Company LP
LEASE NO.:	NMNM000503
LOCATION:	Section 11, T.24 S., R.29 E., NMPM
COUNTY:	Eddy County, New Mexico ▼

WELL NAME & NO.:	Mule 11-14 Fed Com 304H
BOTTOM HOLE FOOTAGE	1288'/N & 2600'/E
ATS/API ID:	30-015-55057
APD ID:	10400066870
Sundry ID:	2791639
Date APD Submitted:	

COA

H2S	Yes ▼		
Potash	None ▼		
Cave/Karst Potential	Low ▼		
Cave/Karst Potential	<input type="checkbox"/> Critical		
Variance	<input checked="" type="checkbox"/> None	<input checked="" type="checkbox"/> Flex Hose	<input checked="" type="checkbox"/> Other
Wellhead	Conventional and Multibowl ▼		
Other	<input type="checkbox"/> 4 String	Capitan Reef None ▼	<input type="checkbox"/> WIPP
Other	Pilot Hole None ▼	<input type="checkbox"/> Open Annulus	
Cementing	Contingency Squeeze None ▼	Echo-Meter Int 1 ▼	Primary Cement Squeeze None ▼
Special Requirements	<input type="checkbox"/> Water Disposal/Injection	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit
Special Requirements	<input type="checkbox"/> Batch Sundry	Waste Prevention None ▼	
Special Requirements Variance	<input checked="" type="checkbox"/> Break Testing	<input checked="" type="checkbox"/> Offline Cementing	<input type="checkbox"/> Casing Clearance

A. HYDROGEN SULFIDE

A Hydrogen Sulfide (H₂S) Drilling Plan shall be activated 500 feet prior to drilling into the **Delaware** formation. As a result, the Hydrogen Sulfide area must meet **43 CFR part 3170 Subpart 3176** requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

B. CASING

1. The **10-3/4** inch surface casing shall be set at approximately **725 feet** (a minimum of **70 feet (Eddy County)** into the Rustler Anhydrite and above the salt when present, and below usable fresh water) and cemented to the surface. The surface hole shall be **14 3/4** inch in diameter.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the **8-5/8** inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.

Option 2:

Operator has proposed to cement in two stages by conventionally cementing the first stage and performing a bradenhead squeeze on the second stage, contingent upon no returns to surface.

- a. First stage: Operator will cement with intent to reach the top of the **Brushy Canyon at 6676' (708 sxs Class H/C+ additives)**.
- b. Second stage:
 - Operator will perform bradenhead squeeze and top-out. Cement to surface. If cement does not reach surface, the appropriate BLM office shall be notified. **(Squeeze 700 sxs Class C)**

Operator has proposed to pump down **10-3/4" X 8-5/8"** annulus after primary cementing stage. Operator must run Echo-meter to verify Cement Slurry/Fluid top in the annulus Or operator shall run a CBL from TD of the **8-5/8"** casing to surface after the second stage BH to verify TOC.

Submit results to the BLM. No displacement fluid/wash out shall be utilized at the top of the cement slurry between second stage BH and top out. Operator must run one CBL per Well Pad. Operator may conduct a negative and positive pressure test during completion to remediate sustained casing pressure.

If cement does not reach surface, the next casing string must come to surface.

Operator must use a limited flush fluid volume of 1 bbl following backside cementing procedures.

3. The minimum required fill of cement behind the **5-1/2** inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification. **Cement excess is less than 25%, more cement is required if washout occurs. Adjust cement volume and excess based on a fluid caliper or similar method that reflects the as-drilled size of the wellbore.**

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
- 2.

Option 1:

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M) psi. Annular which shall be tested to 3500 (70% Working Pressure) psi.**

- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the **8-5/8** inch intermediate casing shoe shall be **5000 (5M)** psi.

Option 2:

Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the **10-3/4** inch surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.

- a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
- b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- c. Manufacturer representative shall install the test plug for the initial BOP test.
- d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- The operator will submit an as-drilled survey well plat of the well completion, but are not limited to, those specified in **43 CFR part 3170 Subpart 3171**
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

BOPE Break Testing Variance (Approved)

- BOPE Break Testing is ONLY permitted for 5M BOPE or less. **(Annular preventer must be tested to a minimum of 70% of BOPE working pressure and shall be higher than the MASP)**
- BOPE Break Testing is NOT permitted to drilling the production hole section.
- Variance only pertains to the intermediate hole-sections and no deeper than the Bone Springs formation.
- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer **(575-706-2779)** prior to the commencement of any BOPE Break Testing operations.
- A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required. (200' TVD tolerance between intermediate shoes is allowable).
- The BLM is to be contacted **(575-361-2822 Eddy County)** 4 hours prior to BOPE tests.
- As a minimum, a full BOPE test shall be performed at **21-day** intervals.
- In the event any repairs or replacement of the BOPE is required, the BOPE shall test as per **43 CFR part 3170 Subpart 3172**.
- If in the event break testing is not utilized, then a full BOPE test would be conducted.

Offline Cementing

Operator has been **(Approved)** to pump the proposed cement program offline in the **Intermediate(s) interval**.

Offline cementing should commence within 24 hours of landing the casing for the interval.

Notify the BLM 4hrs prior to cementing offline at **Eddy County: 575-361-2822**.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

EMAIL or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,

BLM_NM_CFO_DrillingNotifications@BLM.GOV

(575) 361-2822

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per **43 CFR part 3170 Subpart 3172** as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. For at least one well per pad (deepest well preferred) the record of drilling rate (ROP) along with the Gamma Ray (GR) and Neutron (CNL) well logs run from TVD to surface in the vertical section of the hole shall be submitted to the BLM office as well as all other logs run on the full borehole within 30 days from completion. Only digital copies of the logs in .TIF or .LAS formats are necessary; Logs shall be emailed to blm-cfo-geology@doimspp.onmicrosoft.com. The email should have a subject line with the US Well Number / API Number, well name, and the body should include the starting depth and the TVD of the log.

The top of the Rustler, top and bottom of the salt, and the top of the Capitan Reef (if present) are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends of both lead and tail cement, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a

larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR part 3170 Subpart 3172** and **API STD 53 Sec. 5.3**.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.

- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR part 3170 Subpart 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for 8 hours or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of

the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR part 3170 Subpart 3172**.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

Long Vo (LVO) 5/29/2024

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. **NMNM0503**

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator **DEVON ENERGY PRODUCTION COMPANY LP**

3a. Address **333 WEST SHERIDAN AVE, OKLAHOMA CITY, OK 73102** 3b. Phone No. (include area code) **(405) 235-3611**

4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)
SEC 11/T25S/R31E/NMP

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No. **MULE 11-14 FED COM/535H**

9. API Well No.

10. Field and Pool or Exploratory Area
PADUCA/BONE SPRING

11. Country or Parish, State
EDDY/NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input checked="" type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Devon Energy Production Co., L.P. (Devon) respectfully requests to change the well name, BHL and depth on the subject well. Devon is also requesting a variance for offline cementing and break test. Please see attached revised C102, Drill plan, directional plan, variance requests.

API: 30-015-55057

Permitted Well name: MULE 11-14 FED COM 525H
 Proposed Well name: MULE 11-23 FED COM 304H
 Permitted BHL: SWSE, 20 FSL, 1350 FEL, 14-25S-31E
 Proposed BHL: NWNE, 1288 FNL, 2600 FEL, 14-25S-31E
 Permitted TVD/MD: 9140/19363
 Proposed TVD/MD: 10475/22226

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)
CHELSEY GREEN / Ph: (405) 228-8595

Signature (Electronic Submission)

Title **Regulatory Compliance Professional**

Date **05/21/2024**

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title **CARLSBAD**

Office

Date

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: NENE / 450 FNL / 966 FEL / TWSP: 25S / RANGE: 31E / SECTION: 11 / LAT: 32.150873 / LONG: -103.743227 (TVD: 0 feet, MD: 0 feet)

PPP: NWNE / 100 FNL / 1350 FEL / TWSP: 25S / RANGE: 31E / SECTION: 11 / LAT: 32.151844 / LONG: -103.744466 (TVD: 8424 feet, MD: 8491 feet)

BHL: SWSE / 20 FSL / 1350 FEL / TWSP: 25S / RANGE: 31E / SECTION: 14 / LAT: 32.123097 / LONG: -103.74449 (TVD: 9140 feet, MD: 19363 feet)

CONFIDENTIAL

Intent As Drilled

API # 30-015-55057		
Operator Name: DEVON ENERGY PRODUCTION COMPANY, LP.	Property Name: MULE 11-23 FED COM	Well Number 304H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	11	25S	31E		65	FNL	2601	FEL	EDDY
Latitude 32.1519					Longitude 103.7486				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	11	25-S	31-E		100	NORTH	2600	EAST	EDDY
Latitude 32.151872					Longitude 103.748505				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
B	23	25-S	31-E		1208	NORTH	2600	EAST	EDDY
Latitude 32.119724					Longitude 103.748533				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? N

Is this well an infill well? Y

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-015-55054		
Operator Name: DEVON ENERGY PRODUCTION COMPANY, LP	Property Name: MULE 11-14 FED COM	Well Number 525H

KZ 06/29/2018

Offline Cementing

Variance Request

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements.

Section 2 - Blowout Preventer Testing Procedure

Variance Request

Devon Energy requests to only test BOP connection breaks after drilling out of surface casing and while skidding between wells which conforms to API Standard 53 and industry standards. This test will include the Top Pipe Rams, HCR, Kill Line Check Valve, QDC (quick disconnect to wellhead) and Shell of the 10M BOPE to 5M for 10 minutes. If a break to the flex hose that runs to the choke manifold is required due to repositioning from a skid, the HCR will remain open during the shell test to include that additional break. The variance only pertains to intermediate hole-sections and no deeper than the Bone Springs Formation where 5M BOP tests are required. The initial BOP test will follow 43 CFR 3172, and subsequent tests following a skid will only test connections that are broken. The annular preventer will be tested to 100% working pressure. This variance will meet or exceed 43 CFR 3172 per the following: Devon Energy will perform a full BOP test per 43 CFR 3172 before drilling out of the intermediate casing string(s) and starting the production hole, before starting any hole section that requires a 10M test, before the expiration of the allotted 14-days for 5M intermediate batch drilling or when the drilling rig is fully mobilized to a new well pad, whichever is sooner. We will utilize a 200' TVD tolerance between intermediate shoes as the cutoff for a full BOP test. The BLM will be contacted 4hrs prior to a BOPE test. The BLM will be notified if and when a well control event is encountered. Break test will be a 14 day interval and not a 30 day full BOPE test interval. If in the event break testing is not utilized, then a full BOPE test would be conducted.



1. Well Control Response:
 1. Primary barrier remains fluid
 2. In the event of an influx due to being underbalanced and after a realized gain or flow, the order of closing BOPE is as follows:
 - a) Annular first
 - b) If annular were to not hold, Upper pipe rams second (which were tested on the skid BOP test)
 - c) If the Upper Pipe Rams were to not hold, Lower Pipe Rams would be third

Cactus
Wellhead

2-9-17
E Bell

80.7 °F

15:49



50

Date 02-09-17

Tested By E.BELL

Transducer bay2

Transducer Serial 181504

Calibration Date 9/6/15

Job#	Part#	Serial#	Description	Test Pressure
1	TRJ0006341-0007 116966	TRJ6341-7-1	ADPT,DRLG,CW,MBU-3T,13-5/8 10M	15000
2				
3				
4				
5			TRANSDUCER CALIBRATION DUE 03/13/2017	
6				
7				
8				

Start Stop Zero Config Save Print EXIT



10-3/4" 45.50# 0.400" J-55

Dimensions (Nominal)

Outside Diameter	10.750	in.
Wall	0.400	in.
Inside Diameter	9.950	in.
Drift	9.875	in.
Weight, T&C	45.500	lbs/ft
Weight, PE	44.260	lbs/ft

Internal Yield Pressure at Minimum Yield

Collapse	2090	psi
----------	------	-----

Internal Yields Pressure

PE	3580	psi
STC	3580	psi
BTC	3580	psi

Yield Strength, Pipe Body	715	1000 lbs
---------------------------	-----	----------

Joint Strength, STC

STC	493	1000 lbs
BTC	796	1000 lbs


Note: SeAH Steel has produced this specification sheet for general information only. SeAH does not assume liability or responsibility for any loss or injury resulting from the use of information or data contained herein. All applications for the material described are at the customer's own risk and responsibility.



Well: MULE 11-23 FED COM 304H
 County: Eddy
 Wellbore: Permit Plan
 Design: Permit Plan #1

Geodetic System: US State Plane 1983
 Datum: North American Datum 1927
 Ellipsoid: Clarke 1866
 Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
2000.00	0.00	283.40	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2500.00	13.00	283.40	2495.72	13.09	-54.94	-5.43	1.00	Hold Tangent
9399.41	13.00	283.40	9218.30	372.77	-1564.72	-154.75	0.00	Drop to Vertical
10049.41	0.00	283.40	9862.74	389.78	-1636.15	-161.81	2.00	Hold Vertical
10088.72	0.00	179.73	9902.04	389.78	-1636.15	-161.81	0.00	KOP
10988.72	90.00	179.73	10475.00	-183.17	-1633.45	405.36	10.00	Landing Point
22226.20	90.00	179.73	10475.00	-11420.53	-1580.49	11529.37	0.00	BHL



Key Depths	MD (ft)	TVD (ft)
Rustler	0.00	0.00
Salt	1090.00	1090.00
Base of Salt	4213.19	4165.00
Delaware	4441.03	4387.00
Cherry Canyon	5444.75	5365.00
Brushy Canyon	6790.24	6676.00
1st Bone Spring Lime	8464.14	8307.00
Leonard	8584.22	8424.00
Bone Spring 1st	9515.59	9332.00
Bone Spring 2nd	9720.95	9535.00
3rd Bone Spring Lime / Point of Penetration	10767.97	10433.00
exit	22146.20	10475.01

	MD (ft)	TVD (ft)	Lat (°)	Long (°)	Section Footages
SHL	0.00	0.00	32.1508	-103.7433	450' FNL, 966' FEL of Sec 11 in T25S, R31E
KOP	10088.72	9902.04	32.1519	-103.7486	65' FNL, 2601' FEL of Sec 11 in T25S, R31E
Point of Penetration	10767.97	10433.00	32.1519	-103.7485	100' FNL, 2600' FEL of Sec 11 in T25S, R31E
Exit	22146.20	10475.01	32.1197	-103.7485	1208' FNL, 2600' FEL of Sec 23 in T25S, R31E
BHL	22226.20	10475.00	32.1194	-103.7486	1288' FNL, 2600' FEL of Sec 23 in T25S, R31E

Y X MD
 KOP 419513 722329 10088.72



Well: MULE 11-23 FED COM 304H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
100.00	0.00	283.40	100.00	0.00	0.00	0.00	0.00	
200.00	0.00	283.40	200.00	0.00	0.00	0.00	0.00	
300.00	0.00	283.40	300.00	0.00	0.00	0.00	0.00	
400.00	0.00	283.40	400.00	0.00	0.00	0.00	0.00	
500.00	0.00	283.40	500.00	0.00	0.00	0.00	0.00	
600.00	0.00	283.40	600.00	0.00	0.00	0.00	0.00	
665.00	0.00	283.40	665.00	0.00	0.00	0.00	0.00	Rustler
700.00	0.00	283.40	700.00	0.00	0.00	0.00	0.00	
800.00	0.00	283.40	800.00	0.00	0.00	0.00	0.00	
900.00	0.00	283.40	900.00	0.00	0.00	0.00	0.00	
1000.00	0.00	283.40	1000.00	0.00	0.00	0.00	0.00	
1090.00	0.00	283.40	1090.00	0.00	0.00	0.00	0.00	Salt
1100.00	0.00	283.40	1100.00	0.00	0.00	0.00	0.00	
1200.00	0.00	283.40	1200.00	0.00	0.00	0.00	0.00	
1300.00	0.00	283.40	1300.00	0.00	0.00	0.00	0.00	
1400.00	0.00	283.40	1400.00	0.00	0.00	0.00	0.00	
1500.00	0.00	283.40	1500.00	0.00	0.00	0.00	0.00	
1600.00	0.00	283.40	1600.00	0.00	0.00	0.00	0.00	
1700.00	0.00	283.40	1700.00	0.00	0.00	0.00	0.00	
1800.00	0.00	283.40	1800.00	0.00	0.00	0.00	0.00	
1900.00	0.00	283.40	1900.00	0.00	0.00	0.00	0.00	
2000.00	0.00	283.40	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2100.00	2.60	283.40	2099.97	0.53	-2.21	-0.22	2.60	
2200.00	5.20	283.40	2199.73	2.10	-8.82	-0.87	2.60	
2300.00	7.80	283.40	2299.07	4.72	-19.83	-1.96	2.60	
2400.00	10.40	283.40	2397.81	8.39	-35.22	-3.48	2.60	
2500.00	13.00	283.40	2495.72	13.09	-54.94	-5.43	1.00	Hold Tangent
2600.00	13.00	283.40	2593.16	18.30	-76.83	-7.60	0.00	
2700.00	13.00	283.40	2690.60	23.52	-98.71	-9.76	0.00	
2800.00	13.00	283.40	2788.03	28.73	-120.59	-11.93	0.00	
2900.00	13.00	283.40	2885.47	33.94	-142.47	-14.09	0.00	
3000.00	13.00	283.40	2982.91	39.15	-164.36	-16.25	0.00	
3100.00	13.00	283.40	3080.34	44.37	-186.24	-18.42	0.00	
3200.00	13.00	283.40	3177.78	49.58	-208.12	-20.58	0.00	
3300.00	13.00	283.40	3275.22	54.79	-230.00	-22.75	0.00	
3400.00	13.00	283.40	3372.65	60.01	-251.89	-24.91	0.00	
3500.00	13.00	283.40	3470.09	65.22	-273.77	-27.07	0.00	
3600.00	13.00	283.40	3567.53	70.43	-295.65	-29.24	0.00	
3700.00	13.00	283.40	3664.97	75.65	-317.54	-31.40	0.00	
3800.00	13.00	283.40	3762.40	80.86	-339.42	-33.57	0.00	
3900.00	13.00	283.40	3859.84	86.07	-361.30	-35.73	0.00	
4000.00	13.00	283.40	3957.28	91.29	-383.18	-37.90	0.00	
4100.00	13.00	283.40	4054.71	96.50	-405.07	-40.06	0.00	
4200.00	13.00	283.40	4152.15	101.71	-426.95	-42.22	0.00	
4213.19	13.00	283.40	4165.00	102.40	-429.83	-42.51	0.00	Base of Salt
4300.00	13.00	283.40	4249.59	106.92	-448.83	-44.39	0.00	
4400.00	13.00	283.40	4347.02	112.14	-470.71	-46.55	0.00	
4441.03	13.00	283.40	4387.00	114.28	-479.69	-47.44	0.00	Delaware
4500.00	13.00	283.40	4444.46	117.35	-492.60	-48.72	0.00	
4600.00	13.00	283.40	4541.90	122.56	-514.48	-50.88	0.00	
4700.00	13.00	283.40	4639.34	127.78	-536.36	-53.04	0.00	
4800.00	13.00	283.40	4736.77	132.99	-558.24	-55.21	0.00	
4900.00	13.00	283.40	4834.21	138.20	-580.13	-57.37	0.00	
5000.00	13.00	283.40	4931.65	143.42	-602.01	-59.54	0.00	
5100.00	13.00	283.40	5029.08	148.63	-623.89	-61.70	0.00	
5200.00	13.00	283.40	5126.52	153.84	-645.78	-63.86	0.00	
5300.00	13.00	283.40	5223.96	159.06	-667.66	-66.03	0.00	
5400.00	13.00	283.40	5321.39	164.27	-689.54	-68.19	0.00	
5444.75	13.00	283.40	5365.00	166.60	-699.33	-69.16	0.00	Cherry Canyon
5500.00	13.00	283.40	5418.83	169.48	-711.42	-70.36	0.00	
5600.00	13.00	283.40	5516.27	174.70	-733.31	-72.52	0.00	
5700.00	13.00	283.40	5613.71	179.91	-755.19	-74.68	0.00	
5800.00	13.00	283.40	5711.14	185.12	-777.07	-76.85	0.00	
5900.00	13.00	283.40	5808.58	190.33	-798.95	-79.01	0.00	
6000.00	13.00	283.40	5906.02	195.55	-820.84	-81.18	0.00	
6100.00	13.00	283.40	6003.45	200.76	-842.72	-83.34	0.00	
6200.00	13.00	283.40	6100.89	205.97	-864.60	-85.51	0.00	
6300.00	13.00	283.40	6198.33	211.19	-886.49	-87.67	0.00	
6400.00	13.00	283.40	6295.76	216.40	-908.37	-89.83	0.00	



Well: MULE 11-23 FED COM 304H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
6500.00	13.00	283.40	6393.20	221.61	-930.25	-92.00	0.00	
6600.00	13.00	283.40	6490.64	226.83	-952.13	-94.16	0.00	
6700.00	13.00	283.40	6588.08	232.04	-974.02	-96.33	0.00	
6790.24	13.00	283.40	6676.00	236.74	-993.76	-98.28	0.00	Brushy Canyon
6800.00	13.00	283.40	6685.51	237.25	-995.90	-98.49	0.00	
6900.00	13.00	283.40	6782.95	242.47	-1017.78	-100.65	0.00	
7000.00	13.00	283.40	6880.39	247.68	-1039.66	-102.82	0.00	
7100.00	13.00	283.40	6977.82	252.89	-1061.55	-104.98	0.00	
7200.00	13.00	283.40	7075.26	258.10	-1083.43	-107.15	0.00	
7300.00	13.00	283.40	7172.70	263.32	-1105.31	-109.31	0.00	
7400.00	13.00	283.40	7270.13	268.53	-1127.19	-111.47	0.00	
7500.00	13.00	283.40	7367.57	273.74	-1149.08	-113.64	0.00	
7600.00	13.00	283.40	7465.01	278.96	-1170.96	-115.80	0.00	
7700.00	13.00	283.40	7562.45	284.17	-1192.84	-117.97	0.00	
7800.00	13.00	283.40	7659.88	289.38	-1214.73	-120.13	0.00	
7900.00	13.00	283.40	7757.32	294.60	-1236.61	-122.29	0.00	
8000.00	13.00	283.40	7854.76	299.81	-1258.49	-124.46	0.00	
8100.00	13.00	283.40	7952.19	305.02	-1280.37	-126.62	0.00	
8200.00	13.00	283.40	8049.63	310.24	-1302.26	-128.79	0.00	
8300.00	13.00	283.40	8147.07	315.45	-1324.14	-130.95	0.00	
8400.00	13.00	283.40	8244.50	320.66	-1346.02	-133.12	0.00	
8464.14	13.00	283.40	8307.00	324.01	-1360.06	-134.50	0.00	1st Bone Spring Lime
8500.00	13.00	283.40	8341.94	325.88	-1367.90	-135.28	0.00	
8584.22	13.00	283.40	8424.00	330.27	-1386.33	-137.10	0.00	Leonard
8600.00	13.00	283.40	8439.38	331.09	-1389.79	-137.44	0.00	
8700.00	13.00	283.40	8536.82	336.30	-1411.67	-139.61	0.00	
8800.00	13.00	283.40	8634.25	341.51	-1433.55	-141.77	0.00	
8900.00	13.00	283.40	8731.69	346.73	-1455.44	-143.94	0.00	
9000.00	13.00	283.40	8829.13	351.94	-1477.32	-146.10	0.00	
9100.00	13.00	283.40	8926.56	357.15	-1499.20	-148.26	0.00	
9200.00	13.00	283.40	9024.00	362.37	-1521.08	-150.43	0.00	
9300.00	13.00	283.40	9121.44	367.58	-1542.97	-152.59	0.00	
9399.41	13.00	283.40	9218.30	372.77	-1564.72	-154.75	0.00	Drop to Vertical
9400.00	12.99	283.40	9218.87	372.80	-1564.85	-154.76	2.01	
9500.00	10.99	283.40	9316.69	377.61	-1585.05	-156.76	2.00	
9515.59	10.68	283.40	9332.00	378.29	-1587.90	-157.04	2.00	Bone Spring 1st
9600.00	8.99	283.40	9415.17	381.63	-1601.92	-158.43	2.00	
9700.00	6.99	283.40	9514.19	384.85	-1615.44	-159.77	2.00	
9720.95	6.57	283.40	9535.00	385.43	-1617.85	-160.00	2.00	Bone Spring 2nd
9800.00	4.99	283.40	9613.64	387.27	-1625.59	-160.77	2.00	
9900.00	2.99	283.40	9713.39	388.88	-1632.36	-161.44	2.00	
10000.00	0.99	283.40	9813.33	389.69	-1635.73	-161.77	2.00	
10049.41	0.00	283.40	9862.74	389.78	-1636.15	-161.81	2.00	Hold Vertical
10088.72	0.00	179.73	9902.04	389.78	-1636.15	-161.81	0.00	KOP
10100.00	1.13	179.73	9913.33	389.67	-1636.14	-161.70	10.00	
10200.00	11.13	179.73	10012.63	379.01	-1636.09	-151.15	10.00	
10300.00	21.13	179.73	10108.57	351.27	-1635.96	-123.69	10.00	
10400.00	31.13	179.73	10198.24	307.29	-1635.76	-80.15	10.00	
10500.00	41.13	179.73	10278.91	248.40	-1635.48	-21.86	10.00	
10600.00	51.13	179.73	10348.12	176.40	-1635.14	49.41	10.00	
10700.00	61.13	179.73	10403.78	93.48	-1634.75	131.50	10.00	
10767.97	67.93	179.73	10433.00	32.16	-1634.46	192.21	10.00	3rd Bone Spring Lime / Point of Penetration
10800.00	71.13	179.73	10444.20	2.15	-1634.32	221.91	10.00	
10900.00	81.13	179.73	10468.15	-94.81	-1633.86	317.89	10.00	
10988.72	90.00	179.73	10475.00	-183.17	-1633.45	405.36	10.00	Landing Point
11000.00	90.00	179.73	10475.00	-194.45	-1633.39	416.53	0.00	
11100.00	90.00	179.73	10475.00	-294.45	-1632.92	515.52	0.00	
11200.00	90.00	179.73	10475.00	-394.45	-1632.45	614.51	0.00	
11300.00	90.00	179.73	10475.00	-494.45	-1631.98	713.50	0.00	
11400.00	90.00	179.73	10475.00	-594.45	-1631.51	812.49	0.00	
11500.00	90.00	179.73	10475.00	-694.45	-1631.03	911.48	0.00	
11600.00	90.00	179.73	10475.00	-794.44	-1630.56	1010.47	0.00	
11700.00	90.00	179.73	10475.00	-894.44	-1630.09	1109.46	0.00	
11800.00	90.00	179.73	10475.00	-994.44	-1629.62	1208.45	0.00	
11900.00	90.00	179.73	10475.00	-1094.44	-1629.15	1307.44	0.00	
12000.00	90.00	179.73	10475.00	-1194.44	-1628.68	1406.43	0.00	
12100.00	90.00	179.73	10475.00	-1294.44	-1628.21	1505.42	0.00	
12200.00	90.00	179.73	10475.00	-1394.44	-1627.73	1604.41	0.00	
12300.00	90.00	179.73	10475.00	-1494.44	-1627.26	1703.40	0.00	
12400.00	90.00	179.73	10475.00	-1594.44	-1626.79	1802.39	0.00	



Well: MULE 11-23 FED COM 304H
 County: Eddy
 Wellbore: Permit Plan
 Design: Permit Plan #1

Geodetic System: US State Plane 1983
 Datum: North American Datum 1927
 Ellipsoid: Clarke 1866
 Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
12500.00	90.00	179.73	10475.00	-1694.43	-1626.32	1901.38	0.00	
12600.00	90.00	179.73	10475.00	-1794.43	-1625.85	2000.37	0.00	
12700.00	90.00	179.73	10475.00	-1894.43	-1625.38	2099.36	0.00	
12800.00	90.00	179.73	10475.00	-1994.43	-1624.90	2198.35	0.00	
12900.00	90.00	179.73	10475.00	-2094.43	-1624.43	2297.34	0.00	
13000.00	90.00	179.73	10475.00	-2194.43	-1623.96	2396.33	0.00	
13100.00	90.00	179.73	10475.00	-2294.43	-1623.49	2495.32	0.00	
13200.00	90.00	179.73	10475.00	-2394.43	-1623.02	2594.31	0.00	
13300.00	90.00	179.73	10475.00	-2494.43	-1622.55	2693.30	0.00	
13400.00	90.00	179.73	10475.00	-2594.42	-1622.08	2792.29	0.00	
13500.00	90.00	179.73	10475.00	-2694.42	-1621.60	2891.28	0.00	
13600.00	90.00	179.73	10475.00	-2794.42	-1621.13	2990.27	0.00	
13700.00	90.00	179.73	10475.00	-2894.42	-1620.66	3089.26	0.00	
13800.00	90.00	179.73	10475.00	-2994.42	-1620.19	3188.25	0.00	
13900.00	90.00	179.73	10475.00	-3094.42	-1619.72	3287.24	0.00	
14000.00	90.00	179.73	10475.00	-3194.42	-1619.25	3386.24	0.00	
14100.00	90.00	179.73	10475.00	-3294.42	-1618.78	3485.23	0.00	
14200.00	90.00	179.73	10475.00	-3394.42	-1618.30	3584.22	0.00	
14300.00	90.00	179.73	10475.00	-3494.41	-1617.83	3683.21	0.00	
14400.00	90.00	179.73	10475.00	-3594.41	-1617.36	3782.20	0.00	
14500.00	90.00	179.73	10475.00	-3694.41	-1616.89	3881.19	0.00	
14600.00	90.00	179.73	10475.00	-3794.41	-1616.42	3980.18	0.00	
14700.00	90.00	179.73	10475.00	-3894.41	-1615.95	4079.17	0.00	
14800.00	90.00	179.73	10475.01	-3994.41	-1615.47	4178.16	0.00	
14900.00	90.00	179.73	10475.01	-4094.41	-1615.00	4277.15	0.00	
15000.00	90.00	179.73	10475.01	-4194.41	-1614.53	4376.14	0.00	
15100.00	90.00	179.73	10475.01	-4294.41	-1614.06	4475.13	0.00	
15200.00	90.00	179.73	10475.01	-4394.40	-1613.59	4574.12	0.00	
15300.00	90.00	179.73	10475.01	-4494.40	-1613.12	4673.11	0.00	
15400.00	90.00	179.73	10475.01	-4594.40	-1612.65	4772.10	0.00	
15500.00	90.00	179.73	10475.01	-4694.40	-1612.17	4871.09	0.00	
15600.00	90.00	179.73	10475.01	-4794.40	-1611.70	4970.08	0.00	
15700.00	90.00	179.73	10475.01	-4894.40	-1611.23	5069.07	0.00	
15800.00	90.00	179.73	10475.01	-4994.40	-1610.76	5168.06	0.00	
15900.00	90.00	179.73	10475.01	-5094.40	-1610.29	5267.05	0.00	
16000.00	90.00	179.73	10475.01	-5194.40	-1609.82	5366.04	0.00	
16100.00	90.00	179.73	10475.01	-5294.39	-1609.35	5465.03	0.00	
16200.00	90.00	179.73	10475.01	-5394.39	-1608.87	5564.02	0.00	
16300.00	90.00	179.73	10475.01	-5494.39	-1608.40	5663.01	0.00	
16400.00	90.00	179.73	10475.01	-5594.39	-1607.93	5762.00	0.00	
16500.00	90.00	179.73	10475.01	-5694.39	-1607.46	5860.99	0.00	
16600.00	90.00	179.73	10475.01	-5794.39	-1606.99	5959.98	0.00	
16700.00	90.00	179.73	10475.01	-5894.39	-1606.52	6058.97	0.00	
16800.00	90.00	179.73	10475.01	-5994.39	-1606.04	6157.96	0.00	
16900.00	90.00	179.73	10475.01	-6094.39	-1605.57	6256.95	0.00	
17000.00	90.00	179.73	10475.01	-6194.38	-1605.10	6355.94	0.00	
17100.00	90.00	179.73	10475.01	-6294.38	-1604.63	6454.93	0.00	
17200.00	90.00	179.73	10475.01	-6394.38	-1604.16	6553.92	0.00	
17300.00	90.00	179.73	10475.01	-6494.38	-1603.69	6652.91	0.00	
17400.00	90.00	179.73	10475.01	-6594.38	-1603.22	6751.90	0.00	
17500.00	90.00	179.73	10475.01	-6694.38	-1602.74	6850.89	0.00	
17600.00	90.00	179.73	10475.01	-6794.38	-1602.27	6949.88	0.00	
17700.00	90.00	179.73	10475.01	-6894.38	-1601.80	7048.87	0.00	
17800.00	90.00	179.73	10475.01	-6994.38	-1601.33	7147.86	0.00	
17900.00	90.00	179.73	10475.01	-7094.37	-1600.86	7246.85	0.00	
18000.00	90.00	179.73	10475.01	-7194.37	-1600.39	7345.84	0.00	
18100.00	90.00	179.73	10475.01	-7294.37	-1599.92	7444.83	0.00	
18200.00	90.00	179.73	10475.01	-7394.37	-1599.44	7543.82	0.00	
18300.00	90.00	179.73	10475.01	-7494.37	-1598.97	7642.81	0.00	
18400.00	90.00	179.73	10475.01	-7594.37	-1598.50	7741.80	0.00	
18500.00	90.00	179.73	10475.01	-7694.37	-1598.03	7840.79	0.00	
18600.00	90.00	179.73	10475.01	-7794.37	-1597.56	7939.78	0.00	
18700.00	90.00	179.73	10475.01	-7894.37	-1597.09	8038.77	0.00	
18800.00	90.00	179.73	10475.01	-7994.36	-1596.61	8137.76	0.00	
18900.00	90.00	179.73	10475.01	-8094.36	-1596.14	8236.75	0.00	
19000.00	90.00	179.73	10475.01	-8194.36	-1595.67	8335.74	0.00	
19100.00	90.00	179.73	10475.01	-8294.36	-1595.20	8434.73	0.00	
19200.00	90.00	179.73	10475.01	-8394.36	-1594.73	8533.73	0.00	
19300.00	90.00	179.73	10475.01	-8494.36	-1594.26	8632.72	0.00	
19400.00	90.00	179.73	10475.01	-8594.36	-1593.79	8731.71	0.00	



Well: MULE 11-23 FED COM 304H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
19500.00	90.00	179.73	10475.01	-8694.36	-1593.31	8830.70	0.00	
19600.00	90.00	179.73	10475.01	-8794.36	-1592.84	8929.69	0.00	
19700.00	90.00	179.73	10475.01	-8894.35	-1592.37	9028.68	0.00	
19800.00	90.00	179.73	10475.01	-8994.35	-1591.90	9127.67	0.00	
19900.00	90.00	179.73	10475.01	-9094.35	-1591.43	9226.66	0.00	
20000.00	90.00	179.73	10475.01	-9194.35	-1590.96	9325.65	0.00	
20100.00	90.00	179.73	10475.01	-9294.35	-1590.49	9424.64	0.00	
20200.00	90.00	179.73	10475.01	-9394.35	-1590.01	9523.63	0.00	
20300.00	90.00	179.73	10475.01	-9494.35	-1589.54	9622.62	0.00	
20400.00	90.00	179.73	10475.01	-9594.35	-1589.07	9721.61	0.00	
20500.00	90.00	179.73	10475.01	-9694.35	-1588.60	9820.60	0.00	
20600.00	90.00	179.73	10475.01	-9794.34	-1588.13	9919.59	0.00	
20700.00	90.00	179.73	10475.01	-9894.34	-1587.66	10018.58	0.00	
20800.00	90.00	179.73	10475.01	-9994.34	-1587.18	10117.57	0.00	
20900.00	90.00	179.73	10475.01	-10094.34	-1586.71	10216.56	0.00	
21000.00	90.00	179.73	10475.01	-10194.34	-1586.24	10315.55	0.00	
21100.00	90.00	179.73	10475.01	-10294.34	-1585.77	10414.54	0.00	
21200.00	90.00	179.73	10475.01	-10394.34	-1585.30	10513.53	0.00	
21300.00	90.00	179.73	10475.01	-10494.34	-1584.83	10612.52	0.00	
21400.00	90.00	179.73	10475.01	-10594.34	-1584.36	10711.51	0.00	
21500.00	90.00	179.73	10475.01	-10694.33	-1583.88	10810.50	0.00	
21600.00	90.00	179.73	10475.01	-10794.33	-1583.41	10909.49	0.00	
21700.00	90.00	179.73	10475.01	-10894.33	-1582.94	11008.48	0.00	
21800.00	90.00	179.73	10475.01	-10994.33	-1582.47	11107.47	0.00	
21900.00	90.00	179.73	10475.01	-11094.33	-1582.00	11206.46	0.00	
22000.00	90.00	179.73	10475.01	-11194.33	-1581.53	11305.45	0.00	
22100.00	90.00	179.73	10475.01	-11294.33	-1581.06	11404.44	0.00	
22146.20	90.00	179.73	10475.01	-11340.53	-1580.84	11450.18	0.00	exit
22200.00	90.00	179.73	10475.01	-11394.33	-1580.58	11503.43	0.00	
22226.20	90.00	179.73	10475.00	-11420.53	-1580.49	11529.37	0.00	BHL

MULE 11-23 FED COM 304H

1. Geologic Formations

TVD of target	10475	Pilot hole depth	N/A
MD at TD:	22226	Deepest expected fresh water	

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Rustler	665		
Salt	1090		
Base of Salt	4165		
Delaware	4387		
Cherry Canyon	5365		
Brushy Canyon	6676		
1st Bone Spring Lime	8307		
Leonard	8424		
Bone Spring 1st	9332		
Bone Spring 2nd	9535		
3rd Bone Spring Lime	10433		

*H2S, water flows, loss of circulation, abnormal pressures, etc.

MULE 11-23 FED COM 304H

2. Casing Program (Primary Design)

Hole Size	Csg. Size	Wt (PPF)	Grade	Conn	Casing Interval		Casing Interval	
					From (MD)	To (MD)	From (TVD)	To (TVD)
14 3/4	10 3/4	45 1/2	J-55	BTC	0	690	0	690
9 7/8	8 5/8	32	P110HSCY	MOFXL	0	9989	0	9989
7 7/8	5 1/2	20	P110EC	DWC/C-IS PLUS	0	22226	0	10475

• All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.

3. Cementing Program (Primary Design)

Casing	# Sks	TOC	Wt. ppg	Yld (ft3/sack)	Slurry Description
Surface	423	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	332	Surf	9	3.27	Lead: Class C Cement + additives
	376	6776	13.2	1.44	Tail: Class H / C + additives
Int 1 Intermediate Squeeze	700	Surf	13.2	1.44	Squeeze Lead: Class C Cement + additives
	332	Surf	9	3.27	Lead: Class C Cement + additives
	376	6776	13.2	1.44	Tail: Class H / C + additives
Production	35	9489	9	3.27	Lead: Class H / C + additives
	1606	10089	13.2	1.44	Tail: Class H / C + additives

Assuming no returns are established while drilling, Devon requests to pump a two stage cement job on the intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. The final cement top will be verified by Echo-meter. Devon will include the Echo-meter verified fluid top and the volume of displacement fluid above the cement slurry in the annulus in all post-drill sundries on wells utilizing this cement program. Devon will report to the BLM the volume of fluid (limited to 1 bbls) used to flush intermediate casing valves following backside cementing procedures

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

4. Pressure Control Equipment (Three String Design)

BOP installed and tested before drilling which hole?		Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-58"	5M	Annular	X	50% of rated working pressure	
			Blind Ram	X		
			Pipe Ram			
			Double Ram	X		
			Other*			
Production	13-5/8"	5M	Annular (5M)	X	50% of rated working pressure	
			Blind Ram	X		
			Pipe Ram			
			Double Ram	X		
			Other*			
			Annular (5M)			
			Blind Ram			
			Pipe Ram			
			Double Ram			
			Other*			
N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.					
Y	A variance is requested to run a 5 M annular on a 10M system					

5. Mud Program (Three String Design)

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	DBE / Cut Brine	10-10.5
Production	OBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Rpeort and sbumitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	Intermediate shoe to TD
PEX	

7. Drilling Conditions

Condition	Specfiy what type and where?
BH pressure at deepest TVD	4902
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogren Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H2S is present
Y	H2S plan attached.

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.,
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pa.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. A that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

- Directional Plan
- Other, describe

Metal One Corp. Metal One	MO-FXL *1 Pipe Body: BMP P110HSCY MinYS125ksi Special Drift 7.875" Connection Data Sheet	CDS#	MO-FXL 8-5/8 32.0
			P110HSCY
			MinYS125ksi
		Date	SD7.875

MO-FXL

Geometry

Imperial

S.I.

Pipe Body

Grade *1	P110HSCY		P110HSCY	
MinYS *1	125	ksi	125	ksi
Pipe OD (D)	8 5/8	in	219.08	mm
Weight	32.00	lb/ft	47.68	kg/m
Actual weight	31.10		46.34	kg/m
Wall Thickness (t)	0.352	in	8.94	mm
Pipe ID (d)	7.921	in	201.19	mm
Pipe body cross section	9.149	in ²	5,902	mm ²
Special Drift Dia. *1	7.875	in	200.03	mm
-	-	-	-	-

Connection

Box OD (W)	8.625	in	219.08	mm
PIN ID	7.921	in	201.19	mm
Make up Loss	3.847	in	97.71	mm
Box Critical Area	5.853	in ²	3686	mm ²
Joint load efficiency	69	%	69	%
Thread Taper	1 / 10 (1.2" per ft)			
Number of Threads	5 TPI			

Performance

Performance Properties for Pipe Body

S.M.Y.S. *1	1,144	kips	5,087	kN
M.I.Y.P. *1	8,930	psi	61.59	MPa
Collapse Strength *1	4,300	psi	29.66	MPa

Note S.M.Y.S.= Specified Minimum YIELD Strength of Pipe body
 M.I.Y.P. = Minimum Internal Yield Pressure of Pipe body

*1: BMP P110HSCY: MinYS125ksi, SD7.875, Collapse Strength 4,300psi


Performance Properties for Connection

Tensile Yield load	789 kips (69% of S.M.Y.S.)
Min. Compression Yield	789 kips (69% of S.M.Y.S.)
Internal Pressure	6,250 psi (70% of M.I.Y.P.)
External Pressure	100% of Collapse Strength
Max. DLS (deg. /100ft)	29

Recommended Torque

Min.	13,600	ft-lb	18,400	N-m
Opti.	14,900	ft-lb	20,200	N-m
Max.	16,200	ft-lb	21,900	N-m
Operational Max.	28,400	ft-lb	38,500	N-m

Note : Operational Max. torque can be applied for high torque application



Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Connection Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Connection Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mtlo.co.jp/mo-con/images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Connection Data Sheet.

11-25-31-A Sundry ID 2791639 Mule 11-14 Fed Com 535H

Mule 11-14 Fed Com 535H

10 3/4		surface csg in a		14 3/4		inch hole.		Design Factors			Surface	
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	B@s	a-B	a-C	Weight	
"A"	45.50		j 55	btc	21.69	6.17	725	11	1.10	11.65	32,988	
"B"				btc			0				0	
w/8.4#/g mud, 30min Sfc Csg Test psig: 1,500							Totals:	725			32,988	
Comparison of Proposed to Minimum Required Cement Volumes Tail Cmt does not circ to sfc.												
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE			Min Dist Hole-Cplg	
14 3/4	0.5563	423	609	403	51	9.00	3251	5M			1.50	
Burst Frac Gradient(s) for Segment(s) A, B = , b All > 0.70, OK.												

8 5/8		casing inside the		10 3/4		Design Factors			Int 1		
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	B@s	a-B	a-C	Weight
"A"	32.00		p 110	mo-flx	2.47	0.79	9,989	1	2.41	1.32	319,648
"B"							0				0
w/8.4#/g mud, 30min Sfc Csg Test psig:							Totals:	9,989			319,648
The cement volume(s) are intended to achieve a top of 0 ft from surface or a 725 overlap.											
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE			Min Dist Hole-Cplg
9 7/8	0.1261	708	1627	1266	29	10.50	2593	3M			0.63
D V Tool(s): sum of sx ≥ CuFt Σ%excess t by stage % : 289 19 1408 2635 108 Class 'C' tail cmt yld > 1.35											

5 1/2		casing inside the		8 5/8		Design Factors			Prod 1		
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	B@s	a-B	a-C	Weight
"A"	20.00		p 110	dwc/c is+	3.48	2.47	22,226	3	5.54	4.66	444,520
"B"							0				0
w/8.4#/g mud, 30min Sfc Csg Test psig: 2,305							Totals:	22,226			444,520
The cement volume(s) are intended to achieve a top of 9789 ft from surface or a 200 overlap.											
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE			Min Dist Hole-Cplg
7 7/8	0.1733	1641	2427	2156	13	9.00					0.79
Class 'C' tail cmt yld > 1.35											

#N/A		5 1/2		Design Factors			<Choose Casing>				
Segment	#/ft	Grade	Coupling	#N/A	Collapse	Burst	Length	B@s	a-B	a-C	Weight
"A"	0		0.00				0				0
"B"	0		0.00				0				0
w/8.4#/g mud, 30min Sfc Csg Test psig:							Totals:	0			0
Cmt vol calc below includes this csg, TOC intended #N/A ft from surface or a #N/A overlap.											
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE			Min Dist Hole-Cplg
0		#N/A	#N/A	0	#N/A						
#N/A Capitan Reef est top XXXX.											

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 350579

CONDITIONS

Operator: DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102	OGRID: 6137
	Action Number: 350579
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	All original COA's still apply. Additionally, if cement is not circulated to surface during cementing operations, then a CBL is required.	8/6/2024