

115%

search report



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Sundry Print Report

09/19/2024

Well Name: RUDMAN FEDERAL**Well Location:** T25N / R9W / SEC
27 / SWNW / 36.37694 / -107.78864**County or Parish/State:**
SAN JUAN / NM**Well Number:** 1**Type of Well:** OIL WELL**Allottee or Tribe Name:****Lease Number:** NMSF078521**Unit or CA Name:****Unit or CA Number:****US Well Number:**
300451302000S1**Operator:** EPIC ENERGY LLC**Notice of Intent****Sundry ID:** 2812484**Type of Submission:** Notice of Intent**Type of Action:** Plug and Abandonment**Date Sundry Submitted:** 09/18/2024**Time Sundry Submitted:** 10:38**Date proposed operation will begin:**
09/18/2024**Procedure Description:** Please see attached P&A Procedure.**Surface Disturbance****Is any additional surface disturbance proposed?:** No**NOI Attachments****Procedure Description**

NOI_P_A_Rudman_Federal__1_20240918103817.pdf

95%

search report

Well Name: RUDMAN FEDERAL

Well Location: T25N / R9W / SEC
27 / SWNW / 36.37694 / -107.78864County or Parish/State:
SAN JUAN / NM

Well Number: 1

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMSF078521

Unit or CA Name:

Unit or CA Number:

US Well Number:
300451302000S1

Operator: EPIC ENERGY LLC

Conditions of Approval**Specialist Review**

General_Requirement_PxA_20240919104311.pdf

2812484_NOIA_1_3004513020_KR_09192024_20240919104204.pdf

Rudman_Federal_No_1_Geo_Rpt_KR_Edit_20240919104155.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: SHAWNA MARTINEZ

Signed on: SEP 18, 2024 10:38 AM

Name: EPIC ENERGY LLC

Title: Regulatory Tech

Street Address: 332 RD 3100

City: AZTEC

State: NM

Phone: (505) 327-4892

Email address: SHAWNA@WALSHENG.NET

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: KENNETH G RENNICK

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5055647742

BLM POC Email Address: krennick@blm.gov

Disposition: Approved

Disposition Date: 09/19/2024

Signature: Kenneth Rennick

P&A Procedure**EPIC Energy – Rudman Federal #1**

White Wash Mancos Dakota

1850' FNL & 790' FWL, Section 27, T25N, R9W

San Juan Co, New Mexico, API #30-045-13020

Plug & Abandonment Procedure:

Note: All cement volumes use 100% excess outside casing and 50' excess inside pipe. Stabilizing wellbore fluid will be 8.33 ppg, sufficient to balance all exposed formation pressures. All cement will be ASTM Class G neat 1.15 ft³/sk or equivalent. If casing pressure tests or the hole stays full (static) tagging plugs will not be required. Dakota was plugged on 9/9/1959. Volumes calculated off 5-1/2" 15.5# casing.

Prior to Mobilization

1. Notify BLM & NMOCD 48 hrs before moving on to location to start P&A operations.
2. Verify all cement volumes based on actual slurry to be pumped. Calculations based on 1.15 ft³/sk.
3. Comply with all COA's from BLM and NMOCD

P&A Procedure

1. MIRU pulling unit/workover rig, cement equipment, clean up tank and related surface equipment.
Note: Monitor and record BH pressures throughout P&A job.
 2. TOH with rods/pump (hot oil/water rods if necessary)
 3. ND WH, NU BOP, RU rig floor and 2 3/8" handling tools.
 4. POOH 2 3/8" production string.
 5. TIH with 5 1/2" casing scraper to 5282'. TOOH LD 4 1/2" scraper.
 6. TIH with CICR and set @ ~5232' (50' above top perforation) . Roll hole with fresh water. PT tubing to 500 psi. PT casing to 500 psi. TOH.
 7. MIRU WL to run CBL, send copy to BLM/NMOCD. Add outside plugs as necessary based on CBL.
-
1. **Plug #1, 5182' - 5232' (Gallup Top 5260', Perfs: 5282' - 5502')**: TIH to CICR, sting out of CICR, mix and pump 6 sxs (6.9 cf) Class G Neat, leaving 50' on top of retainer. PU 200' above plug reverse circulate to clean tubing. WOC and tag plug if hole is not staying full.
 2. **Plug #2, 4450'- 4500' (Mancos Top: 4450')**: Mix & spot 18 sx (20.7 ft³) Class G neat cement in balanced plug. PUH 200' above plug and reverse circulate tubing clean. WOC and tag plug if hole is not staying full.

3. **Plug #3, 2505' – 2655' (Mesa Verde Top: 2605'):** Mix & spot 18 sx (20.7 ft³) Class G neat cement in balanced plug. PUH 100' above plug and reverse circulate tubing clean. WOC and tag plug if hole is not staying full.
4. **Plug #4, 1407' – 1847' (PC Top: 1797', Fruitland Top: 1507'):** Mix & spot 52 sx (59.8 ft³) Class G neat cement in balanced plug. PUH 100' above plug and reverse circulate tubing clean. WOC and tag plug if hole is not staying full.
5. **Plug #5, 1538' – 1688' (Ojo Alamo top: 1638'):** Mix and spot 12 sx (13.8 ft³) Class G neat cement in balanced plug. PUH 100' above plug and reverse circulate tubing clean. WOC and tag plug if necessary. Re-spot cement if necessary.
6. **Plug #6, 0' – 279':** Shoot holes at ~ 279' (50' below report casing shoe) and attempt to circulate out the BH. Mix and pump 80 sx (92 ft³) or until cement circulates to surface. Top off cement as necessary.
8. ND BOP and cut off wellhead below surface casing flange, top off casing and annulus as necessary. Install P&A marker and cut off and/or remove anchors. RD & MOL. Reclaim location/road as per the approved plan.

John Thompson

Engineer

Date Updated: 4/11/2024 (RM)



Hole Size: 12.25"

Surf Csq 8.625" @ 229' KB

Hole Size 7.875"

Prod Csg 5.5", 15.5#, 17#, J-55 @ 6527'
cmt w/ 400sx

Csq Leak (1683'-1745'): Squeezed 8/2005 235sx

Tubing: 175jts 2-3/8", 5-1/2" TECH/TAC, 1jt 2-
 EOT: 5590.91'KB
 SN: 5558'KB
 TAC: 5522'KB

Pump: 2" x 1-1/4" x 8' x 12' RHAC
Rods: 220ea 3/4" guided,
1ea 6', 3ea 4', 2ea 2' Pony Rods

Perfs: 5282'-5502': Gallup

Dakota was P&A'd on 9/9/1959
Cement Plug: 5690'-5830'

PBTD: 5837' KB: Tag at 5826'KB 8/2005
TD: 6527' KB

Production Tubing Detail			
	Length	Top	Bottom
KB Adjustment		12	12.00
175jts 2-3/8" Tubing	5510.74	12.00	5522.74
5-1/2" TECH/TAC	3.00	5522.74	5525.74
1jt 2-3/8" Tubing	31.82	5525.74	5557.56
SN	1.10	5557.56	5558.66
Slotted MA	32.25	5558.66	5590.91

Pump & Rod Detail -
Rod Description:
220ea 3/4" Guided Rods
1ea 6', 3ea 4', 2ea 2' Pony Rods
Pump Description:
2" x 1-1/4" x 8' x 12' RHAC

Pumping Unit:	_____	Gear Sheave:	_____
API Designation:	_____	Stroke Length:	_____
Samson Post SN:	_____	Gear Ratio:	_____
Gear Box SN:	_____	SPM:	_____
Structural Unbalance:	_____	Horse Power:	_____
Power:	_____	Volts:	_____
Power SN:	_____	Amps:	_____
Sheave Size:	_____	Belts:	_____

[illegible]

Well/Facility:	<u>Rudman Fed #1(Proposed)</u>	Well Status:	<u>Producing</u>
Operator:	<u>Epic Energy, Ilc</u>	Orig Oper:	<u>Alex N. Campbell</u>
Lease/Op Agmt:	<u>SF-078521</u>	KB:	<u>12'</u>
Field:	<u>White Wash Mancos DK</u>	API #:	<u>30-045-13020</u>
County:	<u>San Juan</u>	GR/KB:	<u>6542'</u>
State:	<u>NM</u>	TD:	<u>6527'</u>
Spud:	<u>3/19/1959</u>	PBTD:	<u>5680'(tag 5826' 2005)</u>
Comp. Date:	<u>P&A in 9/59: Re-entered '64'</u>	WI:	
1st Prod:	<u>64 (?)</u>	NRI:	
Wellhead Conn:			
Surface Loc:	<u>1850FNL 790FWL</u>		
Sec-Twn-Rge:	<u>E, S27, T25N, R9W</u>		
Pumper:			
Foreman:			
Anchors Tested			
Notes:			

Date Updated: August 2024 (JCT)



Plug #6: Surf - 279
80 sx (92 cf) of Class G Neat
Surface Plug

Hole Size: 12.25"
Surf Csg 8.625" @ 229' KB

Plug #5: 861' - 1011'
18 sx (20.7 cf) of Class G Neat
Ojo Alamo Top: 961'

Plug #4: 1407' - 1847'
52 sx (59.8 cf) of Class G Neat
Pictured Cliffs Top: 1797', Fruitland Top: 1507'

Plug #3: 2505' - 2655'
18 sx (20.7 cf) of Class G Neat
Mesaverde Top: 2605'

Plug #2: 4350' - 4500'
18 sx (20.7 cf) of Class G Neat
Mancos Top: 4450'

Plug #1: 5182'-5232'
6 sx (6.9 cf) of Class G Neat
Gallup Top: 5260'
CIBP: 5232'

Perfs: 5282'-5502': Gallup

Dakota was P&A'd on 9/9/1959
Cement Plug: 5690'-5830'

Prod Csg 5.5", 15.5#, 17#, J-55 @ 6527
cmt w/ 400sx

PBTD: 5830' KB Hole Size 7.875"
TD: 6527' KB

Production Tubing Detail			
Length		Top	Bottom
KB Adjustment		12	12.0
175lbs 2-3/8" Tubing	5510.74	12.00	5522.7
5-1/2" TECH/TAC	3.00	5522.74	5525.7
1jt 2-3/8" Tubing	31.82	5525.74	5557.5
SN	1.10	5557.56	5558.6
Slotted MA	32.25	5558.66	5590.9

Pump & Rod Detail -
Rod Description:
220ea 3/4" Guided Rods
1ea 6', 3ea 4', 2ea 2' Pony Rods
Pump Description:
2" x 1-1/4" x 8' x 12' RHAC

Pumping Unit:	_____	Gear Sheave:	_____
API Designation:	_____	Stroke Length:	_____
Samson Post SN:	_____	Gear Ratio:	_____
Gear Box SN:	_____	SPM:	_____
Structural Unbalance:	_____	Horse Power:	_____
Power:	_____	Volts:	_____
Power SN:	_____	Amps:	_____
Sheave Size:	_____	Belts:	_____

[illegible]

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
FARMINGTON DISTRICT OFFICE
6251 COLLEGE BLVD.
FARMINGTON, NEW MEXICO 87402

AFMSS 2 Sundry ID 2812484

Attachment to notice of Intention to Abandon

Well: Rudman Federal 1

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
2. The following modifications to your plugging program are to be made:
 - a. Modify the Plug 1 TOC to 5145' to account for the BLM geologist's pick for the Gallup.
 - b. Modify the TOC for Plug 3 to 3210' and the BOC to 3360' to account for the BLM geologist's pick for the Cliff House.
 - c. Modify the TOC for Plug 4 to 1320' and the BOC to 1820' to account for the BLM geologist's pick for the Cliff House.
 - d. Make Plug 5 an inside/ outside plug per the well schematic and cover the Ojo Alamo completely. Place the CICR for Plug 5 at 1150' with the squeeze holes at 1200' and the TOC at 825' to account for the BLM geologist's Kirtland and Ojo Alamo tops.
3. Farmington Office is to be notified at least 24 hours before the plugging operations commence at (505) 564-7750.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.

K. Rennick 09/19/2024

**GENERAL REQUIREMENTS FOR
PERMANENT ABANDONMENT OF WELLS ON FEDERAL AND INDIAN LEASES
FARMINGTON FIELD OFFICE**

1.0 The approved plugging plans may contain variances from the following minimum general requirements.

1.1 Modification of the approved plugging procedure is allowed only with the prior approval of the Authorized Officer, Farmington Field Office.

1.2 Requirements may be added to address specific well conditions.

2.0 Materials used must be accurately measured. (densometer/scales)

3.0 A tank or lined pit must be used for containment of any fluids from the wellbore during plugging operations and all pits are to be fenced with woven wire. These pits will be fenced on three sides and once the rig leaves location, the fourth side will be fenced.

3.1 Pits are not to be used for disposal of any hydrocarbons. If hydrocarbons are present in the pit, the fluids must be removed prior to filling in.

4.0 All cement plugs are to be placed through a work string. Cement may be bull-headed down the casing with prior approval. Cement caps on top of bridge plugs or cement retainers may be placed by dump bailer.

4.1 The cement shall be as specified in the approved plugging plan.

4.2 All cement plugs placed inside casing shall have sufficient volume to fill a minimum of 100' of the casing, or annular void(s) between casings, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.

4.3 Surface plugs may be no less than 50' in length.

4.4 All cement plugs placed to fill annular void(s) between casing and the formation shall be of sufficient volume to fill a minimum of 100' of the annular space plus 100% excess, calculated using the bit size, or 100' of annular capacity, determined from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.

4.5 All cement plugs placed to fill an open hole shall be of sufficient volume to fill a minimum of 100' of hole, as calculated from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug. In the absence of a caliper log, an excess of 100% shall be required.

4.6 A cement bond log or other accepted cement evaluation tool is required to be run if one had not been previously ran or cement did not circulate to surface during the original casing cementing job or subsequent cementing jobs.

5.0 All cement plugs spotted across, or above, any exposed zone(s), when; the wellbore is not full of fluid or the fluid level will not remain static, and in the case of lost circulation or partial returns during cement placement, shall be tested by tagging with the work string.

- 5.1 The top of any cement plug verified by tagging must be at or above the depth specified in the approved plan, without regard to any excess.
- 5.2 Testing will not be required for any cement plug that is mechanically contained by use of a bridge plug and/or cement retainer, if casing integrity has been established.
- 5.3 Any cement plug which is the only isolating medium, for a fresh water interval or a zone containing a prospectively valuable deposit of minerals, shall be tested by tagging.
- 5.4 If perforations are required below the surface casing shoe, a 30 minute minimum wait time will be required to determine if gas and/or water flows are present. If flow is present, the well will be shut-in for a minimum of one hour and the pressure recorded. Short or long term venting may be necessary to evacuate trapped gas. **If only a water flow occurs with no associated gas, shut well in and record the pressures. Contact the Engineer as it may be necessary to change the cement weight and additives.**

6.0 Before setting any cement plugs the hole needs to be rolled. All wells are to be controlled by means of a fluid that is to be of a weight and consistency necessary to stabilize the wellbore. This fluid shall be left in place as filler between all plugs.

- 6.1 Drilling mud may be used as the wellbore fluid in open hole plugging operations.
- 6.2 The wellbore fluid used in cased holes shall be of sufficient weight to balance known pore pressures in all exposed formations.

7.0 A blowout preventer and related equipment (BOPE) shall be installed and tested prior to working in a wellbore with any exposed zone(s); (1) that are over pressured, (2) where the pressures are unknown, or (3) known to contain H₂S.

8.0 Within 30 days after plugging work is completed, file a Sundry Notice, Subsequent Report of Abandonment (Form 3160-5), through the Automated Fluid Minerals Support System (AFMSS) with the Field Manager, Bureau of Land Management, 6251 College Blvd., Suite A, Farmington, NM 87402. The report should show the manner in which the plugging work was carried out, the extent, by depth(s), of cement plugs placed, and the size and location, by depth(s), of casing left in the well. Show date well was plugged.

9.0 All permanently abandoned wells are to be marked with a permanent monument as specified in 43 CFR 3162.6(d). Unless otherwise approved.

10.0 If this well is located in a Specially Designated Area (SDA), compliance with the appropriate seasonal closure requirements will be necessary.

All of the above are minimum requirements. Failure to comply with the above conditions of approval may result in an assessment for noncompliance and/or a Shut-in Order being issued pursuant to 43 CFR 3163.1. You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to administrative review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

BLM - FFO - Geologic Report

Well No.	Rudman Federal No 1	Surf. Loc.	1850	Date Completed	9/16/2024	
Lease No.	NMSF078521	Lot 3	Sec	FNL	790	FWL
		County	San Juan	27	T25N	R9W
				State	New Mexico	

Operator:	Epic Energy					
TVD	6527	PBTD	5830	Formation:	Bisti	
Elevation	GL		6570	Elevation	Est. KB	6582 (Estimated)

Geologic Formations	Est. tops	Subsea Elev.	Remarks
Nacimiento Fm.	Surface		Surface /fresh water sands
Ojo Alamo Ss	925	5657	Fresh water aquifer
Kirtland Fm.	1150	5432	
Fruitland Fm.	1420	5162	Coal/gas/possible water
Pictured Cliffs	1770	4812	Possible gas/water
Lewis Shale (Main)	1860	4722	Source rock
Huerfanito Bentonite	2110	4472	Reference bed
Chacra (upper)	2585	3997	Possible gas/water
Lewis Shale Stringer	2830	3752	Source rock
Chacra (lower)	3040	3542	Possible gas/water
Cliff House Ss	3310	3272	Possible gas/water
Menefee Fm.	3420	3162	Coal/water/possible gas
Point Lookout Fm.	4150	2432	Possible gas/water
Mancos Shale	4450	2132	Source rock
Gallup	5245	1337	Oil & gas

Remarks:Reference Well:

-Vertical wellbore, all formation depths are TVD from KB at the wellhead.

-BSC: Behind Surface Casing

-Modify the Plug 1 TOC to 5145' to account for the BLM geologist's pick for the Gallup.

-Modify the TOC for Plug 3 to 3210' and the BOC to 3360' to account for the BLM geologist's pick for the Cliff House.

-Modify the TOC for Plug 4 to 1320' and the BOC to 1820' to account for the BLM geologist's pick for the Pictured Cliffs and the Fruitland.

-Make Plug 5 an inside/outside plug per the well schematic and cover the Ojo Alamo completely. Place the CICR for Plug 5 at 1150' with the squeeze holes at 1200' and the TOC at 825' to account for the BLM geologist's Kirtland and Ojo Alamo tops.

#1
 US Well No. 30-045-05235
 Sec 27 T 25N R 9W
 San Juan County, New Mexico
 (KR Edit 09/18/2024)

Prepared by: Walter Gage

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
Standard Plugging Conditions



This document provides OCD's general plugging conditions of approval. It should be noted that the list below may not cover special plugging programs in unique and unusual cases, and OCD expressly reserves the right to impose additional requirements to the extent dictated by project conditions. The OCD also reserves the right to approve deviations from the below conditions if field conditions warrant a change. A C-103F NOI to P&A must be approved prior to plugging operations. Failure to comply with the conditions attached to a plugging approval may result in a violation of 19.15.5.11 NMAC, which may result in enforcement actions, including but not limited to penalties and a requirement that the well be re-plugged as necessary.

1. Notify OCD office at least 24 hours before beginning work and seek prior approval to implementing any changes to the C-103 NOI to PA.
 - North Contact, Monica Kuehling, 505-320-0243, monica.kuehling@emnrd.nm.gov
 - South Contact, Gilbert Cordero, 575-626-0830, gilbert.cordero@emnrd.nm.gov
2. A Cement Bond Log is required to ensure strata isolation of producing formations, protection of water and correlative rights. A CBL must be run or be on file that can be used to properly evaluate the cement behind the casing.

Note: Logs must be submitted to OCD via OCD permitting. A copy of the log may be emailed to OCD inspector for faster review times, but emailing does not relieve the operators obligation to submit through OCD permitting.

3. Once Plugging operations have commenced, the rig must not rig down until the well is fully plugged without OCD approval. If gap in plugging operations exceeds 30 days, the Operator must file a subsequent sundry of work performed and revised NOI for approval on work remaining. At no time shall the rig be removed from location if it will result in waste or contamination of fresh water.
4. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
5. Fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
 - North, water or mud laden fluids
 - South, mud laden fluids
6. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to an OCD permitted disposal facility.
7. Class of cement shall be used in accordance with the below table for depth allowed.

Class	TVD Lower Limit (feet)
Class A/B	6,000
Class I/II	6,000
Class C or III	6,000
Class G and H	8,000
Class D	10,000

Class E	14,000
Class F	16,000

8. After cutting the well head any "top off cement jobs" must remain static for 30 minutes. Any gas bubbles or flow during this 30 minutes shall be reported to the OCD for approval of next steps.
9. Trucking companies being used to haul oilfield waste fluids (Commercial or Private) to a disposal facility shall have an approved OCD C-133 permit.
 - A copy of this permit shall be available in each truck used to haul waste products.
 - It is the responsibility of the Operator and Contractor to verify that this permit is in place prior to performing work.
 - Drivers shall be able to produce a copy upon request of an OCD Compliance Officer.
10. Filing a [C-103] Sub. Plugging (C-103P) will serve as notification that the well has been plugged.
11. A [C-103] Sub. Release After P&A (C-103Q) shall be filed no later than a year after plugging and a site inspection by OCD Compliance officer to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to meet OCD standards before bonding can be released.
12. Produced water or brine-based fluids **may not** be used during any part of plugging operations without **prior OCD approval**.
13. Cementing;
 - All cement plugs will be neat cement and a minimum of 100' in length. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
 - If cement does not exist between or behind the casing strings at recommended formation depths, the casing perforations will be shot at 50' below the formation top and the cement retainer shall be set no more than 50' from the perforations.
 - WOC (Wait on Cement) time will be:
 - 4 hours for accelerated (calcium chloride) cement.
 - 6 hours on regular cement.
 - Operator must tag all cement plugs unless it meets the below condition.
 - The operator has a passing pressure test for the casing annulus and the plug is only an inside plug.
 - If perforations are made operator must tag all plugs using the work string to tag unless given approval to tag with wireline by the correct contact from COA #1 of this document.
 - This includes plugs pumped underneath a cement retainer to ensure retainer seats properly after cement is pumped.
 - Cement can only be bull-headed with specific prior approval.
 - Squeeze pressures are not to exceed the exposed formations frac gradient or the burst pressure of the casing.
14. A cement plug is required to be set from 50' below to 50' above (straddling) formation tops, casing shoes, casing stubs, any attempted casing cut offs, anywhere the casing is perforated, DV tools.
 - Perforation/Formation top plug. (When there is less than 100ft between the top perforation to the formation top.) These plugs are required to be started no greater than

50ft from the top perforation. However, the plug should be set below the formation top or as close to the formation top as possible for the maximum isolation between the formations. The plug is required to be a 100ft cement plug plus excess.

- Perforation Plug when a formation top is not included. These plugs are required to be started within 50ft of the top perforation. The plug is required to be a 100ft cement plug plus excess.
- Cement caps on top of bridge plugs or cement retainers for perforation plugs, that are not straddling a formation top, may be set using a bailer with a minimum of 35' of cement in lieu of the 100' plug. The bridge plug or retainer must be set within 50ft of the perforations.
- Perforations are required below the surface casing shoe if cement does not exist behind the casing, a 30-minute minimum wait time will be required immediately after perforating to determine if gas and/or water flows are present. If flow is present, the well will be shut-in for a minimum of one hour and the pressure recorded. If gas is detected contact the OCD office for directions.

15. No more than 3000 feet is allowed between cement plugs in cased hole and no more than 2000 feet is allowed in open hole.

16. Formation Tops to be isolated with cement plugs, but not limited to are:

- Northwest See Figure A
- South (Artesia) See Figure B
- Potash See Figure C
 - In the R-111-P (Or as subsequently revised) Area a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, woe 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
- South (Hobbs) See Figure D1 and D2
- Areas not provided above will need to be reviewed with the OCD on a case by case basis.

17. Markers

- Dry hole marker requirements 19.15.25.10.
The operator shall mark the exact location of plugged and abandoned wells with a steel marker not less than four inches in diameter set in cement and extending at least four feet above mean ground level. The marker must include the below information:
 1. Operator name
 2. Lease name and well number
 3. API number
 4. Unit letter
 5. Section, Township and Range
- AGRICULTURE (Below grade markers)
In Agricultural areas a request can be made for a below ground marker. For a below ground marker the operator must file their request on a C-103 notice of intent, and it must include the following;
 - A) Aerial photo showing the agricultural area
 - B) Request from the landowner for the below ground marker.

C) Subsequent plugging report for a well using a below ground marker must have an updated C-102 signed by a certified surveyor for SHL.

Note: A below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to OCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to OCD. OCD requires a current survey to verify the location of the below ground marker, however OCD will accept a GPS coordinate that were taken with a GPS that has an accuracy of within 15 feet.

18. If work has not commenced within 1 year of the approval of this procedure, the approval is automatically expired. After 1 year a new [C-103] NOI Plugging (C-103F) must be submitted and approved prior to work.

Figure A

North Formations to be isolated with cement plugs are:

- San Jose
- Nacimiento
- Ojo Alamo
- Kirtland
- Fruitland
- Picture Cliffs
- Chacra (if below the Chacra Line)
- Mesa Verde Group
- Mancos
- Gallup
- Basin Dakota (plugged at the top of the Graneros)
- Deeper formations will be reviewed on a case-by-case basis

Figure B

South (Artesia) Formations to be isolated with cement plugs are:

- Fusselman
- Montoya
- Devonian
- Morrow
- Strawn
- Atoka
- Permo-Penn
- Wolfcamp
- Bone Springs
- Delaware , in certain areas where the Delaware is subdivided into;
 - 1. Bell Canyon
 - 2. Cherry Canyon
 - 3. Brushy Canyon
- Any salt sections
- Abo
- Yeso
- Glorieta
- San Andres
- Greyburg
- Queen
- Yates

Figure C

Potash Area R-111-P

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All
except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23.
Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec
10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec
24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32
Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec
23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit
A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P.
Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P.
Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec
23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit

A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit

C,D,E,F,K,L,M,N. Sec 25

Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit

A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33

Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit

A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec

33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P.

Sec 16 Unit

I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec

34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11.

Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O, P. Sec 10 Unit B – G, K – N. Sec

35 Unit E – P. Sec 36 Unit E, K, L, M, N.

T 25S – R 31E

Sec 1 Unit C, D, E, F. Sec 2 Unit A – H.

Figure D1 and D2

South (Hobbs) Formations to be isolated with cement plugs are:

The plugging requirements in the Hobbs Area are based on the well location within specific areas of the Area (See Figure D1). The Formations in the Hobbs Area to be isolated with cement plugs are (see Figure D2)

Figure D1 Map




Figure D2 Formation Table

100' Plug to isolate upper and lower fresh water zones (typically 250' to 350')						
Northwest Shelf	Captan Reef Area	Transition Zone	San Simon Channel	South Vacuum Structure	Delaware Basin	Central Basin Platform
Granit Wash (Detrital basement material and fractured pre-Cambrian basement rock)	Siluro-Devonian	Morrow	Siluro-Devonian	Ellenburger	Siluro-Devonian	Granit Wash (Detrital basement material, fractured pre-Cambrian basement rock and fracture Mafic Volcanic intrusives).
Montoya	Mississippian	Atoka	Morrow	McKee	Morrow	Ellenburger
Fusselman	Morrow	Strawn	Wolfcamp	Siluro-Devonian	Atoka	Connell
Woodford	Atoka	Cisco	Abo Reef	Woodford	Strawn	Waddell
Siluro-Devonian	Strawn	Pennsylvanian	Bone Spring	Mississippian	Pennsylvanian	McKee
Chester	Pennsylvanian	Wolfcamp	Delaware	Barnett Shale	Lower Wolfcamp	Simpson Group
Austin	Wolfcamp	Bone Spring	San Andres	Morrow	Upper Wolfcamp	Montoya
Mississippian	Abo Reef, if present	Delaware	Queen	Atoka	Wolfcamp	Fusselman
Morrow	Abo, if present	San Andres	Yates	Strawn	Third Bone Spring Sand (Top of Wolfbone)	Silurian
Atoka	Queen, if present	Grayburg-San Andres	Base of Salt	Canyon	First Bone Spring Sand (Top of Lower Bone Spring)	Devonian
Lower Pennsylvanian	Bone Spring	Queen	Rustler	Pennsylvanian	Bone Spring	Strawn
Cisco-Canyon	Delaware	Seven Rivers		Blinbry	Brushy Canyon	Pennsylvanian
Pennsylvanian	Base Capitan Reef	Yates		Bone Spring	Delaware (Base of Salt)	Wolfcamp
Bough	Seven Rivers	Base of Salt		San Andres	Rustler	Abo
Wolfcamp	Yates	Rustler		Queen		Abo Reef
Abo	Top Capitan Reef			Base of Salt		Drinkard
Abo Reef, if present	Base of Salt			Rustler		Tubb
Yeso (Township 15 South to Township 17 South)	Rustler					Blinbry
Drinkard or Lower Yeso (Township 15 South to Township 17 South)						Paddock
Tubb (Township 15 South to Township 17 South)						Glorieta
Blinbry (Township 15 South to Township 17 South)						San Andres
Paddock (Township 15 South to Township 17 South)						Grayburg
Glorieta						Grayburg-San Andres
San Andres						Queen
Queen (Township 15 South to Township 17 South)						Seven Rivers
Seven Rivers (Township 15 South to Township 17 South)						Yates
Yates (Township 15 South to Township 17 South)						Base of Salt
Base of Salt						Rustler
Rustler						

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 385157

CONDITIONS

Operator: EPIC ENERGY, L.L.C. 332 Road 3100 Aztec, NM 87410	OGRID: 372834
	Action Number: 385157
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
mkuehling	NMOCD agrees with BLM picks for formation tops - Extend Mancos plug to 4350 - Notify NMOCD 24 hours prior to moving on - Monitor string pressures daily report on subsequent - Submit all logs prior to subsequent	9/26/2024