Sundry Print Report 11/06/2024

DEVON

NMNM121489

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name	Well Number	US Well Number	Lease Number	Case Number	Operator
HOGNOSE VIPER	203H	3002552758	NMNM121489	NMNM121489	DEVON
HOGNOSE VIPER	702H	3002552764	NMNM121489	NMNM121489	DEVON
HOGNOSE VIPER	302H	3002552760	NMNM121489	NMNM121489	DEVON

NMNM121489

Notice of Intent

Sundry ID: 2817267

HOGNOSE VIPER

Type of Action: APD Change Type of Submission: Notice of Intent Date Sundry Submitted: 10/16/2024 Time Sundry Submitted: 09:51

3002552762

Date proposed operation will begin: 10/16/2024

602H

Procedure Description: Devon Energy Production Company L.P. respectfully requests the following changes to the approved APD: Offline cementing. All wells on Hognose Viper 23 Wellpad 3 with intermediate strings set above the Wolfcamp formation. Please see attached variance request.

NOI Attachments

Procedure Description

Offline_Cementing___Variance_Request_20241016094825.pdf

Conditions of Approval

Specialist Review

Hognose_Viper_Fed_Com_Sundry_ID_2817267_20241106080529.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: REBECCA DEAL Signed on: OCT 16, 2024 09:48 AM

Name: DEVON ENERGY PRODUCTION COMPANY LP

Title: Regulatory Professional

Street Address: 333 W SHERIDAN AVE

City: OKLAHOMA CITY State: OK

Phone: (405) 228-8429

Email address: REBECCA.DEAL@DVN.COM

Field

Representative Name:

Street Address:

City: State: Zip

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO **BLM POC Title**: Petroleum Engineer

BLM POC Phone: 5759885402 BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved **Disposition Date:** 11/06/2024

Signature: Long Vo

Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR

	FORM APPROVED OMB No. 1004-0137 Expires: October 31, 202
Lagge Comict Ma	

	Expires: October 31, 202
ease Serial No	

DEF	AKTIMENT OF THE INT	LKIUK			p
BUR	EAU OF LAND MANAG	EMENT		5. Lease Serial No.	MULTIPLE
	IOTICES AND REPORT			6. If Indian, Allottee or Tribe	Name
	form for proposals to d Use Form 3160-3 (APD)			MULTIPLE	
	TRIPLICATE - Other instruction	ns on page 2		7. If Unit of CA/Agreement, MULTIPLE	Name and/or No.
1. Type of Well Gas V	Well Other			8. Well Name and No.	
2. Name of Operator DEVON ENERG	GY PRODUCTION COMPANY	LP		9. API Well No. MULTIPLE	
3a. Address 333 WEST SHERIDAN	AVE, OKLAHOMA CITY, 3b. 1	Phone No. <i>(includ</i> 5) 235-3611		10. Field and Pool or Explora	
4. Location of Well (Footage, Sec., T., FMULTIPLE	R.,M., or Survey Description)			11. Country or Parish, State MULTIPLE	
12. CHE	CK THE APPROPRIATE BOX(I	ES) TO INDICAT	E NATURE O	F NOTICE, REPORT OR OT	HER DATA
TYPE OF SUBMISSION			TYPE	OF ACTION	
✓ Notice of Intent	Acidize Alter Casing	Deepen Hydraulic F	racturing	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity
Subsequent Report	Casing Repair Change Plans	New Constr	=	Recomplete Temporarily Abandon	Other
Final Abandonment Notice	Convert to Injection	Plug Back		Water Disposal	
is ready for final inspection.) Devon Energy Production Cor Hognose Viper 23 Wellpad 3 v		· ·	•		•
14. I hereby certify that the foregoing is REBECCA DEAL / Ph: (405) 228-8	,	(Typed) Title	Regulatory F	Professional	
Signature (Electronic Submission	on)	Date	Date 10/16/2024		
	THE SPACE FO	OR FEDERA	L OR STAT	TE OFICE USE	
Approved by					
LONG VO / Ph: (575) 988-5402 / A	Approved		Petrole Title	um Engineer	11/06/2024 Date
Conditions of approval, if any, are attaccertify that the applicant holds legal or ewhich would entitle the applicant to con	equitable title to those rights in the		Office CARL	SBAD	
Title 18 U.S.C Section 1001 and Title 4	3 U.S.C Section 1212, make it a c	erime for any pers	on knowingly	and willfully to make to any d	lepartment or agency of the United States

any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Batch Well Data

HOGNOSE VIPER FED COM 203H, US Well Number: 3002552758, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

HOGNOSE VIPER FED COM 302H, US Well Number: 3002552760, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

HOGNOSE VIPER FED COM 602H, US Well Number: 3002552762, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

HOGNOSE VIPER FED COM 702H, US Well Number: 3002552764, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

Offline Cementing

Variance Request

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements.

BUREAU OF LAND MANAGEMENT

Well Name	Well Number	US Well Number	Lease Number	Case Number	Operator
HOGNOSE VIPER	203H	3002552758	NMNM121489	NMNM121489	DEVON
HOGNOSE VIPER	702H	3002552764	NMNM121489	NMNM121489	DEVON
HOGNOSE VIPER	302H	3002552760	NMNM121489	NMNM121489	DEVON
HOGNOSE VIPER	602H	3002552762	NMNM121489	NMNM121489	DEVON

Notice of Intent

Sundry ID: 2817267

Type of Submission: Notice of Intent Type of Action: APD Change Date Sundry Submitted: 10/16/2024 Time Sundry Submitted: 09:51

Date proposed operation will begin: 10/16/2024

Procedure Description: Devon Energy Production Company L.P. respectfully requests the following changes to the approved APD: Offline cementing. All wells on Hognose Viper 23 Wellpad 3 with intermediate strings set above the Wolfcamp formation. Please see attached variance request.

> **LONG** VO

Digitally signed by LONG VO Date: 2024.11.06 09:04:30 -06'00'

Sundry Print Report 11/06/2024

NOI Attachments

Procedure Description

Offline_Cementing_ Variance_Request_20241016094825.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: REBECCA DEAL Signed on: OCT 16, 2024 09:48 AM

Name: DEVON ENERGY PRODUCTION COMPANY LP

Title: Regulatory Professional

Street Address: 333 W SHERIDAN AVE

City: OKLAHOMA CITY State: OK

Phone: (405) 228-8429

Email address: REBECCA.DEAL@DVN.COM

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

All Previous COAs Still Apply. Variance request procedure is approved as written, please see below general conditions for variance.

Offline Cementing

Operator has been (**Approved**) to pump the proposed cement program offline in the **Intermediate(s) interval**.

Offline cementing should commence within 24 hours of landing the casing for the interval.

Notify the BLM 4hrs prior to cementing offline at Lea County: 575-689-5981.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)
 - Eddy County
 EMAIL or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
 BLM_NM_CFO_DrillingNotifications@BLM.GOV (575) 361-2822
 - ✓ Lea CountyCall the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575) 689-5981
- 1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per **43 CFR part 3170 Subpart 3172** as soon as 2nd Rig is rigged up on well.
- 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
- 3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a

digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

- 1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
- 2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
- 5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
- 6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
- 7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in 43 CFR part 3170 Subpart 3172 and API STD 53 Sec. 5.3.
- 2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
- 3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172.6(b)(9) must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- 5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after

installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR part 3170 Subpart 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per 43 CFR

part 3170 Subpart 3172.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

Form 3160-5 (June 2019)

UNITED STATES

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

	Expires: October 31,
ease Serial No.	

DEPARTMENT OF THE	INTERIOR		Aprics. October 31, 2021
BUREAU OF LAND MAN	JAGEMENT	5. Lease Serial No.	MULTIPLE
SUNDRY NOTICES AND REPO		6. If Indian, Allottee or Trib	e Name
Do not use this form for proposals abandoned well. Use Form 3160-3 (A		I MILLIDIE	
SUBMIT IN TRIPLICATE - Other instr	<u> </u>	7. If Unit of CA/Agreement	, Name and/or No.
1. Type of Well	oonene en page z	MULTIPLE	
Oil Well Gas Well Other		8. Well Name and No.	
2. Name of Operator DEVON ENERGY PRODUCTION COMP	PANY LP	9. API Well No. MULTIPLE	E
3a. Address 333 WEST SHERIDAN AVE, OKLAHOMA CITY,		(code) 10. Field and Pool or Explo	ratory Area
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description, MULTIPLE)	11. Country or Parish, State MULTIPLE	
12. CHECK THE APPROPRIATE B	OX(ES) TO INDICATE NAT	URE OF NOTICE, REPORT OR O	THER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
Notice of Intent	Deepen	Production (Start/Resumo	
Alter Casing	Hydraulic Fracturi		Well Integrity
Subsequent Report Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Abandon	Other
Final Abandonment Notice Convert to Injection	= -	Water Disposal	
Hognose Viper 23 Wellpad 3 with intermediate strings s	et above the Wolfcamp for	nation. Please see attached vari	ance request.
14. I hereby certify that the foregoing is true and correct. Name (<i>Pr</i> REBECCA DEAL / Ph: (405) 228-8429		atory Professional	
(Electronic Submission)		10/16	5/2024
THE SPACE	E FOR FEDERAL OR	STATE OFICE USE	
Approved by			
	Title		Date
Conditions of approval, if any, are attached. Approval of this notice certify that the applicant holds legal or equitable title to those rights which would entitle the applicant to conduct operations thereon.			
Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make			department or agency of the United States

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Batch Well Data

HOGNOSE VIPER FED COM 203H, US Well Number: 3002552758, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

HOGNOSE VIPER FED COM 302H, US Well Number: 3002552760, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

HOGNOSE VIPER FED COM 602H, US Well Number: 3002552762, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

HOGNOSE VIPER FED COM 702H, US Well Number: 3002552764, Case Number: NMNM121489, Lease Number: NMNM121489, Operator: DEVON ENERGY PRODUCTION COMPANY LP

Offline Cementing

Variance Request

Devon Energy requests to offline cement on intermediate strings that are set in formations shallower than the Wolfcamp. Prior to commencing offline cementing operations, the well will be monitored for any abnormal pressures and confirmed to be static. A dual manifold system (equipped with chokes) for the returns will also be utilized as a redundancy. All equipment used for offline cementing will have a minimum 5M rating to match intermediate sections' 5M BOPE requirements.

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 400081

CONDITIONS

Operator:	OGRID:
DEVON ENERGY PRODUCTION COMPANY, LP	6137
333 West Sheridan Ave.	Action Number:
Oklahoma City, OK 73102	400081
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created	Condition	Condition Date
Ву		
pkautz	If cement is not circulated to surface during cementing operations, a Cement Bond Log (CBL) is required.	12/19/2024
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing.	12/19/2024