

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Report

Well Name: SALADO DRAW 16/9 Well Location: T26S / R33E / SEC 16 / County or Parish/State: /

B2PA FED COM SESE /

Well Number: 2H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM000127A Unit or CA Name: Unit or CA Number:

US Well Number: 3002550507 Well Status: Drilling Well Operator: MEWBOURNE OIL

COMPANY

Subsequent Report

Sundry ID: 2709079

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 12/30/2022 Time Sundry Submitted: 02:26

Date Operation Actually Began: 12/02/2022

Actual Procedure: 12/02/22 Spud 17 1/2" hole. TD @ 1150'. Ran 1135' of 13 3/8" 54.5# J55 ST&C Csg. Par Five cmt w/550 sks Class C w/5% Salt, 2% Extender, 5.0 #/sk Kolseal, 5.0#/sk Obsidian pumice & 1/4#/sk Cellophane. (yd @ 2.31 cuft/sk @ 12.5 PPG). Tail w/200 sks Class C w/2% CaCl2 (yd @ 1.34 cuft/sk @ 14.8 PPG). Displaced w/168 bbls of BW. Plug down @ 1:30 A.M. 12/04/22. Circ 294 sks of cmt to the cellar. Tested BOPE to 5000# & Annular to 3500#. At 12:30 A.M. 12/05/22, tested csg to 1500# for 30 mins, held OK. FIT to 10.5 PPG EMW. Drilled out with 12 1/4" bit. 12/07/22 TD'ed 12 1/4" hole @ 4900'. Ran 4885' 9 5/8" 40# J55 LT&C & 36# J55 LT&C Csg. Par Five cmt w/950 sks 35:65 Class C Poz w/5% Salt, 5% Enhancer, 4% Gel, 1% Extender, 3#/sk Kolseal, 0.4#/sk Defoamer, & 1/8#/sk Cellophane (yd @ 2.17 cuft/sk @ 12.5 PPG). Tail w/200 sks Class C Neat (yd @ 1.32 cuft/sk @ 14.8 PPG). Displaced w/370 bbls of FW. Plug down @ 4:45 P.M. 12/07/22. Circ 181 sks of cmt to the pit. Set Vault csg hanger through BOP w/150k#. At 5:30 A.M. 12/08/22, tested csg to 1500# for 30 mins, held OK. FIT to 10.0 PPG EMW. Drilled out at 8 3/4" bit. 12/12/22 TD'ed 8 3/4" hole @ 10105. Ran 10021' of 7" 29# HPP110 BT&C Csg. Par Five cmt w/500 sks PVL w/1.2% Retarder, 0.3% Fluid loss, 3#/sk Kolseal, 0.8 #/sk Defoamer, 32% Potter beads & 10% Strength enhancer (yd @ 3.05 cuft/sk @ 9.8 PPG). Tail w/400 sks Class H w/0.5% Fluid loss & 0.3% Retarder (yd @ 1.18 cuft/sk @ 15.6 PPG). Displaced w/369 bbls of OBM. Plug down @ 3:00 P.M. 12/12/22. Circ 90 sks of cmt to the pit. Set Vault csg hanger through BOP w/173k#. At 9:45 A.M. 12/13/22, tested csg to 1500# for 30 mins, held OK. Fit to 10.5 PPG EMW. Drilled out at 6 1/8" bit. 12/26/22 TD'ed 6 1/8" hole @ 20855' MD. Ran 20855' 4 1/2" 13.5#HCP110 CDC HTQ Csg from 9795' (top of liner) to 20855'. Par Five cmt w/750 sks 35:65 Poz Class H w/10% Strength enhancer, 4% Gel, 0.6% Retarder, 0.5% Fluid loss & 10#/sk Obsidian pumice (1.85 ft³/sk @ 13.5 ppg). Pumped 3 bbls sugar FW. Drop dart. Pumped 20 bbls of sugar FW & 241 bbls of sugar BW (calculated volume). Lift pressure 1400#@ 3 BPM. Plug down @ 11:00 P.M. 12/28/22. Bumped plug w/1710#. Shift wet shoe sub w/2336# & pump additional 2 bbls sugar

Page 1 of 2

eived by <u>OCD: 1/10/2023 2:19:13 PM</u> Well Name: SALADO DRAW 16/9

B2PA FED COM

Well Location: T26S / R33E / SEC 16 /

SESE /

Well Number: 2H

Type of Well: OIL WELL

Allottee or Tribe Name:

County or Parish/State: /

Page 2 o

Lease Number: NMNM000127A

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002550507

Well Status: Drilling Well

Operator: MEWBOURNE OIL

COMPANY

BW. Set packer w/90k#. Sting out from liner hanger w/1800#on DP. Displaced 7" csg w/312 bbls of BW w/polymer sweep. Circ 167 sks of cmt off liner top. At 2:00 A.M. 12/29/22, tested liner top to 2500#for 30 mins, held OK. Rig released to walk @ 12:00 P.M. 12/29/22.

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JACKIE LATHAN Signed on: DEC 30, 2022 02:26 PM

Name: MEWBOURNE OIL COMPANY

Title: Regulatory

Street Address: PO Box 5270

City: Hobbs State: NM

Phone: (575) 393-5905

Email address: Jlathan@mewbourne.com

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: Jonathon W Shepard

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972

Disposition: Accepted

BLM POC Email Address: jshepard@blm.gov

Signature: Jonathon Shepard

Disposition Date: 01/05/2023

Page 2 of 2

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 174807

CONDITIONS

Operator:	OGRID:
MEWBOURNE OIL CO	14744
P.O. Box 5270	Action Number:
Hobbs, NM 88241	174807
	Action Type:
	[C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
sarah.clellar	i None	2/13/2025