

Well Name: MONEY GRAHAM FED COM	Well Location: T26S / R29E / SEC 32 / LOT 4 / 32.0007313 / -104.0005813	County or Parish/State: EDDY / NM
Well Number: 154H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM138607	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001553591	Well Status: Drilling Well	Operator: TAP ROCK OPERATING LLC

Subsequent Report

Sundry ID: 2735944

Type of Submission: Subsequent Report	Type of Action: Drilling Operations
Date Sundry Submitted: 06/15/2023	Time Sundry Submitted: 09:00
Date Operation Actually Began: 05/26/2023	

Actual Procedure: Well spud on 5/26/2023 at 08:30 5/26/2023: Drill 17.5 inch surface hole to 403 ft. 5/26/2023: Run 13.375 inch 54.5 lb J-55 surface casing to 388 ft. Pump 20 bbl water spacer, followed by 500 sks of 14.8 ppg tail cmt. Drop plug and displace with 53 bbls freshwater. 30 bbls of cement returned back to surface. EST TOC at 0 ft. Pressure test casing to 1500 PSI for 30 minutes, good test. 5/26/2023: Test BOPS. Drill 12.25 intermediate hole to 2859 ft. 5/29/2023: Run 9.625 inch 40 lb J-55 intermediate casing to 2844 ft. Pump 20 bbls water spacer, followed by 860 sks of 13.2 ppg lead cmt 210 sks of 14.8 ppg tail cmt. Drop plug and displace with 212 bbls of brine. 86 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test. 6/1/2023: Drill 8.75 inch production hole to 8436 ft then switch to 7.785 inch hole to 16340. 6/7/2023: Run 5.5 inch 20 lb P-110 production casing to 16325 ft MD. Pump 40 bbls water spacer, then 490 sks of 10.5 ppg lead cmt and 1375 sks of 13.2 tail cmt. Drop plug and displace with 20 bbls sugar water and 340 bbls fresh water. 0 bbls cement returned to surface. Est TOC at 102 ft. Surface Casing Details: Casing ran: 5/26/2023, Fluid Type Fresh Water, Hole 17.5 inch, Csg Size 13.375 inch, Weight 54.5 lbs, Grade J-55, Est TOC 0 ft, Depth set 388 ft, Cement 500 sacks, Yield 1.34 tail, Class C. Pressure test: 1500 PSI, Pressure Drop: 0. Intermediate Casing Details: Casing ran: 5/29/2023, Fluid Type diesel brine emulsion, Hole 12.5 inch to 2859, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 2844 ft, Cement 1070 sks, Yield 1.67 lead/1.34 tail, Class C, Pressure Held 1500 psi, Pres Drop 0. Production Casing details: Casing Date: 6/7/2023, Fluid Type oil based mud, Hole 8.75 inch to 8436 ft then 7.875 inch to 16340, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 16325 ft, EST TOC 102 ft, Cement 1865 sacks, yield 4.12 lead/1.53 tail, Class C. 6/6/2023: TD Reached at 16340 MD, 9087 ft TVD. Plug Back Measured depth at 16273 ft MD, 9086 ft TVD. Rig Release on 6/9/2023 at 03:00

Well Name: MONEY GRAHAM FED
COM

Well Location: T26S / R29E / SEC 32 /
LOT 4 / 32.0007313 / -104.0005813

County or Parish/State: EDDY /
NM

Well Number: 154H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM138607

Unit or CA Name:

Unit or CA Number:

US Well Number: 3001553591

Well Status: Drilling Well

Operator: TAP ROCK
OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JEFFREY TRLICA

Signed on: JUN 15, 2023 08:59 AM

Name: TAP ROCK OPERATING LLC

Title: Regulatory Analyst

Street Address: 523 PARK POINT DRIVE SUITE 200

City: GOLDEN

State: CO

Phone: (720) 772-5910

Email address: JTRLICA@TAPRK.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: JONATHON W SHEPARD

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972

BLM POC Email Address: jshepard@blm.gov

Disposition: Accepted

Disposition Date: 06/27/2023

Signature: Jonathon Shepard

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 233691

CONDITIONS

Operator: TAP ROCK OPERATING, LLC 523 Park Point Drive Golden, CO 80401	OGRID: 372043
	Action Number: 233691
	Action Type: [C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
jeffrey.harrison	Surface casing set 187' short of BLM COA and approved APD. If surface casing shoe at 388' is NOT 70' below the top of the Rustler formation, please submit a C-103A with an explanation for setting short.	5/2/2025
jeffrey.harrison	Pressure test results required for production string on subsequent sundry.	5/2/2025