

Sundry Print Repor

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: POKER LAKE UNIT 22 Well Location: T24S / R30E / SEC 22 /

NWNW / 32.20747 / -103.87544 DTD

County or Parish/State: EDDY /

Well Number: 181H Type of Well: CONVENTIONAL GAS

Allottee or Tribe Name:

WELL

**Unit or CA Number:** 

NMNM71016X

Lease Number: NMLC068431,

NMLC068905

**US Well Number: 3001549885 Operator: XTO PERMIAN OPERATING** 

LLC

# **Notice of Intent**

**Sundry ID: 2871285** 

Type of Submission: Notice of Intent Type of Action: APD Change

Date Sundry Submitted: 09/03/2025 **Time Sundry Submitted: 11:22** 

Date proposed operation will begin: 09/03/2025

Procedure Description: Effective Date: 2/1/23 XTO Permian Operating LLC respectfully requests to make the following changes for well file cleanup: BLM previously approved sundry Id # 2862993. XTO inadvertently left out the directional plan. Attachments: Updated directional plan. No new surface disturbance.

Unit or CA Name: POKER LAKE UNIT

# **NOI Attachments**

# **Procedure Description**

PLU\_22\_DTD\_181H\_Plan\_3\_Standard\_Report\_20250903112202.pdf

Page 1 of 2

eived by OCD: 9/5/2025 8:01:22 AM Well Name: POKER LAKE UNIT 22

DTD

Well Location: T24S / R30E / SEC 22 / NWNW / 32.20747 / -103.87544

County or Parish/State: Page 2 of

NM

Well Number: 181H

Type of Well: CONVENTIONAL GAS

**Allottee or Tribe Name:** 

Lease Number: NMLC068431,

NMLC068905

Unit or CA Name: POKER LAKE UNIT

**Unit or CA Number:** NMNM71016X

**US Well Number: 3001549885** 

**Operator: XTO PERMIAN OPERATING** 

LLC

# **Operator**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Signed on: SEP 03, 2025 11:22 AM **Operator Electronic Signature: LACEY GRANILLO** 

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 HOLIDAY HILL ROAD City: MIDLAND State: TX

Phone: (432) 894-0057

Email address: LACEY.GRANILLO@EXXONMOBIL.COM

# **Field**

**Representative Name:** 

**Street Address:** 

City:

State:

Zip:

Phone:

**Email address:** 

# **BLM Point of Contact**

**BLM POC Name: ZOTA M STEVENS BLM POC Title:** Petroleum Engineer

**BLM POC Phone:** 5752345998 BLM POC Email Address: ZSTEVENS@BLM.GOV

**Disposition:** Approved Disposition Date: 09/05/2025

Signature: Zota Stevens

Page 2 of 2

Form 3160-5 (June 2019)

# **UNITED STATES** DEI

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 202

PARTMENT OF THE INTERIOR	
EAU OF LAND MANAGEMENT	5. Lease Serial No.

BUR	EAU OF LAND MANAGEMEN	5. Lease Serial No. NMLC068431	
Do not use this t	NOTICES AND REPORTS ON form for proposals to drill or a Use Form 3160-3 (APD) for su	o re-enter an	
	TRIPLICATE - Other instructions on pa	7. If Unit of CA/Agreement, Name and/or No. POKER LAKE UNIT/MMNM71016X	
1. Type of Well Oil Well Gas V	Vell Other	8. Well Name and No. POKER LAKE UNIT 22 DTD/181H	
2. Name of Operator XTO PERMIAN	OPERATING LLC	9. API Well No. 3001549885	
3a. Address 6401 HOLIDAY HILL R	OAD BLDG 5, MIDLAND, 3b. Phone No. (432) 683-2	. (include area code) 10. Field and Pool or Exploratory Area WILDCAT G-06 S243026M; WC-15 G-06 S233036D/BONE SPRING	
4. Location of Well (Footage, Sec., T.,F SEC 22/T24S/R30E/NMP	R.,M., or Survey Description)	11. Country or Parish, State EDDY/NM	
12. CHE	CK THE APPROPRIATE BOX(ES) TO IN	DICATE NATURE OF NOTICE, REPORT OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION	
Notice of Intent  Subsequent Report	Casing Repair New	raulic Fracturing Reclamation Well Integrity V Construction Recomplete Other	
Final Abandonment Notice		g and Abandon Temporarily Abandon g Back Water Disposal	
the proposal is to deepen directional the Bond under which the work will completion of the involved operation completed. Final Abandonment Notis ready for final inspection.)  Effective Date: 2/1/23  XTO Permian Operating LLC of BLM previously approved summatty in advertently left out the Attachments: Updated direction	ally or recomplete horizontally, give subsurul be perfonned or provide the Bond No. on ons. If the operation results in a multiple contices must be filed only after all requirement respectfully requests to make the follow dry Id # 2862993.  directional plan.  In onal plan. No new surface disturbance.	including estimated starting date of any proposed work and approximate duration to face locations and measured and true vertical depths of all pertinent markers and zo file with BLM/BIA. Required subsequent reports must be filed within 30 days followed mpletion or recompletion in a new interval, a Form 3160-4 must be filed once testing including reclamation, have been completed and the operator has detennined that the interval of the cleanup:	ones. Attach owing ng has beer
14. I hereby certify that the foregoing is LACEY GRANILLO / Ph: (432) 894	true and correct. Name (Printed/Typed) 1-0057	Regulatory Analyst Title	
Signature (Electronic Submission	on)	Date 09/03/2025	

# THE SPACE FOR FEDERAL OR STATE OFICE USE

Approved by Petroleum Engineer 09/05/2025 ZOTA M STEVENS / Ph: (575) 234-5998 / Approved Title Date Conditions of approval, if any, are attached. Approval of this notice does not warrant or Office CARLSBAD certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

#### **GENERAL INSTRUCTIONS**

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

#### SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

#### **NOTICES**

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

(Form 3160-5, page 2)

# **Additional Information**

#### **Location of Well**

0. SHL: NWNW / 1106 FNL / 665 FWL / TWSP: 24S / RANGE: 30E / SECTION: 22 / LAT: 32.20747 / LONG: -103.87544 ( TVD: 0 feet, MD: 0 feet )
PPP: NENW / 500 FNL / 1650 FWL / TWSP: 24S / RANGE: 30E / SECTION: 22 / LAT: 32.209157 / LONG: -103.872253 ( TVD: 12171 feet, MD: 12521 feet )
PPP: SESW / 0 FNL / 1636 FWL / TWSP: 25S / RANGE: 30E / SECTION: 10 / LAT: 32.225034 / LONG: -103.872241 ( TVD: 12171 feet, MD: 15161 feet )
PPP: NENW / 100 FNL / 1650 FWL / TWSP: 24S / RANGE: 30E / SECTION: 3 / LAT: 32.210531 / LONG: -103.872252 ( TVD: 12171 feet, MD: 15161 feet )
BHL: LOT 4 / 50 FNL / 1650 FWL / TWSP: 24S / RANGE: 30E / SECTION: 3 / LAT: 32.253518 / LONG: -103.874707 ( TVD: 12171 feet, MD: 28065 feet )

# **ROC**

NX34, HP549, HP552 - Eddy County (NAD27 NME) (HP 549) - PLU 22 DTD - Plans PLU 22 DTD - 181H

OH

Plan: Plan 3

# **Standard Planning Report**

10 February, 2023

#### Planning Report

LMRKPROD3 Database:

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

PLU 22 DTD - 181H Well:

Wellbore: ОН Plan 3 Design:

Site

Design

**Local Co-ordinate Reference:** 

TVD Reference: MD Reference:

North Reference:

**Survey Calculation Method:** 

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549)

RKB30 @ 3431.0usft (H&P 549)

Grid

Minimum Curvature

Project NX34, HP549, HP552 - Eddy County (NAD27 NME)

Map System: US State Plane 1927 (Exact solution) NAD 1927 (NADCON CONUS)

Geo Datum:

New Mexico East 3001 Map Zone:

System Datum: Mean Sea Level

(HP 549) - PLU 22 DTD - Plans

Site Position: Northing: 439,453.20 usft Latitude: 32° 12' 26.439 N 641,685.30 usft Longitude: 103° 52' 30.880 W From: Мар Easting: Grid Convergence: **Position Uncertainty:** 0.0 usft Slot Radius: 13-3/16 " 0.24

Well PLU 22 DTD - 181H

32° 12' 26.445 N **Well Position** +N/-S 1.0 usft Northing: 439,454.20 usft Latitude: +E/-W 90.0 usft

Easting: 641,775.30 usft Longitude: 103° 52' 29.832 W **Position Uncertainty** 0.0 usft Wellhead Elevation: **Ground Level:** 3.401.0 usft

ОН Wellbore **Model Name** Declination Field Strength Magnetics Sample Date **Dip Angle** (°) (°) (nT) IGRF2020 9/28/2022 6.53 59.80 47,318.76206425

**Audit Notes:** Version: Phase: PLAN Tie On Depth: 0.0

Vertical Section: Depth From (TVD) +N/-S +E/-W Direction (usft) (usft) (usft) (°) 0.0 0.0 0.0 359.79

2/10/2023 **Plan Survey Tool Program** Date

Plan 3

**Depth From** Depth To (usft) (usft) Survey (Wellbore) **Tool Name** Remarks

0.0 27,375.2 Plan 3 (OH) XOMR2\_OWSG MWD+IFR1+ OWSG MWD + IFR1 + Multi-St

# **Planning Report**

LMRKPROD3 Database:

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

(HP 549) - PLU 22 DTD - Plans Site:

Well: PLU 22 DTD - 181H

Wellbore: ОН Design: Plan 3 Local Co-ordinate Reference:

**Survey Calculation Method:** 

TVD Reference: MD Reference:

North Reference:

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549)

RKB30 @ 3431.0usft (H&P 549)

Grid

n Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,844.1	12.88	72.96	1,838.7	21.1	68.9	2.00	2.00	0.00	72.96	
5,816.7	12.88	72.96	5,711.3	280.6	915.7	0.00	0.00	0.00	0.00	
6,460.8	0.00	0.00	6,350.0	301.7	984.7	2.00	-2.00	-11.33	-180.00	
10,360.6	0.00	0.00	10,249.8	301.7	984.7	0.00	0.00	0.00	0.00	KOP 181H Plan 3
11,485.6	90.00	359.79	10,966.0	1,017.9	982.0	8.00	8.00	-0.02	359.79	
11,685.6	90.00	359.79	10,966.0	1,217.9	981.3	0.00	0.00	0.00	0.00	FTP 181H v1
27,325.2	90.00	359.79	10,966.0	16,857.4	923.8	0.00	0.00	0.00	0.00	LTP 181H v1
27,375.2	90.00	359.79	10,966.0	16,907.4	923.6	0.00	0.00	0.00	0.00	BHL 181H v1

# **Planning Report**

Database: LMRKPROD3

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

Well: PLU 22 DTD - 181H

Wellbore: OH
Design: Plan 3

Local Co-ordinate Reference:

TVD Reference:

North Reference:

Survey Calculation Method:

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549) RKB30 @ 3431.0usft (H&P 549)

Grid

anned Survey									
Measured			Vertical			Vertical	Dogleg	Build	Turn
Depth	Inclination	Azimuth	Depth	+N/-S	+E/-W	Section	Rate	Rate	Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	E00.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.00	0.00	500.0						0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	2.00	72.96	1,300.0	0.5	1.7	0.5	2.00	2.00	0.00
1,400.0	4.00	72.96	1,399.8	2.0	6.7	2.0	2.00	2.00	0.00
1,500.0	6.00	72.96	1,499.5	4.6	15.0	4.5	2.00	2.00	0.00
1,600.0	8.00	72.96	1,598.7	8.2	26.7	8.1	2.00	2.00	0.00
1,700.0	10.00	72.96	1,697.5	12.8	41.6	12.6	2.00	2.00	0.00
1,800.0	12.00	72.96	1,795.6	18.3	59.9	18.1	2.00	2.00	0.00
1,844.1	12.88	72.96	1,795.0	21.1	68.9	20.9	2.00	2.00	0.00
			1,030.7					2.00	0.00
1,900.0	12.88	72.96	1,893.2	24.8	80.9	24.5	0.00	0.00	0.00
2,000.0	12.88	72.96	1,990.7	31.3	102.2	30.9	0.00	0.00	0.00
2,100.0	12.88	72.96	2,088.1	37.8	123.5	37.4	0.00	0.00	0.00
								0.00	
2,200.0	12.88	72.96	2,185.6	44.4	144.8	43.8	0.00		0.00
2,300.0	12.88	72.96	2,283.1	50.9	166.1	50.3	0.00	0.00	0.00
2,400.0	12.88	72.96	2,380.6	57.4	187.4	56.7	0.00	0.00	0.00
2,500.0	12.88	72.96	2,478.1	64.0	208.7	63.2	0.00	0.00	0.00
2,600.0	12.88	72.96	2,575.6	70.5	230.1	69.6	0.00	0.00	0.00
2,700.0	12.88	72.96	2,673.0	77.0	251.4	76.1	0.00	0.00	0.00
2,800.0	12.88	72.96	2,770.5	83.6	272.7	82.6	0.00	0.00	0.00
			2,770.5					0.00	
2,900.0	12.88	72.96	2,868.0	90.1	294.0	89.0	0.00	0.00	0.00
3,000.0	12.88	72.96	2,965.5	96.6	315.3	95.5	0.00	0.00	0.00
3,100.0	12.88	72.96	3,063.0	103.1	336.6	101.9	0.00	0.00	0.00
3,200.0	12.88	72.96	3,160.5	109.7	358.0	108.4	0.00	0.00	0.00
3,300.0	12.88	72.96	3,160.5	116.2	379.3	114.8	0.00	0.00	0.00
3,400.0	12.88	72.96	3,355.4	122.7	400.6	121.3	0.00	0.00	0.00
3,500.0	12.88	72.96	3,452.9	129.3	421.9	127.7	0.00	0.00	0.00
3,600.0	12.88	72.96	3,550.4	135.8	443.2	134.2	0.00	0.00	0.00
3,700.0	12.88	72.96	3,647.9	142.3	464.5	140.6	0.00	0.00	0.00
3,800.0	12.88	72.96	3,745.4	148.9	485.9	140.0	0.00	0.00	0.00
3,900.0	12.88	72.96	3,842.8	155.4	507.2	153.5	0.00	0.00	0.00
4,000.0	12.88	72.96	3,940.3	161.9	528.5	160.0	0.00	0.00	0.00
4,100.0	12.88	72.96	4,037.8	168.5	549.8	166.4	0.00	0.00	0.00
4,200.0	12.88	72.96	4,135.3	175.0	571.1	172.9	0.00	0.00	0.00
4,300.0	12.88	72.96	4,133.3	181.5	592.4	172.9	0.00	0.00	0.00
4,400.0	12.88	72.96	4,330.3	188.1	613.7	185.8	0.00	0.00	0.00
4,500.0	12.88	72.96	4,427.7	194.6	635.1	192.3	0.00	0.00	0.00
4,600.0	12.88	72.96	4,525.2	201.1	656.4	198.7	0.00	0.00	0.00
4,700.0	12.88	72.96	4,622.7	207.7	677.7	205.2	0.00	0.00	0.00
4,800.0	12.88	72.96	4,720.2	214.2	699.0	211.6	0.00	0.00	0.00
4,900.0	12.88	72.96	4,817.7	220.7	720.3	218.1	0.00	0.00	0.00
5,000.0	12.88	72.96	4,915.2	227.2	741.6	224.5	0.00	0.00	0.00
5,100.0	12.88	72.96	5,012.6	233.8	763.0	231.0	0.00	0.00	0.00

# **Planning Report**

Database: LMRKPROD3

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

Well: PLU 22 DTD - 181H

Wellbore: OH
Design: Plan 3

Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

**Survey Calculation Method:** 

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549) RKB30 @ 3431.0usft (H&P 549)

Grid

ed Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,200.0 5,300.0	12.88 12.88	72.96 72.96	5,110.1 5,207.6	240.3 246.8	784.3 805.6	237.4 243.9	0.00 0.00	0.00 0.00	0.00 0.00
5,400.0	12.88	72.96	5,305.1	253.4	826.9	250.3	0.00	0.00	0.00
5,500.0	12.88	72.96 72.96	5,402.6	259.9	848.2	256.8	0.00	0.00	0.00
5,600.0	12.88	72.96	5,500.1	266.4	869.5	263.2	0.00	0.00	0.00
5,700.0	12.88	72.96	5,597.5	273.0	890.9	269.7	0.00	0.00	0.00
5,800.0	12.88	72.96	5,695.0	279.5	912.2	276.1	0.00	0.00	0.00
5,816.7	12.88	72.96	5,711.3	280.6	915.7	277.2	0.00	0.00	0.00
5,900.0	11.22	72.96	5,792.8	285.7	932.4	282.3	2.00	-2.00	0.00
6,000.0	9.22	72.96	5,891.2	290.9	949.3	287.4	2.00	-2.00	0.00
6,100.0	7.22	72.96	5,990.1	295.1	963.0	291.5	2.00	-2.00	0.00
6,200.0	5.22	72.96	6,089.6	298.2	973.3	294.7	2.00	-2.00	0.00
6,300.0	3.22	72.96	6,189.3	300.4	980.4	296.8	2.00	-2.00	0.00
6,400.0	1.22	72.96	6,289.2	301.5	984.1	297.9	2.00	-2.00	0.00
6,460.8	0.00	0.00	6,350.0	301.7	984.7	298.1	2.00	-2.00	-119.99
6,500.0	0.00	0.00	6,389.2	301.7	984.7	298.1	0.00	0.00	0.00
6,600.0	0.00	0.00	6,489.2	301.7	984.7	298.1	0.00	0.00	0.00
6,700.0	0.00	0.00	6,589.2	301.7	984.7	298.1	0.00	0.00	0.00
6,800.0	0.00	0.00	6,689.2	301.7	984.7	298.1	0.00	0.00	0.00
6,900.0	0.00	0.00	6,789.2	301.7	984.7	298.1	0.00	0.00	0.00
7,000.0	0.00	0.00	6,889.2	301.7	984.7	298.1	0.00	0.00	0.00
7,100.0	0.00	0.00	6,989.2	301.7	984.7	298.1	0.00	0.00	0.00
7,200.0	0.00	0.00	7,089.2	301.7	984.7	298.1	0.00	0.00	0.00
7,300.0	0.00	0.00	7,189.2	301.7	984.7	298.1	0.00	0.00	0.00
7,400.0	0.00	0.00	7,289.2	301.7	984.7	298.1	0.00	0.00	0.00
7,500.0	0.00	0.00	7,389.2	301.7	984.7	298.1	0.00	0.00	0.00
7,600.0	0.00	0.00	7,489.2	301.7	984.7	298.1	0.00	0.00	0.00
7,700.0	0.00	0.00	7,589.2	301.7	984.7	298.1	0.00	0.00	0.00
7,800.0	0.00	0.00	7,689.2	301.7	984.7	298.1	0.00	0.00	0.00
7,900.0	0.00	0.00	7,789.2	301.7	984.7	298.1	0.00	0.00	0.00
8,000.0	0.00	0.00	7,889.2	301.7	984.7	298.1	0.00	0.00	0.00
8,100.0	0.00	0.00	7,989.2	301.7	984.7	298.1	0.00	0.00	0.00
8,200.0	0.00	0.00	8,089.2	301.7	984.7	298.1	0.00	0.00	0.00
8,300.0	0.00	0.00	8,189.2	301.7	984.7	298.1	0.00	0.00	0.00
8,400.0	0.00	0.00	8,289.2	301.7	984.7	298.1	0.00	0.00	0.00
8,500.0 8,600.0	0.00 0.00	0.00 0.00	8,389.2 8,489.2	301.7 301.7	984.7 984.7	298.1 298.1	0.00 0.00	0.00 0.00	0.00 0.00
8,700.0		0.00		301.7					0.00
8,700.0	0.00 0.00	0.00	8,589.2 8,689.2	301.7 301.7	984.7 984.7	298.1 298.1	0.00 0.00	0.00 0.00	0.00
8,900.0	0.00	0.00	8,089.2 8,789.2	301.7 301.7	984.7 984.7	298.1	0.00	0.00	0.00
9,000.0	0.00	0.00	8,889.2	301.7	964.7 984.7	298.1	0.00	0.00	0.00
9,100.0	0.00	0.00	8,989.2	301.7	984.7	298.1	0.00	0.00	0.00
9,200.0	0.00	0.00	9,089.2	301.7	984.7	298.1	0.00	0.00	0.00
9,300.0	0.00	0.00	9,189.2	301.7	984.7	298.1	0.00	0.00	0.00
9,400.0	0.00	0.00	9,289.2	301.7	984.7	298.1	0.00	0.00	0.00
9,500.0	0.00	0.00	9,389.2	301.7	984.7	298.1	0.00	0.00	0.00
9,600.0	0.00	0.00	9,489.2	301.7	984.7	298.1	0.00	0.00	0.00
9,700.0	0.00	0.00	9,589.2	301.7	984.7	298.1	0.00	0.00	0.00
9,800.0	0.00	0.00	9,689.2	301.7	984.7	298.1	0.00	0.00	0.00
9,900.0	0.00	0.00	9,789.2	301.7	984.7	298.1	0.00	0.00	0.00
10,000.0	0.00	0.00	9,889.2	301.7	984.7	298.1	0.00	0.00	0.00
10,100.0	0.00	0.00	9,989.2	301.7	984.7	298.1	0.00	0.00	0.00
10,200.0	0.00	0.00	10,089.2	301.7	984.7	298.1	0.00	0.00	0.00

# **Planning Report**

Database: LMRKPROD3

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

Well: PLU 22 DTD - 181H

Wellbore: OH
Design: Plan 3

Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

Well PLU 22 DTD - 181H RKB30 @ 3431.0usft (H&P 549) RKB30 @ 3431.0usft (H&P 549)

Grid

Survey Calculation Method: Minimum

anned Cumrey									
lanned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,300.0	0.00	0.00	10,189.2	301.7	984.7	298.1	0.00	0.00	0.00
10,360.6	0.00	0.00	10,249.8	301.7	984.7	298.1	0.00	0.00	0.00
10,400.0	3.15	359.79	10,289.2	302.8	984.7	299.2	8.00	8.00	-0.53
10,500.0	11.15	359.79	10,388.3	315.2	984.6	311.6	8.00	8.00	0.00
10,600.0	19.15	359.79	10,484.8	341.3	984.5	337.7	8.00	8.00	0.00
10,700.0	27.15	359.79	10,576.6	380.6	984.4	377.0	8.00	8.00	0.00
10,800.0	35.15	359.79	10,662.1	432.3	984.2	428.7	8.00	8.00	0.00
10,900.0	43.15	359.79	10,739.6	495.4	984.0	491.8	8.00	8.00	0.00
11,000.0	51.15	359.79	10,807.6	568.7	983.7	565.0	8.00	8.00	0.00
11,100.0	59.15	359.79	10,864.7	650.7	983.4	647.0	8.00	8.00	0.00
11,200.0	67.15	359.79	10,909.8	739.8	983.1	736.2	8.00	8.00	0.00
11,300.0	75.15	359.79	10,942.1	834.4	982.7	830.8	8.00	8.00	0.00
11,400.0	83.15	359.79	10,960.9	932.5	982.3	928.9	8.00	8.00	0.00
11,485.6	90.00	359.79	10,966.0	1,017.9	982.0	1,014.3	8.00	8.00	0.00
11,500.0	90.00	359.79	10,966.0	1,032.3	982.0	1,028.7	0.00	0.00	0.00
11,500.0	90.00	359.79 359.79	10,966.0	1,032.3		1,028.7 1,128.7	0.00	0.00	0.00
					981.6				
11,685.6	90.00	359.79	10,966.0	1,217.9	981.3	1,214.3	0.00	0.00	0.00
11,700.0	90.00	359.79	10,966.0	1,232.3	981.2	1,228.7	0.00	0.00	0.00
11,800.0	90.00	359.79	10,966.0	1,332.3	980.9	1,328.7	0.00	0.00	0.00
11,900.0	90.00	359.79	10,966.0	1,432.3	980.5	1,428.7	0.00	0.00	0.00
12,000.0	90.00	359.79	10,966.0	1,532.3	980.1	1,528.7	0.00	0.00	0.00
12,100.0	90.00	359.79	10,966.0	1,632.3	979.8	1,628.7	0.00	0.00	0.00
12,200.0	90.00	359.79	10,966.0	1,732.3	979.4	1,728.7	0.00	0.00	0.00
12,300.0	90.00	359.79	10,966.0	1,832.3	979.0	1,828.7	0.00	0.00	0.00
12,400.0	90.00	359.79	10,966.0	1,932.3	978.7	1,928.7	0.00	0.00	0.00
12,500.0	90.00	359.79	10,966.0	2,032.3	978.3	2,028.7	0.00	0.00	0.00
12,600.0	90.00	359.79	10,966.0	2,132.3	977.9	2,128.7	0.00	0.00	0.00
12,700.0	90.00	359.79	10,966.0	2,232.3	977.6	2,228.7	0.00	0.00	0.00
12,800.0	90.00	359.79	10,966.0	2,332.3	977.2	2,328.7	0.00	0.00	0.00
12,900.0	90.00	359.79	10,966.0	2,432.3	976.8	2,428.7	0.00	0.00	0.00
13,000.0	90.00	359.79	10,966.0	2,532.3	976.5	2,528.7	0.00	0.00	0.00
13,100.0	90.00	359.79	10,966.0		976.3	2,628.7		0.00	0.00
				2,632.3			0.00		
13,200.0	90.00	359.79	10,966.0	2,732.3	975.7	2,728.7	0.00	0.00	0.00
13,300.0	90.00	359.79	10,966.0	2,832.3	975.4	2,828.7	0.00	0.00	0.00
13,400.0	90.00	359.79	10,966.0	2,932.3	975.0	2,928.7	0.00	0.00	0.00
13,500.0	90.00	359.79	10,966.0	3,032.3	974.6	3,028.7	0.00	0.00	0.00
13,600.0	90.00	359.79	10,966.0	3,132.3	974.3	3,128.7	0.00	0.00	0.00
13,700.0	90.00	359.79	10,966.0	3,232.3	973.9	3,228.7	0.00	0.00	0.00
13,800.0	90.00	359.79	10,966.0	3,332.3	973.5	3,328.7	0.00	0.00	0.00
13,900.0	90.00	359.79	10,966.0	3,432.3	973.2	3,428.7	0.00	0.00	0.00
14,000.0	90.00	359.79	10,966.0	3,532.3	972.8	3,528.7	0.00	0.00	0.00
14,100.0	90.00	359.79	10,966.0	3,632.3	972.4	3,628.7	0.00	0.00	0.00
14,200.0	90.00	359.79	10,966.0	3,732.3	972.1	3,728.7	0.00	0.00	0.00
14,300.0	90.00	359.79	10,966.0	3,832.3	971.7	3,828.7	0.00	0.00	0.00
14,400.0	90.00	359.79	10,966.0	3,932.3	971.3	3,928.7	0.00	0.00	0.00
14,400.0	90.00	359.79	10,966.0	3,932.3 4,032.3	971.3 971.0	3,926.7 4,028.7	0.00	0.00	0.00
14,500.0		359.79 359.79	10,966.0						
	90.00			4,132.3	970.6	4,128.7	0.00	0.00	0.00
14,700.0	90.00	359.79 350.70	10,966.0	4,232.3	970.2	4,228.7	0.00	0.00	0.00
14,800.0	90.00	359.79	10,966.0	4,332.3	969.8	4,328.7	0.00	0.00	0.00
14,900.0	90.00	359.79	10,966.0	4,432.3	969.5	4,428.7	0.00	0.00	0.00
15,000.0	90.00	359.79	10,966.0	4,532.3	969.1	4,528.7	0.00	0.00	0.00
15,100.0	90.00	359.79	10,966.0	4,632.3	968.7	4,628.7	0.00	0.00	0.00
15,200.0	90.00	359.79	10,966.0	4,732.3	968.4	4,728.7	0.00	0.00	0.00

# **Planning Report**

Database: LMRKPROD3

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

Well: PLU 22 DTD - 181H

Wellbore: OH
Design: Plan 3

Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

**Survey Calculation Method:** 

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549) RKB30 @ 3431.0usft (H&P 549)

Grid

lanned Survey									
•									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,300.0	90.00	359.79	10,966.0	4,832.3	968.0	4,828.7	0.00	0.00	0.00
15,400.0	90.00	359.79	10,966.0	4,932.3	967.6	4,928.7	0.00	0.00	0.00
15,500.0	90.00	359.79	10,966.0	5,032.3	967.3	5,028.7	0.00	0.00	0.00
15,600.0	90.00	359.79	10,966.0	5,132.3	966.9	5,128.7	0.00	0.00	0.00
15,700.0	90.00	359.79	10,966.0	5,232.3	966.5	5,228.7	0.00	0.00	0.00
15,800.0	90.00	359.79	10,966.0	5,332.3	966.2	5,328.7	0.00	0.00	0.00
15,900.0	90.00	359.79	10,966.0	5,432.3	965.8	5,428.7	0.00	0.00	0.00
16,000.0	90.00	359.79	10,966.0	5,532.3	965.4	5,528.7	0.00	0.00	0.00
16,100.0	90.00	359.79	10,966.0	5,632.3	965.1	5,628.7	0.00	0.00	0.00
16,200.0	90.00	359.79	10,966.0	5,732.3	964.7	5,728.7	0.00	0.00	0.00
16,300.0	90.00	359.79	10,966.0	5,832.3	964.3	5,828.7	0.00	0.00	0.00
16,400.0	90.00	359.79	10,966.0	5,932.3	964.0	5,928.7	0.00	0.00	0.00
16,500.0	90.00	359.79	10,966.0	6,032.3	963.6	6,028.7	0.00	0.00	0.00
16,600.0	90.00	359.79	10,966.0	6,132.3	963.2	6,128.7	0.00	0.00	0.00
16,700.0	90.00	359.79	10,966.0	6,232.3	962.9	6,228.7	0.00	0.00	0.00
16,800.0	90.00	359.79	10,966.0	6,332.3	962.5	6,328.7	0.00	0.00	0.00
16,900.0	90.00	359.79	10,966.0	6,432.3	962.1	6,428.7	0.00	0.00	0.00
17,000.0	90.00	359.79	10,966.0	6,532.3	961.8	6,528.7	0.00	0.00	0.00
17,100.0	90.00	359.79	10,966.0	6,632.3	961.4	6,628.7	0.00	0.00	0.00
17,200.0	90.00	359.79	10,966.0	6,732.3	961.0	6,728.7	0.00	0.00	0.00
17,300.0	90.00	359.79	10,966.0	6,832.3	960.7	6,828.7	0.00	0.00	0.00
17,400.0	90.00	359.79	10,966.0	6,932.3	960.3	6,928.7	0.00	0.00	0.00
17,500.0	90.00	359.79	10,966.0	7,032.3	959.9	7,028.7	0.00	0.00	0.00
17,600.0	90.00	359.79	10,966.0	7,132.3	959.6	7,128.7	0.00	0.00	0.00
17,700.0	90.00	359.79	10,966.0	7,232.2	959.2	7,228.7	0.00	0.00	0.00
17,800.0	90.00	359.79	10,966.0	7,332.2	958.8	7,328.7	0.00	0.00	0.00
17,900.0	90.00	359.79	10,966.0	7,432.2	958.5	7,428.7	0.00	0.00	0.00
18,000.0	90.00	359.79	10,966.0	7,532.2	958.1	7,528.7	0.00	0.00	0.00
18,100.0	90.00	359.79	10,966.0	7,632.2	957.7	7,628.7	0.00	0.00	0.00
18,200.0	90.00	359.79	10,966.0	7,732.2	957.3	7,728.7	0.00	0.00	0.00
18,300.0	90.00	359.79	10,966.0	7,832.2	957.0	7,828.7	0.00	0.00	0.00
18,400.0	90.00	359.79	10,966.0	7,932.2	956.6	7,928.7	0.00	0.00	0.00
18,500.0	90.00	359.79	10,966.0	8,032.2	956.2	8,028.7	0.00	0.00	0.00
18,600.0	90.00	359.79	10,966.0	8,132.2	955.9	8,128.7	0.00	0.00	0.00
18,700.0	90.00	359.79	10,966.0	8,232.2	955.5	8,228.7	0.00	0.00	0.00
18,800.0	90.00	359.79	10,966.0	8,332.2	955.1	8,328.7	0.00	0.00	0.00
18,900.0	90.00	359.79	10,966.0	8,432.2	954.8	8,428.7	0.00	0.00	0.00
19,000.0	90.00	359.79	10,966.0	8,532.2	954.4	8,528.7	0.00	0.00	0.00
19,100.0	90.00	359.79	10,966.0	8,632.2	954.0	8,628.7	0.00	0.00	0.00
19,200.0	90.00	359.79	10,966.0	8,732.2	953.7	8,728.7	0.00	0.00	0.00
19,300.0	90.00	359.79	10,966.0	8,832.2	953.3	8,828.7	0.00	0.00	0.00
19,400.0	90.00	359.79	10,966.0	8,932.2	952.9	8,928.7	0.00	0.00	0.00
19,500.0	90.00	359.79	10,966.0	9,032.2	952.6	9,028.7	0.00	0.00	0.00
19,600.0	90.00	359.79	10,966.0	9,132.2	952.2	9,128.7	0.00	0.00	0.00
19,700.0	90.00	359.79	10,966.0	9,232.2	951.8	9,228.7	0.00	0.00	0.00
19,800.0	90.00	359.79	10,966.0	9,332.2	951.5	9,328.7	0.00	0.00	0.00
19,900.0	90.00	359.79	10,966.0	9,432.2	951.1	9,428.7	0.00	0.00	0.00
20,000.0	90.00	359.79	10,966.0	9,532.2	950.7	9,528.7	0.00	0.00	0.00
20,100.0	90.00	359.79	10,966.0	9,632.2	950.4	9,628.7	0.00	0.00	0.00
20,200.0	90.00	359.79	10,966.0	9,732.2	950.0	9,728.7	0.00	0.00	0.00
20,300.0	90.00	359.79	10,966.0	9,832.2	949.6	9,828.7	0.00	0.00	0.00
20,400.0	90.00	359.79	10,966.0	9,932.2	949.3	9,928.7	0.00	0.00	0.00
20,500.0	90.00	359.79	10,966.0	10,032.2	948.9	10,028.7	0.00	0.00	0.00

# Planning Report

Database: LMRKPROD3

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

**Well:** PLU 22 DTD - 181H

Wellbore: OH
Design: Plan 3

Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

**Survey Calculation Method:** 

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549) RKB30 @ 3431.0usft (H&P 549)

Grid

Design.									
Planned Survey									
Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Vertical Section	Dogleg Rate	Build Rate	Turn Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
20,600.0	90.00	359.79	10,966.0	10,132.2	948.5	10,128.7	0.00	0.00	0.00
20,700.0	90.00	359.79	10,966.0	10,232.2	948.2	10,228.7	0.00	0.00	0.00
20,800.0	90.00	359.79	10,966.0	10,332.2	947.8	10,328.7	0.00	0.00	0.00
•									
20,900.0	90.00	359.79	10,966.0	10,432.2	947.4	10,428.7	0.00	0.00	0.00
21,000.0	90.00	359.79	10,966.0	10,532.2	947.1	10,528.7	0.00	0.00	0.00
21,100.0	90.00	359.79	10,966.0	10,632.2	946.7	10,628.7	0.00	0.00	0.00
21,200.0	90.00	359.79	10,966.0	10,732.2	946.3	10,728.7	0.00	0.00	0.00
21,300.0	90.00	359.79	10,966.0	10,832.2	946.0	10,828.7	0.00	0.00	0.00
21,400.0	90.00	359.79	10,966.0	10,932.2	945.6	10,928.7	0.00	0.00	0.00
21,500.0	90.00	359.79	10,966.0	11,032.2	945.2	11,028.7	0.00	0.00	0.00
21,600.0	90.00	359.79	10,966.0	11,132.2	944.8	11,128.7	0.00	0.00	0.00
21,700.0	90.00	359.79	10,966.0	11,232.2	944.5	11,228.7	0.00	0.00	0.00
21,800.0	90.00	359.79	10,966.0	11,332.2	944.1	11,328.7	0.00	0.00	0.00
21,900.0	90.00	359.79	10,966.0	11,432.2	943.7	11,428.7	0.00	0.00	0.00
22,000.0	90.00	359.79	10,966.0	11,532.2	943.4	11,528.7	0.00	0.00	0.00
22,100.0	90.00	359.79	10,966.0	11,632.2	943.0	11,628.7	0.00	0.00	0.00
22,200.0	90.00	359.79	10,966.0	11,732.2	942.6	11,728.7	0.00	0.00	0.00
22,300.0	90.00	359.79	10,966.0	11,832.2	942.3	11,828.7	0.00	0.00	0.00
22,400.0	90.00	359.79	10,966.0	11,932.2	941.9	11,928.7	0.00	0.00	0.00
22,500.0	90.00	359.79	10,966.0	12,032.2	941.5	12,028.7	0.00	0.00	0.00
22,600.0	90.00	359.79	10,966.0	12,132.2	941.2	12,128.7	0.00	0.00	0.00
22,700.0	90.00	359.79	10,966.0	12,232.2	940.8	12,228.7	0.00	0.00	0.00
22,800.0	90.00	359.79	10,966.0	12,332.2	940.4	12,328.7	0.00	0.00	0.00
22,900.0	90.00	359.79	10,966.0	12,432.2	940.1	12,428.7	0.00	0.00	0.00
23,000.0	90.00	359.79	10,966.0	12,532.2	939.7	12,528.7	0.00	0.00	0.00
23,100.0	90.00	359.79	10,966.0	12,632.2	939.3	12,628.7	0.00	0.00	0.00
23,200.0	90.00	359.79	10,966.0	12,732.2	939.0	12,728.7	0.00	0.00	0.00
23,300.0	90.00	359.79	10,966.0	12,832.2	938.6	12,828.7	0.00	0.00	0.00
23,400.0	90.00	359.79	10,966.0	12,932.2	938.2	12,928.7	0.00	0.00	0.00
23,500.0	90.00	359.79	10,966.0	13,032.2	937.9	13,028.7	0.00	0.00	0.00
23,600.0	90.00	359.79	10,966.0	13,132.2	937.5	13,128.7	0.00	0.00	0.00
23,700.0	90.00	359.79	10,966.0	13,232.2	937.1	13,228.7	0.00	0.00	0.00
23,800.0	90.00	359.79	10,966.0	13,332.2	936.8	13,328.7	0.00	0.00	0.00
00.000.0	00.00	050.70	40.000.0	40.400.0	000.4	10 100 7	0.00	0.00	
23,900.0	90.00	359.79	10,966.0	13,432.2	936.4	13,428.7	0.00	0.00	0.00
24,000.0	90.00	359.79	10,966.0	13,532.2	936.0	13,528.7	0.00	0.00	0.00
24,100.0	90.00	359.79	10,966.0	13,632.2	935.7	13,628.7	0.00	0.00	0.00
24,200.0	90.00	359.79	10,966.0	13,732.2	935.3	13,728.7	0.00	0.00	0.00
24,300.0	90.00	359.79	10,966.0	13,832.2	934.9	13,828.7	0.00	0.00	0.00
24 400 0	00.00	250.70	10.066.0	12 020 0	024.0	12 000 7	0.00	0.00	0.00
24,400.0	90.00	359.79	10,966.0	13,932.2	934.6	13,928.7	0.00	0.00	0.00
24,500.0	90.00	359.79	10,966.0	14,032.2	934.2	14,028.7	0.00	0.00	0.00
24,600.0	90.00	359.79	10,966.0	14,132.2	933.8	14,128.7	0.00	0.00	0.00
24,700.0	90.00	359.79	10,966.0	14,232.2	933.5	14,228.7	0.00	0.00	0.00
24,800.0	90.00	359.79	10,966.0	14,332.2	933.1	14,328.7	0.00	0.00	0.00
24 000 0	00.00	250.70	10.066.0	14 420 0	020.7	14 400 7	0.00	0.00	0.00
24,900.0	90.00	359.79	10,966.0	14,432.2	932.7	14,428.7	0.00	0.00	0.00
25,000.0	90.00	359.79	10,966.0	14,532.2	932.3	14,528.7	0.00	0.00	0.00
25,100.0	90.00	359.79	10,966.0	14,632.2	932.0	14,628.7	0.00	0.00	0.00
25,200.0	90.00	359.79	10,966.0	14,732.2	931.6	14,728.7	0.00	0.00	0.00
25,300.0	90.00	359.79	10,966.0	14,832.2	931.2	14,828.7	0.00	0.00	0.00
05 400 0	00.00	250.70	10.060.0	14 020 0	000.0	14 000 7	0.00	0.00	0.00
25,400.0	90.00	359.79	10,966.0	14,932.2	930.9	14,928.7	0.00	0.00	0.00
25,500.0	90.00	359.79	10,966.0	15,032.2	930.5	15,028.7	0.00	0.00	0.00
25,600.0	90.00	359.79	10,966.0	15,132.2	930.1	15,128.7	0.00	0.00	0.00
25,700.0	90.00	359.79	10,966.0	15,232.2	929.8	15,228.7	0.00	0.00	0.00
25,800.0	90.00	359.79	10,966.0	15,332.2	929.4	15,328.7	0.00	0.00	0.00
<u> </u>									

# **Planning Report**

Database: LMRKPROD3

Company: ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

Site: (HP 549) - PLU 22 DTD - Plans

Well: PLU 22 DTD - 181H

Wellbore: OH
Design: Plan 3

Local Co-ordinate Reference:

TVD Reference:

North Reference:

Survey Calculation Method:

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549) RKB30 @ 3431.0usft (H&P 549)

Grid

lanned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
25,900.0	90.00	359.79	10,966.0	15,432.2	929.0	15,428.7	0.00	0.00	0.00
26,000.0	90.00	359.79	10,966.0	15,532.2	928.7	15,528.7	0.00	0.00	0.00
26,100.0	90.00	359.79	10,966.0	15,632.2	928.3	15,628.7	0.00	0.00	0.00
26,200.0	90.00	359.79	10,966.0	15,732.2	927.9	15,728.7	0.00	0.00	0.00
26,300.0	90.00	359.79	10,966.0	15,832.2	927.6	15,828.7	0.00	0.00	0.00
26,400.0	90.00	359.79	10,966.0	15,932.2	927.2	15,928.7	0.00	0.00	0.00
26,500.0	90.00	359.79	10,966.0	16,032.2	926.8	16,028.7	0.00	0.00	0.00
26,600.0	90.00	359.79	10,966.0	16,132.2	926.5	16,128.7	0.00	0.00	0.00
26,700.0	90.00	359.79	10,966.0	16,232.2	926.1	16,228.7	0.00	0.00	0.00
26,800.0	90.00	359.79	10,966.0	16,332.2	925.7	16,328.7	0.00	0.00	0.00
26,900.0	90.00	359.79	10,966.0	16,432.2	925.4	16,428.7	0.00	0.00	0.00
27,000.0	90.00	359.79	10,966.0	16,532.2	925.0	16,528.7	0.00	0.00	0.00
27,100.0	90.00	359.79	10,966.0	16,632.2	924.6	16,628.7	0.00	0.00	0.00
27,200.0	90.00	359.79	10,966.0	16,732.2	924.3	16,728.7	0.00	0.00	0.00
27,300.0	90.00	359.79	10,966.0	16,832.2	923.9	16,828.7	0.00	0.00	0.00
27,325.2	90.00	359.79	10,966.0	16,857.4	923.8	16,853.9	0.00	0.00	0.00
27,375.2	90.00	359.79	10,966.0	16,907.4	923.6	16,903.9	0.00	0.00	0.00

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
KOP 181H Plan 3 - plan hits target cent - Point	0.00 ter	0.00	10,249.8	301.7	984.7	439,755.91	642,759.97	32° 12' 29.389 N	103° 52' 18.357 W
LTP 181H v1 - plan hits target cen - Rectangle (sides W		359.79 39.0 D0.0)	10,966.0	16,857.4	923.8	456,311.60	642,699.10	32° 15' 13.227 N	103° 52' 18.237 W
FTP 181H v1 - plan hits target cent - Point	0.00 ter	0.00	10,966.0	1,217.9	981.3	440,672.10	642,756.60	32° 12' 38.456 N	103° 52' 18.350 W
BHL 181H v1 - plan misses target of - Rectangle (sides W			10,966.0 .2usft MD (1	16,907.4 0966.0 TVD,	923.5 16907.4 N, 923	456,361.60 3.6 E)	642,698.80	32° 15' 13.722 N	103° 52' 18.238 W

# Planning Report

LMRKPROD3 Database: Company:

ROC

Project: NX34, HP549, HP552 - Eddy County (NAD27

NME)

(HP 549) - PLU 22 DTD - Plans Site:

Well: PLU 22 DTD - 181H

Wellbore: ОН Design: Plan 3 Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

**Survey Calculation Method:** 

Well PLU 22 DTD - 181H

RKB30 @ 3431.0usft (H&P 549)

RKB30 @ 3431.0usft (H&P 549)

Grid

rmations						
	Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
	701.0	701.0	Rustler			
	1,060.0	1,060.0	Top Salt			
	3,778.1	3,724.0	Base Salt			
	4,003.8	3,944.0	Delaware			
	4,905.5	4,823.0	Cherry Canyon			
	6,291.7	6,181.0	Brushy Canyon			
	7,596.8	7,486.0	Basal Brushy Canyon			
	7,856.8	7,746.0	Bone Spring			
	7,881.8	7,771.0	Bone Spring Lime Fm			
	7,978.8	7,868.0	Avalon Shale			
	8,313.8	8,203.0	Avalon Lime			
	8,460.8	8,350.0	Lower Avalon Shale			
	8,643.8	8,533.0	1st Bone Spring Lime			
	8,809.8	8,699.0	1st Bone Spring Ss			
	9,206.8	9,096.0	2nd Bone Spring Lime			
	9,666.8	9,556.0	2nd Bone Spring Ss			
	9,721.8	9,611.0	2nd Bone Spring A Sand			
	9,786.8	9,676.0	2nd Bone Spring T/B Carb			
	9,888.8	9,778.0	2nd Bone Spring C Sand			
	9,958.8	9,848.0	3rd Bone Spring Lm			
	10,349.8	10,239.0	3rd Bone Spring Sh			
	10,535.5	10,423.0	3rd Bone Spring Sh Base			
	10,770.9	10,638.0	3rd Bone Spring Ss			
	11,277.6	10,936.0	Red Hills SS			
	11,485.6	10,966.0	TD			
	11,485.6	10,966.0	Landing Point			

Plan Annotations				
Measure		Local C	oordinates	
Depth (usft)	Depth (usft)	+N/-S (usft)	+E/-W (usft)	Comment
1,200	1,200.0	0.0	0.0	Begin 2°/100 Build
1,844	.1 1,838.7	21.1	68.9	Hold 12.88° Inc at 72.96° Azm
5,816	5.7 5,711.3	280.6	915.7	Begin 2°/100 Drop
6,460	0.8 6,350.0	301.7	984.7	Hold Vertical
10,360	10,249.8	301.7	984.7	KOP, Begin 8°/100 Build
11,485	5.6 10,966.0	1,017.9	982.0	LP, Hold 90° Inc at 359.79° Azm
27,325	5.2 10,966.0	16,857.4	923.8	LTP
27,375	5.2 10,966.0	16,907.4	923.6	TD at 27375.2



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

DTD

Sundry Print Repo

Well Name: POKER LAKE UNIT 22 Well Location: T24S / R30E / SEC 22 /

NWNW / 32.20747 / -103.87544

County or Parish/State: EDDY /

Well Number: 181H Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Unit or CA Name: POKER LAKE UNIT **Unit or CA Number:** 

NMNM71016X

**US Well Number: 3001549885 Operator: XTO PERMIAN OPERATING** 

LLC

# **Notice of Intent**

Lease Number: NMLC068905

Sundry ID: 2862993

Type of Submission: Notice of Intent Type of Action: APD Change

Date Sundry Submitted: 07/14/2025 **Time Sundry Submitted:** 08:53

Date proposed operation will begin: 07/14/2025

Procedure Description: Effective Date: 2/1/23 XTO Permian Operating LLC respectfully requests to make the following changes for well file cleanup: BLM previously approved sundry Id #2824165, OCD previously approved sundry Id #443220, dedicated acres. BLM previously approved sundry Id #2697961, OCD previously approved sundry Id #158818, with drill plan. Dedicated acres: f/ 480.49 t/ 1041.01 TD: f/ 26799' MD / 11018' TVD t/ 27435' MD/ 10930' TVD FTP: f/ 100' FSL 1650' FWL t/ 500' FNL 1650' FWL Sec 22, 24S 30E; Lease NMLC068431 Attachments: Updated drilling plan and directional surveys. Updated C-102 on new form. No new surface disturbance.

# **NOI Attachments**

# **Procedure Description**

POKER\_LAKE\_UNIT\_22\_DTD\_181H\_C\_102\_FINAL\_11\_20\_2024\_20250714085244.pdf

Poker\_Lake\_Unit\_22\_DTD\_181H\_Post\_Execution\_Drilling\_Template\_\_\_RC\_\_\_DJ\_\_June\_16\_\_202507140852 41.pdf

Page 1 of 2

eived by OCD: 9/5/2025 8:01:22 AM Well Name: POKER LAKE UNIT 22

DTD

Well Location: T24S / R30E / SEC 22 / NWNW / 32.20747 / -103.87544

County or Parish/State: Page 17 of

NM

Well Number: 181H

Type of Well: CONVENTIONAL GAS

**Allottee or Tribe Name:** 

Lease Number: NMLC068905

Unit or CA Name: POKER LAKE UNIT

**Unit or CA Number:** NMNM71016X

**US Well Number: 3001549885** 

**Operator: XTO PERMIAN OPERATING** LLC

# **Operator**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Signed on: JUL 16, 2025 03:04 PM **Operator Electronic Signature: LACEY GRANILLO** 

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 HOLIDAY HILL ROAD City: MIDLAND State: TX

Phone: (432) 894-0057

Email address: LACEY.GRANILLO@EXXONMOBIL.COM

# **Field**

**Representative Name:** 

**Street Address:** 

City:

State:

Zip:

Phone:

**Email address:** 

# **BLM Point of Contact**

**BLM POC Name: CHRISTOPHER WALLS BLM POC Title:** Petroleum Engineer

**BLM POC Phone:** 5752342234 BLM POC Email Address: cwalls@blm.gov

**Disposition:** Accepted Disposition Date: 08/01/2025

Signature: Chris Walls

Page 2 of 2

Form 3160-5 (June 2019)

# **UNITED STATES** DEPARTMENT OF THE INTERIOR

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

	Expires: October 31, 2
ease Serial No	

BURI	EAU OF LAND MANAGEMENT	5. Lease Serial No. NMLC068905			
Do not use this t	OTICES AND REPORTS ON Worm for proposals to drill or to Use Form 3160-3 (APD) for suc	re-enter an	6. If Indian, Allottee or Tribe	Name	
	TRIPLICATE - Other instructions on pag		7. If Unit of CA/Agreement,		
1. Type of Well Oil Well Gas W			POKER LAKE UNIT/NMNM71016X  8. Well Name and No. POKER LAKE UNIT 22 DTD/181H		
2. Name of Operator XTO PERMIAN			9. API Well No. 300154988		
3a. Address 6401 HOLIDAY HILL R		(include area code)	10. Field and Pool or Explora		
	(432) 683-22	WILDCAT G-06 S243026M/BONE	E SPRING		
4. Location of Well (Footage, Sec., T.,R SEC 22/T24S/R30E/NMP	,M., or Survey Description)		11. Country or Parish, State EDDY/NM		
12. CHE	CK THE APPROPRIATE BOX(ES) TO INI	DICATE NATURE C	OF NOTICE, REPORT OR OT	THER DATA	
TYPE OF SUBMISSION		TYPE	E OF ACTION		
✓ Notice of Intent	Acidize Deep Alter Casing Hydr	en [ aulic Fracturing [	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair New	Construction [	Recomplete	Other	
		and Abandon	Temporarily Abandon		
Final Abandonment Notice	Convert to Injection Plug peration: Clearly state all pertinent details, i	Back	Water Disposal		
completion of the involved operation completed. Final Abandonment Notice ready for final inspection.)  Effective Date: 2/1/23  XTO Permian Operating LLC representation of the second state of the second stat		npletion or recomplets, including reclamates, including reclamates, including reclamates, including reclamates, including reclamates, including the sundry ld #443 wed sundry ld #158 ease NMLC068431	tion in a new interval, a Form ition, have been completed and liftle cleanup: 3220, dedicated acres. 3818, with drill plan.	3160-4 must be filed once testing has been the operator has detennined that the site	
LACEY GRANILLO / Ph: (432) 894	, , , , , , , , , , , , , , , , , , , ,	Regulatory A	Analyst		
Signature (Electronic Submission	n)	Date	07/16/2	2025	
	THE SPACE FOR FED	ERAL OR STA	TE OFICE USE		
Approved by					
CHRISTOPHER WALLS / Ph: (575	5) 234-2234 / Accepted	Petrole Title	eum Engineer	08/01/2025 Date	
	ned. Approval of this notice does not warran equitable title to those rights in the subject leduct operations thereon.		LSBAD		
Title 18 U.S.C Section 1001 and Title 4.	3 U.S.C Section 1212, make it a crime for ar	ny person knowingly	and willfully to make to any c	lepartment or agency of the United States	

any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

#### **GENERAL INSTRUCTIONS**

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

#### SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

#### **NOTICES**

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

# **Additional Information**

#### **Location of Well**

0. SHL: NWNW / 1106 FNL / 665 FWL / TWSP: 24S / RANGE: 30E / SECTION: 22 / LAT: 32.20747 / LONG: -103.87544 ( TVD: 0 feet, MD: 0 feet )

PPP: SWNE / 100 FSL / 1577 FWL / TWSP: 24S / RANGE: 30E / SECTION: 15 / LAT: 32.210805 / LONG: -103.872488 ( TVD: 12171 feet, MD: 15161 feet )

PPP: SWSW / 100 FSL / 890 FEL / TWSP: 24S / RANGE: 30E / SECTION: 15 / LAT: 32.21079 / LONG: -103.874708 ( TVD: 12171 feet, MD: 12521 feet )

PPP: NWNE / 300 FNL / 313 FWL / TWSP: 24S / RANGE: 30E / SECTION: 10 / LAT: 32.253158 / LONG: -103.876545 ( TVD: 12171 feet, MD: 17801 feet )

BHL: LOT 4 / 200 FNL / 881 FWL / TWSP: 24S / RANGE: 30E / SECTION: 3 / LAT: 32.253518 / LONG: -103.874707 ( TVD: 12171 feet, MD: 28065 feet )

Ō
02.
T
C-1
Ξ
ò
$\overline{}$
$^{\circ}$
≶
9
$\subseteq$
$\overline{}$
18
$\cap$
$\Box$
22
7
$\neg$
$\exists$
Ф
1
79
_
ells/
ē
≶
<
6
ш
1
$\Box$
22
•
$\subseteq$
┙
1
08
.08
/
<u>:</u>
ni:
Unit
<e td="" unit∖<=""></e>
<e td="" unit∖<=""></e>
Unit
Lake Unit
ter Lake Unit∖
oker Lake Unit\
Poker Lake Unit∖
Poker Lake Unit∖
03 Poker Lake Unit^
,003 Poker Lake Unit^
,003 Poker Lake Unit^
,003 Poker Lake Unit^
NM\003 Poker Lake Unit\
,003 Poker Lake Unit^
y — NM\003 Poker Lake Unit\
rgy — NM\003 Poker Lake Unit\
y — NM\003 Poker Lake Unit\
rgy — NM\003 Poker Lake Unit\
Energy — NM\003 Poker Lake Unit\
nergy — NM\003 Poker Lake Unit\
0 Energy — NM\003 Poker Lake Unit\
XTO Energy — NM\003 Poker Lake Unit\
13 XTO Energy — NM\003 Poker Lake Unit\
.013 XTO Energy — NM\003 Poker Lake Unit\
13 XTO Energy — NM\003 Poker Lake Unit\
.013 XTO Energy — NM\003 Poker Lake Unit\
18.013 XTO Energy — NM\003 Poker Lake Unit\
P:\618.013 XTO Energy — NM\003 Poker Lake Unit\
18.013 XTO Energy — NM\003 Poker Lake Unit\
P:\618.013 XTO Energy — NM\003 Poker Lake Unit\


<u>C-10</u>	2			Energy, 1	State of New Minerals & Natura	al Resources Departmen	t		Revised July, 09 2024		
	electronically D Permitting			OI	L CONVERSI	ON DIVISION					
								Submital	☐ Initial Submittal		
					Type				M Amended 1	Report	
									☐ As Drilled		
					WELL LOCA	TION INFORMATION					
API Nu			Pool Code			Pool Name	<b>-</b>		20		
Property	30-015-4	9885	Property N	9779	8	WILDCA	1 G-06 S2	43026M;	Well Number		
riopen	y Code		rioperty I	vaine	POKER L	AKE UNIT 22 DTD				181H	
OGRID	No.		Operator 1	Name					Ground Leve		
	37307	75			XTO PERMIA	N OPERATING, LL	C.		- 3	3,401'	
Surface	Owner: S	State Fee	]Tribal ⊠Fe	ederal		Mineral Owner:	State Fee	□Tribal 🛛 I	Federal		
					0.6	W1. Z					
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	L	ongitude	County	
D	22	24\$	30E		1,106 FNL	665 FWL	32.207	470 -	103.875440	EDDY	
								-			
UL	Section	Township	Range	Lot	Botton Ft. from N/S	Hole Location Ft. from E/W	Latitude	т	ongitude	County	
CL	3	248	30E	3	50 FNL				C		
	3	245	30E	3	50 FINL	1,650 FWL	32.253	935 -	103.872222	EDDY	
	ed Acres	Infill or Defi		Definin	g Well API	Overlapping Spacing	Unit (Y/N)	Consolidati			
1,041.01 DEFINING					N U						
Order N	lumbers.					Well Setbacks are under Common Ownership:   ☑ Yes ☐ No					
					Vial. C	Off Doint (VOD)					
UL	Section	Township	Range	Lot	Ft. from N/S	Off Point (KOP)  Ft. from E/W	Latitude	L	ongitude	County	
D	22	245	30E		1,106 FNL		32.207		103.875440	EDDY	
	22	243	302		1,100114L	003 TWE	32.207	470	103.073440	LDD1	
***	Ι	T	T =	T	1	ake Point (FTP)	T				
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude		ongitude	County	
С	22	24\$	30E		500 FNL	1,650 FWL	32.209	0157   -	103.872253	EDDY	
					Last Ta	ake Point (LTP)					
UL	Section	Township	Range	Lot	Ft. from N/S	Ft. from E/W	Latitude	L	ongitude	County	
	3	24\$	30E	3	100 FNL	1,650 FWL	32.253	3798 -	103.872221	EDDY	
Unitized	d Area of Are	ea of Interest		Spacing I	Jnit Type : 🛛 Horiz	zontal DV artical	Groun	nd Elevation			
				Spacing c	1)pe : <b>23</b> 110112	Vertical			3,401'		
ODED V	TOD CEDT	IFICATIONS				SURVEYOR CERTIFIC	ATIONS				
			4i J I							G G.114 G	
best of n	ny knowledg	e and belief, and	d, if the well is	s vertical or	nd complete to the directional well,	I hereby certify that the vactual surveys made by n	ne or under my				
in the la	nd including	the proposed b	ottom hole lo	cation or has	sed mineral interest s a right to drill this	correct to the best of my	ренеј				
unlease	d mineral int	uant to a contract terest, or a volur	ntary pooling	agreement o				/	at DILLON	140	
		etofore entered	-		. ,. 1			/3	AFTINEW MEXIC	THAP SO THAP	
received	d the consent	ontal well, I fur of at least one l	lessee or own	er of a worki	ing interest or				00700	\ \ \	
which a	ny part of the	erest in each tro e well's complet	ed interval wi					PAC	23786	/ <b>/%</b> /	
compuls	sory pooling	order from the a	tivision.			1/	1/	1			
	OD-1	. V		0.10.5 = .			//		23786 88/ONAL	8U.	
Signatu	- •	• •	11/2 Date	2/2024		Signature and Seal of Pro	ofessional Surv				
orgnatul			Date			Signature and Sear Of PTO	nessional Surv	-Cy01			
Mano	j Venkat	esh				MARK DILLON HARP 237	86		11/20/2024		
Printed	-					Certificate Number		f Survey	.,,,		
		esh@exxo	nmobil.co	om							
Email A	ddress					YH			618 01300		

Note: No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.

#### ACREAGE DEDICATION PLATS

This grid represents a standard section. You may superimpose a non-standard section, or larger area, over this grid. Operators must outline the dedicated acreage in a red box, clearly show the well surface location and bottom hole location, if it is a directionally drilled, with the dimensions from the section lines in the cardinal directions. If this is a horizontal wellbore show on this plat the location of the First Take Point and Last Take Point, and the point within the Completed interval (other then the First Take Point and Last Take Point) that is closest to any outer boundary of the tract.

Surveyor shall use the latest United States government survey or dependent resurvey. Well locations will be in reference to the New Mexico Principal Meridian. If the land in not surveyed, contact the OCD Engineering Bureau. Independent subdivision surveys will not be acceptable.



SEC. 10

SEC. 15

**FTP** 

500' FNL 1,650' FWL

PPP #4 0' FNL 1,640' FWL

 $\simeq$ 

0' FNL 1,636' FWL


PPP #2

PPP #1 0' FNL 1,650' FWL

> SHL/KOP 1,106' FNL 665' FWL

> > SEC. 22

2.636' FNL 1,647' FWL



LOT ACREAGE TABLE SECTION 3 T-24-S R-30-E LOT 1 = 40.42 ACRES LOT 2 = 40.45 ACRES LOT 3 = 40.49 ACRES LOT 4 = 40.52 ACRES

	LINE TABLE							
LINE	AZIMUTH	LENGTH						
L1	057*51'19"	1,161.18'						
L2	359*47'15"	16,289.88						

-E		<u>L</u>
  -	<u> </u>   	
NMLC 0068905	<u> </u>	
 	  - 	
-	-     	
 	  -  -  -  -	
	<u>                                     </u>	
NMNM 0002862		
       <del>====</del> - <del>=-</del> =	 	
•	Γ	

	COORE	DINA	ATE TAB	LE	
SHL/KOI	O (NAD 83 N	MF)	SHI /KOI	 2 (NAD 27 NI	MF
Y =		N		439,454.1	
X=	682,959.1	F	X =		
LAT. =				32.207346	
	103.875440				
	NAD 83 NME			NAD 27 NME	
	440,131.2	_		440,072.1	
X=				642,758.5	
	32.209157			32.209033	
	103.872253		LONG =	103.871766	۱۸۱۰
	(NAD 83 NN			(NAD 27 NM	
	440,631.1			440,572.0	
X=	683,940.4		X =	642,756.7	
	32.210531			32.210407	
	103.872252	_			
	(NAD 83 NN			(NAD 27 NM	
	443,271.1			443,211.9	
		_			
X =	683,930.7		X =		
LAT. =			LAT. =		
	103.872247			103.871759	
	(NAD 83 NM		PPP #3	(NAD 27 NM	E)
	445,907.3			445,848.1	
X =			X =		
	32.225034			32.224911	
	103.872241			103.871754	
	(NAD 83 NM			(NAD 27 NM	
	451,181.3			451,122.0	
X =			X =		
	32.239532			32.239408	
LONG. =	103.872231	°W		103.871743	
LTP (I	NAD 83 NME	)		NAD 27 NME	
Y =	456,371.1		Y =	456,311.6	
X =	683,882.3	Е	X =	642,699.2	Е
LAT. =			LAT. =	32.253674	°N
LONG. =	103.872221	°W	LONG. =	103.871732	°W
BHL (I	NAD 83 NME	Ξ)		NAD 27 NME	
				AMU ZI INIVIL	
			Y =		
	456,420.9	Ń		456,361.5	Ν
Y = X =	456,420.9	Ń E	Y = X =	456,361.5	N E
Y = X = LAT. =	456,420.9 683,881.8 32.253935	N E °N	Y = X = LAT. =	456,361.5 642,698.7 32.253811	N E °N
Y = X = LAT. = LONG. =	456,420.9 683,881.8 32.253935 103.872222	N E °N °W	Y = X = LAT. = LONG. =	456,361.5 642,698.7 32.253811 103.871733	N E °N
Y = X = LAT. = LONG. = COF	456,420.9 683,881.8 32.253935 103.872222 RNER COOR	N E °N °W	Y = X = LAT. = LONG. =	456,361.5 642,698.7 32.253811 103.871733 <b>AD 83 NME)</b>	N E °N °W
Y = X = LAT. = LONG. = COF A-Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4	N E °N °W RDIN	Y = X = LAT. = LONG. = ATES (NA	456,361.5 642,698.7 32.253811 103.871733 <b>AD 83 NME)</b> 684,967.0	N E °N °W
Y = X = LAT. = LONG. = COF A - Y = B - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9	N E °N °W RDIN N N	Y =     X =     LAT. =     LONG. =     ATES (NA     A - X =     B - X =	456,361.5 642,698.7 32.253811 103.871733 <b>AD 83 NME)</b> 684,967.0 684,964.0	N E °W E E
Y = X = LAT. = LONG. = COF A - Y = B - Y = C - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0	N E °N °W RDIN N N N	Y = X = LAT. = LONG. = ATES (NA A - X = C - X =	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,967.0 684,964.0 684,961.1	N E E E
Y = X = LAT. = LONG. = COF A - Y = B - Y = C - Y = D - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1	N E °N °W RDIN N N N N	Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = D - X =	456,361.5 642,698.7 32.253811 103.871733 <b>XD 83 NME)</b> 684,967.0 684,964.0 684,948.3	N
Y = X = LAT. = LONG. = COF A - Y = C - Y = C - Y = E - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5	N E °N °W <b>DIN</b> N N N N N N	Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = D - X = E - X =	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,967.0 684,964.0 684,948.3 684,935.6	N
Y = X = LAT. = LONG. = COF A - Y = B - Y = C - Y = D - Y = F - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3	N E °N W DIN N N N N N N N	Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = D - X = F - X =	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,967.0 684,964.0 684,964.1 684,948.3 684,935.6 684,920.4	N
Y = X = LAT. = LONG. = COF A - Y = B - Y = C - Y = D - Y = F - Y = G - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6		Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = D - X = E - X = G - X = G - X = G - X = C - X	456,361.5 642,698.7 32.253811 103.871733 <b>3D 83 NME)</b> 684,967.0 684,961.1 684,948.3 684,935.6 684,920.4 684,905.1	N E S S S S S S S S S S S S S S S S S S
Y = X = LAT. = LONG. = COP A-Y = B-Y = C-Y = D-Y = E-Y = F-Y = G-Y = H-Y = X = X = X = X = X = X = X = X = X =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5	N E °N °W RDIN N N N N N	Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = E - X = F - X = G - X = H - X =	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,967.0 684,964.0 684,964.1 684,948.3 684,935.6 684,920.4 684,905.1 683,628.8	N E °N °W E E E E E E
Y = X = LAT. = LONG. = COF A-Y = B-Y = C-Y = D-Y = E-Y = F-Y = G-Y = I-Y =	456,420.9 683,881.8 32.253935 103.872222 8NER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4	N E °N °W RDIN N N N N N N	Y = X = LAT. = LONG. = ATES (N/A = X = B - X = C - X = E - X = E - X = G - X =	456,361.5 642,698.7 32.253811 103.871733 <b>D 83 NME)</b> 684,967.0 684,964.0 684,961.1 684,948.3 684,935.6 684,920.4 684,905.1 683,628.8 683,623.8	N E S S S S S S S S S S S S S S S S S S
Y = X = LAT. = LONG. = COF A-Y = B-Y = C-Y = D-Y = E-Y = F-Y = G-Y = H-Y = J-Y = J-Y = J-Y = S-X = X = X = X = X = X = X = X = X = X =	456,420.9 683,881.8 32.253935 103.872222 8NER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9	N	Y = X = LAT. = LONG. = ATES (NA - X = B - X = C - X = D - X = E - X = F - X = G - X = H - X = J - X =	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,967.0 684,964.0 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8	N E °N °W E E E E E E E E E
Y = X = LAT. = LAT. = LONG. = COF A-Y = B-Y = C-Y = D-Y = E-Y = F-Y = G-Y = H-Y = J-Y = K-Y = K-Y = K-Y = X = LAT.	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9	N E °N °W RDIN N N N N N N N	Y = X = LAT. = LONG. = ATES (NA - X = B - X = C - X = D - X = E - X = F - X = G - X = H - X = J - X = J - X = L - X = J - X = L - X = J - X = L - X =	456,361.5 642,698.7 32.253811 103.871733 <b>XD 83 NME)</b> 684,967.0 684,964.0 684,935.6 684,920.4 684,905.1 683,623.8 683,623.0 683,623.0	N E * * * * * * * * * * * * * * * * * *
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  C-Y =  F-Y =  G-Y =  H-Y =  I-Y =  K-Y =  L-Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 445,178.3	N	Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = E - X = F - X = G - X = H - X = I - X = J - X = K - X = L -	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,964.0 684,964.0 684,935.6 684,920.4 684,905.1 683,623.8 683,623.0 683,611.0 683,598.6	N E S S S S S S S S S S S S S S S S S S
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  F-Y =  G-Y =  H-Y =  J-Y =  K-Y =  K-Y =  M-Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2	N   E   °N   °W   RDIN   N   N   N   N   N   N   N   N   N	Y = X = LAT. = LONG. = A - X = B - X = C - X = D - X = E - X = F - X = G - X = H - X = J - X = J - X = L - X = M - X	456,361.5 642,698.7 32,253811 103,871733 <b>ND 83 NME)</b> 684,961.0 684,964.0 684,948.3 684,935.6 684,920.4 684,905.1 683,623.8 683,623.0 683,621.0 683,598.6 683,588.6	N E S S S S S S S S S S S S S S S S S S
Y =  X =  LAT. =  LONG. =  COF  A - Y =  B - Y =  C - Y =  C - Y =  G - Y =  H - Y =  J - Y =  K - Y =  L - Y =  N - Y =  N - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0	N	Y = LAT. = LONG. = ATES (NA A-X = B-X = C-X = C-	456,361.5 642,698.7 32.253811 103.871733 <b>ND 83 NME)</b> 684,967.0 684,964.0 684,964.0 684,935.6 684,935.6 684,920.4 684,905.1 683,623.8 683,623.0 683,611.0 683,598.6 683,588.6	N E S S S S S S S S S S S S S S S S S S
Y = X = LAT. = LAT. = LONG. = COP A - Y = B - Y = C - Y = D - Y = E - Y = F - Y = I - Y = J - Y = K - Y = M - Y = M - Y = N - Y = COP	456,420.9 683,881.8 32.253935 103.872222 MER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 448,540.9 453,815.2 456,469.0 RNER COOR	N	Y = X = LAT. = LONG. = ATES (NA A - X = B - X = C - X = D - X = E - X = G - X = H - X = I - X = J - X = K - X = M -	456,361.5 642,698.7 32.253811 103.871733 0684,967.0 684,964.0 684,961.1 684,948.3 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.0 683,631.0 683,598.6 683,598.6 683,583.6	E E E E E E E E E E E E E E E E E E E
Y =  X =  LAT. =  LONG. =  COP  A - Y =  B - Y =  C - Y =  D - Y =  E - Y =  F - Y =  G - Y =  I - Y =  L - Y =  M - Y =  N - Y =  COP  A - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 RNER COOR	N E °N °W RDIN N N N N N N N N N N N N N N N N N N	Y =  X =  LAT. =  LONG. =  ATES (NA  A - X =  B - X =  C - X =  D - X =  E - X =  F - X =  G - X =  H - X =  J - X =  K - X =  M - X =  N - X =  ATES (NA  A - X =	456,361.5 642,698.7 32.253811 103.871733 684,967.0 684,964.0 684,935.6 684,935.6 684,905.1 683,623.8 683,623.0 683,611.0 683,598.6 683,598.6 683,598.6 683,583.6 683,568.4 AD 27 NME)	E E E E E E E E E E E E E E E E E E E
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  F-Y =  H-Y =  J-Y =  K-Y =  M-Y =  N-Y =  COF  A-Y =  B-Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 RNER COOF 440,584.3 443,224.8	N E °N °W RDIN N N N N N N N N N N N N N N N N N N	Y =  X =  LAT. =  LONG. =  ATES (NA  A - X =  B - X =  C - X =  D - X =  E - X =  F - X =  G - X =  I - X =  I - X =  M - X =  M - X =  ATES (NA  A - X =  B - X =  A - X =  A - X =  A - X =  A - X =  A - X =  B - X =	456,361.5 642,698.7 32.253811 103.871733 <b>D 83 NME)</b> 684,967.0 684,964.0 684,935.6 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.8 683,623.8 683,633.6 683,598.6 683,598.6 683,583.6	E E E E E E E E E E E E E E E E E E E
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  F-Y =  H-Y =  J-Y =  K-Y =  N-Y =  COF  A-Y =  B-Y =  COF  A-Y =  B-Y =  C-Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 445,178.3 453,815.2 456,469.0 451,178.3 453,815.2 456,469.0 470,627.5 440,584.3 443,224.8	N E °N °W RDIN N N N N N N N N N N N N N N N N N N	Y =  X =  LAT. =  LONG. =  ATES (NA  A - X =  B - X =  C - X =  D - X =  E - X =  F - X =  G - X =  I - X =  I - X =  X - X =  M - X =  N - X =  ATES (NA  A - X =  B - X =  C - X =	456,361.5 642,698.7 32.253811 103.871733 AD 83 NME) 684,967.0 684,964.0 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.8 683,6363.6 683,583.6 683,583.6 683,583.6 683,583.6 683,583.6 683,783.3 643,783.3	N E S S S S S S S S S S S S S S S S S S
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  F-Y =  J-Y =  K-Y =  M-Y =  N-Y =  N-Y =  B-Y =  COF  A-Y =  B-Y =  COF  COF  COF  COF  COF  COF  COF  CO	456,420.9 683,881.8 32 253935 103,872222 8NER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 8NER COOF 440,584.3 443,224.8 445,859.8 448,495.9	N E N E N N N N N N N N N N N N N N N N	Y = LAT.	456,361.5 642,698.7 32.253811 103.871733 <b>XD 83 NME)</b> 684,967.0 684,964.0 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.8 683,6363.63.8 683,6363.64 <b>XD 27 NME)</b> 643,783.3 643,780.4 643,777.5	N E E E E E E E E E E E E E E E E E E E
Y =  X =  LAT. =  LONG. =  COF  A - Y =  B - Y =  C - Y =  D - Y =  E - Y =  F - Y =  J - Y =  J - Y =  M - Y =  N - Y =  COF  A - Y =  B - Y =  C - Y =  D - Y =  C - Y =  D - Y =  C - Y =  D - Y =  C - Y =  D - Y =  C - Y =  D - Y =  C - Y =  D - Y =  E - Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 RNER COOF 440,584.3 443,24.8 445,859.8 448,495.9 451,132.1	N	Y =  X =  LAT. =  LONG. =  A - X =  B - X =  C - X =  B - X =  C - X =  F - X =  G - X =  H - X =  I - X =  X - X =  M - X =  N - X =  A - X =  B - X =  C - X =  D - X =  G - X =  H - X =  C - X =  D - X =  C - X =  D - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  E - X =	456,361.5 642,698.7 32,253811 103,871733 ND 83 NME) 684,967.0 684,964.0 684,965.1 684,935.6 684,920.4 684,905.1 683,623.8 683,623.0 683,6363.6 683,583.6 683,583.6 683,780.4 643,777.5 643,764.9	N E E E E E E E E E E E E E E E E E E E
Y =  X =  LAT. =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  B-Y =  F-Y =  G-Y =  H-Y =  I-Y =  J-Y =  K-Y =  N-Y =  COF  A-Y =  B-Y =  COF  A-Y =  B-Y =  C-Y =  C	456,420.9 683,881.8 32.253935 103.872222 840,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 448,540.9 80,80,80,80,80,80,80,80,80,80,80,80,80,8	N	Y =  X =  LAT. =  LAT. =  LONG. =  A-X=  B-X=  C-X=  D-X=  E-X=  F-X=  H-X=  J-X=  K-X=  N-X=  M-X=  N-X=  A-X=  B-X=  D-X=  C-X=  D-X=  D-X=  C-X=  D-X=  C-X=  D-X=  C-X=  C	456,361.5 642,698.7 32.253811 103.871733 684,967.0 684,967.0 684,961.1 684,935.6 684,935.6 684,935.6 683,623.8 683,623.0 683,623.0 683,638.6 683,588.6 683,588.6 40 27 NME) 643,780.4 643,777.5 643,764.9 643,752.2 643,737.2	N
Y = X = LAT. = LAT. = LAT. = LAT. = LAT. = LAT. = S = LAT. = C-Y = B-Y = C-Y = L-Y = L-Y = L-Y = L-Y = L-Y = C-Y =	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 RNER COOR 440,584.3 443,224.8 445,859.8 444,859.9 451,132.1 453,767.9 456,418.1	N	Y =  X =  LAT. =  LONG. =  A-X=  B-X=  C-X=  D-X=  E-X=  G-X=  H-X=  J-X=  K-X=  N-X=  N-X=  A-X=  B-X=  C-X=  G-X=  H-X=  C-X=  C-X	456,361.5 642,698.7 32.253811 103.871733 684,967.0 684,964.0 684,961.1 684,935.6 684,935.6 684,920.4 684,905.1 683,623.8 683,623.0 683,611.0 683,598.6 683,583.6 683,583.6 683,583.6 683,583.6 683,780.4 643,777.5 643,764.9	
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  H-Y =  I-Y =  M-Y =  N-Y =  COF  A-Y =  COF  A-	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 445,939.9 4445,903.9 445,40.9 451,178.3 453,815.2 456,469.0 RNER COOF 440,584.3 443,224.8 445,859.8 448,495.9 451,132.1 453,767.9 456,418.1 440,568.4	N	Y =  X =  LAT. =  LONG. =  ATES (NA  A - X =  B - X =  C - X =  D - X =  E - X =  F - X =  G - X =  H - X =  L - X =  M - X =  N - X =  ATES (NA  A - X =  B - X =  C - X =  D - X =  F - X =  G - X =  C - X =  D - X =  E - X =  G - X =  D - X =  C - X =  D - X =  E - X =  G - X =  H - X =	456,361.5 642,698.7 32.253811 103.871733 684,967.0 684,964.0 684,961.1 684,935.6 684,905.1 683,623.8 683,623.8 683,623.0 683,611.0 683,583.6 683,583.6 683,583.6 683,583.6 683,783.3 643,780.4 643,777.5 643,764.9 643,764.2	
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  H-Y =  H-Y =  L-Y =  M-Y =  N-Y =  COF  A-Y =  B-Y =  COF  A	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 445,903.9 445,903.9 445,40.9 451,178.3 453,815.2 456,469.0 RNER COOF 440,584.3 443,224.8 445,859.8 448,495.9 451,132.1 453,767.9 456,418.1 440,568.4 443,209.2	N	Y =  X =  LAT. =  LAT. =  LONG. =  ATES (N/A  A - X =  B - X =  C - X =  D - X =  E - X =  H - X =  I - X =  M - X =  M - X =  M - X =  ATES (N/A  A - X =  B - X =  C - X =  C - X =  D - X =  ATES (N/A  A - X =  B - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =	456,361.5 642,698.7 32.253811 103.871733 3D 83 NME) 684,967.0 684,964.0 684,963.6 684,935.6 684,920.4 684,905.1 683,628.8 683,623.0 683,611.0 683,598.6 683,583.6 683,583.6 683,583.6 683,583.6 683,780.4 643,777.5 643,764.9 643,775.2 643,752.2 643,722.0 642,445.1	
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  H-Y =  I-Y =  M-Y =  N-Y =  COF  A-Y =  COF  A-	456,420.9 683,881.8 32.253935 103.872222 8NER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 445,409.9 451,178.3 453,815.2 456,469.0 8NER COOF 440,584.3 443,224.8 445,859.8 444,959.9 451,132.1 453,767.9 455,461.1 440,566.4 443,209.2 445,844.7	N	Y =	456,361.5 642,698.7 32.253811 103.871733 3D 83 NME) 684,964.0 684,964.0 684,965.1 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.8 683,623.8 683,623.0 683,611.0 683,598.6 683,583.6 683,583.6 683,780.4 643,775.5 643,764.9 643,775.2 643,737.2 643,737.2 642,445.1 642,440.2 642,449.5	
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  H-Y =  H-Y =  L-Y =  M-Y =  N-Y =  COF  A-Y =  B-Y =  COF  A	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 445,409.0 RNER COOF 440,584.3 443,224.8 445,859.8 448,495.9 451,132.1 453,767.9 456,418.1 440,568.4 440,568.4 440,568.4 440,568.4 443,209.2 445,843.7 440,568.4	N	Y =  X =  LAT. =  LAT. =  LONG. =  ATES (N/A  A - X =  B - X =  C - X =  D - X =  E - X =  H - X =  I - X =  M - X =  M - X =  M - X =  ATES (N/A  A - X =  B - X =  C - X =  C - X =  D - X =  ATES (N/A  A - X =  B - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =  C - X =  D - X =	456,361.5 642,698.7 32.253811 103.871733 3D 83 NME) 684,967.0 684,964.0 684,965.1 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.8 683,623.8 683,623.8 683,623.8 683,758.6 683,588.6 683,588.6 683,588.6 683,588.6 683,588.6 683,758.2 643,777.5 643,764.9 643,775.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 644,722.0 642,445.1 642,440.2 642,439.5 642,447.6	
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  D-Y =  E-Y =  H-Y =  J-Y =  M-Y =  N-Y =  COF  A-Y =  B-Y =  COF  A-Y =  B-Y =  COF  A-Y =  B-Y =  C-Y =  B-Y =  C-Y =  B-Y =  C-Y	456,420.9 683,881.8 32.253935 103.872222 8NER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 445,409.9 451,178.3 453,815.2 456,469.0 8NER COOF 440,584.3 443,224.8 445,859.8 444,959.9 451,132.1 453,767.9 455,461.1 440,566.4 443,209.2 445,844.7	N	Y =	456,361.5 642,698.7 32.253811 103.871733 D 83 NME) 684,967.0 684,964.0 684,961.1 684,935.6 684,935.6 683,623.8 683,623.0 683,631.0 683,598.6 683,588.4 D 27 NME) 643,780.4 643,777.5 643,764.9 643,737.2 643,722.0 642,445.1 642,440.2 642,439.5	
Y =  X =  LAT. =  LONG. =  COP  A - Y =  B - Y =  C - Y =  D - Y =  E - Y =  F - Y =  H - Y =  J - Y =  K - Y =  N - Y =  COP  A - Y =  B - Y =  COP  A - Y =  B - Y =  COP  A - Y =  B - Y =  C - Y =  D - Y =  F - Y =  C - Y =  D - Y =  X	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 RNER COOR 440,584.3 443,224.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 448,470.9 451,132.1 440,568.4 443,209.2 445,844.7 448,481.7 448,481.7 4451,118.9 453,755.8	N	Y = LAT.	456,361.5 642,698.7 32.253811 103.871733 684,967.0 684,964.0 684,961.1 684,948.3 684,935.6 684,955.1 683,623.8 683,623.8 683,623.0 683,611.0 683,598.6 683,588.4 AD 27 NME) 643,780.4 643,777.2 643,777.2 643,722.0 642,445.1 642,440.2 642,445.3 642,440.3	
Y =  X =  LAT. =  LONG. =  COF  A-Y =  B-Y =  C-Y =  B-Y =  F-Y =  H-Y =  J-Y =  M-Y =  N-Y =  COF  A-Y =  B-Y =  H-Y =  J-Y =  M-Y =  M-Y =  N-Y =  COF  A-Y =  B-Y =  C-Y =  B-Y =  C-Y =  B-Y =  C-Y =  D-Y =  E-Y =  F-Y =  G-Y =  L-Y =  L-	456,420.9 683,881.8 32.253935 103.872222 RNER COOF 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 456,477.6 440,627.5 443,268.4 445,903.9 445,40.9 451,178.3 453,815.2 456,469.0 RNER COOF 440,584.3 443,224.8 445,859.8 448,495.9 451,132.1 453,767.9 456,418.1 440,568.4 443,209.2 445,844.7 448,481.7 448,481.7	N	Y =  X =  LAT. =  LAT. =  LONG. =  A-X=  B-X=  C-X=  D-X=  E-X=  F-X=  H-X=  J-X=  M-X=  M-X=  M-X=  D-X=  B-X=  C-X=  H-X=  H-X=  J-X=  M-X=  M	456,361.5 642,698.7 32.253811 103.871733 D 83 NME) 684,967.0 684,964.0 684,961.1 684,935.6 684,935.6 683,623.8 683,623.0 683,631.0 683,598.6 683,588.4 D 27 NME) 643,780.4 643,777.5 643,764.9 643,737.2 643,722.0 642,445.1 642,440.2 642,439.5	
Y = X = LAT. = LAT. = LAT. = LONG. = COPA	456,420.9 683,881.8 32.253935 103.872222 RNER COOR 440,643.4 443,283.9 445,919.0 448,555.1 451,191.5 453,827.3 440,627.5 443,268.4 445,903.9 448,540.9 451,178.3 453,815.2 456,469.0 RNER COOR 440,584.3 443,224.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 445,859.8 448,470.9 451,132.1 440,568.4 443,209.2 445,844.7 448,481.7 448,481.7 4451,118.9 453,755.8	N	Y =  X =  LAT. =  LAT. =  LONG. =  A-X=  B-X=  C-X=  D-X=  E-X=  F-X=  J-X=  K-X=  N-X=  N-X=  A-X=  A	456,361.5 642,698.7 32.253811 103.871733 <b>XD 83 NME)</b> 684,967.0 684,964.0 684,965.1 684,935.6 684,920.4 684,905.1 683,623.8 683,623.8 683,623.8 683,623.8 683,623.8 683,623.8 683,783.3 643,780.4 644,777.5 643,764.9 643,775.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.2 643,737.3 642,445.1 642,440.2 642,439.5 642,439.5 642,439.5 642,439.5	

NMLC 0068431 NMLC 0068430 DRILLING PLAN: BLM COMPLIANCE (Supplement to BLM 3160-3)

ExxonMobil
Poker Lake Unit 22 DTD 181H
TD 27435 MD / 10930 TVD
SHL: 1106' FNL & 665' FWL , Section 22, T24S, R30E
BHL: 50' FNL & 1650' FWL , Section 3, T24S, R30E
Eddy County, NM

# 1. Geologic Name of Surface Formation

Quaternary

#### 2. Estimated Tops of Geological Markers & Depths of Anticipated Fresh Water, Oil or Gas

Formation	Well Depth	Water/Oil/Gas
RSLR	312'	Water
SLDO	681'	Water
SALT_B	3705'	Water
DLWR	3927'	Water/Oil/Gas
CRCN	4844'	Water/Oil/Gas
BSPG_LM	7750'	Water/Oil/Gas
AVLN	7870'	Water/Oil/Gas
AVLNL	8308'	Water/Oil/Gas
BSPG1_LM	8487'	Water/Oil/Gas
BSPG1_SS	8735'	Water/Oil/Gas
BSPG2_SH	8992'	Water/Oil/Gas
BSPG2_LM	9090'	Water/Oil/Gas
BSPG2_TB	9669'	Water/Oil/Gas
BSPG3_LM	9855'	Water/Oil/Gas
HRKY	10237'	Water/Oil/Gas
BSPG3_SH	10249'	Water/Oil/Gas
BSPG3_Red_Hills	10935'	Water/Oil/Gas
RED HILLS TARGET TOP	10948'	Water/Oil/Gas
RED HILLS TARGET TOP	10939'	Water/Oil/Gas

	INC °	Azimuth °	TVD (ft)	Y offset (ft)	
SHL	0	0	0	439454.20	641775.30
KOP	3.27	216.94	9860.79		
LP	89.89	0.11	10965.34	441254.86	642763.66
FTP	49.19	353.67	10787.51	439936.83	642723.71
LTP	90.47	0.83	10929.36	456134.04	642723.41
BHL	90.05	0.65	10928.60	456354.74	642725.68

# 3. Primary Casing Design Primary Design:

· ······o., 2 co.g										
Hole Size (in.)	MD	Casing TVD	OD Csg	Weight	Grade	Collar	New/Used	SF Burst	SF Collapse	SF Tension
12.25"	0' – 1050'	1050'	9-5/8"	47	J55	BTC	New	1.31	5.47	15.17
8.75"	0' - 3721.3'	3721.3'	7-5/8"	29.7	P-110	BTC	New	2.27	2.65	1.79
8.75"	3721.3' - 10235'	10235'	7-5/8"	29.7	L-80	BTC	New	1.65	1.91	2.10
6.75"	0' – 9977.1'	9977.1'	5-1/2"	23	P-110	Freedom	New	1.21	2.34	1.72
6.75"	9977.1' - 27415'	27290.4'	5-1/2"	23	P-110	Talon	New	1.21	2.21	1.86

Wellhead:

A multi-bowl wellhead system will be utilized. The well design chosen is: 3-String Slim / Non-Potash

Wellhead will be installed by manufacturer's representatives.

Manufacturer will monitor welding process to ensure appropriate temperature of seal.

#### 4. Cement Program

	Primary Cementing									
Hole Section	Slurry Type	No. Sacks	Density (ppg)	Yield (ft3/sack)	TOC (ft)	Casing Setting Depth (MD)	Excess (%)	Slurry Description		
Surface 1	Lead	200	12.8	1.95	30	1,050	-	Surface 1 Class H Lead Cement		
Surface 1	Tail	300	14.8	1.34	550	1,050	-	Surface 1 Class H Tail Cement		
Intermediate 1	Lead									
Intermediate 1	Tail	435	15.6	1.23	4880	10,235	50%	Intermediate 1 Class C Lead Cement		
Production 1	Lead									
Production 1	Tail	1370	13.2	1.38	6228	27,415	25%	Production 1 Class H Lead Cement		
				Remedial Cementing						
Casing	Slurry Type	No. Sacks	Density (ppg)	Yield (ft3/sack)	Cemente	Cemented Interval Excess (		Slurry Description		
Intermediate 1	Bradenhead Squeeze	800	14.8	1.51	30-4880		100%	Intermediate Class C Bradenhead Squeeze Cement		

# 5. Pressure Control Equipment

C!	_	Summary:
Section	-	Summarv:

Section 5 Summary:
Once the permanent WH is installed on the casing, the blow out preventer equipment (BOP) will consist of a minimum 5M Hydril and a minimum 10M triple Ram BOP.
All BOP testing will be done by an independent service company. Operator will Test as per 43CFR-3172
Requested Variances
4A) Offline Cementing Variance
XOM requests the option to offline cement and remediate (if needed) surface and intermediate casing strings where batch drilling is approved and if unplanned remediation is needed.
XOM will ensure well is static with no pressure on the csg annulus, as with all other casing strings where batch drilling operations occur before moving off the rig. Offline cement
operations will then be conducted after the rig is moved off the current well to the next well in the batch sequence. The TA cap will also be installed when applicable per wellhead manufacturer's procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.
illiditulacture s procedure and pressure inside the casing will be monitored via the valve on the FA cap as per standard batter of miling ops.
5A) Break Test Variance
A break testing variance is requested to ONLY test broken pressure seals on the BOP equipment when moving from wellhead to wellhead for the intermediate hole sections which is in compliance with API Standard 53. The maximum anticipated surface pressure is less than 4800psi and the deepest intermediate casing point does not penetrate the Wolfcamp
Formation.
5B) Flex Hose Variance  A variance is requested to allow use of a flex hose as the cheke line from the ROB to the Cheke Manifold. If this hose is used a sequential analysis catification and prossure text.
A variance is requested to allow use of a flex hose as the choke line from the BOP to the Choke Manifold. If this hose is used, a copy of the manufacturer's certification and pressure test chart will be kept on the rig. Attached is an example of a certification and pressure test chart. The manufacturer does not require anchors.
8A) Open Hole Logging Variance
Open hole logging will not be done on this well.
10A) Spudder Rig Variance
XOM requests the option to utilize a spudder rig (Atlas Copco RD20 or Equivalent) to set and cement surface casing.
10B) Batch Drilling Variance
XOM requests a variance to be able to batch drill this well. In doing so, XOM will set casing and ensure that the well is cemented properly (unless approval is given for offline cementing)
and the well is static. XOM will contact the BLM to skid the rig to drill the remaining wells on the pad. Once surface and intermediate strings are all completed, XOM will begin drilling the production hole on each of the wells.

#### 6. Mud Circulation System

INTERVAL	Hole Size	Mud Type	MW (ppq)	Viscosity (sec/qt)	Fluid Loss (cc)	
0' - 1050'	12.25"	Fresh Water	10	-	NC	Fresh Water
1050' - 10235'	8.75"	Brine / BDE	10-10.10	48	NC	Fluid type will be based upon on well conditions. A fully saturated system will be used across the salt interval.
10235' - 27415'	6.75"	ОВМ	10.10-11.15	48-50	NC - 20	

Section 6 Summary
-------------------

The necessary mud products for weight addition and fluid loss control will be on location at all times.

Pump viscous sweeps as needed for hole cleaning. Pump speed will be recorded on a daily drilling report after mudding up. An EDR (Electronic Drilling Recorder) will be used to detect changes in loss or gain of mud volume. A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Use available solids controls equipment to help keep mud weight down after mud up. Rig up solids control equipment to operate as a closed loop system.

#### 7. Auxiliary Well Control and Monitoring Equipment

Section	7	Summarv:
Section	•	Summarv:

A Kelly cock will be in the drill string at all times.

A full opening drill pipe stabbing valve having appropriate connections will be on the rig floor at all times.

H2S monitors will be on location when drilling below the 9-5/8" casing.

# 8. Logging, Coring and Testing Program

#### Section 8 Summary:

Open hole logging will not be done on this well.

#### 9. Abnormal Pressures and Temperatures / Potential Hazards

#### Section 9 Summary:

The estimated bottom hole temperature of 75F to 95F. No H2S is expected but monitors will be in place to detect any H2S occurrences. Should these circumstances be encountered the operator and drilling contractor are prepared to take all necessary steps to ensure safety of all personnel and environment. Lost circulation is possible throughout the well.

#### 10. Anticipated Starting Date and Duration of Operations

# Section 10 Summary:

Anticipated spud date will be after BLM approval. Move in operations and drilling is expected to take 40 days.

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 503253

# CONDITIONS

Operator:	OGRID:
XTO PERMIAN OPERATING LLC.	373075
6401 HOLIDAY HILL ROAD	Action Number:
MIDLAND, TX 79707	503253
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

#### CONDITIONS

Created I		Condition Date
dmcclu	re None	9/18/2025