

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources

Form C-104
Revised August 1, 2011

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-45931	⁵ Pool Name PURPLE SAGE; WOLFCAMP (GAS)	⁶ Pool Code 98220
⁷ Property Code 325469	⁸ Property Name POKER LAKE UNIT 17 TWR	⁹ Well Number 901H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
D	20	24S	31E		283	North	533	West	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	29	24S	31E		187	South	308	West	Eddy
¹² Lse Code F	¹³ Producing Method Code F	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date				

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
373075	XTO Permian Operating	Gas
34053	Plains Marketing, LP	Oil
005380	XTO Energy, Inc	Wtr

IV. Well Completion Data

²¹ Spud Date 5/2/2020	²² Ready Date 8/4/2021	²¹⁷³³ MD TD 11787 TVD	²¹⁷²¹ MD PBTB 11787 TVD	²⁵ Perforations 12,086- 21,569	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
17.5	13.375	822	705		
12.25	9.625	10751	3125		
8.5	5.5	21723	3825		
	2-7/8	11174			

V. Well Test Data

³¹ Date New Oil 8/8/21	³² Gas Delivery Date 8/10/21	³³ Test Date 8/10/21	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 0	³⁶ Csg. Pressure 0
³⁷ Choke Size	³⁸ Oil 1591	³⁹ Water 5216	⁴⁰ Gas 4330		⁴¹ Test Method Flowing
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Cassie Evans</i>			OIL CONSERVATION DIVISION		
Printed name: Cassie Evans			Approved by:		
Title: Regulatory Analyst			Title:		
E-mail Address: cassie.evans@exxonmobil.com			Approval Date:		
Date: 02/28/22	Phone: 432.218.3671				

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

AS-DRILLED PLAT

¹ API Number 30-015-45931	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 325469	⁵ Property Name POKER LAKE UNIT 17 TWR	⁶ Well Number 901H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC.	⁹ Elevation 3,492'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	20	24 S	31 E		283	NORTH	533	WEST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	29	24 S	31 E		187	SOUTH	308	WEST	EDDY

¹² Dedicated Acres 640	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY.

	SHL (NAD83 NME) Y = 440,273.3 X = 704,225.7 LAT. = 32.209291 °N LONG. = 103.806671 °W KOP (NAD83 NME) Y = 440,459.9 X = 704,060.0 LAT. = 32.209806 °N LONG. = 103.807203 °W FTP (NAD83 NME) Y = 439,822.8 X = 704,059.1 LAT. = 32.208055 °N LONG. = 103.807216 °W CORNER COORDINATES (NAD83 NME) A - Y = 440,553.0 N , X = 703,690.4 E B - Y = 440,561.0 N , X = 705,012.8 E C - Y = 437,910.5 N , X = 703,713.5 E D - Y = 437,919.8 N , X = 705,032.9 E E - Y = 435,272.1 N , X = 703,726.1 E F - Y = 435,280.3 N , X = 705,047.7 E G - Y = 432,631.2 N , X = 703,744.9 E H - Y = 432,639.3 N , X = 705,065.7 E I - Y = 429,989.7 N , X = 703,762.6 E J - Y = 429,997.9 N , X = 705,083.2 E SHL (NAD27 NME) Y = 440,214.5 X = 663,041.7 LAT. = 32.209168 °N LONG. = 103.806187 °W KOP (NAD27 NME) Y = 440,401.1 X = 662,876.0 LAT. = 32.209683 °N LONG. = 103.806719 °W FTP (NAD27 NME) Y = 439,763.9 X = 662,875.2 LAT. = 32.207931 °N LONG. = 103.806732 °W CORNER COORDINATES (NAD27 NME) A - Y = 440,494.1 N , X = 662,506.5 E B - Y = 440,502.0 N , X = 663,828.9 E C - Y = 437,851.6 N , X = 662,529.5 E D - Y = 437,860.9 N , X = 663,848.9 E E - Y = 435,213.3 N , X = 662,540.0 E F - Y = 435,221.5 N , X = 663,863.6 E G - Y = 432,572.5 N , X = 662,560.7 E H - Y = 432,580.6 N , X = 663,881.5 E I - Y = 429,931.0 N , X = 662,578.3 E J - Y = 429,939.2 N , X = 663,898.9 E	17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Cassie Evans</i> 02/28/22 Signature Date Cassie Evans Printed Name cassie.evans@exxonmobil.com E-mail Address 18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 8-9-2021 Date of Survey Signature and Seal of Professional Surveyor: <i>Mark Dillon Harp</i> MARK DILLON HARP 23786 Certificate Number JC 2018010199
--	---	---

Intent ☐ As Drilled ☒

API # 30-015-45931		
Operator Name: XTO PERMIAN OPERATING, LLC.	Property Name: POKER LAKE UNIT 17 TWR	Well Number 901H

Kick Off Point (KOP)

UL D	Section 20	Township 24S	Range 31E	Lot	Feet 95	From N/S FNL	Feet 369	From E/W FWL	County EDDY
Latitude 32.209806					Longitude 103.807203			NAD 83	

First Take Point (FTP)

UL D	Section 20	Township 24S	Range 31E	Lot	Feet 732	From N/S FNL	Feet 362	From E/W FWL	County EDDY
Latitude 32.208055					Longitude 103.807216			NAD 83	

Last Take Point (LTP)

UL M	Section 29	Township 24S	Range 31E	Lot	Feet 351	From N/S FSL	Feet 315	From E/W FWL	County EDDY
Latitude 32.181996					Longitude 103.807315			NAD 83	

Is this well the defining well for the Horizontal Spacing Unit? ☐

Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018



PO Box 4482, Midland, TX 79704 | 972-505-0433

MWD Survey Certification

State of New Mexico
County of Eddy

I, Dustin Trevino, certify that: I am employed by True Shot, LLC.; that I did on the day(s) of 5/2/2020 through 5/2/2020 conduct or supervise the taking of MWD surveys from a depth of 186 feet to a depth of 736 feet, that the data is true, correct, complete and within the limitations of the tool as set forth by True Shot, LLC; that I am authorized and qualified to make this report; that these surveys were conducted at the request of XTO Permian Operating LLC. for the Poker Lake Unit 17 TWR 901H (API No. 30-015-45931) located in Eddy County, New Mexico; and that I have reviewed this report and find that it conforms to the principles and procedures as set forth by True Shot, LLC.

A handwritten signature in black ink, appearing to read 'Dustin Trevino', is written over a horizontal line.

9/4/2020

Dustin Trevino
President

Cc: XTO Permian Operating



Oilfield Services, Central U.S. Land
Schlumberger Drilling and Measurements
Drilling Group
Geo Market Area: South West Texas Basin
7220 W I-H 20
Midland, Texas 79706
Phone : (432) 742-5400 (Main)
Fax : (432) 742-5606 (Shared)

July 15, 2020

XTO PERMIAN OPERATING LLC.
6401 HOLIDAY HILL ROAD, BUILDING
MIDLAND, TX 79707

Re:

20 24S 31E Eddy NM
N 32.209168 W -103.806186

CLIENT: XTO PERMIAN OPERATING LLC.
WELL: Poker Lake Unit 17 TWR 901H
FIELD: PURPLE SAGE-WOLFCAMP

RIG: Citadel 1
COUNTY: Eddy
API NO: 30-015-45931
JOB NO: 20MLE0459

Enclosed, please find the original copy of the survey performed on the referenced well by Drilling & Measurements, a division of Schlumberger Technology Corporation (P-5 No. 754900).

Other information required by your office is as follows.

<u>Name & Title of Surveyor</u>	<u>Drainhole Number</u>	<u>Surveyed Depths</u>	<u>Dates Performed</u>	<u>Type of Survey</u>
Musab Hassan FE	Poker Lake Unit 17 TWR 901H Original Hole	890.00 Ft 21679.00 Ft	May 21, 2020 July 12, 2020	XBOLT G2 Third Party Corrected

Oilfield Services, Central U.S. Land

Schlumberger Drilling and Measurements

Drilling Group

Geo Market Area: South West Texas Basin

7220 W I-H 20

Midland, Texas 79706

Phone : (432) 742-5400 (Main)

Fax : (432) 742-5606 (Shared)

Schlumberger

Well Reference:

20 24S 31E Eddy NM

N 32.209168 W -103.806186

I, Musab Hassan certify that; I am employed by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I did on the day(s) of May 21, 2020 through July 12, 2020, conduct or supervise the taking of the XBOLT G2 & Third Party Corrected surveys from a depth of 890.00 feet to a depth of 21679.00 feet referenced to driller's depth; that the data is true, correct, complete and within the limitations of the tool as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO PERMIAN OPERATING LLC. for the Poker Lake Unit 17 TWR 901H Well (Original Hole) API No. 30-015-45931 in New Mexico; and that I have reviewed this report and find that it conforms to the principals and procedures as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation.

By
Musab Hassan
FE



Subscribed and Sworn to before me this _____ day of _____ (month) _____ (yr)

My Commission expires:

Notary Public

(signature)

(County State)

Schlumberger

XTO Poker Lake Unit 17 TWR 901H 0 to 21733ft MD Survey Geodetic

Report
(Def Survey)

Report Date: July 12, 2020 - 04:45 PM
Client: XTO
Field: NM Eddy County (NAD 27)
Structure / Slot: XTO Poker Lake Unit 17 TWR 901H / New Slot
Well: Poker Lake Unit 17 TWR 901H
Borehole: Poker Lake Unit 17 TWR 901H
UWI / API#: Unknown / 30-015-45931
Survey Name: XTO Poker Lake Unit 17 TWR 901H 0 to 21733ft MD
Survey Date: May 18, 2020
Tort / AHD / DDI / ERD Ratio: 220.131' / 10673.547' ft / 6.637' / 0.906
Coordinate Reference System: NAD27 New Mexico State Plane, Eastern Zone, US Feet
Location Lat / Long: N 32° 12' 33.00393", W 103° 48' 22.27103"
Location Grid N/E Y/X: N 440214.500 ftUS, E 663041.700 ftUS
CRS Grid Convergence Angle: 0.2810 °
Grid Scale Factor: 0.99993954
Version / Patch: 2.10.818.0

Survey / DLS Computation: Minimum Curvature / Lubinski
Vertical Section Azimuth: 179.620 ° (Grid North)
Vertical Section Origin: 0.000 ft, 0.000 ft
TVD Reference Datum: RKB
TVD Reference Elevation: 3517.000 ft above MSL
Seabed / Ground Elevation: 3492.000 ft above MSL
Magnetic Declination: 6.647 °
Total Gravity Field Strength: 998.4298mgn (9.80665 Based)
Gravity Model: GARM
Total Magnetic Field Strength: 47784.564 nT
Magnetic Dip Angle: 59.872 °
Declination Date: June 27, 2020
Magnetic Declination Model: HDGM 2020
North Reference: Grid North
Grid Convergence Used: 0.2810 °
Total Corr Mag North->Grid North: 6.3657 °
Local Coord Referenced To: Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (ft/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
Surface Location	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	440214.50	663041.70	32.209168	-103.806186	0.00	0.00
	186.00	0.90	34.10	185.99	-1.20	1.21	0.82	0.48	440215.71	663042.52	32.209171	-103.806184	1.46	34.10
	371.00	0.90	32.70	370.97	-3.62	3.64	2.42	0.01	440218.14	663044.12	32.209178	-103.806179	4.37	33.63
	464.00	0.80	33.10	463.96	-4.77	4.79	3.17	0.11	440219.29	663044.87	32.209181	-103.806176	5.75	33.46
	555.00	0.70	34.90	554.95	-5.76	5.78	3.83	0.11	440220.28	663045.53	32.209184	-103.806174	6.94	33.54
	646.00	1.10	41.80	645.94	-6.86	6.89	4.73	0.45	440221.39	663046.43	32.209187	-103.806171	8.36	34.49
Last 3rd Party Survey	736.00	0.80	45.80	735.93	-7.93	7.97	5.76	0.34	440222.47	663047.46	32.209190	-103.806168	9.83	35.85
13-3/8" Casing	832.00	1.43	7.62	831.91	-9.58	9.63	6.40	0.98	440224.13	663048.10	32.209194	-103.806166	11.56	33.61
First SLB Survey	890.00	1.94	358.76	889.88	-11.28	11.33	6.47	0.98	440225.83	663048.17	32.209199	-103.806165	13.05	29.75
	982.00	1.74	6.57	981.84	-14.23	14.27	6.60	0.35	440228.77	663048.30	32.209207	-103.806165	15.72	24.82
	1076.00	1.78	9.56	1075.79	-17.08	17.13	7.01	0.11	440231.63	663048.70	32.209215	-103.806163	18.51	22.24
	1171.00	1.91	19.45	1170.74	-20.02	20.08	7.78	0.36	440234.58	663049.48	32.209223	-103.806161	21.53	21.18
	1266.00	1.56	19.18	1265.70	-22.73	22.79	8.73	0.37	440237.29	663050.43	32.209230	-103.806158	24.41	20.96
	1361.00	0.89	357.76	1360.69	-24.69	24.75	9.13	0.84	440239.25	663050.82	32.209236	-103.806157	26.38	20.24
	1455.00	1.04	0.12	1454.67	-26.27	26.33	9.10	0.17	440240.83	663050.80	32.209240	-103.806157	27.86	19.06
	1550.00	1.10	2.73	1549.65	-28.04	28.10	9.14	0.08	440242.60	663050.84	32.209245	-103.806156	29.55	18.02
	1644.00	2.27	342.58	1643.61	-30.72	30.78	8.63	1.38	440245.28	663050.33	32.209252	-103.806158	31.97	15.96
	1739.00	3.15	342.98	1738.50	-35.02	35.07	7.30	0.93	440249.57	663049.00	32.209264	-103.806162	35.83	11.76
	1834.00	3.29	344.08	1833.35	-40.15	40.19	5.79	0.16	440254.69	663047.49	32.209278	-103.806167	40.61	8.20
	1928.00	4.83	337.50	1927.11	-46.42	46.44	3.54	1.71	440260.94	663045.24	32.209295	-103.806174	46.58	4.35
	2022.00	6.04	329.28	2020.69	-54.35	54.35	-0.50	1.53	440268.85	663041.20	32.209317	-103.806187	54.35	359.47
	2117.00	7.05	326.90	2115.07	-63.57	63.53	-6.24	1.10	440278.03	663035.46	32.209342	-103.806206	63.84	354.39
	2212.00	6.70	325.89	2209.39	-73.08	73.00	-12.53	0.39	440287.50	663029.17	32.209369	-103.806226	74.07	350.26
	2307.00	6.33	326.16	2303.77	-82.06	81.94	-18.56	0.39	440296.44	663023.14	32.209393	-103.806245	84.02	347.24
	2401.00	6.12	325.48	2397.22	-90.53	90.37	-24.28	0.24	440304.87	663017.42	32.209416	-103.806263	93.58	344.96
	2496.00	7.11	326.55	2491.58	-99.65	99.45	-30.39	1.05	440313.95	663011.31	32.209442	-103.806283	103.99	343.01
	2591.00	6.93	324.41	2585.87	-109.26	109.02	-36.97	0.33	440323.51	663004.73	32.209468	-103.806304	115.12	341.27
	2685.00	6.40	323.67	2679.24	-118.13	117.85	-43.37	0.57	440332.34	662998.33	32.209492	-103.806325	125.58	339.79
	2780.00	6.04	321.60	2773.68	-126.36	126.03	-49.62	0.45	440340.52	662992.09	32.209515	-103.806345	135.45	338.51
	2875.00	6.82	320.84	2868.08	-134.69	134.32	-56.28	0.83	440348.81	662985.42	32.209538	-103.806366	145.64	337.27
	2969.00	5.85	325.66	2961.50	-143.02	142.61	-62.51	1.18	440357.10	662979.19	32.209561	-103.806386	155.70	336.33
	3064.00	5.27	327.42	3056.06	-150.73	150.28	-67.59	0.84	440364.77	662974.11	32.209582	-103.806403	165.78	335.78
	3158.00	6.93	324.25	3149.52	-159.00	158.52	-73.23	1.80	440373.01	662968.48	32.209604	-103.806421	174.62	335.21
	3252.00	6.53	324.28	3242.87	-167.99	167.46	-79.66	0.43	440381.95	662962.04	32.209629	-103.806441	185.44	334.56
	3347.00	6.05	322.57	3337.30	-176.39	175.82	-85.86	0.54	440390.31	662955.85	32.209652	-103.806461	195.67	333.97
	3442.00	5.73	325.50	3431.80	-184.31	183.71	-91.59	0.46	440398.20	662950.12	32.209674	-103.806480	205.27	333.50
	3536.00	6.18	330.16	3525.29	-192.60	191.96	-96.76	0.70	440406.45	662944.94	32.209697	-103.806498	214.97	333.25
	3631.00	5.55	328.23	3619.80	-200.98	200.31	-101.73	0.69	440414.79	662939.98	32.209720	-103.806512	224.66	333.08
	3726.00	5.09	326.86	3714.39	-208.44	207.74	-106.45	0.50	440422.23	662935.26	32.209740	-103.806527	233.42	332.87
	3820.00	3.89	332.56	3808.10	-214.79	214.06	-110.20	1.36	440428.55	662931.51	32.209758	-103.806539	240.76	332.76
	3915.00	3.17	334.82	3902.92	-220.04	219.30	-112.80	0.77	440433.78	662928.91	32.209772	-103.806548	246.61	332.78
	4010.00	2.52	321.07	3997.80	-224.06	223.30	-115.23	0.99	440437.79	662926.48	32.209783	-103.806555	251.28	332.70
	4105.00	1.74	328.62	4092.73	-226.93	226.16	-117.29	0.87	440440.64	662924.41	32.209791	-103.806562	254.76	332.59
	4199.00	1.72	332.09	4186.69	-229.40	228.62	-118.70	0.11	440443.11	662923.01	32.209798	-103.806567	257.60	332.56
	4294.00	1.51	321.96	4281.65	-231.66	230.87	-120.14	0.37	440445.35	662921.57	32.209804	-103.806571	260.25	332.51
	4389.00	1.28	319.66	4376.62	-233.46	232.66	-121.59	0.25	440447.15	662920.11	32.209809	-103.806576	262.52	332.41
	4484.00	1.15	324.16	4471.60	-235.05	234.24	-122.84	0.17	440448.73	662918.87	32.209813	-103.806580	264.50	332.33
	4579.00	0.99	326.06	4566.59	-236.51	235.70	-123.85	0.17	440450.18	662917.85	32.209817	-103.806583	266.26	332.28
	4674.00	1.05	327.85	4661.57	-237.94	237.11	-124.78	0.07	440451.60	662916.93	32.209821	-103.806586	267.94	332.25
	4769.00	0.90	325.74	4755.56	-239.28	238.45	-125.65	0.16	440452.94	662916.06	32.209825	-103.806589	269.53	332.21
	4862.00	0.98	329.05	4849.55	-240.59	239.75	-126.48	0.10	440454.24	662915.23	32.209828	-103.806591	271.19	332.19
	4957.00	1.04	334.57	4944.53	-242.07	241.23	-127.27	0.12	440455.71	662914.44	32.209833	-103.806594	272.74	332.18
	5052.00	0.15	57.03	5039.53	-242.92	242.08	-127.53	1.09	440456.56	662914.17	32.209835	-103.806595	273.62	332.22
	5147.00	0.04	116.39	5134.52	-242.97	242.13	-127.40	0.14	440456.61	662914.31	32.209835	-103.806594	273.60	332.25
	5242.00	0.19	299.81	5229.52	-243.03	242.19	-127.51	0.24	440456.68	662914.20	32.209835	-103.806595	273.71	332.23
	5336.00	0.11	291.00	5323.52	-243.14	242.30	-127.73	0.09	440456.79	662913.98	32.209835	-103.806595	273.90	332.20
	5431.00	0.19	181.52	5418.52	-243.02	242.18	-127.81	0.26	440456.66	662913.89	32.209835	-103.806596	273.84	332.18
	5525.00	0.82	155.92	5512.52	-242.25	241.41	-127.54	0.70	440455.89	662914.16	32.209833	-103.806595	273.03	332.15
	5620.00	0.86	145.51	5607.51	-241.03	240.20	-126.86	0.17	440454.68	662914.84	32.209830	-103.806593	271.64	332.16
	5715.00	0.79	151.37	5702.50	-239.87	239.04	-126.15	0.12	440453.52	662915.56	32.209827	-103.806590	270.28	332.18
	5810.00	0.72	149.17	5797.49	-238.78	237.95	-125.53	0.08	440452.43	662916.18	32.209824	-103.806588	269.03	332.19
	5905.00	0.75	148.65	5892.48	-237.73	236.91	-124.90	0.03	440451.39	662916.81	32.209821	-103.806586	267.81	332.20
	6000.00	0.77	153.56	5987.48	-236.62	235.80	-124.29	0.07	440450.29	662917.42	32.209818	-103.806584	266.55	332.21
	6094.00	0.93	162.56	6081.47	-235.33	234.51	-123.78	0.22	440448.99	662917.93	32.209814	-103.806583	265.17	332.17
	6189.00	0.86	169.39	6176.45	-233.89	233.07	-123.42	0.18	440447.56	662918.29				

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (ft/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	8938.00	0.81	228.20	8925.16	-197.46	196.69	-116.61	0.26	440411.18	662925.10	32.209710	-103.806560	228.66	329.34
	9032.00	0.94	222.92	9019.15	-196.46	195.68	-117.63	0.16	440410.17	662924.08	32.209707	-103.806564	228.32	328.99
	9127.00	0.62	219.75	9114.14	-195.50	194.72	-118.49	0.34	440409.21	662923.22	32.209705	-103.806566	227.94	328.68
	9222.00	0.67	223.22	9209.13	-194.70	193.92	-119.20	0.07	440408.41	662922.51	32.209702	-103.806569	227.62	328.42
	9317.00	0.75	227.70	9304.13	-193.89	193.09	-120.04	0.10	440407.58	662921.67	32.209700	-103.806571	227.36	328.13
	9411.00	0.87	238.16	9398.12	-193.10	192.30	-121.10	0.20	440406.79	662920.61	32.209698	-103.806575	227.26	327.80
	9506.00	1.14	247.90	9493.10	-192.38	191.57	-122.59	0.34	440406.06	662919.12	32.209696	-103.806580	227.43	327.38
	9601.00	1.82	262.24	9588.07	-191.83	191.01	-124.96	0.81	440405.50	662916.75	32.209694	-103.806587	228.25	326.81
	9695.00	2.22	260.36	9682.01	-191.35	190.50	-128.23	0.43	440404.99	662913.48	32.209693	-103.806598	229.64	326.05
	9790.00	2.22	263.31	9776.94	-190.85	189.98	-131.87	0.12	440404.47	662909.83	32.209692	-103.806610	231.26	325.23
	9885.00	2.20	273.40	9871.87	-190.77	189.87	-135.52	0.41	440404.36	662906.19	32.209691	-103.806622	233.28	324.48
	9980.00	2.29	265.75	9966.80	-190.76	189.84	-139.23	0.33	440404.33	662902.47	32.209691	-103.806634	235.43	323.74
	10074.00	1.90	265.76	10060.73	-190.53	189.59	-142.66	0.41	440404.07	662899.05	32.209691	-103.806645	237.27	323.04
	10169.00	2.00	283.78	10155.68	-190.83	189.87	-145.84	0.65	440404.35	662895.87	32.209692	-103.806655	239.41	322.47
	10264.00	1.79	279.06	10250.63	-191.48	190.49	-149.92	0.28	440404.88	662892.79	32.209693	-103.806665	241.79	321.98
	10453.00	1.26	271.14	10439.56	-192.02	191.00	-153.91	0.30	440405.49	662887.80	32.209695	-103.806681	245.29	321.14
	10547.00	1.14	251.12	10533.54	-191.75	190.72	-155.83	0.46	440405.21	662885.88	32.209694	-103.806687	246.28	320.75
	10641.00	1.13	242.27	10627.52	-191.02	189.98	-157.53	0.19	440404.47	662884.18	32.209692	-103.806693	246.80	320.33
9-5/8" Casing	10752.00	1.25	251.67	10738.50	-190.15	189.09	-159.65	0.20	440403.58	662882.06	32.209690	-103.806700	247.48	319.83
	10771.00	1.27	253.10	10757.49	-190.03	188.87	-160.05	0.20	440403.46	662881.66	32.209689	-103.806701	247.64	319.74
	10866.00	1.05	277.21	10852.48	-189.84	188.77	-161.92	0.56	440403.26	662879.79	32.209689	-103.806707	248.70	319.38
	10961.00	0.80	288.72	10947.46	-190.17	189.09	-163.41	0.33	440403.58	662878.30	32.209690	-103.806712	249.92	319.17
	11056.00	0.57	269.09	11042.46	-190.39	189.30	-164.51	0.34	440403.79	662877.20	32.209690	-103.806715	250.79	319.01
	11150.00	0.68	201.48	11136.09	-183.79	182.68	-167.58	9.02	440397.17	662874.13	32.209672	-103.806725	247.90	317.47
	11244.00	18.16	194.08	11222.42	-162.97	161.82	-173.76	10.23	440376.31	662867.96	32.209615	-103.806746	237.44	312.96
	11339.00	26.80	184.90	11315.15	-127.23	126.04	-179.20	9.79	440340.54	662862.51	32.209517	-103.806764	219.09	305.12
	11433.00	34.41	180.68	11396.00	-79.50	78.30	-181.33	8.41	440292.79	662860.38	32.209385	-103.806771	197.51	293.35
	11528.00	42.64	178.97	11470.26	-20.38	19.18	-181.07	8.73	440233.68	662860.64	32.209223	-103.806771	182.08	276.05
FTP [328' FNL, 350 FWL]	11622.00	46.07	181.61	11537.47	45.31	-46.51	-181.45	4.15	440167.99	662860.26	32.209042	-103.806774	187.31	255.62
	11623.00	41.28	181.64	11538.16	46.03	-47.23	-181.47	4.15	440167.27	662860.24	32.209040	-103.806774	187.51	255.41
	11718.00	51.28	178.15	11600.86	117.35	-118.55	-181.25	9.10	440095.95	662860.46	32.208944	-103.806774	216.58	236.81
	11813.00	58.24	175.31	11655.65	194.77	-195.95	-176.75	7.72	440018.56	662864.96	32.208832	-103.806761	222.69	222.05
	11893.00	64.07	175.72	11694.23	264.64	-265.78	-171.28	7.30	439948.74	662870.43	32.208440	-103.806744	316.19	212.80
	11940.00	68.09	177.92	11713.28	307.54	-308.67	-169.91	9.56	439905.85	662872.80	32.208322	-103.806737	351.86	208.69
	11967.00	74.58	179.23	11728.31	352.04	-353.16	-167.81	14.06	439861.37	662873.90	32.208199	-103.806734	391.00	205.42
	12034.00	79.46	179.44	11738.87	397.82	-398.94	-167.28	10.39	439815.59	662874.43	32.208073	-103.806734	432.59	202.75
	12081.00	84.64	179.27	11745.37	444.35	-445.47	-166.75	11.03	439769.06	662874.96	32.207946	-103.806733	475.66	200.52
	12130.00	89.84	178.79	11747.72	493.28	-494.39	-165.93	10.66	439720.14	662875.78	32.207811	-103.806731	521.49	198.55
	12176.00	90.04	179.68	11747.77	539.27	-540.38	-165.31	1.98	439674.15	662876.40	32.207685	-103.806729	565.10	197.01
	12230.00	91.49	181.70	11747.05	593.26	-594.37	-165.96	4.60	439620.17	662875.75	32.207536	-103.806732	617.10	195.60
	12288.00	91.09	181.29	11745.75	651.21	-652.33	-167.47	0.99	439562.21	662874.24	32.207377	-103.806738	673.49	194.40
	12382.00	90.59	181.66	11744.37	745.15	-746.29	-169.89	0.66	439468.25	662871.82	32.207119	-103.806747	765.39	192.82
	12477.00	90.62	181.47	11743.36	840.09	-841.25	-172.49	0.20	439373.30	662869.22	32.206858	-103.806757	858.75	191.59
	12572.00	90.15	181.48	11742.73	935.04	-936.22	-174.93	0.49	439278.34	662866.78	32.206597	-103.806767	952.42	190.58
	12666.00	89.49	181.75	11743.02	1028.98	-1030.18	-177.58	0.76	439184.38	662864.13	32.206338	-103.806777	1045.37	189.78
	12760.00	89.51	181.98	11743.84	1122.90	-1124.13	-180.64	0.25	439090.44	662861.07	32.206080	-103.806788	1138.55	189.13
	12854.00	89.85	182.32	11744.37	1216.81	-1218.06	-184.17	0.51	438996.52	662857.54	32.205822	-103.806801	1231.90	188.60
	12949.00	89.81	181.76	11744.53	1311.73	-1313.00	-185.55	0.60	438901.68	662854.16	32.205561	-103.806814	1326.33	188.13
	13043.00	90.14	180.86	11744.46	1405.68	-1406.97	-189.70	0.98	438807.82	662852.01	32.205303	-103.806822	1421.66	187.58
	13138.00	90.56	180.27	11743.88	1500.67	-1501.97	-190.64	0.76	438712.63	662851.08	32.205042	-103.806826	1514.01	187.23
	13232.00	90.65	179.43	11742.89	1594.66	-1595.96	-190.39	0.90	438618.64	662851.32	32.204783	-103.806827	1607.27	186.80
	13326.00	91.02	179.37	11741.52	1688.65	-1689.94	-189.41	0.40	438524.66	662852.31	32.204525	-103.806825	1700.52	186.39
	13421.00	91.16	180.03	11739.71	1783.63	-1784.92	-188.91	0.71	438429.69	662852.80	32.204264	-103.806825	1794.89	186.04
	13515.00	91.11	179.48	11737.85	1877.61	-1878.90	-188.51	0.59	438335.71	662853.21	32.204006	-103.806826	1888.34	185.73
	13610.00	90.35	179.99	11736.64	1972.60	-1973.90	-188.07	0.96	438240.73	662853.65	32.203745	-103.806826	1982.83	185.44
	13799.00	90.25	179.68	11735.65	2161.60	-2162.89	-187.52	0.17	438051.74	662854.19	32.203225	-103.806827	2171.01	184.96
	13893.00	91.49	179.77	11734.22	2255.59	-2256.88	-187.07	1.32	437957.76	662854.64	32.202967	-103.806827	2264.62	184.74
	13988.00	89.90	179.32	11733.07	2350.58	-2351.86	-186.32	1.74	437862.78	662855.39	32.202706	-103.806826	2359.23	184.53
	14082.00	89.76	179.93	11733.35	2444.58	-2445.86	-185.70	0.67	437768.79	662856.01	32.202447	-103.806825	2452.90	184.34
	14177.00	88.98	179.78	11734.39	2539.57	-2540.85	-185.46	0.84	437673.80	662856.25	32.202186	-103.806826	2547.61	184.17
	14366.00	88.53	180.54	11738.50	2728.51	-2729.81	-185.99	0.47	437484.86	662855.72	32.201667	-103.806831	2736.14	183.90
	14461.00	88.58	181.05	11740.89	2823.46	-2824.77	-187.31	0.54	437389.91	662854.41	32.201406	-103.806837	2830.97	183.79
	14556.00	88.29	179.94	11743.49	2918.42	-2919.73	-188.13	1.21	437294.96	662853.58	32.201145	-103.806841	2925.78	183.69
	14651.00	87.95	179.65	11745.20	3013.40	-3014.70	-187.21	1.77	437199.98	662854.50	32.200894	-103.806839	3020.51	183.55
	14745.00	89.80	179.84	11745.57	3107.39	-3108.70	-186.21	0.98	437106.00	662855.50	32.200625	-103.806838	3114.27	183.43
	14840.00	89.51	180.25	11746.07	3202.39	-3203.70	-186.29	0.59	437011.00	662855.42	32.200364	-103.806839	3209.11	183.33
	14935.00	90.24	179.86	11746.28	3297.39	-3298.69	-186.38	0.87	436916.01	662855.33	32.200103	-103.806841	3303.96	183.23
	15029.00	90.49	180.77	11745.68	3391.38	-3392.69	-186.90	1.00	436822.02	662854.81	32.199845	-103.806844	3397.83	183.15
	15124.00	90.31	180.02	11745.02	3486.36	-3487.68	-187.55	0.						

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	19947.00	89.84	178.68	11771.04	8308.23	-8309.38	-145.65	0.32	431905.64	662896.06	32.186330	-103.806789	8310.65	181.00
	20041.00	89.95	177.72	11771.22	8402.20	-8403.33	-142.70	1.03	431811.70	662899.01	32.186071	-103.806781	8404.54	180.97
	20136.00	90.00	178.01	11771.26	8497.15	-8498.26	-139.16	0.31	431716.77	662902.55	32.185810	-103.806771	8499.40	180.94
	20230.00	90.52	179.29	11770.83	8591.14	-8592.23	-136.94	1.47	431622.80	662904.77	32.185552	-103.806765	8593.33	180.91
	20325.00	88.54	178.88	11771.61	8686.12	-8687.21	-135.43	2.13	431527.83	662906.28	32.185291	-103.806762	8688.27	180.89
	20419.00	89.71	179.76	11773.05	8780.11	-8781.19	-134.31	1.56	431433.85	662907.40	32.185033	-103.806760	8782.22	180.88
	20514.00	89.76	180.09	11773.49	8875.11	-8876.19	-134.19	0.35	431338.86	662907.52	32.184771	-103.806761	8877.21	180.87
	20607.00	90.11	179.78	11773.59	8968.11	-8969.19	-134.08	0.50	431245.87	662907.63	32.184516	-103.806762	8970.19	180.86
	20702.00	89.33	180.47	11774.06	9063.10	-9064.19	-134.29	1.10	431150.88	662907.42	32.184255	-103.806764	9065.18	180.85
	20796.00	89.36	182.02	11775.13	9157.05	-9158.16	-136.33	1.65	431056.91	662905.38	32.183996	-103.806772	9159.17	180.85
	20891.00	89.31	181.16	11776.23	9251.99	-9253.11	-138.97	0.91	430961.96	662902.74	32.183735	-103.806782	9254.16	180.86
	20985.00	89.25	181.25	11777.41	9345.95	-9347.09	-140.94	0.12	430868.00	662900.77	32.183477	-103.806790	9348.15	180.86
	21080.00	89.20	181.04	11778.70	9440.90	-9442.06	-142.84	0.23	430773.03	662898.87	32.183216	-103.806798	9443.14	180.87
	21174.00	89.35	180.94	11779.89	9534.87	-9536.04	-144.46	0.19	430679.06	662897.25	32.182958	-103.806804	9537.13	180.87
	21269.00	89.55	181.01	11780.80	9629.84	-9631.02	-146.08	0.22	430584.08	662895.63	32.182697	-103.806811	9632.13	180.87
	21364.00	89.22	181.35	11781.82	9724.80	-9725.99	-148.04	0.50	430489.11	662893.67	32.182436	-103.806819	9727.12	180.87
	21459.00	89.46	180.95	11782.91	9819.76	-9820.97	-149.94	0.49	430394.15	662891.77	32.182175	-103.806827	9822.11	180.87
	21553.00	88.31	180.39	11784.74	9913.72	-9914.94	-151.04	1.36	430300.18	662890.67	32.181916	-103.806832	9916.09	180.87
LTP [330' FSL, 314 FWL]	21590.00	88.75	181.17	11785.69	9950.70	-9951.92	-151.55	2.43	430263.20	662890.16	32.181815	-103.806834	9953.08	180.87
	21648.00	89.45	182.40	11786.60	10008.65	-10009.89	-153.35	2.43	430205.24	662888.35	32.181655	-103.806841	10011.06	180.88
Last Survey	21679.00	89.63	182.36	11786.85	10039.61	-10040.86	-154.64	0.59	430174.27	662887.07	32.181570	-103.806845	10042.05	180.88
Projection to Bit [186' FSL, 308' FWL]	21733.00	89.63	182.36	11787.20	10093.55	-10094.81	-156.87	0.00	430120.32	662884.84	32.181422	-103.806853	10096.03	180.89

Survey Type:

Def Survey

Survey Error Model:
Survey Program:

ISCWSA Rev 0 *** 3-D 95.000% Confidence 2.7955 sigma

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
Surface	1	0.000	25.000	1/98.425	17.500	13.375	NAL_MWD-NON_SLB-Depth Only	Poker Lake Unit 17 TWR 901H / XTO Poker Lake Unit 17 TWR 901H 0 to 21733ft MD
Surface	1	25.000	25.000	Act Stns	17.500	13.375	NAL_MWD-NON_SLB-Depth Only	Poker Lake Unit 17 TWR 901H / XTO Poker Lake Unit 17 TWR 901H 0 to 21733ft MD
Surface	1	25.000	736.000	Act Stns	17.500	13.375	NAL_MWD-NON_SLB	Poker Lake Unit 17 TWR 901H / XTO Poker Lake Unit 17 TWR
Intermediate	1	736.000	10752.000	Act Stns	12.250	9.625	NAL_MWD_1.0_DEG	Poker Lake Unit 17 TWR 901H / XTO Poker Lake Unit 17 TWR
Production Lateral	1	10752.000	21733.000	Act Stns	8.500	7.000	NAL_MWD_IFR1+MS	Poker Lake Unit 17 TWR 901H / XTO Poker Lake Unit 17 TWR

...Poker Lake Unit 17 TWR 901H\XTO Poker Lake Unit 17 TWR 901H 0 to 21733ft MD

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Well Name: POKER LAKE UNIT 17
TWR

Well Location: T24S / R31E / SEC 20 /
NWNW / 32.209291 / -103.806671

County or Parish/State: EDDY /
NM

Well Number: 901H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMLC0061705B,
NMLC061705B

Unit or CA Name: POKER LAKE

Unit or CA Number:
NMNM071016X, NMNM71016X

US Well Number: 3001545931

Well Status: Drilling Shut In

Operator: XTO PERMIAN
OPERATING LLC

Subsequent Report

Sundry ID: 2658046

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 02/19/2022

Time Sundry Submitted: 02:49

Date Operation Actually Began: 08/04/2021

Actual Procedure: XTO Permian Operating, LLC respectfully submits the Completions Sundry for the well above. KOP depth @ , PBTD @ . Run RCB/GR/CCL pressure test 5.5 in csg to 8321 psi for 30 min tested good. Perf and frac 68 stages, 1088 total shot, from 12086 to 21569 using 517744 bbl of fluid and 23829686 lbs proppant. Tag and drill out plug. Run 2-7/8 L80 6.5# tbgr set at 11174 pkr depth @ 11160. Ready date is 08/04/21, First production date 08/08/21.

Well Name: POKER LAKE UNIT 17
TWR**Well Location:** T24S / R31E / SEC 20 /
NWNW / 32.209291 / -103.806671**County or Parish/State:** EDDY /
NM**Well Number:** 901H**Type of Well:** OIL WELL**Allottee or Tribe Name:****Lease Number:** NMLC0061705B,
NMLC061705B**Unit or CA Name:** POKER LAKE**Unit or CA Number:**
NMNM071016X, NMNM71016X**US Well Number:** 3001545931**Well Status:** Drilling Shut In**Operator:** XTO PERMIAN
OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: CASSIE EVANS**Signed on:** FEB 19, 2022 02:49 PM**Name:** XTO PERMIAN OPERATING LLC**Title:** Regulatory Analyst**Street Address:** 6401 Holiday Hill Road, Bldg 5**City:** Midland**State:** TX**Phone:** (432) 218-3671**Email address:** CASSIE.EVANS@EXXONMOBIL.COM

Field Representative

Representative Name:**Street Address:****City:****State:****Zip:****Phone:****Email address:**

Submit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505				State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised April 3, 2017											
WELL COMPLETION OR RECOMPLETION REPORT AND LOG																			
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name POKER LAKE UNIT 17 TWR 6. Well Number: 901H											
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER																			
8. Name of Operator XTO PERMIAN OPERATING LLC.								9. OGRID 373075											
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707								11. Pool name or Wildcat PURPLE SAGE;WOLFCAMP (GAS)											
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County									
Surface:	D	20	24S	31E		283	North	533	West	Eddy									
BH:	M	29	24S	31E		187	South	308	West	Eddy									
13. Date Spudded 5/2/2020	14. Date T.D. Reached 7/12/2020		15. Date Rig Released 7/14/2020			16. Date Completed (Ready to Produce) 8/4/2021			17. Elevations (DF and RKB, RT, GR, etc.) 3493 GL										
18. Total Measured Depth of Well 21,733			19. Plug Back Measured Depth 21,721			20. Was Directional Survey Made? Yes			21. Type Electric and Other Logs Run CBL										
22. Producing Interval(s), of this completion - Top, Bottom, Name 12,086- 21,569 PURPLE SAGE;WOLFCAMP (GAS)																			
23. CASING RECORD (Report all strings set in well)																			
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED									
13 3/8"		68.0		822'		17 1/2"		705											
9 5/8"		40.0		10,751'		12 1/4"		3125											
5 1/2"		23.0		21,723'		8 1/2"		3825											
24. LINER RECORD						25. TUBING RECORD													
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET												
					2 7/8"L80 6.5#	11,174	11,160												
26. Perforation record (interval, size, and number) 12,086- 21,569 2spf, 1088 Total Shots 68 stages						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>12,086- 21,569</td> <td>517,744 bbl fluid + 23,829,686 lbs proppant</td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </table>						DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	12,086- 21,569	517,744 bbl fluid + 23,829,686 lbs proppant				
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED																		
12,086- 21,569	517,744 bbl fluid + 23,829,686 lbs proppant																		
28. PRODUCTION																			
Date First Production 8/8/21		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>)					Well Status (<i>Prod. or Shut-in</i>) Producing												
Date of Test 8/10/21	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 1591	Gas - MCF 4330	Water - Bbl. 5216	Gas - Oil Ratio 2722												
Flow Tubing Press. 0	Casing Pressure 0	Calculated 24-Hour Rate	Oil - Bbl. 1591	Gas - MCF 4330	Water - Bbl. 5216	Oil Gravity - API - (<i>Corr.</i>)													
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>) Sold									30. Test Witnessed By										
31. List Attachments C-104 NW, C-102 & Supplement , Directional Survey (Log uploaded to NMOCD)																			
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.									33. Rig Release Date:										
34. If an on-site burial was used at the well, report the exact location of the on-site burial:																			
Latitude				Longitude				NAD83											
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief																			
Signature				Printed Name Cassie Evans		Title Regulatory Analyst			Date 02/28/22										
E-mail Address cassie.evans@exxonmobil.com																			

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 897'	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 4,037'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinbry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 4,281'	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T. Rustler 537'	T. Entrada	
T. Wolfcamp 11,437'	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 84729

ACKNOWLEDGMENTS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 84729
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 84729

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 84729
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	File 3160-4 Completion Report within 10 days of BLM approval.	12/16/2025