

<b>Well Name:</b> RED TANK 24 FED COM	<b>Well Location:</b> T22S / R32E / SEC 24 / NENW / 32.3827698 / -103.6299184	<b>County or Parish/State:</b> LEA / NM
<b>Well Number:</b> 01	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM87268	<b>Unit or CA Name:</b> 1 RED TANK 24 FED COM	<b>Unit or CA Number:</b> NMNM105328
<b>US Well Number:</b> 300253503500S1	<b>Operator:</b> EOG RESOURCES INCORPORATED	

**Notice of Intent**

**Sundry ID:** 2890487

**Type of Submission:** Notice of Intent

**Type of Action:** Plug and Abandonment

**Date Sundry Submitted:** 01/13/2026

**Time Sundry Submitted:** 01:55

**Date proposed operation will begin:** 01/24/2026

**Procedure Description:** EOG PROPOSES TO PLUG THIS WELL USING THE ATTACHED PROCEDURE. CURRENT AND PROPOSED WELLBORE DIAGRAMS ARE ALSO ATTACHED.

**Surface Disturbance**

**Is any additional surface disturbance proposed?:** No

**NOI Attachments**

**Procedure Description**

Red\_Tank\_24\_Fed\_Com\_1\_PA\_WBD\_20260113135435.pdf

Red\_Tank\_24\_Fed\_Com\_1\_PA\_Prog\_\_20260113135417.pdf

Red\_Tank\_24\_Fed\_Com\_1\_PA\_current\_WBD\_20260113135408.pdf

Well Name: RED TANK 24 FED COM

Well Location: T22S / R32E / SEC 24 / NENW / 32.3827698 / -103.6299184

County or Parish/State: LEA / NM

Well Number: 01

Type of Well: CONVENTIONAL GAS WELL

Allottee or Tribe Name:

Lease Number: NMNM87268

Unit or CA Name: 1 RED TANK 24 FED COM

Unit or CA Number: NMNM105328

US Well Number: 300253503500S1

Operator: EOG RESOURCES INCORPORATED

### Conditions of Approval

#### Specialist Review

Red\_Tank\_24\_Fed\_Com\_1\_Sundry\_ID\_2890487\_P\_A\_20260318150056.pdf

### Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: MORGAN HRNCIRIK

Signed on: JAN 13, 2026 01:54 PM

Name: EOG RESOURCES INCORPORATED

Title: Sr. Regulatory Administrator

Street Address: 5509 CHAMPIONS DRIVE

City: MIDLAND

State: TX

Phone: (432) 257-2428

Email address: MORGAN\_HRNCIRIK@EOGRESOURCES.COM

### Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

### BLM Point of Contact

BLM POC Name: LONG VO

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5759885402

BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved

Disposition Date: 03/18/2026

Signature: Long Vo

Form 3160-5  
(October 2024)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB No. 1004-0220  
Expires: October 31, 2027

**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**

5. Lease Serial No.
6. If Indian, Allottee or Tribe Name

<b>SUBMIT IN TRIPLICATE - Other instructions on page 2</b>		7. If Unit of CA/Agreement, Name and/or No.
1. Type of Well <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		8. Well Name and No.
2. Name of Operator		9. API Well No.
3a. Address	3b. Phone No. (include area code)	10. Field and Pool or Exploratory Area
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)		11. Country or Parish, State

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)	Title	
Signature	Date	

**THE SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

## GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

## SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

*Item 13*: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

## Additional Information

### Location of Well

0. SHL: NENW / 660 FNL / 2150 FWL / TWSP: 22S / RANGE: 32E / SECTION: 24 / LAT: 32.3827698 / LONG: -103.6299184 ( TVD: 0 feet, MD: 0 feet )

BHL: NENW / 660 FNL / 2150 FWL / TWSP: 22S / SECTION: / LAT: 0.0 / LONG: 0.0 ( TVD: 0 feet, MD: 0 feet )

Well Name: Red Tank 24 Fed Com 1  
 Location: 660 FNL 2150 FWL  
 County: Lea, NM  
 Lat/Long: 32.3827095,-103.6300125 NAD83  
 API #: 30-025-35035  
 Spud Date: 6/26/00  
 Compl. Date: 9/26/00



**Formation Tops**

Top of Salt	900
Bottom of Salt	4,728
Delaware	4,838
Bone Spring	9,010
Wolfcamp	11,940
Strawn	13,530
Morrow	14,358

**Proposed Wellbore Diagram:**

KB:  
GL: 3753

17-1/2" Hole

-----  
 13-3/8" 48# & 68# H-40 STC @ 1,010'  
 Cmt w/ 750 sx Class C (circ) to surface

12.25" Hole

Cement to Surface  
 9-5/8" 40#HCK-55 LTC @ 4,790'  
 Cmt w/ 1580 sx Class C (circ) to surface

-----

TOC 4580 - calculated

8.75" Hole

7-5/8" 39# P110 LTC to 12,200'  
 Cmt w/ 890 Class C. Test CSG 5,000 psi good


-----

Liner top @ 11,706'

No CBL or temp survey  
 drilled cement out 100' above liner top

5" CSG 20.63# & 18# P110 STL to 15,346'  
 320 sx Class C cmt

6-1/2" Vertical to 15,100'



Spot 35 sxs Class C cement to surface  
 Perf @ 100'

WOC & Tag  
 Perf @ 1,050' & spot 70 sxs class C cement to 830'

No WOC spacer plug  
 Perf @ 3,000' & spot 40 sxs class C cement

WOC & Tag  
 Covers Delaware, bottom of salt, salt string shoe  
 Spot 50 sxs Class C cement @ 4,888' to 4,580'

Spacer plug no tag  
 Spot 40 sxs Class H Cement @ 7,200' to 6,980

WOC & Tag  
 Covers Bone Springs  
 Spot 25 sxs Class H cement from 9,836' to 9,616'

WOC & Tag  
 Covers Int Shoe, WFMP, Liner Top  
 Spot 80 sxs Class H Cement from 12,250' to 11,554'

3-1/2" tbg initial to 11,711'

WOC & Tag  
 Spot 25 sxs Class H Cement from 13,580' to 13,285'

Run CBL to verify cement

WOC & Tag  
 Spot 25 sxs Class H Cement from 14,468' to 14,314'  
 Set CIBP @ 14,468', test to 500 psi  
 14,508'-14,534' - 4 shots/ft - 144 Holes  
 Perforate 14,787' to 14,803' 6 shots/ft - 96 Holes  
 Perforate 14,882' to 14,898 6 shots/ft - 96 Holes

**Not to Scale**  
 By: CC 1/8/26

**Red Tank 24 Fed Com 1 P&A  
Capital AFE#**

Well Name	Red Tank 24 Federal Com 1 P&A				
Surface Location	32.3827095,-103.6300125 NAD83			AFE/Sub Code	/231
RKB – Sea Level		Area/Field	Red Tank	Spud Date	1/9/01
G.L. Elevation	3,753	County/Province	Lea	Original Rig Contractor	-
API	<b>30-025-35035</b>	State / Country	NM	Formation	Atoka
Comp Date	<b>9/26/26</b>	Total MD	15,100'	Top Perf	14,508'
KOP	-	Average Lateral TVD	-	Wellhead MFG	Weatherford

STRING NAME	STRING OD	STRING WEIGHT	DESCRIPTION	FINAL DEPTH
SURFACE	13.325	48 & 68	13-3/8 H40	1,010'
Salt String	9.625	40	9-5/8 HCK-55 LTC	4,790'
Intermediate	7.625	39	7 P110 LTC	12,200'
Liner	5.0	18 & 20	5 P110 STL	11,706' to 15,100'


**Summary of Procedure:** LD TBG, Set CIBP, Run CBL/Gyro, Spot plugs

**PROCEDURE:**

1. Notify state 24 hours before beginning work.
2. MIRU & Kill well.
3. ND/NU WH/BOP
4. LD Entire string of 3-1/2" Production TBG. Please have workstring on location.
5. RIH & set CIBP @ 14,468' (50' above top of first perf). Test to 500 psi.
6. Run gyro/CBL tandem to verify all cement and surveys.
7. TIH & spot 25 sxs Class H cement from 14,468' to 14,314'. WOC & Tag
8. TOOH to 13,580'
9. Spot 25 sxs Class H cement from 13,580' to 13,285'. Plug covers the Strawn. WOC & Tag.
10. TOOH to 12,250'
11. Spot 80 sxs Class H cement from 12,250' to 11,554'. Covers Int. Shoe, WFMP & liner top. WOC & Tag
12. TOOH to 9,836'
13. Spot 25 sxs Class H cement from 9,836' to 9,616'. Covers the bone springs. WOC & Tag
14. TOOH to 7,200'.
15. Spot 40 sxs Class H cement from 7,200' to 6,980'. Spacer plug no tag
16. TOOH to 4,888'
17. Spot 50 sxs Class C cement @ 4,888' to 4,580'. Covers delaware, bottom of salt, salt string shoe. WOC & Tag
18. TOOH
19. RIH & perf @ 3,000'. POOH
20. TIH w/ packer and squeeze 40 sxs class c cement. Spacer plug no tag
21. TOOH



- 
- 22. RIH & perf @ 1,050'. POOH
  - 23. TIH w/ packer & squeeze 70 sxs Class C cement to 830'. Covers top of salt and surface shoe. WOC & tag
  - 24. TOOH
  - 25. RIH & perf @ 100'
  - 26. TIH w/ packer & squeeze 35 sxs Class C cement to surface.
  - 27. Dig out cellar, cut off wellhead and verify cement behind all casing strings.
  - 28. Install dry hole marker, clean location and RDMO.

Production Engineer:  Date: 1/9/26

Chris Caskey

Well Name: Red Tank 24 Fed Com 1  
 Location: 660 FNL 2150 FWL  
 County: Lea, NM  
 Lat/Long: 32.3827095,-103.6300125 NAD83  
 API #: 30-025-35035  
 Spud Date: 6/26/00  
 Compl. Date: 9/26/00





**Formation Tops**

Top of Salt	900
Bottom of Salt	4,728
Delaware	4,838
Bone Spring	9,010
Wolfcamp	11,940
Strawn	13,530
Morrow	14,358

**Current Wellbore Diagram:**

KB:  
 GL: 3753



3-1/2" tbg initial to 11,711'

14,508'-14,534' - 4 shots/ft - 144 Holes  
 Perforate 14,787 to 14,803' 6 shots/ft - 96 Holes  
 Perforate 14,882' to 14,898 6 shots/ft - 96 Holes

**Not to Scale**  
 By: CC 1/8/26

<b>Well Name:</b> RED TANK 24 FED COM	<b>Well Location:</b> T22S / R32E / SEC 24 / NENW / 32.3827698 / -103.6299184	<b>County or Parish/State:</b> LEA / NM
<b>Well Number:</b> 01	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM87268	<b>Unit or CA Name:</b> 1 RED TANK 24 FED COM	<b>Unit or CA Number:</b> NMNM105328
<b>US Well Number:</b> 300253503500S1	<b>Operator:</b> EOG RESOURCES INCORPORATED	

**Notice of Intent**

**Sundry ID:** 2890487

**Type of Submission:** Notice of Intent

**Type of Action:** Plug and Abandonment

**Date Sundry Submitted:** 01/13/2026

**Time Sundry Submitted:** 01:55

**Date proposed operation will begin:** 01/24/2026

**Procedure Description:** EOG PROPOSES TO PLUG THIS WELL USING THE ATTACHED PROCEDURE. CURRENT AND PROPOSED WELLBORE DIAGRAMS ARE ALSO ATTACHED.

**Surface Disturbance**

**Is any additional surface disturbance proposed?:** No

**NOI Attachments**

**Procedure Description**

Red\_Tank\_24\_Fed\_Com\_1\_PA\_WBD\_20260113135435.pdf

Red\_Tank\_24\_Fed\_Com\_1\_PA\_Prog\_\_20260113135417.pdf

Red\_Tank\_24\_Fed\_Com\_1\_PA\_current\_WBD\_20260113135408.pdf

**APPROVAL SUBJECT TO  
GENERAL REQUIREMENTS AND  
SPECIAL STIPULATIONS  
ATTACHED**

<b>Well Name:</b> RED TANK 24 FED COM	<b>Well Location:</b> T22S / R32E / SEC 24 / NENW / 32.3827698 / -103.6299184	<b>County or Parish/State:</b> LEA / NM
<b>Well Number:</b> 01	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM87268	<b>Unit or CA Name:</b> 1 RED TANK 24 FED COM	<b>Unit or CA Number:</b> NMNM105328
<b>US Well Number:</b> 300253503500S1	<b>Operator:</b> EOG RESOURCES INCORPORATED	

**Operator**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

**Operator Electronic Signature:** MORGAN HRNCIRIK **Signed on:** JAN 13, 2026 01:54 PM

**Name:** EOG RESOURCES INCORPORATED

**Title:** Sr. Regulatory Administrator

**Street Address:** 5509 CHAMPIONS DRIVE

**City:** MIDLAND **State:** TX

**Phone:** (432) 257-2428

**Email address:** MORGAN\_HRNCIRIK@EOGRESOURCES.COM

**Field**

**Representative Name:**

**Street Address:**

**City:** **State:** **Zip:**

**Phone:**

**Email address:**

**APPROVED** by Long Vo  
 Petroleum Engineer  
 Carlsbad Field Office  
 575-988-50402  
 LVO@BLM.GOV

Lea County Notification: 575-689-5981

Eddy County Notification: [BLM\\_NM\\_CFO\\_PluggingNotifications@BLM.GOV](mailto:BLM_NM_CFO_PluggingNotifications@BLM.GOV)

Secondary Contact: 575-361-2822

Form 3160-5  
(October 2024)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB No. 1004-0220  
Expires: October 31, 2027

**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**

5. Lease Serial No.

6. If Indian, Allottee or Tribe Name

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well

Oil Well     Gas Well     Other

8. Well Name and No.

2. Name of Operator

9. API Well No.

3a. Address

3b. Phone No. (include area code)

10. Field and Pool or Exploratory Area

4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)

11. Country or Parish, State

**12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has detennined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Title

Signature

Date

**THE SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Long Vo



Title

Petroleum Engineer

Date

3-18-2026

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Carlsbad Field Office

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

## GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

## SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

*Item 13*: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

## Additional Information

### Location of Well

0. SHL: NENW / 660 FNL / 2150 FWL / TWSP: 22S / RANGE: 32E / SECTION: 24 / LAT: 32.3827698 / LONG: -103.6299184 ( TVD: 0 feet, MD: 0 feet )

BHL: NENW / 660 FNL / 2150 FWL / TWSP: 22S / SECTION: / LAT: 0.0 / LONG: 0.0 ( TVD: 0 feet, MD: 0 feet )

**Well Name:** Red Tank 24 Fed Com 1  
**Location:** 660 FNL 2150 FWL  
**County:** Lea, NM  
**Lat/Long:** 32.3827095,-103.6300125 NAD83  
**API #:** 30-025-35035  
**Spud Date:** 6/26/00  
**Compl. Date:** 9/26/00





**Formation Tops**

Top of Salt	900
Bottom of Salt	4,728
Delaware	4,838
Bone Spring	9,010
Wolfcamp	11,940
Strawn	13,530
Morrow	14,358

**Proposed Wellbore Diagram:**

**KB:**  
**GL:** 3753



**Perf and circulate**  
 35 sxs Class C cement to surface  
 Perf @ 100'

WOC & Tag  
 Perf @ 1448' & squeeze 130 sxs class C cement to 949' (In 91 sxs/Out 39 sxs)

**Base of Salt, WOC and Tag**  
 Perf @ 4580' & squeeze 35 sxs class C cement to 4447' (In 24 sxs/Out 11 sxs)

**Not to Scale**  
 By: CC 1/8/26

WOC & Tag  
 Covers Delaware, salt string shoe Spot 58 sxs  
 Class C cement @ 5010' to 4692'.

Spacer plug **WOC and Tag**  
 Spot 40 sxs Class H Cement @ 7,200' to 6,980

WOC & Tag  
 Covers Bone Springs  
 Spot 43 sxs Class H cement from 9060' to 8869'.

WOC & Tag  
 Covers Int Shoe, WFMP, Liner Top  
 Spot 89 sxs Class H Cement from 12,250' to 11,543'

3-1/2" tbg initial to 11,711' **\*Run CBL from CIBP to surface.**

**Submit results to BLM.**

Run CBL from CIBP to surface to verify cement

Set CIBP @ 14044'. Leak test CIBP. Spot cement from 14044' to 13344'. WOC and Tag. 66 sxs Class H.

WOC & Tag  
 Spot 25 sxs Class H Cement from 14,458' to 14,193'

Set CIBP @ 14,458'.  
 14,508'-14,534' - 4 shots/ft - 144 Holes  
 Perforate 14,787 to 14,803' 6 shots/ft - 96 Holes  
 Perforate 14,882' to 14,898 6 shots/ft - 96 Holes

**Perforation Records:**  
 14094' to 14100' Morrow  
 14580' to 14898' Atoka

**REVISED**  
 10:58 am, Mar 18, 2026

**Red Tank 24 Fed Com 1 P&A  
Capital AFE#**

Well Name	Red Tank 24 Federal Com 1 P&A				
Surface Location	32.3827095,-103.6300125 NAD83			AFE/Sub Code	/231
RKB – Sea Level		Area/Field	Red Tank	Spud Date	1/9/01
G.L. Elevation	3,753	County/Province	Lea	Original Rig Contractor	-
API	<b>30-025-35035</b>	State / Country	NM	Formation	Atoka
Comp Date	<b>9/26/26</b>	Total MD	15,100'	Top Perf	14,508'
KOP	-	Average Lateral TVD	-	Wellhead MFG	Weatherford

STRING NAME	STRING OD	STRING WEIGHT	DESCRIPTION	FINAL DEPTH
SURFACE	13.325	48 & 68	13-3/8 H40	1,010'
Salt String	9.625	40	9-5/8 HCK-55 LTC	4,790'
Intermediate	7.625	39	7 P110 LTC	12,200'
Liner	5.0	18 & 20	5 P110 STL	11,706' to 15,100'

**Summary of Procedure:** LD TBG, Set CIBP, Run CBL/Gyro, Spot plugs

**PROCEDURE:**

1. Notify state 24 hours before beginning work.
2. MIRU & Kill well.
3. ND/NU WH/BOP
4. LD Entire string of 3-1/2" Production TBG. Please have workstring on location.
5. RIH & set CIBP @ **14,458'** (50' above top of first perf).
6. **Spot cement from 14,458' to 14,193' with 25 sxs Class H cement. WOC and Tag. (Atoka)**
7. **RIH & set CIBP @ 14044'. Leak test CIBP. Spot cement from 14044' to 13344' with 66 sxs Class H. WOC and Tag. (Morrow)**
8. Run gyro/CBL tandem to verify all cement and surveys.
9. TOOH to 12,250'
10. Spot **89 sxs** Class H cement from 12,250' to **11,543'**. Covers Int. Shoe, WFMP & liner top. WOC & Tag
11. TOOH to **9,060'**
12. Spot **43 sxs** Class H cement from **9,060' to 8869'**. Covers the bone springs. WOC & Tag
13. TOOH to 7,200'.
14. Spot 40 sxs Class H cement from 7,200' to 6,980'. Spacer plug **WOC and Tag.**
15. TOOH to **4,580'**
16. Spot **58 sxs** Class C cement @ **5010' to 4692'**. Covers Delaware, T. salt, string shoe. WOC & Tag
17. TOOH
18. RIH & perf @ **4580'**. POOH
19. TIH w/ packer and squeeze **35 sxs** class C cement. **(In 24 sxs/Out 11 sxs) WOC and Tag (B. Salt)**
20. TOOH


**REVISED**

10:58 am, Mar 18, 2026



- 22. RIH & perf @ 1,448'. POOH
- 23. TIH w/ packer & squeeze 130 sxs Class C cement to 949'. Covers top of salt and surface shoe. WOC & tag (In 91 sxs/Out 39 sxs)
- 24. TOOH
- 25. RIH & perf @ 100'
- 26. Circulate from surface 35 sxs Class C cement to surface inside/outside.
- 27. Dig out cellar, cut off wellhead and verify cement behind all casing strings.
- 28. Install dry hole marker, clean location and RDMO.

**REVISED**  
10:58 am, Mar 18, 2026

Production Engineer:  Date: 1/9/26

Chris Caskey

Well Name: Red Tank 24 Fed Com 1  
 Location: 660 FNL 2150 FWL  
 County: Lea, NM  
 Lat/Long: 32.3827095,-103.6300125 NAD83  
 API #: 30-025-35035  
 Spud Date: 6/26/00  
 Compl. Date: 9/26/00





**Formation Tops**

Top of Salt	900
Bottom of Salt	4,728
Delaware	4,838
Bone Spring	9,010
Wolfcamp	11,940
Strawn	13,530
Morrow	14,358

**Current Wellbore Diagram:**

KB:  
GL: 3753



3-1/2" tbg initial to 11,711'

14,508'-14,534' - 4 shots/ft - 144 Holes  
 Perforate 14,787 to 14,803' 6 shots/ft - 96 Holes  
 Perforate 14,882' to 14,898 6 shots/ft - 96 Holes

Perforation Records:  
 14094' to 14100' Morrow  
 14580' to 14898' Atoka

**Not to Scale**  
By: CC 1/8/26

**REVISED**  
 10:58 am, Mar 18, 2026

Lesser Prairie Chicken Area

**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

**Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Lea County, call 575-689-5981. Eddy County, please email notifications to: [BLM NM CFO PluggingNotifications@BLM.GOV](mailto:BLM_NM_CFO_PluggingNotifications@BLM.GOV). The Eddy County inspector on call phone, 575-361-2822, will remain active as a secondary contact.**

**Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.**

**Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.**

**Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours for Class C or accelerated cement (calcium chloride) and 6 hours for Class H. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.**

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

Fluid used to mix the cement in R111Q shall be saturated with the salts common to the section penetrated, and in suitable proportions but not less than 1% and not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

**Above Ground Level Marker:** If outside of Lesser Prairie-Chicken Habitat an above ground level marker shall be utilized. All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified *BY PHONE* (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within fourteen (14) calendar days of the well being plugged. If the cut off cannot be done by the 14<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds). A weep hole shall be left if a metal plate is welded in place.

**Below Ground Level Marker:** If within Lesser Prairie-Chicken Habitat a below ground level marker shall be utilized. All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified *BY PHONE* (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within fourteen (14) calendar days of the well being plugged. If the cut off cannot be done by the 14<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing. The following information shall be permanently inscribed on the plate: well name and number, name of operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

Operator to verify the ground marker type with the BLM before setting dry hole Marker.

**Subsequent Plugging Reporting:** Within 30 days after plugging work is completed, file via the AFMSS 2 WISx Module a Subsequent Report of Plugging and Abandonment to BLM. Please include the following information:

- The report should give in detail the manner in which the plugging work was carried out, the Extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left In the well.
- The final copy of CBL.
- Any email correspondence regarding changes to originally approved procedure.
- Show date well was plugged.

**Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

**Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:**

From March 1<sup>st</sup> through June 15<sup>th</sup> annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted.



# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm



In Reply Refer To: 1310

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo “interim” reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo “final” reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines **(Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure)**. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. **This will apply to well pads, facilities, and access roads.** Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.

For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.

The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.

Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and

access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.

It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.

At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech/Environmental Protection Specialist  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Jose Martinez-Colon  
Environmental Protection Specialist  
575-234-5951

Angela Mohle  
Environmental Protection Specialist  
575-234-9226

Robert Duenas  
Environmental Protection Specialist  
575-234-2229

Terry Gregston  
Environmental Protection/HAZMAT Specialist  
575-234-5958

Sundry ID		2890487					
Plug Type	Top	Bottom	Length	Tag	Sacks	Cement Class	Notes
<b>Surface Plug</b> 13.375 inch- Shoe Plug	0.00 949.90	100.00 1060.00	100.00 110.10	Tag/Verify Tag/Verify	35.00	C	Perf and circulate from 100' to surface. Verify at surface.
<b>Top of Salt @ 1397</b>	1333.03	1448.00	114.97	Tag/Verify	130.00	C	Perf and squeeze from 1448' to 949'. WOC and Tag. (In 91 sxs/Out 39 sxs)
<b>Base of Salt @ 4543</b> 9.625 inch- Shoe Plug	4447.57 4692.10	4580.00 4840.00	132.43 147.90	Tag/Verify Tag/Verify	35.00	C	Perf and squeeze from 4580' to 4447'. WOC and Tag. (In 24 sxs/Out 11 sxs)
<b>Delaware @ 4960</b>	4860.40	5010.00	149.60	If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations	58.00	C	Spot cement from 5010' to 4692'. WOC and Tag.
<b>Spacer Plug @ 7150</b>	7028.50	7200.00	171.50	If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations	40.00	H	Spot cement from 7200' to 7028'. WOC and Tag.

				If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations			
<b>Bonesprings @ 9010</b>	8869.90	9060.00	190.10		43.00	H	Spot cement from 9060' to 8869'. WOC and Tag.
<b>Liner Top @ 11711</b>	11543.89	11761.00	217.11	If solid			
<b>Wolfcamp @ 11940</b>	11770.60	11990.00	219.40	If solid			
<b>7.625 inch- Shoe Plug</b>	12028.00	12250.00	222.00	Tag/Verify	89.00	H	Spot cement from 12250' to 11543'. WOC and Tag.
<b>Strawn @ 13530</b>	13344.70	13580.00	235.30	If solid			
<b>Atoka @ 13720</b>	13532.80	13770.00	237.20	base no need to Tag (CIBP present			
<b>Perforations Plug (If No CIBP)</b>	13909.00	14150.00	241.00	Tag/Verify			
				If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations			
<b>CIBP Plug</b>	14009.00	14044.00	35.00		66.00	H	Set CIBP at 14044'. Leak test CIBP. Spot cement from 14044' to 13344'. WOC and Tag.
<b>Morrow @ 14358</b>	14164.42	14408.00	243.58	If solid			

				If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations			
<b>CIBP Plug</b>	14423.00	14458.00	35.00		25.00	H	Set CIBP at 14458'. Spot 25 sxs on top. WOC and Tag at 14193'.
<b>Perforations Plug (If No CIBP)</b>	14458.00	14948.00	490.00	Tag/Verify			
<b>5 inch- Shoe Plug</b>	14899.00	15150.00	251.00	Tag/Verify			

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole.  
 Class H >7500'  
 Class C <7500'

Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

Medium, Secretary: Top of salt to surface If no salt take the deepest fresh water or Karst Depth

High, Critical: Bottom of Karst to surface or Deepest fresh water, whichever is greater  
 R111P: 50 Feet from Base of Salt to surface.

Class C: 1.32 ft<sup>3</sup>/sx  
 Class H: 1.06 ft<sup>3</sup>/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement Requirement:

Wild Life

13.375 inch- Shoe Plug @  
 9.625 inch- Shoe Plug @  
 7.625 inch- Shoe Plug @  
 5 inch- Shoe Plug @

Low

Within Lesser Prairie Chicken Area

1010.00  
 4790.00  
 12200.00 TOC @ 4580.00  
 15100.00 TOC @ 11711.00

Perforatons Top @ 14094.00 Perforation 14100.00  
 Perforatons Top @ 14508.00 Perforation 14898.00

CIBP @ 14044.00  
 CIBP @ 14458.00

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 564918

**CONDITIONS**

Operator: EOG RESOURCES INC 5509 Champions Drive Midland, TX 79706	OGRID: 7377
	Action Number: 564918
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

**CONDITIONS**

Created By	Condition	Condition Date
gcordero	Run CBL with zero psi, keep hole loaded, log to surface.	4/3/2026
gcordero	Spot 25 sacks cement 5810' - 5710' - T Cherry Canyon	4/3/2026
gcordero	Adhere to current Plug & Abandon (P&A) Conditions Of Approvals (COA).	4/3/2026
gcordero	A Cement Bond Log (CBL) is required to be submitted to electronic permitting.	4/3/2026
gcordero	Submit Cement Bond Logs (CBL) prior to submittal of C-103P.	4/3/2026