Submit 3 Copies To Appropriate District Office District District Energy, Minerals and Natural Resources	Form C-103 May 27, 2004
1625 N. French Dr. Hobbs NM 88240	WELL API NO. 30-007-20573
District II 1301 W. Grand Ave., Artesia, NM 88210 - ODE CONSERVATION DIVISION	
District III 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, WET CONSERVATE Santa Fe, NM 87505	6. State Oil & Gas Lease No.
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 Santa Fe, NVI 87505	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR B
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other Coalbed Methane	8. Well Number 98
2. Name of Operator	9. OGRID Number 180514
EL PASO ENERGY RATON, L.L.C.	10 Paul same an Wildorf
3. Address of Operator PO BOX 190, RATON, NM 87740	10. Pool name or Wildcat Van Bremmer – Vermejo Gas
4. Well Location	
Unit Letter <u>G</u> : <u>1843</u> feet from the <u>North</u> line and <u>1</u>	714 feet from the <u>East</u> line
Section 8 Township 29N Range 19E NMPM	Colfax County
11. Elevation (Show whether DR, RKB, RT, GR, etc. 7,927' (GL)	
Pit or Below-grade Tank Application or Closure	
Pit typeDepth to GroundwaterDistance from nearest fresh water wellDistance	ance from nearest surface water
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Co	nstruction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR	
TEMPORARILY ABANDON	
POLE ON ALTER GASING [] MOLTIFEL COMITE [] CAGING/OLIMEN	1 30B
OTHER: OTHER:	Completion 🖂
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent date: SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or rec	
02/03//05 Schlumberger ran Cement Bond Log. Cement to surface.	'
02/28/05 Schlumberger perf'd 1st stage - 2236' - 2240', 2268' - 2271' 28 Holes HES frac'd 1st stage - Pumped 377.829 scf 70% quality nitrogen foam with 20# Linear	gel with 36.267 lbs 16/30 brown sand.
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733' - 1735', 1808' - 1811, 1839' - 1841' 28 Hole	S
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g	S
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear g 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes	s el with 7,682 lbs 16/30 brown sand.
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes	gel with 36,400 lbs 16/30 brown sand.
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on pro	gel with 61,709 lbs 16/30 brown sand.
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on pro-	gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction.
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on pro	gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction. a and belief. I further certify that any pit or below-
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 rd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 rd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage- Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceeding to the best of my knowledg grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	gel with 7,682 lbs 16/30 brown sand. gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction. e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan .
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 rd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 rd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on pro-	gel with 7,682 lbs 16/30 brown sand. gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. bduction. e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan . nalyst DATE 05/27/05
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceed tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE Shirley A Mitchell Email address: shirley.mitchell@elpaso.co	gel with 7,682 lbs 16/30 brown sand. gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction. e and belief. I further certify that any pit or below- or an (attached) alternative OCD-approved plan malyst DATE 05/27/05 m Telephone No. (505) 445-6785
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceed tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE Shirley A Mitchell Email address: shirley.mitchell@elpaso.co	gel with 7,682 lbs 16/30 brown sand. gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction. e and belief. I further certify that any pit or below- or an (attached) alternative OCD-approved plan malyst DATE 05/27/05 m Telephone No. (505) 445-6785
HES frac'd 1 st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2 nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2 nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3 rd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3 rd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4 th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceed to the best of my knowledg grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE Shully Miller TITLE Regulatory A TITLE Regulatory A Mitchell Email address: shirley.mitchell@elpaso.com	gel with 7,682 lbs 16/30 brown sand. gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction. e and belief. I further certify that any pit or below- or an (attached) alternative OCD-approved plan malyst DATE 05/27/05 m Telephone No. (505) 445-6785
HES frac'd 1st stage - Pumped 377,829 scf 70% quality nitrogen foam with 20# Linear 03/01/05 Schlumberger perf'd 2nd stage - 1733'- 1735', 1808'- 1811, 1839'- 1841' 28 Hole HES frac'd 2nd stage - Pumped 303,959 scf 70% quality nitrogen foam with 20# Linear g Schlumberger perf'd 3nd stage - 998'- 1000', 1040'- 1044, 1086'- 1090' 40 holes HES frac'd 3nd stage - Pumped 381,398 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 760'- 769', 795'- 798' 48 Holes HES frac'd 4th stage - Pumped 340,324 scf 70% quality nitrogen foam with 20# Linear 04/19/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceed that the information above is true and complete to the best of my knowledger grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE Shully Mitchell Email address: shirley.mitchell@elpaso.co	gel with 7,682 lbs 16/30 brown sand. gel with 36,400 lbs 16/30 brown sand. gel with 61,709 lbs 16/30 brown sand. duction. e and belief. I further certify that any pit or below- or an (attached) alternative OCD-approved plan malyst DATE 05/27/05 m Telephone No. (505) 445-6785