

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-007-20525		5. Indicate Type of Lease STATE ☐ FEE ☒	
		State Oil & Gas Lease No.			
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER <u>Coalbed Methane</u>			7. Lease Name or Unit Agreement Name VPR B		
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER					
2. Name of Operator EL PASO ENERGY RATON, L.L.C.			8. Well No. 59		
3. Address of Operator PO BOX 190 RATON, NEW MEXICO 87740			9. Pool name or Wildcat Van Bremmer - Vermejo Gas 97047		
4. Well Location Unit Letter H : 1641 Feet From The North Line and 1022 Feet From The East Line Section 3 Township 29N Range 18E NMPM Colfax County 10. Date Spudded 01/24/05 11. Date T.D. Reached 01/25/05 12. Date Compl. (Ready to Prod.) 04/23/05 13. Elevations (DF& RKB, RT, GR, etc.) 8,120' 14. Elev. Casinghead 8,120' 15. Total Depth 2,815' 16. Plug Back T.D. 2,694' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By 0 - TD Rotary Tools Cable Tools 19. Producing Interval(s), of this completion - Top, Bottom, Name 765' - 2,530' Raton - Vermejo Coals 20. Was Directional Survey Made 21. Type Electric and Other Logs Run Compensated Density Single Induction Log and Cement Bond Log 22. Was Well Cored No					
23. CASING RECORD (Report all strings set in well)					
CASING SIZE		WEIGHT LB./FT.		DEPTH SET	
8 5/8"		23 lbs		304'	
5 1/2"		15.5 lbs		2,782'	
				7 7/8"	
				355 sks	
24. LINER RECORD					
SIZE		TOP		BOTTOM	
25. TUBING RECORD					
SIZE		DEPTH SET		PACKER SET	
2 7/8"		2,576'			
26. Perforation record (interval, size, and number) 2420'- 2423', 2493'- 2495', 2498'- 2500', 2528'- 2530' 36 Holes 2308'- 2312', 2317'- 2320' 28 Holes 1147'- 1151', 1213'- 1218', 1287'- 1290' 48 Holes 1001'- 1006', 1081'- 1094', 1092'- 1095' 48 Holes 765'- 770', 786'- 792' 44 Holes					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 765' - 2530' AMOUNT AND KIND MATERIAL USED 220,925 lbs 16/30 brown sand					
28. PRODUCTION					
Date First Production 04/24/05		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing, insert pump, and 2' x 1 1/4" x 10' pumping unit. Flowing gas up 5 1/2" casing.		Well Status (Prod. or Shut-in) Production	
Date of Test 04/24/05		Hours Tested 24 Hours		Choke Size Full 2"	
Flow Tubing Press. 300 psi		Casing Pressure 40 psi		Calculated 24-Hour Rate N/A	
				Oil - Bbl. N/A	
				Gas - MCF 59	
				Water - Bbl. 194	
				Gas - Oil Ratio N/A	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.				Test Witnessed By Lyn Essman	
30. List Attachments					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature Shirley Mitchell		Printed Name Shirley A. Mitchell		Title Regulatory Analyst	
E-mail Address shirley.mitchell@elpaso.com		Date 05/27/05			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or reopened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T Raton <u>334'</u>
T. Blinebry	T. Gr. Wash	T. Morrison	T Vermejo <u>2,225'</u>
T. Tubb	T. Delaware Sand	T. Todilto	T Trinidad <u>2,551'</u>
T. Drinkard	T. Bone Springs	T. Entrada	T. _____
T. Abo	T. _____	T. Wingate	T. _____
T. Wolfcamp	T. _____	T. Chinle	T. _____
T. Penn	T. _____	T. Permian	T. _____
T. Cisco (Bough C)	T. _____	T. Penn "A"	T. _____

OIL OR GAS SANDS OR ZONES

Co. 1, from.....to.....	No. 3, from.....to.....
Co. 2, from.....to.....	No. 4, from.....to.....

IMPORTANT WATER SANDS

include data on rate of water inflow and elevation to which water rose in hole.

o. 1, from.....to.....feet.....

o. 2, from.....to.....feet.....

o. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology