

Submit 3 Copies To Appropriate District Office  
 District I  
 1625 N. French Dr., Hobbs, NM 88240  
 District II  
 1301 W. Grand Ave., Artesia, NM 88210  
 District III  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 May 27, 2004

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. **30-007-20625**

5. Indicate Type of Lease  
 STATE  FEE

6. State Oil & Gas Lease No.  
**SEP 1 2005**

7. Lease Name or Unit Agreement Name  
**OIL CONSERVATION DIVISION VPR A**

8. Well Number **160**

9. OGRID Number **180514**

10. Pool name or Wildcat **96970 Stubblefield Canyon - Vermejo Gas**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
**7,877' (GL)**

Pit or Below-grade Tank Application  or Closure

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK  PLUG AND ABANDON   
 TEMPORARILY ABANDON  CHANGE PLANS   
 PULL OR ALTER CASING  MULTIPLE COMPL

OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK  ALTERING CASING   
 COMMENCE DRILLING OPNS.  P AND A   
 CASING/CEMENT JOB

OTHER: **Completion**

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 06/10/05 Schlumberger ran Acoustic Cement Bond Log. Estimated cement top at surface. ✓  
 07/12/05 Schlumberger perf'd 1<sup>st</sup> stage - 1948'- 1951', 1964'- 1969' 32 Holes  
 HES frac'd 1<sup>st</sup> stage - Pumped 350,296 scf 70% quality nitrogen foam with 20# Linear gel with 45,005 lbs 16/30 sand.  
 Schlumberger perf'd 2<sup>nd</sup> stage - 1791'- 1795', 1818'- 1820' 24 Holes  
 HES frac'd 2<sup>nd</sup> stage - Pumped 164,684 scf 70% quality nitrogen foam with 20# Linear gel with 36,143 lbs 16/30 sand.  
 Schlumberger perf'd 3<sup>rd</sup> stage - 1084'- 1088', 1098'- 1102', 1176'- 1178', 1205'- 1209' 28 Holes  
 HES frac'd 3<sup>rd</sup> stage - Pumped 223,423 scf 70% quality nitrogen foam with 20# Linear gel with 63,642 lbs 16/30 sand.  
 07/20/05 RIH tubing, rods and pump. Well is ready to be tested and put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCDC guidelines , a general permit  or an (attached) alternative OCD-approved plan .

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 09/14/05  
 Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785

For State Use Only

APPROVED BY: [Signature] TITLE DISTRICT SUPERVISOR DATE 9/19/05  
 Conditions of Approval (if any): \_\_\_\_\_