22Submit 3 Copies To Appropriate State of New Mexico	Form C-103
District Office Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	WELL API NO. 30-007-20638
District II 1301 W. Grand Avg. Actoria NIM 88210 OIL CONSERVATION DIVISION	
District III 1301 W. Grand Ave., Artesia, NM 88210 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 D := D D-J - A-t NIM 97410	STATE FEE
District IV Santa Fe, Nivi 87303	6. State Oil & Gas Lease No.
1220 S St. Francis Dr., Santa Fe, NM	4
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease (value of othe Agreement (value
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR A
PROPOSALS.)	8. Well Number 188
1. Type of Well: Oil Well Gas Well Other Coalbed Methane	
2. Name of Operator	9. OGRID Number 180514
EL PASO ENERGY RATON, L.L.C.	
3. Address of Operator	10. Pool name or Wildcat
PO BOX 190, RATON, NM 87740	Stubblefield Canyon - Vermejo Gas
4. Well Location	
Unit Letter F: 2075 feet from the North line and 150	2 feet from the West line
Section 8 Township 31N Range 20E NMPM	Colfax County
11. Elevation (Show whether DR, RKB, RT, GR, e	
8,196' (GL)	
Pit or Below-grade Tank Application or Closure	
Pit type Depth to Groundwater Distance from nearest fresh water well	Distance from nearest confees water
ł	
Pit Liner Thickness: mil Below-Grade Tank; Volume bbis;	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WO	
-	RILLING OPNS. PANDA
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMI	-
TOLE STOTIC TOTIC STOTIC STOTI	
OTHER: OTHER:	Completion 🛛
13. Describe proposed or completed operations. (Clearly state all pertinent details,	and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions:	Attach wellbore diagram of proposed completion
or recompletion.	
1	
·	
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'.	
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' - 2211'	(7) 1 2 2 35
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' - 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of	cement to surface.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' - 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface.	cement to surface. Oil Conservation Division
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' - 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface.	cement to surface. Oil Conservation Division
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linea	cement to surface. Oil Conservation Division
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linea Patterson perf'd 2nd stage - 1762' - 1765' 12 Holes	Oil Conservation Division 1220 S. St. Francis Drive 1821 Santa Fe, NM 87505
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1 st stage - 2258' - 2263' 20 Holes HES frac'd 1 st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2 nd stage - 1762' - 1765' 12 Holes HES frac'd 2 nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear	Oil Conservation Division 1220 S. St. Francis Drive 1821 Santa Fe, NM 87505
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1 st stage - 2258'-2263' 20 Holes HES frac'd 1 st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2 nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2 nd stage - 1762'-1765' 12 Holes HES re-frac'd 2 nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2 nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear	Oil Conservation Division 1220 S. St. Francis Drive 18 John 18
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1 st stage - 2258'-2263' 20 Holes HES frac'd 1 st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2 nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2 nd stage - 1762'-1765' 12 Holes HES re-frac'd 2 nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3 rd stage - 1234'-1236', 1297'-1299' 16 Holes	Oil Conservation Division 1220 S. St. Francis Drive Santa Fe, NM 87505 gel with 4,366 lbs 16/30 sand.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258'-2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762'-1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762'-1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson foam with Linear Patterson perf'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson foam with Linear Patterson perf'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson foam with Linear Patterson perf'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson foam with Linear Patterson perf'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson foam with Linear Patterson perf'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson foam with Linear Patterson perf'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson	Oil Conservation Division 1220 S. St. Francis Drive Santa Fe, NM 87505 gel with 4,366 lbs 16/30 sand.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258'-2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762'-1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762'-1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes	Oil Conservation Division 1220 S. St. Francis Drive 124,192 lbs 16/30 sand. gel with 4,366 lbs 16/30 sand. gel with 12,626 lbs 16/30 sand. gel with 30,971 lbs 16/30 sand.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762' - 1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762' - 1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqe'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear	Oil Conservation Division 1220 S. St. Francis Drive 124,192 lbs 16/30 sand. gel with 4,366 lbs 16/30 sand. gel with 12,626 lbs 16/30 sand. gel with 30,971 lbs 16/30 sand.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258'-2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762'-1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762'-1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes	Oil Conservation Division 1220 S. St. Francis Drive 124,192 lbs 16/30 sand. gel with 4,366 lbs 16/30 sand. gel with 12,626 lbs 16/30 sand. gel with 30,971 lbs 16/30 sand.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762' - 1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762' - 1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear P	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 124,192 lbs 16/30 sand. gel with 4,366 lbs 16/30 sand. gel with 12,626 lbs 16/30 sand. gel with 30,971 lbs 16/30 sand. gel with 47,396 lbs 16/30 sand.
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762' - 1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762' - 1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqe'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Francis Drive 1250 S. St. Francis Drive 1261 Santa Fe, NM 87505 127 Santa Fe, NM 87505 128 Santa Fe, NM 87505 129 Santa Fe, NM 87505 120 Sa
Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258'-2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762'-1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762'-1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3rd stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 3rd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES frac'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Francis Drive 1240 S. St. Francis Drive 1250 S. St. Franci
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' −2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage − 2258' − 2263' 20 Holes HES frac'd 1st stage − Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage − Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage − Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage − Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3rd stage − 1234' − 1236', 1297' − 1299' 16 Holes HES frac'd 3rd stage − Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage − 687' − 691', 796' − 798', 838' − 842' 40 Holes HES fraqc'd 4th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage − Pumped 3th stage − 1234' − 1236', 1297' − 1299' 16 Holes HeS frac'd 3th stage − 1234' − 1236', 1297' − 1299' 16 Holes HeS frac'd 3th stage − 1234' − 1236'	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Francis Drive 1240 S. St. Francis Drive 1250 S. St. Franci
Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' – 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258'-2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762'-1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762'-1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3rd stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 3rd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES frac'd 3th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes	Oil Conservation Division 1220 S. St. Francis Drive gel with 24,192 lbs 16/30 sand. gel with 4,366 lbs 16/30 sand. gel with 12,626 lbs 16/30 sand. gel with 30,971 lbs 16/30 sand. gel with 47,396 lbs 16/30 sand. gel with 47,396 lbs 16/30 sand. dge and belief. I further certify that any pit or belowdor an (attached) alternative OCD-approved plan Analyst DATE 10/03/05
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' − 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762' - 1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3rd stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 3rd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqc'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Francis Drive 1240 S. St. Francis Drive 1250 S. St. Franci
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' − 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762' - 1765' 12 Holes HES re-frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson perf'd 3rd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 3rd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES frac'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 4th stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1298', 838' - 842' 40 Holes HES frac'd 2nd stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1298', 838' - 842' 40 Holes HES frac'd 2nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 2nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 2nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 2nd stage - Pumped 253,099 scf 70% quality nitrogen foam with	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Franci
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' −2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258'-2263' 20 Holes HES frac'd !st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - 1762'-1765' 12 Holes HES frac'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1762'-1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3nd stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 3nd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687'-691', 796'-798', 838'-842' 40 Holes HES frac'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 5th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 5th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 5th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 5th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd 5th stage - Pumped 197,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 5th stage - 1234'-1236', 1297'-1299' 16 Holes HES frac'd	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Franci
07/26/05 Patterson ran Acoustic Cement Bond Log. Estimated cement top at 2,238'. Patterson perf'd squeeze holes in casing from 2210' − 2211' HES pumped 280 sks Trinidad blend cement in casing. Circulated 15 bbls of 07/30/05 Schlumberger ran Cement Bond Log. Estimated cement top at surface. 08/04/05 Patterson perf'd 1st stage - 2258' - 2263' 20 Holes HES frac'd 1st stage - Pumped 563,992 scf 70% quality nitrogen foam with Linear Patterson perf'd 2nd stage - Pumped 278,750 scf 70% quality nitrogen foam with Linear Patterson re-perf'd 2nd stage - 1762' - 1765' 12 Holes HES re-frac'd 2nd stage - Pumped 379,070 scf 70% quality nitrogen foam with Linear Patterson perf'd 3rd stage - 1234' - 1236', 1297' - 1299' 16 Holes HES frac'd 3rd stage - Pumped 253,099 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqc'd 4th stage - 687' - 691', 796' - 798', 838' - 842' 40 Holes HES fraqc'd 4th stage - Pumped 394,980 scf 70% quality nitrogen foam with Linear Patterson perf'd 4th stage - 1234' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1236' - 1	Oil Conservation Division 1220 S. St. Francis Drive 1220 S. St. Francis Drive 1230 S. St. Francis Drive 1230 S. St. Francis Drive 124,192 lbs 16/30 sand. 1250 Sand Fe, NM 87505 1261 with 4,366 lbs 16/30 sand. 1262 gel with 12,626 lbs 16/30 sand. 1263 gel with 30,971 lbs 16/30 sand. 1264 gel with 47,396 lbs 16/30 sand. 1265 gel with 47,396 lbs 16/30 sand. 1266 gel with 47,396 lbs 16/30 sand. 1276 gel with 47,396 lbs 16/30 sand.