Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural Resou	rces May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II	OIL CONSERVATION DIVISION	ON 30-007-20671
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.	/. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410		STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	7. State Oil & Gas Lease No.
87505		
	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO	F .
PROPOSALS.)	ICATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR A
1. Type of Well: Oil Well	Gas Well 🛛 Other Coalbed Methane	8. Well Number 234
2. Name of Operator		9. OGRID Number
	SO E & P COMPANY, L.P.	
3. Address of Operator	11 100 NATION NA 077 10	10. Pool name or Wildcat
	X 190, RATON, NM 87740	
4. Well Location		
Unit Letter P:	953 feet from the South line and	1253 feet from the <u>East</u> line
Section 9 Tow	rnship 31N Range 20E N	MPM Colfax County
	11. Elevation (Show whether DR, RKB, RT,	GR, etc.)
	8,021' (GL)	Harris Control of the
Pit or Below-grade Tank Application	1 Title and 1 Titl	
Pit typeDepth to Ground		Distance from nearest surface water
Pit Liner Thickness: mi	l Below-Grade Tank; Volume	bbls: Construction Material
12. Check	Appropriate Box to Indicate Nature of	Notice, Report or Other Data
		•
	NTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	-	AL WORK ALTERING CASING
TEMPORARILY ABANDON		NCE DRILLING OPNS.⊠ PAND A □
PULL OR ALTER CASING	MULTIPLE COMPL 🗍 CASING	CEMENT JOB
OTHER:	☐ OTHER:	
		etails, and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion		
or recompletion.		S 5. F.
	Drill 11" surface hole to 326'. Run 8 jts. of	
Halliburton mixed an	d pumped 100 sx Midcon II cement, 14 ppg,	yield 1.66. Circulate 8 bbls of cement to surface.
woc 8 hrs. Test sui	face 8 5/8" csg to 500 psi for 30 minutes.	
03/29/06 Drill 7 7/8" hole fro	m 326' - 2,330'. Reached TD at 2,330' at 7	:30 n m
MIRU Patterson and log well. Logger's TD at 2,320'.		
	5.5 #, J-55 LT & C casing at 2,287'.	
	ped 302 sks Midcon II cement. Circulated 13	8 bbls of cement to surface.
	2	
Manufacture of Carlos about Comments		
grade tank has been/will be constructed of	I above is true and complete to the best of my k	mowledge and belief. I further certify that any pit or below- permit or an (attached) alternative OCD-approved plan .
9/ 2	Pin 1 11	per unit un an (accavered) accernance OCD-approved pign u.
SIGNATURE Shurket TITLE Regulatory Analyst DATE 04/13/2006		
Type or print name Shirley A. Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785		
For State Use Only		
APPROVED BY: 1/4 C John TITLE DISTRICT SUPERVISOR DATE 4/17/06		
Conditions of Approval (f any)://	THILE DESIRIE	I SUITERVISOR DATE 1/1/100
The state of the s		