Office a	State of New Mexico	roini C-103
Office District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II	OIL CONSERVATION DIVISION	30-007-20715
1301 W. Grand Ave., Artesia, NM 88210		7. Indicate Type of Lease
District III	1220 South St. Francis Dr.	STATE 🗍 FEE 🛛
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	7. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM		
87505		
	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
PROPOSALS.)	LICATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR B
1. Type of Well: Oil Well	Gas Well 🛛 Other Coalbed Methane	8. Well Number 215
2. Name of Operator	<u> </u>	9. OGRID Number
•	SO E & P COMPANY, L.P.	
3. Address of Operator	SO E & T COMPANY, LAT.	10. Pool name or Wildcat
1	OX 190, RATON, NM 87740	10. Tool hame of Wildean
		_
4. Well Location	<b>✓</b> ✓	
Unit Letter <u>K</u> :	1410 feet from the South line and 1890	feet from theWest_line
Section 24 Towns	hip √30N Range √ 17E NMPM	Colfax County
	11. Elevation (Show whether DR, RKB, RT, GR,	
	8,607' (GL)	
Pit or Below-grade Tank Application		
	<del>_</del>	m
Pit typeDepth to Ground	waterDistance from nearest fresh water well	Distance from nearest surface water
Pit Liner Thickness: m	il Below-Grade Tank: Volume bbls;	Construction Material
12 Check	Appropriate Box to Indicate Nature of Notice	ce. Report or Other Data
12. 611001	repropried box to indicate reduce of reduce	o, Report of Other Bata
NOTICE OF I	NTENTION TO: SI	IBSEQUENT REPORT OF
		JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON 🔲 REMEDIAL W	ORK ALTERING CASING
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	PLUG AND ABANDON   REMEDIAL W CHANGE PLANS   COMMENCE	ORK ☐ ALTERING CASING ☐ DRILLING OPNS.⊠ P AND A ☐
PERFORM REMEDIAL WORK	PLUG AND ABANDON   REMEDIAL W CHANGE PLANS   COMMENCE	ORK ☐ ALTERING CASING ☐ DRILLING OPNS.⊠ P AND A ☐
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING	PLUG AND ABANDON   REMEDIAL W COMMENCE   MULTIPLE COMPL   CASING/CEM	ORK ☐ ALTERING CASING ☐ DRILLING OPNS.⊠ P AND A ☐
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING OTHER:	PLUG AND ABANDON   REMEDIAL W COMMENCE   MULTIPLE COMPL   CASING/CEM OTHER:	ORK
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:  13. Describe proposed or com	PLUG AND ABANDON REMEDIAL W CHANGE PLANS COMMENCE I MULTIPLE COMPL CASING/CEM OTHER: appleted operations. (Clearly state all pertinent details,	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB DENT J
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:  13. Describe proposed or comof starting any proposed with the proposed or comof starting any proposed or comof starting and starting and starting any proposed or comof starting and starting a	PLUG AND ABANDON   REMEDIAL W COMMENCE   MULTIPLE COMPL   CASING/CEM OTHER:	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB DENT J
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:  13. Describe proposed or com	PLUG AND ABANDON REMEDIAL W CHANGE PLANS COMMENCE I MULTIPLE COMPL CASING/CEM OTHER: appleted operations. (Clearly state all pertinent details,	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB DENT J
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:  13. Describe proposed or composed or recompletion.	PLUG AND ABANDON REMEDIAL W CHANGE PLANS COMMENCE I MULTIPLE COMPL CASING/CEM OTHER: appleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:	ORK ALTERING CASING DRILLING OPNS. P AND A DENT JOB Dand give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:  13. Describe proposed or composed or compos	PLUG AND ABANDON REMEDIAL W COMMENCE I CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8",	ORK ALTERING CASING DRILLING OPNS. P AND A DENT JOB Dand give pertinent dates, including estimated date Attach wellbore diagram of proposed completion 24#, 155 ST & C casing at 328'.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield	ORK ALTERING CASING DRILLING OPNS. P AND A DENT JOB Dand give pertinent dates, including estimated date Attach wellbore diagram of proposed completion 24#, 155 ST & C casing at 328'.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and	PLUG AND ABANDON REMEDIAL W COMMENCE I CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8",	ORK ALTERING CASING DRILLING OPNS. P AND A DENT JOB Dand give pertinent dates, including estimated date Attach wellbore diagram of proposed completion 24#, 155 ST & C casing at 328'.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed an WOC 8 hrs. Test su	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield reface 8 5/8" csg to 500 psi for 30 minutes.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB Dand give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 . Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB Dand give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 . Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield reface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB Dand give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 . Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1:	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield reface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.  5.5 #, J-55 LT & C casing at 2,825'.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB Dand give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1:	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield reface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB Dand give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1:	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield reface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.  5.5 #, J-55 LT & C casing at 2,825'.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB Dand give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or come of starting any proposed was or recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1: HES mixed and pump	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.  5.5 #, J-55 LT & C casing at 2,825'. ped 320 sks Midcon II cement. Circulated 22 bbls	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB DATE and give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or come of starting any proposed or come of recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1: HES mixed and pump	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.  5.5 #, J-55 LT & C casing at 2,825'. ped 320 sks Midcon II cement. Circulated 22 bbls in above is true and complete to the best of my knowless.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB DATE And give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or come of starting any proposed or come of recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1: HES mixed and pump	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM DTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 10 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.	ORK ALTERING CASING DRILLING OPNS. PAND A DENT JOB DATE And give pertinent dates, including estimated date. Attach wellbore diagram of proposed completion 24#, J55 ST & C casing at 328'.  1.66 Circulated 7 bbls of cement to surface.
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1: HES mixed and pumposed to the proposed work of the proposed wo	PLUG AND ABANDON COMMENCE IN CHANGE PLANS COMMENCE IN CASING/CEM DTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 10 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.	ORK
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1: HES mixed and pumporare tank has been/will be constructed of SIGNATURE	PLUG AND ABANDON  COMMENCE I CHANGE PLANS  COMMENCE I CASING/CEM  OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 10 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for	ORK
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or comof starting any proposed wor recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test su  06/11/06 Drill 7 7/8" hole from MIRU Patterson and Run 71 jts 5 ½", 1: HES mixed and pump  I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Shirley A. No.	PLUG AND ABANDON  COMMENCE I CHANGE PLANS  COMMENCE I CASING/CEM  OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 10 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield arface 8 5/8" csg to 500 psi for	ORK
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING TOTHER:  13. Describe proposed or composed or composed or composed or completion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 8 hrs. Test	PLUG AND ABANDON  COMMENCE I CHANGE PLANS  COMMENCE I CASING/CEM  OTHER:  Impleted operations. (Clearly state all pertinent details, work). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 10 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", ad pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.	ORK
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING  OTHER:  13. Describe proposed or come of starting any proposed was or recompletion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 8 hrs. Test sum WOC 8 hrs. Test sum WOC 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 8 hrs. Test sum WOC 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 8 hrs. Test s	PLUG AND ABANDON  COMMENCE REMEDIAL W COMMENCE REMEDIAL W COMMENCE REMEDIAL W COMMENCE REMEDIAL WORK). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.  5.5 #, J-55 LT & C casing at 2,825'. ped 320 sks Midcon II cement. Circulated 22 bbls or closed according to NMOCD guidelines , a general permit TITLE Regulatory And Mitchell E-mail address: shirley.mitchell@el	ORK
PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING TOTHER:  13. Describe proposed or composed or composed or composed or completion.  06/10/06 Spud @ 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 9:30 a.m. Halliburton mixed and WOC 8 hrs. Test sum WOC 8 hrs. Test	PLUG AND ABANDON  COMMENCE REMEDIAL W COMMENCE REMEDIAL W COMMENCE REMEDIAL W COMMENCE REMEDIAL WORK). SEE RULE 1103. For Multiple Completions:  Drill 11" surface hole to 338'. Run 8 jts. of 8 5/8", and pumped 100 sx Midcon II cement, 14 ppg, yield rface 8 5/8" csg to 500 psi for 30 minutes.  Drill 338' - 2,965'. Reached TD 2,965' at 1:00 a.m. log well. Logger's TD at 2,947'.  5.5 #, J-55 LT & C casing at 2,825'. ped 320 sks Midcon II cement. Circulated 22 bbls or closed according to NMOCD guidelines , a general permit TITLE Regulatory And Mitchell E-mail address: shirley.mitchell@el	ORK