

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
Revised June 10, 2003

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

WELL API NO.

30-007-20717

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER Coalbed Methane
b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

7. Lease Name or Unit Agreement Name

VPR B

2. Name of Operator
EL PASO E & P COMPANY, L.P.

8. Well No.

218

3. Address of Operator
PO BOX 190
RATON, NEW MEXICO 87740

9. Pool name or Wildcat

Van Bremmer - Vermejo Gas

4. Well Location

Unit Letter A : 643 Feet From The North Line and 1048 Feet From The East Line

Section 22 Township 30N Range 17E NMPM Colfax County

10. Date Spudded 06/20/2006 11. Date T.D. Reached 06/21/06 12. Date Compl. (Ready to Prod.) 07/25/2006 13. Elevations (DF& RKB, RT, GR, etc.) 8,930' 14. Elev. Casinghead 8,930'

15. Total Depth 3,025' 16. Plug Back T.D. 2,860' 17. If Multiple Compl. How Many Zones? 0 18. Intervals Drilled By Rotary Tools Cable Tools 0 - TD

19. Producing Interval(s), of this completion - Top, Bottom, Name 2447' - 2696' Raton - Vermejo Coals 20. Was Directional Survey Made

21. Type Electric and Other Logs Run Compensated Density Single Induction Log and Cement Bond Log 22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23 lbs	327'	11"	100 sks	
5 1/2"	15.5 lbs	2,865'	7 7/8"	377 sks	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET
					2 7/8"	2,772'

26. Perforation record (interval, size, and number)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.		
2552' - 2554', 2624' - 2627', 2693' - 2696'	32 Holes		DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	
2447' - 2451'	16 Holes		2447' - 2696'	18,500 lbs 16/30 sand	
				Water w/Linear gel	

28. PRODUCTION

Date First Production 08/28/2006		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing, insert pump and 2' x 1 1/4" x 10' Pumping unit. Flowing gas up 5 1/2" casing.			Well Status (Prod. or Shut-in) Production	
Date of Test 08/28/2006	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl. 98
Flow Tubing Press. 220 psi	Casing Pressure 180 psi	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 0	Water - Bbl. 98	Oil Gravity - API - (Corr.) N/A

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel. Test Witnessed By Tim Mehn

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature Shirley Mitchell Printed Name Shirley A. Mitchell Title Regulatory Analyst Date 09/29/2006
E-mail Address shirley.mitchell@elpaso.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depth shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. <u>Raton</u> 618'
T. Blinebry	T. Gr. Wash	T. Morrison	T. <u>Vermejo</u> 2,431'
T. Tubb	T. Delaware Sand	T. Todilto	T. <u>Trinidad</u> 2,705'
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology