

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

WELL API NO.

30-007-20428

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR B

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒ Coalbed Methane

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. Box 190, Raton, NM 87740

8. Well No.

47

9. Pool name or Wildcat

4. Well Location

Unit Letter N : 1282 feet from the South line and 1487 feet from the West line

Section 11 Township 29N Range 18E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8076' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/24/03 Spud @ 5:45 p.m. Drill 11" surface hole to 350'. Run 8 jts. of 8 5/8", 24#, J55 ST&C casing to 341'. Halliburton mixed and pumped 105 sx Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 70 psi with 6% salt, 5#/sx gilsonite, .3% versaset and .25 #/sk flocele. Circulate 8 bbl of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

07/25/03 Drill 7 7/8" hole from 350' - 2810'. Reached TD 2810' at 9:30 p.m.

07/26-03 MIRU Schlumberger & log well. Ran 12 jts of 5 1/2", 17#, J55 and 52 jts. of 5 1/2", 15.5#, J55 LT&C casing to 2726'. MIRU Halliburton. Mix and pump 40 bbls gel pre flush. Pumped 415 sx Midcon II PP, 13 ppg, yield 2.04 at 4 bpm with 100 psi, 6% salt, 5 lb/sx Gilsonite, .3% Versaset, .1% Super CBL and 1/4 #/sk flocele. Bumped plug on fly. Float held. No returns. The hole would go on vacuum intermittently until displacement. No blow. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 07-30-03

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 7/31/03

Conditions of approval, if any: