

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
JAN 12 1983
OIL CONSERVATION DIVISION
SANTA FE

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.D.S.	
LAND OFFICE	
OPERATOR	

1. Indicate Type of Lease
State ☐ Fee ☒
2. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐
Name of Operator
Yates Petroleum Corporation
Address of Operator
207 South 4th St., Artesia, NM 88210
Location of Well
UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM
THE West LINE, SECTION 5 TOWNSHIP 10N RANGE 27E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name
T-4 Cattle Co.
9. Well No.
1-5
10. Field and Pool, or Wildcat
Wildcat
11. Elevation (Show whether DF, RT, GR, etc.)
4311' GR
12. County
Quay

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 5:30 PM 12-31-82. Ran 9 joints of 13-3/8" 48# K-55 ST&C casing set at 377'. 1-Texas Pattern notched guide shoe at 377'. Insert float at 334'. Cemented w/425 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 1:15 AM 1-2-83. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 30 sacks. WOC. Drilled out at 7:15 PM 1-2-83. Nipped up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY Carl Ulvog TITLE Production Supervisor DATE 1-10-83
DISTRICT SUPERVISOR
CONDITIONS OF APPROVAL, IF ANY: