| Office District 1 | State of New Mexic | 0 | Form C-103 |
|--|--|--|---|
| | Energy, Minerals and Natural | Resources | May 27, 2004 |
| 1625 N. French Dr., Hobbs, NM 88240 | | WELL AF | 1 |
| <u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210 | OIL CONSERVATION DI | IVISION 7 T | 30-007-20775 |
| District III | 1220 South St. Francis | | ndicate Type of Lease ATE FEE |
| 1000 Rio Brazos Rd., Aztec, NM 87410 | Santa Fe, NM 8750 | | tate Oil & Gas Lease No. |
| <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM | , | ,, , | ante on the one bease i.e. |
| 87505 | | | |
| | ICES AND REPORTS ON WELLS SALS TO DRILL OR TO DEEPEN OR PLUG E | | Name or Unit Agreement Name |
| | CATION FOR PERMIT" (FORM C-101) FOR S | | VPR B |
| PROPOSALS.) | | 8. Well N | |
| 1. Type of Well: Oil Well | Gas Well Other Coalbed Meth | 9. OGRII | |
| 2. Name of Operator EL PASO E & P COMPANY, L.P. | | 9. OGRII | Number |
| 3. Address of Operator | | 10. Pool : | name or Wildcat |
| P.O. BOX 190, RATON, NM 87740 | | | |
| 4. Well Location | | | |
| Unit Letter B: 1300 feet from the North line and 1505 feet from the East line | | | |
| Section 19 Township 29N Range 19E NMPM Colfax County | | | |
| Section 19 10 | 11. Elevation (Show whether DR, RA | | County |
| 7,957' (GL) | | | |
| Pit or Below-grade Tank Application or Closure | | | |
| Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water | | | |
| Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material | | | |
| 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data | | | |
| 12. Check Appropriate Box to Indicate Nature of Notice, Report of Other Data | | | |
| NOTICE OF IN | ITENTION TO: | SUBSEQUEN | IT REPORT OF: |
| PERFORM REMEDIAL WORK | PLUG AND ABANDON ☐ R | EMEDIAL WORK | ☐ ALTERING CASING ☐ |
| TEMPORARILY ABANDON | · · · · · · · · · · · · · · · · · · · | OMMENCE DRILLING OPN | IS.⊠ PANDA 🔲 |
| PULL OR ALTER CASING | MULTIPLE COMPL | ASING/CEMENT JOB | |
| OTHER; | пІо | TUED. | |
| OTIEC. | | | |
| | pleted operations. (Clearly state all pert | THER: tinent details, and give nerting | ent dates, including estimated date |
| 13. Describe proposed or com | pleted operations. (Clearly state all pertork). SEE RULE 1103. For Multiple C | tinent details, and give perti | nent dates, including estimated date re diagram of proposed completion |
| 13. Describe proposed or com | pleted operations. (Clearly state all pertork). SEE RULE 1103. For Multiple C | tinent details, and give perti | nent dates, including estimated date re diagram of proposed completion |
| 13. Describe proposed or composed or starting any proposed wor recompletion. | ork). SEE RULE 1103. For Multiple (| tinent details, and give pertic Completions: Attach wellbo | re diagram of proposed completion |
| 13. Describe proposed or composed or starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. D | ork). SEE RULE 1103. For Multiple (rill 11" surface hole to 322'. Run 10 jts | tinent details, and give perticompletions: Attach wellbo | re diagram of proposed completion & C casing at 307'. |
| 13. Describe proposed or composed of starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. D Halliburton mixed and | ork). SEE RULE 1103. For Multiple Crill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 | completions: Attach wellbo s. of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circula | re diagram of proposed completion & C casing at 307'. |
| 13. Describe proposed or composed of starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. D Halliburton mixed and | ork). SEE RULE 1103. For Multiple (rill 11" surface hole to 322'. Run 10 jts | completions: Attach wellbo s. of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circula | re diagram of proposed completion & C casing at 307'. |
| 13. Describe proposed or composed of starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. D Halliburton mixed and WOC 8 hrs. Test sur | ork). SEE RULE 1103. For Multiple C rill 11" surface hole to 322'. Run 10 jts I pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim | cinent details, and give perticompletions: Attach wellboom, of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulantes. | re diagram of proposed completion & C casing at 307'. |
| 13. Describe proposed or compof starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. D Halliburton mixed and WOC 8 hrs. Test sur | ork). SEE RULE 1103. For Multiple Crill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 | cinent details, and give perticompletions: Attach wellboom, of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulantes. | re diagram of proposed completion & C casing at 307'. |
| 13. Describe proposed or composed or starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. Described by the second of the second with the second | ork). SEE RULE 1103. For Multiple Carill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim as 322' - 2581'. Reached TD 2581' as yell. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C | cinent details, and give perturbed by the completions: Attach wellboom as of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulates. the 24:00 a.m. casing at 2474'. | the diagram of proposed completion & C casing at 307'. the 7 bbls of cement to surface. |
| 13. Describe proposed or composed or starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. Described by the second of the second with the second | ork). SEE RULE 1103. For Multiple Carill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim as 322' - 2581'. Reached TD 2581' as g well. Logger's TD at 2560'. | cinent details, and give perturbed by the completions: Attach wellboom as of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulates. the 24:00 a.m. casing at 2474'. | the diagram of proposed completion & C casing at 307'. the 7 bbls of cement to surface. |
| 13. Describe proposed or composed or starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. Described by the second of the second with the second | ork). SEE RULE 1103. For Multiple Carill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim as 322' - 2581'. Reached TD 2581' as yell. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C | cinent details, and give perturbed by the completions: Attach wellboom as of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulates. the 24:00 a.m. casing at 2474'. | the diagram of proposed completion & C casing at 307'. the 7 bbls of cement to surface. |
| 13. Describe proposed or composed watering any proposed water or recompletion. 03/09/07 Spud @ 5:30 p.m. Described by the sum of th | ork). SEE RULE 1103. For Multiple Carill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim and 322' - 2581'. Reached TD 2581' and gwell. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C and 278 sks Midcon II cement. Circula | cinent details, and give perticompletions: Attach wellboom of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulates. t 24:00 a.m. casing at 2474'. ted 4 bbls of cement to surface. | the diagram of proposed completion & C casing at 307'. te 7 bbls of cement to surface. |
| 13. Describe proposed or composed watering any proposed water or recompletion. 03/09/07 Spud @ 5:30 p.m. Data of the sum | ork). SEE RULE 1103. For Multiple Carill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim and 322' - 2581'. Reached TD 2581' and gwell. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C and 278 sks Midcon II cement. Circula above is true and complete to the best of the service of | completions: Attach wellboompletions: Attach w | the diagram of proposed completion & C casing at 307'. the 7 bbls of cement to surface. |
| 13. Describe proposed or composed watering any proposed water or recompletion. 03/09/07 Spud @ 5:30 p.m. Data of the sum | ork). SEE RULE 1103. For Multiple Carill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim and 322' - 2581'. Reached TD 2581' and gwell. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C and 278 sks Midcon II cement. Circula | completions: Attach wellboompletions: Attach w | the diagram of proposed completion & C casing at 307'. the 7 bbls of cement to surface. |
| 13. Describe proposed or composed water of starting any proposed water or recompletion. 03/09/07 Spud @ 5:30 p.m. Described by 5:30 p.m. | rill 11" surface hole to 322'. Run 10 jts l pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim m 322' - 2581'. Reached TD 2581' a pg well. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C ed 278 sks Midcon II cement. Circula above is true and complete to the best of closed according to NMOCD guidelines , a | cinent details, and give perticompletions: Attach wellbooks, of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulantes. t 24:00 a.m. casing at 2474'. ted 4 bbls of cement to surfacted 4 bbls of cement to surface and belief general permit or an (attach egulatory Analyst | the diagram of proposed completion A C casing at 307'. The 7 bbls of cement to surface. The results of cement to surface. |
| 13. Describe proposed or compost starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. Described by the second work of the second wor | rill 11" surface hole to 322'. Run 10 jts l pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim m 322' - 2581'. Reached TD 2581' a pg well. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C ed 278 sks Midcon II cement. Circula above is true and complete to the best of closed according to NMOCD guidelines , a | cinent details, and give perticompletions: Attach wellbooks, of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulantes. t 24:00 a.m. casing at 2474'. ted 4 bbls of cement to surfacted 4 bbls of cement to surface and belief general permit or an (attach egulatory Analyst | te diagram of proposed completion & C casing at 307'. te 7 bbls of cement to surface. ace. I further certify that any pit or belowed) alternative OCD-approved plan |
| 13. Describe proposed or composed water of starting any proposed water or recompletion. 03/09/07 Spud @ 5:30 p.m. Described by 5:30 p.m. | rill 11" surface hole to 322'. Run 10 jts l pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim m 322' - 2581'. Reached TD 2581' a pg well. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C ed 278 sks Midcon II cement. Circula above is true and complete to the best of closed according to NMOCD guidelines , a | cinent details, and give perticompletions: Attach wellbooks, of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulantes. t 24:00 a.m. casing at 2474'. ted 4 bbls of cement to surfacted 4 bbls of cement to surface and belief general permit or an (attach egulatory Analyst | the diagram of proposed completion A C casing at 307'. The 7 bbls of cement to surface. The results of cement to surface. |
| 13. Describe proposed or compost starting any proposed wor recompletion. 03/09/07 Spud @ 5:30 p.m. Described by the second work of the second wor | rill 11" surface hole to 322'. Run 10 jts pumped 100 sx Midcon II cement, 1 face 8 5/8" csg to 500 psi for 30 mim an 322' - 2581'. Reached TD 2581' and well. Logger's TD at 2560'. ppf, J-55, and 8 jts 17 ppf, J-55 LT&C and 278 sks Midcon II cement. Circular above is true and complete to the best of closed according to NMOCD guidelines , a TITLE Relitchell E-mail address: shirley. | cinent details, and give perticompletions: Attach wellbooks, of 8 5/8", 24 #, J55 ST & 14 ppg, yield 1.66. Circulantes. t 24:00 a.m. casing at 2474'. ted 4 bbls of cement to surfacted 4 bbls of cement to surface and belief general permit or an (attach egulatory Analyst | A C casing at 307'. The Tables of cement to surface. The Tables of cement to surface. The Tables of cement to surface. The Tables of CD-approved plan . DATE 03/13/2007 The Delephone No. (505) 445-6785 |