

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

2007 MAY 22 PM 12:31

WELL API NO.

30-007-20784

7. Indicate Type of Lease

STATE ☐ FEE ☒

7. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other Coalbed Methane

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

P.O. BOX 190, RATON, NM 87740

4. Well Location

Unit Letter A : 470 feet from the North line and 1060 feet from the East line

Section 7 Township 29N Range 19E NMPM Colfax County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

7,982' (GL)

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

04/11/07 Spud @ 7:15 p.m. Drill 11" surface hole to 333'. Run 8 jts. of 8 5/8", 24 #, J55 ST & C casing at 323'. Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.66. Circulate 8 bbls of cement to surface. ✓
WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

04/12/07 Drill 7 7/8" hole from 333' - 2665'. Reached TD 2665' at 4:00 a.m. MIRU Superior and log well. Logger's TD at 2647'. Run 55 jts 5 1/2", 15.5 ppf, J-55, and 8 jts 17 ppf, J-55 LT&C casing at 2552'. HES mixed and pumped 318 sks Midcon II cement. Circulated 10 bbls of cement to surface. ✓

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE

Shirley Mitchell

TITLE Regulatory Analyst

DATE 04/26/2007

Type or print name
For State Use Only

Shirley A. Mitchell

E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785

APPROVED BY:

Ed Martin

TITLE

DISTRICT SUPERVISOR

DATE 5/24/07

Conditions of Approval (if any):