

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO.

30-007-20729

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER Coal Bed Methane

b. Type of Completion:

NEW ☒ WORK ☐ PLUG ☐ DIFF.
WELL ☒ OVER ☐ DEEPEN ☐ BACK ☐ RESVR. OTHER

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

PO BOX 190, RATON, NEW MEXICO 87740

7. Lease Name or Unit Agreement Name

VPR A

8. Well No.

282

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter F : 1782 Feet From The North Line and 1339 Feet From The West Line

Section 4 Township 31N Range 20E NMPM Colfax County

10. Date Spudded
01/12/2007

11. Date T.D. Reached
01/13/2007

12. Date Compl. (Ready to Prod.)
04/27/2007

13. Elevations (DF& R(B. RT, GR, etc.)
8,044'

14. Elev. Casinghead
8,044'

15. Total Depth

2425'

16. Plug Back T.D.

2340'

17. If Multiple Compl. How Many
Zones?

18. Intervals
Drilled By

Rotary Tools

0 - TD

Cable Tools

NONE

19. Producing Interval(s), of this completion - Top, Bottom, Name

899' - 2149' Vermejo - Raton Coals

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

Compensated Density and Cement Bond Log

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	324	11"	100 sks	None
5 1/2"	15.5	2351'	7 7/8"	367 sks	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	2219'	No

26. Perforation record (interval, size, and number)

2139'- 2143', 2147'- 2149' 24 Holes
1925'- 1927', 1942'- 1944', 1946'- 1948', 1965'- 1967', 2019'- 2021 40 Holes
1631'- 1634', 1652'- 1654', 1668'- 1670' 32 Holes
1147'- 1149', 1164'- 1166', 1210'- 1212', 1243'- 1245', 1278'- 1280' 40 Holes
899'- 901', 933'- 935', 1002'- 1005' 28 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED

899' - 2149' 167,057 lbs 20/40 sand

1,258,102 scf nitrogen foam

20# Linear gel

28. PRODUCTION

Date First Production
05/23/2007

Production Method (Flowing, gas lift, pumping - Size and type pump)
Pumping water up 2 7/8" tubing, pc pump.. Flowing gas up 5
1/2" Casing.

Well Status (Prod. or Shut-in)
Production

Date of Test
05/23/2007

Hours Tested
24 hrs.

Choke Size
Full 2"

Prod'n For
Test Period

Oil - Bbl
N/A

Gas - MCF
35

Water - Bbl.
205

Gas - Oil Ratio
N/A

Flow Tubing
Press.
0

Casing Pressure
55

Calculated 24-
Hour Rate

Oil - Bbl.
N/A

Gas - MCF
35

Water - Bbl.
205

Oil Gravity - API - (Corr.)
N/A

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel.

Test Witnessed By:
Steven Medina

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature: Shirley Mitchell Printed Shirley A. Mitchell Title Regulatory Analyst Date: 06/11/07

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton Top <u>Surface</u>
T. Blinebry	T. Gr. Wash	T. Morrison	T. Vermejo <u>1,924'</u>
			Trinidad <u>2,153'</u>
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology