Submit To Appropriate District Office State of New Mexico Form C-105 State Lease - 6 copies Energy, Minerals and Natural Resources Revised March 25, 1999 Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 87240 WELL API NO. 30-007-20395 OIL CONSERVATION DIVISION 5. Indicate Type of Lease District II 811 South First, Artesia, NM 87210 1220 South St Francis **STATE** FEE District III 1000 Rio Brazos Rd., Aztec, NM 87410 State Oil & Gas I se No. Santa Fe, NM 87505 District 1V 1220 South St Francis, Santa Fe, NM 87505 WELL COMPLETION OR RECOMPLETION REPORT AND LOG la. Type of Well: Lease Name or Unit Agreement Name OIL WELL GAS WELL DRY OTHER X COALBED METHANE b. Type of Completion: VPR D NEW WORK PLUG DIFF. OVER DEEPEN BACK ___ RESVR. WELL ___ OTHER 2. Name of Operator Well No. EL PASO ENERGY RATON, L.L.C. 110 3. Address of Operator 9. Pool name or Wildcat PO BOX 190 RATON, NEW MEXICO 87740 Castle Rock Park - Vermejo Gas 4. Well Location Feet From The East Line Unit Letter 906 Feet From The <u>938</u> Township 30N NMPM COLFAX Section Range 11, Date T.D. Reached 12. Date Compl. (Ready to Prod.) 13. Elevations (DF& R(B. RT, GR, etc.) 10. Date Spudded 14. Elev. Casinghead 02/27/03 02/26/03 08/21/03 9050 9050' 15. Total Depth 16 Plug Back T.D. 17. If Multiple Compl. How Many 18. Intervals Rotary Tools Cable Tools Zones? Drilled By 0 - TD 2920' 19. Producing Interval(s), of this completion - Top, Bottom, Name Was Directional Survey Made 2480' - 2717 VERMEJO COALS No 21. Type Electric and Other Logs Run Was Well Cored Array Induction, Epithermal Neutron Litho Density, Mud Log, After Frac and Cement Bond Log. CASING RECORD (Report all strings set in well) 23. DEPTH SET CEMENTING RECORD CASING SIZE WEIGHT LB./FT. HOLE SIZE AMOUNT PULLED 8 5/8" 23 lb. 335' 11" 100 sx. None 2935 15.5 lb. 7 7/8" 5 ½" 438 sx. LINER RECORD TUBING RECORD 24. 25. SIZE TOP BOTTOM SACKS CEMENT SCREEN SIZE DEPTH SET PACKER SET 2 7/8 2764' N/A 26. Perforation record (interval, size, and number) 27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. 2714'- 2717' 8 Holes DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED Did not perforate 2nd stage due to sand over perf interval. 2654'- 2656' 5 Holes 2577'- 2580' 8 Holes 2480'- 2484' 15 Holes 2480' - 2717' 1,615,810 lbs 20/40 Ottawa/TLC Sand **PRODUCTION** 28 Production Method (Flowing, gas lift, pumping - Size and type pump)
Pumping water up 2 7/8 tubing w/ 2'X 1 '4'' X 10' insert pump. Well Status (Prod. or Shut-in) Date First Production 08/28/03 Production Flowing gas up 5 1/2" casing. Date of Test Hours Tested Choke Size Prod'n For Oil - Bbl Gas - MCF Water - Bbl. Gas - Oil Ratio 08/28/03 Full 2" Test Period N/A 24 Hours N/A 294 Flow Tubing Gas - MCF Calculated 24-Oil - Bbl. Water - Bbl. Oil Gravity - API - (Corr.) Casing Pressure

294

Title: Senior Specialist

N/A

Test Witnessed By:

Press.

30. List Attachments

200 psi

Sold, used for fuel.

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Signature Shurley Fritchell

Hour Rate

N/A

Printed

Name:

31 I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Shirley A. Mitchell

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

		Southeaste	ern New Mexico			Northwester	rn New Mexico
T. Anhy				T. Ojo Alar	mo		T. Penn. "B"
T. Salt			T. Strawn	T. Kirtland	T. Ojo AlamoT. Kirtland		T. Penn. "C"
B. Salt			T. Atoka	T. Pictured	T. Pictured Cliffs		T. Penn. "D"
T. Yates			T. Miss	T. Cliff Ho	T. Cliff House		T. Leadville
T. 7 Rivers			T. Devonian	T. Menefee	T. Menefee		T. Madison
T. Queen			T. Silurian	T. Point Lo	T. Point Lookout		T. Elbert
T. Grayburg			T. Montoya	T Mancos	T. Mancos		T. McCracken
T. San Andres			T. Simpson	T. Gallup	T. Gallup		T. Ignacio Otzte
T. Glorieta			T McKee	Rase Green	Base Greenhorn		T. Ignacio Otzte
T. Paddock			T. McKee T. Ellenburger	Dase Orcen T Dakota	T Dakota		T. Granite T Raton – Surface 0'
T Blinehry		·· -	T. Gr. Wash	T. Marrison	T. Dakota T. Morrison		T.Vermejo <u>2,472'</u>
T. Blinebry T.Tubb			T. Delaware Sand	T Todilto	T. MorrisonT.Todilto		T Trinidad $\frac{2,721}{2,721}$
T.Tubb T. Drinkard			T. Bone Springs	T.Tounto T Entrada			T Timidad <u>2,721</u>
Γ. Abo	aru		T. Done Springs	T. Wingate			Ţ,
r Walf			T	T. Wingate			T.
I. WOIIC	amp		T.	I. Cilling			T
r Cirr	(D l-	C)	T	T. Perman	li .		
							OIL OR GAS SANDS OR ZONESto.
Include	data on	rate of water	IMPORTA inflow and elevation to which	ANT WATER SAN water rose in hole	NDS e.		to
No 1 4	rom		toto			teet	
. NU. 1, 1		No. 2, fromtoto					
No. 2, fi	rom		to	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		feet	
No. 2, fi	rom		totototototototo			feet	
No. 2, fi	rom	Thickness	totototototo	ORD (Attach add	ditiona	feet	sary)