Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resource	es May 27, 2004 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	OH CONGERNATION DAMAGE	20.007.20762
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE FEE
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505		
	S AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION OF THIS FORM FOR PROPOSALS	STO DRILL OR TO DEEPEN OR PLUG BACK TO A ON FOR PERMIT" (FORM C-101) FOR SUCH	VPR B
PROPOSALS.)	WILL COLL COLL INCOL	8. Well Number 152
	Well Other Coalbed Methane	
2. Name of Operator	E & P COMPANY, L.P.	9. OGRID Number 180514
3. Address of Operator		10. Pool name or Wildcat
•	190, RATON, NM 87740	Van Bremmer – Vermejo Gas
4. Well Location		
Unit Letter <u>D</u> : <u>1117</u> feet from the <u>North</u> line and <u>135</u> feet from the <u>West</u> line		
Section 19 Township 29N Range 19E NMPM Colfax County		
11	. Elevation (Show whether DR, RKB, RT, C	R, etc.)
100	7,946' (GL)	
Pit or Below-grade Tank Application or Clo		
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appr	ropriate Box to Indicate Nature of N	otice, Report or Other Data
NOTICE OF INTE	NTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A		
PULL OR ALTER CASING MI	ULTIPLE COMPL	EMENT JOB
	5,10,110,10	
OTHER:	OTHER:	Completion ⊠
OTHER: 13. Describe proposed or completed operations of the second of t	OTHER:	Completion
OTHER: 13. Describe proposed or completed operation SEE RULE 1103. For Multiple Complete Com	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completi	Completion
OTHER: 13. Describe proposed or completed operation SEE RULE 1103. For Multiple Completed O4/29/07 Superior ran CBL. Estimated top	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completi	Completion
OTHER: 13. Describe proposed or completed operation SEE RULE 1103. For Multiple Completed top 105/24/07 Superior ran CBL. Estimated top 105/24/07 Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st stage - Pumpe	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completion of cement at 30°. 2273'- 2276', 2295'- 2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge	Completion ent dates, including estimated date of starting any proposed work). on or recompletion. foam with 9,000 lbs 20/40 mesh sand.
OTHER: 13. Describe proposed or completed operation SEE RULE 1103. For Multiple Completed Operation of Superior ran CBL. Estimated top Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st Superior perf'd 2nd stage -	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions of cement at 30°. 2273'- 2276', 2295'- 2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'- 2050', 2087'- 2089', 2118'- 2120' 32 H	Completion ent dates, including estimated date of starting any proposed work). on or recompletion. foam with 9,000 lbs 20/40 mesh sand. Toles
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed SEE RULE 1103. For Multiple Completed operating SEE RULE 1103. For Multiple Completed Superior ran CBL. Estimated top Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 3stage - Pumped 3stage - Pumped 3stage - Pumped 3stage - Superior perf'd 3rd stage - Pumped 3stage - Pumped	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: 2273'-2276', 2295'-2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'-2050', 2087'-2089', 2118'-2120' 32 Holes 332,306 scf 70% quality nitrogen with linear ge 1755'-1757', 1770'-1772', 1776'-1782', 1818	Completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. loles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed SEE RULE 1103. For Multiple Completed operating SEE RULE 1103. For Multiple Completed SEE RULE 1103. For Multiple Completed Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 1st Superior perf'd 3nd stage - Pumped 1st Superior perf'd 3nd stage - Pumped 1st	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: 2273'-2276', 2295'-2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'-2050', 2087'-2089', 2118'-2120' 32 Holes 332,306 scf 70% quality nitrogen with linear ge 1755'-1757', 1770'-1772', 1776'-1782', 1818 12,029 scf 70% quality nitrogen with linear ge	Completion Ent dates, including estimated date of starting any proposed work). In or recompletion. Foam with 9,000 lbs 20/40 mesh sand. Ioles Foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes Foam with 25,500 lbs 20/40 mesh sand.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed SEE RULE 1103. For Multiple Completed operating SEE RULE 1103. For Multiple Completed SEE RULE 1103. For Multiple Completed Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 1st Superior perf'd 3nd stage - Pumped 1st Superior perf'd 4th stage - Pumped 1st Superior perf'	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: 2273'-2276', 2295'-2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'-2050', 2087'-2089', 2118'-2120' 32 Holes 332,306 scf 70% quality nitrogen with linear ge 1755'-1757', 1770'-1772', 1776'-1782', 1818 12,029 scf 70% quality nitrogen with linear ge 1096'-1098', 1138'-1142', 1166'-1168', 1180'-1168	Completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. loles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes
OTHER: 13. Describe proposed or completed operation SEE RULE 1103. For Multiple Completed 05/24/07 Superior ran CBL. Estimated top 05/24/07 Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 3 Superior perf'd 3nd stage - Pumped 3 Superior perf'd 3nd stage - HES frac'd 3nd stage - Pumped 1 Superior perf'd 4th stage - HES frac'd 4th stage - Pumped 1 Superior perf'd 4th s	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: 2273'-2276', 2295'-2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'-2050', 2087'-2089', 2118'-2120' 32 In 32,306 scf 70% quality nitrogen with linear ge 1755'-1757', 1770'-1772', 1776'-1782', 1818 12,029 scf 70% quality nitrogen with linear ge 1996'-1098', 1138'-1142', 1166'-1168', 1180', 340,108 scf 70% quality nitrogen with linear ge	Completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. foles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed 05/24/07 Superior ran CBL. Estimated top 05/24/07 Superior perf'd 1st stage - Pumped 1 Superior perf'd 2nd stage - Pumped 3 Superior perf'd 3rd stage - Pumped 3 Superior perf'd 3rd stage - Pumped 1 Superior perf'd 4th stage - Pumped 1 Superior perf'd 4th stage - Pumped Superior perf'd 5th stage - Pumped Super	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: 2273'-2276', 2295'-2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'-2050', 2087'-2089', 2118'-2120' 32 Is 332,306 scf 70% quality nitrogen with linear ge 1755'-1757', 1770'-1772', 1776'-1782', 1818 12,029 scf 70% quality nitrogen with linear ge 096'-1098', 1138'-1142', 1166'-1168', 1180', 340,108 scf 70% quality nitrogen with linear ge 43'-846', 857'-859', 885'-887', 894'-896', 91 322,272 scf 70% quality nitrogen with linear ge	Completion ⊠ ent dates, including estimated date of starting any proposed work). In or recompletion. foam with 9,000 lbs 20/40 mesh sand. Ioles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes I foam with 22,500 lbs 20/40 mesh sand. 0'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes I foam with 10,200 lbs 20/40 mesh sand.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed 05/24/07 Superior ran CBL. Estimated top 05/24/07 Superior perf'd 1st stage - Pumped 1 Superior perf'd 2nd stage - Pumped 3 Superior perf'd 3rd stage - Pumped 3 Superior perf'd 3rd stage - Pumped 1 Superior perf'd 4th stage - Pumped 1 Superior perf'd 4th stage - Pumped Superior perf'd 5th stage - Pumped Super	OTHER: ions. (Clearly state all pertinent details, and give pertinetions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: Attach wellbore diagram of proposed completions: 2273'-2276', 2295'-2298' 16 Holes 43,384 scf 70% quality nitrogen with linear ge 2046'-2050', 2087'-2089', 2118'-2120' 32 In 32,306 scf 70% quality nitrogen with linear ge 1755'-1757', 1770'-1772', 1776'-1782', 1818 12,029 scf 70% quality nitrogen with linear ge 1096'-1098', 1138'-1142', 1166'-1168', 1180', 340,108 scf 70% quality nitrogen with linear ge 43'-846', 857'-859', 885'-887', 894'-896', 91	Completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866' - 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes el foam with 22,500 lbs 20/40 mesh sand. 0' - 912', 937' - 939', 955' - 957', 968' - 970' 68 Holes foam with 10,200 lbs 20/40 mesh sand.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed operating SEE RULE 1103. For Multiple Completed operating SEE RULE 1103. For Multiple Completed operations of the second of the second of the second operation operation of the second operation of the second operation of the second operation operat	OTHER: OTHER:	Completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. foles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes el foam with 22,500 lbs 20/40 mesh sand. 0'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes foam with 10,200 lbs 20/40 mesh sand. ut on production.
OTHER: 13. Describe proposed or completed operations SEE RULE 1103. For Multiple Completed 04/29/07 Superior ran CBL. Estimated top 05/24/07 Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1 Superior perf'd 2nd stage - Pumped 3 Superior perf'd 3rd stage - Pumped 3 Superior perf'd 3rd stage - HES frac'd 3rd stage - Pumped 1 Superior perf'd 4th stage - HES frac'd 4th stage - Pumped Superior perf'd 5th stage - Pumped Superior perf'd 5th stage - Pumped Clean out well bore. RIH tubing,	OTHER: OTHER:	Completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866' - 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes el foam with 22,500 lbs 20/40 mesh sand. 0' - 912', 937' - 939', 955' - 957', 968' - 970' 68 Holes foam with 10,200 lbs 20/40 mesh sand.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed 04/29/07 Superior ran CBL. Estimated top 05/24/07 Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1 Superior perf'd 2nd stage - Pumped 3 Superior perf'd 3nd stage - Pumped 3 Superior perf'd 3nd stage - HES frac'd 3nd stage - Pumped 1 Superior perf'd 4th stage - Pumped Superior perf'd 4th stage - Pumped Superior perf'd 5th stage - Pumped Superior perf'd 5th stage - Pumped Superior perf'd 5th stage - Pumped O6/04/07 Clean out well bore. RIH tubing, I hereby certify that the information above grade tank has been/will be constructed or close	OTHER: OTHER:	completion ment dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. Itoles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes el foam with 22,500 lbs 20/40 mesh sand. 20'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes foam with 10,200 lbs 20/40 mesh sand. at on production.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed operating Superior perf'd 1st stage - HES frac'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 1st Superior perf'd 3nd stage - Pumped 1st Superior perf'd 4nd stage - Pumped 1st Superior perf'd 4nd stage - Pumped Superior perf'd 5nd stage - Pumped Superior perf'd 5nd stage - Pumped 1st Superior perf'd 5nd stage - Pum	OTHER: OTHER:	completion ment dates, including estimated date of starting any proposed work). If oam with 9,000 lbs 20/40 mesh sand. Itoles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes lef foam with 22,500 lbs 20/40 mesh sand. 20'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes I foam with 10,200 lbs 20/40 mesh sand. 21 on production.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed operations of Superior perf'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 1st Superior perf'd 3nd stage - Pumped 1st Superior perf'd 4th stage - Pumped Superior perf'd 5th stage - Pumped Superior perf'd 5th stage - Pumped O6/04/07 Clean out well bore. RIH tubing, I hereby certify that the information above grade tank has been/will be constructed or close SIGNATURE Type or print name Shirley A Mitchel	OTHER: OTHER:	completion ment dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. foles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes el foam with 22,500 lbs 20/40 mesh sand. 0'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes foam with 10,200 lbs 20/40 mesh sand. at on production. Owledge and belief. I further certify that any pit or belowermit □ or an (attached) alternative OCD-approved plan □. ONLY ORDITION
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed operating SUPPRINT STATE OF SUPPRINT OF SUPPRINT OF STATE OF SUPPRINT OF STATE OF SUPPRINT OF STATE OF STATE OF SUPPRINT OF STATE OF STAT	OTHER: OTHERE OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHERE	completion ent dates, including estimated date of starting any proposed work). foam with 9,000 lbs 20/40 mesh sand. loles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes el foam with 22,500 lbs 20/40 mesh sand. 0'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes foam with 10,200 lbs 20/40 mesh sand. or on production.
OTHER: 13. Describe proposed or completed operating SEE RULE 1103. For Multiple Completed operations of Superior perf'd 1st stage - Pumped 1st Superior perf'd 2nd stage - Pumped 1st Superior perf'd 3nd stage - Pumped 1st Superior perf'd 4th stage - Pumped Superior perf'd 5th stage - Pumped Superior perf'd 5th stage - Pumped O6/04/07 Clean out well bore. RIH tubing, I hereby certify that the information above grade tank has been/will be constructed or close SIGNATURE Type or print name Shirley A Mitchel	OTHER: OTHERE OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHERE	completion ment dates, including estimated date of starting any proposed work). If oam with 9,000 lbs 20/40 mesh sand. Itoles foam with 18,200 lbs 20/40 mesh sand. - 1820', 1866'- 1869' 76 Holes foam with 25,500 lbs 20/40 mesh sand. 1182' 40 Holes lef foam with 22,500 lbs 20/40 mesh sand. 20'- 912', 937'- 939', 955'- 957', 968'- 970' 68 Holes I foam with 10,200 lbs 20/40 mesh sand. 21 on production.