Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural-Resource	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	er en	WELL API NO.
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION 1220 South St. Flancis Dr.	30-007-20831 7. Indicate Type of Lease
District III	1220 South St. Fishers Dr.	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	7. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505 AM 1	Land on the one person were
87505 SUNDRY NOT	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPO	SALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
	CATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR A
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well Other Coalbed Methane	8. Well Number 267
2. Name of Operator	2.3	9. OGRID Number
EL PAS	O E & P COMPANY, L.P.	
3. Address of Operator		10. Pool name or Wildcat
	190, RATON, NM 87740	·
4. Well Location		
Unit Letter <u>E</u> : <u>2114</u> feet from the <u>North</u> line and <u>463</u> feet from the <u>West</u> line		
Section 20 Township 31N Range 20E NMPM Colfax County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 8, 163(GL)		
Pit or Below-grade Tank Application ☐ or Closure ☐		
Pit typeDepth to GroundwaterDistance from nearest fresh water wellDistance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN		SUBSEQUENT REPORT OF:
<u> </u>	PLUG AND ABANDON REMEDIAL	_
TEMPORARILY ABANDON		E DRILLING OPNS. P AND A
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CE	EMENT JOB
OTHER:	□ OTHER:	П
		ils, and give pertinent dates, including estimated dates
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
07/05/07 0 10 1115		24# 155 OT 0 O 1 1 200
07/25/07 Spud @ 11:15 a.m. Drill 11" surface hole to 332'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 322'. Halliburton mixed and pumped 100 sks Midcon II cement. Circulated 6 bbls of cement to surface.		
WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.		
Wood in st. Test surf	ace 0 3/0 esg to 500 psi for 50 initiates.	
	n 332' - 2435'. Reached TD at 2435' at 12:00	p.m.
MIRU Superior and log well. Logger's TD 2419'.		
Run 50 jts 5 ½, 15.5 ppf, J-55, and 8 jts 17 ppf, J-55 LT&C casing at 2367'. HES mixed and pumped 359 sks Midcon II cement. Circulated 14 bbls of cement to surface.		
TIES mixed and pumpe	d 339 sks Wildcoll II cellient. Circulated 14 obis	of cement to surface.
		wledge and belief. I further certify that any pit or below mit [] or an (attached) alternative OCD-approved plan [].
SIGNATURE QALANA	Pritchell TITLE Regulatory	A no.livet DATE 00/20/2007
Type or print name Shirley A. Mi		
For State Use Only		
10	no A. nictoir	T CLIDEDVICAD _ / /
APPROVED BY:	Jaston TITLE VISIRIU	T SUPERVISOR DATE 9/5-/07
Conditions of Approval (if any):		, ,