

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO. 30-007-20792
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> DRY <input type="checkbox"/> OTHER <u>Coal Bed Methane</u>	7. Lease Name or Unit Agreement Name VPR A
b. Type of Completion: NEW <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> OTHER <input type="checkbox"/>	8. Well No. 276
2. Name of Operator EL PASO E & P COMPANY, L.P.	9. Pool name or Wildcat Stubblefield Canyon Raton - Vermejo Gas
3. Address of Operator PO BOX 190, RATON, NEW MEXICO 87740	

4. Well Location Unit Letter <u>O</u> : <u>861</u> Feet From The <u>South</u> Line and <u>1609</u> Feet From The <u>East</u> Line Section <u>7</u> Township <u>31N</u> Range <u>20E</u> NMPM Colfax County					
10. Date Spudded 04/25/2007	11. Date T.D. Reached 04/26/2007	12. Date Compl. (Ready to Prod.) 08/03/2007	13. Elevations (DF& R(B. RT, GR, etc.) 8,296'	14. Elev. Casinghead 8,296'	
15. Total Depth 2,335'	16. Plug Back T.D. 2,532'	17. If Multiple Compl. How Many Zones? 0 - TD	18. Intervals Drilled By 0 - TD	19. Producing Interval(s), of this completion - Top, Bottom, Name 929'- 2,345' Vermejo - Raton Coals	
21. Type Electric and Other Logs Run Compensated Density and Cement Bond Log / Gamma Ray			22. Was Directional Survey Made NO		
23. CASING RECORD (Report all strings set in well)			24. Was Well Cored No		

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	324'	11"	100 sks	None
5 1/2"	15.5	2,553'	7 7/8"	363 sks	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2,408'	No

26. Perforation record (interval, size, and number) 2340'- 2345' 20 Holes 2148'- 2152', 2230'- 2233', 2238'-2245' 40 Holes 1276'- 1279', 1295'- 1298', 1301'- 1311', 1348'-1350', 1370'-1374' 98 Holes 929'- 933', 1022'- 1025', 1037'- 1040', 1053'- 1061' 72 Holes	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	929'- 2,345'	76,932 lbs 20/40 sand
		921,470 scf 70% quality nitrogen foam
	With 20# linear gel	

28. PRODUCTION							
Date First Production 09/13/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing, pc pump.. Flowing gas up 5 1/2" Casing.				Well Status (Prod. or Shut-in) Production	
Date of Test 09/13/2007	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period N/A	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl. 187	Gas - Oil Ratio N/A
Flow Tubing Press. 0	Casing Pressure 77	Calculated 24-Hour Rate N/A	Oil - Bbl. N/A	Gas - MCF 0	Water - Bbl. 187	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.	Test Witnessed By: Vern Little/ Jake Middlebrook
---	--

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.			
Signature: <u>Shirley Mitchell</u>	Printed Shirley A. Mitchell	Title Regulatory Analyst	Date: 10/16/2007

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105. /

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinebry	T. Gr. Wash
T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo	T.
T. Wolfcamp	T.
T. Penn	T.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzite
Base Greenhorn	T. Granite
T. Dakota	T. Raton Top <u>0'</u>
T. Morrison	T. Vermejo <u>2,148'</u>
	Trinidad <u>2,378'</u>
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology