

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO. 30-007-20818
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> DRY <input type="checkbox"/> OTHER <u>Coal Bed Methane</u>	7. Lease Name or Unit Agreement Name VPR A
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> OTHER <input type="checkbox"/>	8. Well No. 305
2. Name of Operator EL PASO E & P COMPANY, L.P.	9. Pool name or Wildcat Stubblefield Canyon Raton - Vermejo Gas
3. Address of Operator PO BOX 190, RATON, NEW MEXICO 87740	

4. Well Location Unit Letter P : 817 Feet From The South Line and 300 Feet From The East Line Section 22 Township 31N Range 20E NMPM Colfax County				
10. Date Spudded 05/29/2007	11. Date T.D. Reached 05/30/2007	12. Date Compl. (Ready to Prod.) 08/13/2007	13. Elevations (DF& R(B. RT, GR, etc.) 8,028'	14. Elev. Casinghead 8,028'
15. Total Depth 2,315'	16. Plug Back T.D. 2,194'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By 0 - TD	Cable Tools NONE
19. Producing Interval(s), of this completion - Top, Bottom, Name 804'- 2010' Vermejo - Raton Coals				20. Was Directional Survey Made NO
21. Type Electric and Other Logs Run Compensated Density and Cement Bond Log				22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	324'	11"	100 sks	None
5 1/2"	15.5	2,194'	7 7/8"	261 sks	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2,057'	No
26. Perforation record (interval, size, and number)				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.			
804'- 808', 850'- 860', 880'- 888', 914'- 917' 100 Holes				DEPTH INTERVAL			
1086'- 1090', 1108'- 1111' 28 Holes				AMOUNT AND KIND MATERIAL USED			
1845'- 1848', 1858'- 1862' 28 Holes				804'- 2010'			
1973'- 1978', 1993'- 1998', 2002'- 2010' 72 Holes				94,773 lbs 20/40 sand			
				969,886 scf nitrogen foam			
				20# Linear gel			

28. PRODUCTION							
Date First Production 09/18/2007		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing, pc pump.. Flowing gas up 5 1/2" Casing.			Well Status (Prod. or Shut-in) Production		
Date of Test 09/18/2007	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl. 187	Gas - Oil Ratio N/A
Flow Tubing Press. 0	Casing Pressure 22	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 0	Water - Bbl. 187	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.	Test Witnessed By: Vern Little
---	--

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.			
Signature: <i>Shirley Mitchell</i>	Printed Shirley A. Mitchell	Title Regulatory Analyst	Date: 11/02/2007

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy_____	T. Canyon_____
T. Salt_____	T. Strawn_____
B. Salt_____	T. Atoka_____
T. Yates_____	T. Miss_____
T. 7 Rivers_____	T. Devonian_____
T. Queen_____	T. Silurian_____
T. Grayburg_____	T. Montoya_____
T. San Andres_____	T. Simpson_____
T. Glorieta_____	T. McKee_____
T. Paddock_____	T. Ellenburger_____
T. Blinberry_____	T. Gr. Wash_____

T. Tubb_____	T. Delaware Sand_____
T. Drinkard_____	T. Bone Springs_____
T. Abo_____	T. _____
T. Wolfcamp_____	T. _____
T. Penn_____	T. _____
T. Cisco (Bough C)_____	T. _____

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzite
Base Greenhorn	T. Granite
T. Dakota	T. Raton Top <u>Surface</u>
T. Morrison	T. Vermejo <u>1,840'</u>
	Trinidad <u>2,020'</u>

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology