Submit 3 Copies To Appropriate District	State of New Mex	xico	Form C-103
Office District I	Energy, Minerals and Natural Resources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	-		WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION	DIVISION	30-007-20901
District III	1220 South St. France		7. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87		STATE FEE S
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa I C, IVIVI 67.	303	7. State Oil & Gas Lease No.
	ICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			VPR B
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well Other Coalbed Me	thane	8. Well Number 238
2. Name of Operator	Gus Weii 🖂 Other Coalbed Me	thane	9. OGRID Number
•	O E & P COMPANY, L.P.		
3. Address of Operator			10. Pool name or Wildcat
P.O. BOX	K 190, RATON, NM 87740		
4. Well Location			
Unit Letter <u>J</u> : 1421 feet from the <u>South</u> line and <u>1765</u> feet from the <u>East</u> line			
Section 4 Township 29N Range 19E NMPM Colfax County			
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7,490' (GL)			
Pit or Below-grade Tank Application ☐ or Closure ☐			
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water			
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN	ITENTION TO:	SUBS	EQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON 🔲	REMEDIAL WORK	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRIL	LING OPNS.⊠ PAND A □
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	JOB
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated dat of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
01/13/08 Spud @ 6:30 p.m. Drill 11" surface hole to 323'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 324'. Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.66. Circulated 6 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.			
01/14/08 Drill 7 7/8" hole from 323' - 2,075'. Reached TD 2,075' at 6:30 p.m. MIRU Weatherford and log well. Logger's TD at 2,051'. Run 41 jts 5 ½", 15.5 ppf, J-55, and 9 jts 17 ppf, J-55 LT & C casing at 1,985'. HES mixed and pumped 224 sks Midcon II cement. Circulated 10 bbls of cement to surface.			
I hereby certify that the information grade tank has been/will be constructed or SIGNATURE Shurley En	closed according to NMOCD guidelines	, a general permit 🗌 o	and belief. I further certify that any pit or below- r an (attached) alternative OCD-approved plan
Type or print name For State Use Only		Regulatory Analyst ey.mitchell@elpaso	DATE01/22/2008 .com
APPROVED BY: Martin TITLE DISTRICT SUPERVISOR DATE 1/28/08 Conditions of Approval (if any):			