Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-007-20900
District III	1220 South St. Francis Dr.	7. Indicate Type of Lease STATE ☐ FEE ☒
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	STATE FEE 7. State Oil & Gas Lease No.
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Sunta 1 C, 1 CO 1 5 0 5	7. State Off & Gas Lease No.
87505		
	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A ICATION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS.)	CATION FOR TERMIT (FORM C-101) FOR SUCH	VPR B
1. Type of Well: Oil Well	Gas Well Other Coalbed Methane	8. Well Number 241
2. Name of Operator		9. OGRID Number
EL PAS	O E & P COMPANY, L.P.	
3. Address of Operator		10. Pool name or Wildcat
P.O. BO	X 190, RATON, NM 87740	
4. Well Location		
Unit Letter <u>L</u> : <u>2288</u> feet from the <u>South</u> line and <u>80</u> feet from the <u>West</u> line		
Section 3 Township 29N Range 19E NMPM Colfax County		
O THE Proposition of the Proposi	11. Elevation (Show whether DR, RKB, RT, GR,	
The state of the s	7,694' (GL)	
Pit or Below-grade Tank Application	or Closure 🗌	
Pit typeDepth to GroundwaterDistance from nearest fresh water wellDistance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
_		DRILLING OPNS.⊠ PANDA □
PULL OR ALTER CASING		
TOLE ON METER ONGING	MOETH EL COM E	WEIN TOOL
OTHER:	☐ OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion		
or recompletion.		
01/14/08 Spud @ 8:30 a.m. Drill 11" surface hole to 323'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 324'.		
Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.66. Circulated 6 bbls of cement to surface.		
WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.		
01/15/08 Drill 7 7/8" hole from 323' - 2,265'. Reached TD 2,265' at 1:15 p.m.		
MIRU Weatherford and log well. Logger's TD at 2,223'.		
Run 45 jts 5 ½", 15.5 ppf, J-55, and 9 jts 17 ppf, J-55 LT & C casing at 2,162'.		
HES mixed and pumped 231 sks Midcon II cement. Did not circulate to surface. Prep for remedial cement squeeze job.		
	above is true and complete to the best of my know	
grade tank has been/will be constructed o	r closed according to NMOCD guidelines , a general perm	iit 📙 or an (attached) alternative OCD-approved plan 🔲.
SIGNATURE Shirly nitchell TITLE Regulatory Analyst DATE 01/22/2008		
Type or print name Shirley A. M		<u>nalyst</u> DATE <u>01/22/2008</u> elpaso.com Telephone No. (505) 445-6785
For State Use Only		
10.		PAUDENIIAAD / .
APPROVED BY:	Martin TITLE DISTRIC	T SUPERVISOR DATE 1/28/08
Conditions of Approval (if any):		