Submit 3 Copies To Appropriate District	State of New Mexico		
Office <u>District I</u>	Energy, Minerals and Natural R	Resources May 27, 200	
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.	
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIV	I / Indicate Lyne of Lease	
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis	Dr. STATE FEE	
District IV	Santa Fe, NM 87505	7. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM ' 87505			
	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		ICIT	
PROPOSALS.)		VIKD	
1. Type of Well: Oil Well	Gas Well Other Coalbed Methan		
2. Name of Operator		9. OGRID Number	
3. Address of Operator	SO E & P COMPANY, L.P.	10. Pool name or Wildcat	
P.O. BOX 190, RATON, NM 87740			
4. Well Location			
	1453 feet from the North line a	and 124 feet from the East line	
Section 30 Townsh		NMPM Colfax County	
0	11. Elevation (Show whether DR, RKI		
	7,681' (GL		
Pit or Below-grade Tank Application			
Pit typeDepth to Ground	waterDistance from nearest fresh water v	well Distance from nearest surface water	
Pit Liner Thickness: mi	l Below-Grade Tank: Volume	bbls; Construction Material	
12. Check	Appropriate Box to Indicate Natur	e of Notice, Report or Other Data	
NOTICE OF I	NTENTION TO:	SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WOR			
-		OMMENCE DRILLING OPNS.⊠ P AND A □	
PULL OR ALTER CASING] MULTIPLE COMPL CA	SING/CEMENT JOB	
OTHER:	ПОТ	HER:	
		nent details, and give pertinent dates, including estimated d	
~ · · · ·	vork). SEE RULE 1103. For Multiple Co	ompletions: Attach wellbore diagram of proposed completi	
or recompletion.			
01/24/08 Spud @ 7:15 p.m. Drill 11" surface hole to 335'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 325'.			
Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.66. Circulated 6 bbls of cement to surface.			
	urface 8 5/8" csg to 500 psi for 30 minute		
	m 335' - 2,220'. Reached TD 2,220' a	at 2:30 a.m.	
MIRU Weatherford and log well. Logger's TD at 2,186'. Run 45 jts 5 ½'', 15.5 ppf, J-55, and 10 jts 17 ppf, J-55 LT & C casing at 2,497.40'.			
	ped 239 sks Midcon II cement. Circulated		
		6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
		f my knowledge and belief. I further certify that any pit or belov general permit 🗌 or an (attached) alternative OCD-approved plan 🗖	
0.7		per an per ant	
SIGNATURE Shirly	<u> </u>	ulatory Analyst DATE 01/31/2008	
Type or print name Shirley A. A.	Iitchell E-mail address: shirley.n	nitchell@elpaso.com Telephone No. (505) 445-6785	
For State Use Only	1 1 5016	ASSIAS ALIBERIJAAS	
APPROVED BY:	Wartin TITLE DR	STRICT SUPERVISOR DATE 2/4/08	
Conditions of Approval (if any):		• •	
2008 FEB 4 PM 12 28			
	RECEIVED		
	//12/23/3		