District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes \(\subseteq \text{No} \subseteq \)

Type of action: Registration of a pit or below-grade tank \(\subseteq \text{Closure of a pit or below-grade tank} \(\subseteq \text{X} \)

	<u> </u>	
Operator: Hess Corporation Telephone: (432) 758-6738 c-mail address: cmoore@hess.com		
Address: P.O. Box 840 Seminole, Texas 79360		
Facility or well name: WBDU 021H API#: 3	ility or well name: WBDU 021H API#: 30-021-20431 U/L or Qtr/Qtr H Sec 2 T 18N R 29E	
County: Harding Latitude 35.820361 Longitude 103.824533 NAD: 1927 1983		
Surface Owner: Federal State Private Indian		
Pit	Below-grade tank	
Type: Drilling M Production Disposal D	Volume:bbl Type of fluid:	
Workover Emergency	Construction material:	
Lined 🗵 Unlined 🗌	Double-walled, with leak detection? Yes [] If not	
ner type: Synthetic [X] Thickness 12 mil Clay [
Pit Volume 4000 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet	(20 points)
	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
	Yes	(20 1.4.)
Wellhead protection area: (Less than 200 feet from a private domestic		(20 points)
water source, or less than 1000 feet from all other water sources.)	No.	(0 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)
	200 feet or more, but less than 1000 feet	(10 points)
angulari salara, and persaman and spiralism with the salara spiralism and spiralism an	1000 feet or more	(0 points)
	Ranking Score (Total Points)	10
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite of offsite. If offsite, name of facility (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No Yes If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments: The working pit contents were transferred to the back reserve pint and the deep bury trench was dug in the working pit area. The		
deep bury trench was then lined with a 12 mil. liner. All pit contents were then transferred into the lined bury pit and capped		
with a 20 mil. liner. Bury pit was backfilled and contoured with 3' of soil capable of supporting native plant growth to prevent		
erosion and the ponding of rainwater. No ground water was encountered during this pit closure.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit, or an (attached) alternative OCD-approved plan Date: Printed Name/TitleTeff Raines/Agent Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or		
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. Approval: Printed Name/Title Signature Signature DISTRICT SUPERVISOR Date: 2/3/09		
		7-701