Office	State of New IV		Form C-103
District I	Energy, Minerals and Na	tural Resources	June 19, 2008 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240			1
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATIO	N DIVISION	30-019-20138
District III	1220 South St. Fr	ancis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM		STATE FEE X
District IV	Sama PC, INIVI	07303	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505			NA
	CES AND REPORTS ON WELL	S	7 Lease Name or Unit Agreement Name
PROPOSALS.)			
	Gas Well X Other		
2. Name of Operator			
SWEPI LP		AITIAL	
3. Address of Operator	CONFIDE	NIIAL	10. Pool name or Wildcat
P.O. Box 576, Houston, TX 77001		• • • • • • • • • • • • • • • • • • • •	Wildcat
4 Well Location			
SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A IFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH ROPOSALS.)  Type of Well: Oil Well			
Section 3			
	11. Elevation (Show whether L	R, RKB, RT, GR, etc	
	4640.8+/- graded		The state of the s
10 Ct 1 A	: 1 D 1 1 1 1	NI ( CNI-C'	Daniel Odan Data
12. Check A	ppropriate Box to Indicate	Nature of Notice,	, Report or Other Data
NOTICE OF IN	TENTION TO:	QHE	SSEQUENT REPORT OF:
		REMEDIAL WOR	
PERFORM REMEDIAL WORK	PLUG AND ABANDON		<del>-</del>
TEMPORARILY ABANDON	CHANGE PLANS		RILLING OPNS. P AND A
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN	NT JOB X
DOWNHOLE COMMINGLE			
		AT11E6	
OTHER:		OTHER:	
OTHER:  13. Describe proposed or compl	eted operations. (Clearly state a		nd give pertinent dates, including estimated date
13. Describe proposed or compl	eted operations. (Clearly state a	Il pertinent details, ar	nd give pertinent dates, including estimated date attach wellbore diagram of proposed completion
13. Describe proposed or compl of starting any proposed wo	eted operations. (Clearly state a rk). SEE RULE 1103. For Mult	Il pertinent details, ar	nd give pertinent dates, including estimated date attach wellbore diagram of proposed completion
13. Describe proposed or compl	eted operations. (Clearly state a rk). SEE RULE 1103. For Mult	Il pertinent details, ar	nd give pertinent dates, including estimated date attach wellbore diagram of proposed completion
13. Describe proposed or compl of starting any proposed wo or recompletion.	rk). SEE RULE 1103. For Mult	Il pertinent details, ar iple Completions: A	attach wellbore diagram of proposed completion
13. Describe proposed or compl of starting any proposed wo or recompletion.	rk). SEE RULE 1103. For Mult	Il pertinent details, ar iple Completions: A	nd give pertinent dates, including estimated date attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet.
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot	rk). SEE RULE 1103. For Mult	Il pertinent details, ar iple Completions: A  Float shoe set at 14	attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet.
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of less	rk). SEE RULE 1103. For Mult - 10.75-inch, K-55 STC casing. ad cement; class "C" blended o	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt.
13. Describe proposed or complete of starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leaver expanding agent + 3.0% by wt. acc	rk). SEE RULE 1103. For Mult - 10.75-inch, K-55 STC casing. ad cement; class "C" blended elerator + 2.5% by wt. extende	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @	attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet.
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of less	rk). SEE RULE 1103. For Mult - 10.75-inch, K-55 STC casing. ad cement; class "C" blended elerator + 2.5% by wt. extende	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt.
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (1)	rk). SEE RULE 1103. For Multi- - 10.75-inch, K-55 STC casing. ad cement; class "C" blended elerator + 2.5% by wt. extended LCM).	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (1)	rk). SEE RULE 1103. For Multi- - 10.75-inch, K-55 STC casing. ad cement; class "C" blended elerator + 2.5% by wt. extended LCM).	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt.
13. Describe proposed or complete of starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lese expanding agent + 3.0% by wt. accelbs./sack lost circulation material ()  Mixed and pumped 365 sacks of ta	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended the company of the company of the cement; class "C" blended celerator.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (1)	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended the company of the company of the cement; class "C" blended celerator.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (Mixed and pumped 365 sacks of tall Returned 100+ bbls. cement back to	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complete of starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lese expanding agent + 3.0% by wt. accelbs./sack lost circulation material ()  Mixed and pumped 365 sacks of ta	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complosed starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lest expanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of tall Returned 100+ bbls. cement back to the same tested casing to 1500 psi for the same tested casing tested casin	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complor of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (Mixed and pumped 365 sacks of tall Returned 100+ bbls. cement back to	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complosed starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lest expanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of tall Returned 100+ bbls. cement back to the same tested casing to 1500 psi for the same tested casing tested casin	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
of starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lexexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (Mixed and pumped 365 sacks of take the Returned 100+ bbls. cement back to the Pressure tested casing to 1500 psi for the Field data are available on rig for the starting any proposed work of the sacks of the pressure tested casing to 1500 psi for the sacks of the pressure tested casing to 1500 psi for the sacks of the sacks of the pressure tested casing to 1500 psi for the sacks of t	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complosed starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lest expanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of tall Returned 100+ bbls. cement back to the same tested casing to 1500 psi for the starting and pumped 365 sacks of tall Returned 100+ bbls. cement back to the same tested casing to 1500 psi for the starting any proposed or completion.	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and  cement (113 bbls. @	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complosed starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leaver and agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of take the sack of take the sack to the sac	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and  cement (113 bbls. @	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complosed starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leaver and agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of take the sack of take the sack to the sac	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @  cr + 0.6% by wt. and  cement (113 bbls. @	Attach wellbore diagram of proposed completion 495 feet. Float collar set at 1446 feet. 11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leavenanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for the sack of ta  Field data are available on rig for the sack of ta  April 9, 2009	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg) with 4.0% by wt. extender.
13. Describe proposed or complosed starting any proposed work or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leaver and agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of take the sack of take the sack to the sac	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg) with 4.0% by wt. extender.
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leavenanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for the sack of ta  Field data are available on rig for the sack of ta  April 9, 2009	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg) with 4.0% by wt. extender.
13. Describe proposed or complete of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for sacks of ta  Spud Date:  April 9, 2009	rk). SEE RULE 1103. For Multi- 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended CCM).  il cement; class "C" blended consurface.  or 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  rement (225 bbls @  r + 0.6% by wt. and  ement (113 bbls. @  Date:	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg) with 4.0% by wt. extender.
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of leavenanding agent + 3.0% by wt. accelbs./sack lost circulation material (  Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for the sack of ta  Field data are available on rig for the sack of ta  April 9, 2009	rk). SEE RULE 1103. For Multi- 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended CCM).  il cement; class "C" blended consurface.  or 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg) with 4.0% by wt. extender.
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (Mixed and pumped 365 sacks of take the Returned 100+ bbls. cement back to the Pressure tested casing to 1500 psi for the Field data are available on rig for the Spud Date:  April 9, 2009  I hereby certify that the information at Signature 14. If the same proposed work and pumped 365 sacks of take the same proposed	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended coo surface.  for 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @  Date:  best of my knowled  gulatory Coordinator	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg ) with 4.0% by wt. extender.  ge and belief.  DATE:4/17/2009
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material ( Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for the same same same same same same same sam	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended coo surface.  for 30 minutes.  verification.  Rig Release	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @  Date:  best of my knowled  gulatory Coordinator	495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg) with 4.0% by wt. extender.
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material (Mixed and pumped 365 sacks of take the Returned 100+ bbls. cement back to the Pressure tested casing to 1500 psi for the Field data are available on rig for the Spud Date:  April 9, 2009  I hereby certify that the information at Signature 14. If the same proposed work and pumped 365 sacks of take the same proposed	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.  verification.  Rig Release  above is true and complete to the cergstrom E-mail addresser	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @  Date:  best of my knowled gulatory Coordinator is:michael.bergstr	Attach wellbore diagram of proposed completion  495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg ) with 4.0% by wt. extender.  ge and belief.  r DATE:4/17/2009  om@shell.com PHONE:303-222-6347
13. Describe proposed or complete of starting any proposed wor or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material ( Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for the same same same same same same same sam	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.  verification.  Rig Release  above is true and complete to the cergstrom E-mail addresser	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @  Date:  best of my knowled gulatory Coordinator is:michael.bergstr	Attach wellbore diagram of proposed completion  495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg ) with 4.0% by wt. extender.  ge and belief.  r DATE:4/17/2009  om@shell.com PHONE:303-222-6347
13. Describe proposed or complete of starting any proposed wo or recompletion.  Installed 1495 feet of 40.5 lbs./foot  Mixed and pumped 425 sacks of lesexpanding agent + 3.0% by wt. accelbs./sack lost circulation material ( Mixed and pumped 365 sacks of ta  Returned 100+ bbls. cement back to  Pressure tested casing to 1500 psi for the same same same same same same same sam	rk). SEE RULE 1103. For Multi 10.75-inch, K-55 STC casing.  ad cement; class "C" blended celerator + 2.5% by wt. extended LCM).  il cement; class "C" blended consurface.  for 30 minutes.  verification.  Rig Release  above is true and complete to the cergstrom E-mail addresser	Il pertinent details, ar iple Completions: A  Float shoe set at 14  cement (225 bbls @ cr + 0.6% by wt. and  cement (113 bbls. @  Date:  best of my knowled  gulatory Coordinator	Attach wellbore diagram of proposed completion  495 feet. Float collar set at 1446 feet.  11.5 lbs. per gallon (ppg)) with 5.0% by wt. ti-foamer + 3 lbs./sack extender + 0.25  13.5 ppg ) with 4.0% by wt. extender.  ge and belief.  r DATE:4/17/2009  om@shell.com PHONE:303-222-6347



## **Shell Exploration & Production**

State of New Mexico
Energy, Minerals and Natural Resources Dept.
Oil Conservation Division-District 4
1220 South St. Francis Drive
Sante Fe, New Mexico 87505
Attn.: Ed Martin, District Supervisor

Shell Exploration & Production Co.

Regulatory Affairs-EP Americas 4582 S. Ulster Street Parkway Suite 1400 Denver, Colorado 80237

## CONFIDENTIAL

April 17, 2009

Subject: Casing/Cement Report

Shell Exploration & Production Co., Latigo Ranch 3-3 (API No. 30-019-20138)

Guadalupe County, New Mexico

Dear Mr. Martin:

Shell Exploration & Production Company, dba SWEPI LP (Shell) is submitting the casing/cement report for installation of the surface casing string for the subject well to New Mexico Oil Conservation Division-District 4 (OCD) for your review and record keeping. Shell requests that OCD hold any information regarding this well confidential for the period designated under NMOCD rules. All documents submitted are clearly marked as "confidential".

If you have any questions or require any additional information regarding these reports, please contact me at (303) 222-6347, or David Janney at Kleinfelder in Albuquerque at (505) 344-7373.

Regards,

Michael L. Bergstrom Regulatory Coordinator

Shell Exploration & Production Company

Michael L. Bergetron

Attachments: Form C-103

THE OF VED