Submit 1 Copy To Appropriate District Office	State of New Mexico		Form C-103	
District I	Energy, Minerals and Natural Resources		October 13, 2009 WELL API NO.	
District II			30-021-20428	
1301 W. Grand Ave., Artesia, NM 88210 District III	W. Gladid Ave., Artesia, two 60210		5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	1000 Rio Brazos Rd., Aztec, NM 87410		STATE L 6. State Oil & Gas	FEE X
1220 S. St. Francis Dr., Santa Fe, NM			o. State on & Gas	Lease IVO.
87505 SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or	Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			WBDU	
1. Type of Well: Oil Well Gas Well X Other X CO2			8. Well Number 011G	
2. Name of Operator Hess Corporation			9. OGRID Number 495	
3. Address of Operator PO Box 840			10. Pool name or Wildcat	
Seminole TX 79360			West Bravo	Dome CO2 Gas
4. Well Location Unit Letter G : 2310 feet from the NORTH line and 1650 feet from the EAST line				
Section 1 Township 18N Range 29E			NMPM	CountyHARDING
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4511 GR				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐				
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A				
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB				
DOWNHOLE COMMINGLE				
OTHER:		OTHER: Reque	st Approval	X
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date				
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
proposed completion of recompletion.				
Requesting approval for the tubingless completion.				
This well has fiberglass casing from surface to the productive interval (TUBB). Steel casing will be used across the TUBB.				
The fiberglass casing must penetrate the Cimarron at a minimum.				
The optimum point for the setting the fiberglass casing				
is at the midpoint of the Cimarron formation.				
Spud Date: 06/07/2007	Rig Release Da	te:		
Spud Date. 007 077 2007	Mig Release Da	iic.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
(A)	l. sala			
SIGNATURE XUALI	TITLE ENG	INEERING TEC	CH DA	TE <u>1/8/2010</u>
Type or print name Rita C. S	mith E-mail address	: rsmith@he	ss.com PHO	ONE: <u>432-758-672</u> 6
For State Use Only	A A RIF	TRIAT ALIS	BUAS -	, ,
APPROVED BY: Conditions of Approval (if any):	TITLE DIS	TRICT SUPE	RVISOR_DAT	TE //21//0