

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-021-20505
5. Indicate Type of Lease STATE ☐ FEE ☒	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Mitchell	
8. Well Number	181F
9. OGRID Number	495
10. Pool name or Wildcat (96387) West Bravo Dome CO2 Gas	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4479'	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other CO2 SUPPLY

2. Name of Operator
HESS Corporation

3. Address of Operator
PO Box 840
Seminole TX 79360

4. Well Location
Unit Letter F : 2210 feet from the NORTH line and 1650 feet from the WEST line
Section 18 Township 19N Range 30E NMPM County HARDING

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: Request Approval Tubingless Completion ☒		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Requesting approval for the tubingless completion.

This well will have fiberglass casing from surface to the productive interval (GRANITE WASH).

Steel casing will be used across the GRANITE WASH.

The fiberglass casing must penetrate the Cimarron at a minimum.

The optimum point for the setting the fiberglass casing is at

the midpoint of the GRANITE WASH formation.

Proposed Completion:

MIRU on well.

Swab well

TIH and perf 4.5" csg

RD

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rita C. Smith TITLE ENGINEERING TECH DATE 1/12/2010

Type or print name RITA C. SMITH E-mail address: rsmith@hess.com PHONE: 432-758-6726

For State Use Only

APPROVED BY: Ed Martin TITLE **DISTRICT SUPERVISOR** DATE 1/21/10

Conditions of Approval (if any):