Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-1	
District I 1625 N. French Dr., Hobbs, NM 88240	Energy, Minerals and Natural Resources		June 19, 2 WELL API NO.	008
District II	OIL CONSERVATION DIVISION		30-053-20040	
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.		5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE   FEE   XX	
1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Nam	ie
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Black Butte	
1. Type of Well: Oil Well  Gas Well  Other: Wildcat			8. Well Number 1	
2. Name of Operator			9. OGRID Number	
3. Address of Operator c/o Walsh Engineering 1615 E. Warner Rd. #4, Tempe, AZ 85284			10. Pool name or Wildcat Wildcat	
4. Well Location: N34 25' 25.0": 1	W106 40' 29.9" WGS84			
			feet from theline	
Section 6 Township 2N Range 3E			NMPM Socorro County	
	11. Elevation (Show whether DR) 5136' GR	, RKB, RT, GR, etc.		
12. Check A	ppropriate Box to Indicate N	lature of Notice,	Report or Other Data	
NOTICE OF IN	SEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON □	K □ ALTERING CASING		
TEMPORARILY ABANDON  PULL OR ALTER CASING	CHANGE PLANS   COMMENCE DRI  MULTIPLE COMPL   CASING/CEMEN'			
DOWNHOLE COMMINGLE	MOLTIFLE COMPL	CASING/CEMEN	1306	
OTHER	_	0.71150		
OTHER:  13. Describe proposed or compl	eted operations. (Clearly state all )	OTHER:	Spud [] d give pertinent dates, including estimated	date
			tach wellbore diagram of proposed comple	
			55, ST&C casing and set at 987.47' KB. Cemet irculated 20 bbls of good cement to surface.	nted
12/22/09 Nippled up the bradenheacasing to 600 psi for 30 min. —		Holiday. 12/28/09 Pre	ssure tested BOP & surface equip. to 1300psi a	and
1/04/10 Reached intermediate TD 8-	-3/4" at 2711'KB. Ran 67 its (2686.0"	1') of 5-1/2", 20#, J-5	5, ST&C casing and set on mandrel at 2703' K	В
with the insert float at 2662' Kl Nitrogen and tailed with 50 sx	B. Cemented with 330 sx (472 cu.ft.) c (64.5 cu.ft.) of 50/50 Poz cement with	of 50/50 Poz cement w .3% Versaset, 0.1% F	vith .3% Versaset, 2% FDP, .1% Halad 766, 60 Ialad 766. Bumped the plug to 1000 psi, held	%
	,		d Logs; Found top of cement at 2526'KB.	2100
	YkB. Ran open hole logs; Temporaril P to 650psi, held 30min, good test. Rig		2578'KB, displaced drilling mud from above C on 1/09/10.	ЛВР
12/20/09		1/09/10		
		<u>l</u>		
Spud Date:	Rig Release D	ate:		
I hereby certify that the information a	bove is true and complete to the be	est of my knowledge	e and belief.	
1,4,5		.150	10/000	
SIGNATURE Joy M	TITLE <i>MA</i>	IAGER	DATE 1/19/2010 PHONE: 480-831-5800	
Type or print name TAY KENTE For State Use Only	E-mail address: JA	Kenteraeaou	.Com PHONE: 480-831-5800	
APPROVED BY:  Conditions of Approval (if any):	artes TITLE DE	STRICT SUP	RVISOR DATE 2/15/10	
Conditions of Approval (II ally).				